

PB-236 313

CONFERENCE ON RECYCLING TREATED
MUNICIPAL WASTEWATER THROUGH FOREST
AND CROPLAND

William E. Sopper, et al

Pennsylvania State University

Prepared for:

Environmental Protection Agency

March 1974

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE
5285 Port Royal Road, Springfield Va. 22151

**SELECTED WATER
RESOURCES ABSTRACTS**
INPUT TRANSACTION FORM

1. Report No. 2.

PB 236 313

W 74-12869

4. Title ***Conference on Recycling Treated Municipal
Wastewater Through Forest and Cropland**

3. Report Date

5. Author(s)

William E. Sopper and Louis T. Kardos (ed.)

6. Performing Organization
Report No.

7. Organization

**The Pennsylvania State University,
University Park, Pennsylvania 16802-
Institute for Research on Land and Water Resources.**

10. **EPA Project
R-800678, Program
Element 1B3045**

12. Sponsor's Organization

**Environmental Protection Agency, Technology Series,
EPA Project Report No. EPA-660/2-74-003, March 1974, 463 p.**

13. Type of Report and
Period Covered

14. Abstract

Intense interest in preserving the quality of ^{the} environment has reactivated interest in the management of wastewaters by applying them to the land. Use of land application approaches for wastewater management must be updated to conform to ~~our~~ new concepts of conserving and protecting the quality of ~~our~~ land and water resources. Design and operation of land-based wastewater management systems is dependent on site selection, the degree of water renovation desired, and the planned use of the site as well as the basic physical, chemical, and biochemical processes which influence system performance. The 32 individual papers included in this report are presented in sections which cover municipal wastewater characteristics, the function of the soil in the treatment process, vegetation responses, system design and cost, examples of operating systems, and the status of guidelines for land disposal of wastewater. (EPA)

(See W74-12870 thru W74-12901)

17a. Descriptors ***Waste water disposal,**

***Pollution abatement, *Wastewater treatment, *Tertiary treatment, *Conferences,
*Crop response, *Groundwater recharge, *Soil-water-plant relationships, *Municipal
wastes, Cycling nutrients, Agronomic crops, Forests, Sprinkler irrigation,
Environmental effects, Land use, Design data, Pathogenic bacteria, Costs, *Water reuse,**

17b. Identifiers

***Wastewater reuse, *Wastewater irrigation.**

Copy Available from GPO Sup Doc
as **EPA-660/2-74-003**, \$ **1.20** ;
microfiche from NTIS as PB

17c. COWRR Field & Group

03C, 04B, 05D 05E, 03E

18. Availability

19. Security Class.
(Report)

21. No. of
Pages

Send To:

20. Security Class.
(Page)

22. Price

**WATER RESOURCES SCIENTIFIC INFORMATION CENTER
U.S. DEPARTMENT OF THE INTERIOR
WASHINGTON, D. C. 20240**

Abstractor

Institution

EPA-660/2-74-003
March 1974

CONFERENCE ON RECYCLING TREATED MUNICIPAL
WASTEWATER THROUGH FOREST AND CROPLAND

By

William E. Sopper
Louis T. Kardos
The Pennsylvania State University
University Park, PA 16802

Project R-800678
Program Element 1BB045

Project Officer

Richard E. Thomas
Robert S. Kerr Environmental Research Laboratory
U.S. Environmental Protection Agency
Ada, Oklahoma 74820

Prepared for

OFFICE OF RESEARCH AND DEVELOPMENT
U.S. ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460

EPA Review Notice

This report has been reviewed by the Environmental Protection Agency and approved for publication. Approval does not signify that the contents necessarily reflect the views and policies of the Environmental Protection Agency, nor does mention of trade names or commercial products constitute endorsement or recommendation for use.

Preface

The Wastewater Renovation and Conservation Project was initiated at the Pennsylvania State University in 1962 under the direction of Dr. Michael A. Farrell, former Director of the Agricultural Experiment Station. An interdisciplinary team consisting of agricultural, civil, and sanitary engineers, agronomists, foresters, geologists, ecologists, microbiologists, biochemists and zoologists was assembled to investigate the feasibility and environmental impacts of disposal of treated municipal wastewater on the land through spray irrigation. From these investigations the "Living Filter" concept was evolved. The term "Living Filter" was first suggested by Mr. Gilbert Aberg, Science Information Officer, Department of Public Information, for the title of a film produced in 1965 depicting some of the early results of the project. Since then, the term "Living Filter Concept" has become more or less synonymous with the idea of spray irrigation of municipal wastewater on the land.

During the past 5 years there has been a tremendous increase in interest in spray irrigation of municipal wastewater and sludge throughout the United States. At the same time there appeared to be a lack of definitive information on the parameters and constraints which must be considered in the design and operation of land disposal systems under varying environmental conditions.

To partially meet this demand for information, this symposium on Recycling Treated Municipal Wastewater and Sludge Through Forest and Cropland was organized and held on August 21-24, 1972 at The Pennsylvania State University. The specific purpose was to review and discuss current knowledge related to the potential of using land areas for the disposal of wastewaters and to determine technological gaps and research needs. The sessions were attended by over 400 participants from 45 States, Canada, Puerto Rico, Virgin Islands, and New Zealand.

The Program Planning Committee consisted of Louis T. Kardos, Earl A. Myers, John B. Nesbitt, Richard R. Parizek, and William E. Sopper, from The Pennsylvania State University and James O. Evans and Elwood L. Shafer, Jr. from the U.S. Forest Service.

Financial support was provided by The Pinchot Institute for Environmental Forestry Research, Northeastern Forest Experiment Station, Forest Service, U.S. Department of Agriculture, and the Office of Research and Monitoring, Environmental Protection Agency, Washington, D.C.

The program was conducted by the College of Agriculture and the Institute for Research on Land and Water Resources as a continuing education service of The Pennsylvania State University.

William E. Sopper
Louis T. Kardos
Symposium Co-Directors

CONTENTS

Keynote Address Needed Directions in Land Disposal	1
Maurice K. Goddard	

SESSION I

TREATED MUNICIPAL WASTEWATER--WHAT IS IT?

Chemical and Biological Quality of Treated Sewage Effluents..... Joseph V. Hunter and Teresa A. Kotalik	6
Chemical and Biological Quality of Municipal Sludge..... James R. Peterson, Cecil Lue-Hing and D. Zenz	28

FUNDAMENTAL FUNCTIONS OF THE SOIL AND ITS ASSOCIATED BIOSPHERE

The Soil as a Physical Filter..... Richard E. Thomas	40
The Soil as a Chemical Filter..... Boyd G. Ellis	47
The Soil as a Biological Filter..... Robert H. Miller	73
Site Selection Criteria for Wastewater Disposal -- Soils and Hydrogeologic Considerations..... Richard R. Parizek	95

SESSION II

WASTEWATER QUALITY CHANGES DURING RECYCLING

Renovation of Municipal Wastewater Through Land Disposal by Spray Irrigation..... Louis T. Kardos and William E. Sopper	131
Renovating Secondary Sewage Effluent by Groundwater Recharge with Infiltration Basins..... Herman Bouwer	146
Phosphorus and Nitrate Levels in Groundwater as Related to Irrigation of Jack Pine with Sewage Effluent..... Dean H. Urie	157

Restoration of Acid Spoil Banks with Treated Sewage Sludge.....	165
T. R. Lejcher and S. H. Kunkle	

SESSION III

SOIL RESPONSES

Effects of Land Disposal of Wastewater on Soil Phosphorus Relations.....	179
J. E. Hook, L. T. Kardos and W. E. Sopper	
Effects of Land Disposal of Wastewater on Exchangeable Cations and Other Chemical Elements.....	196
Louis T. Kardos and William E. Sopper	
Factors Affecting Nitrification-Denitrification in Soils.....	204
F. E. Broadbent	
Biotoxic Elements in Soils.....	215
T. D. Hinesly and R. L. Jones	
Microbial Hazards in Disposing Wastewater on Soil.....	217
D. H. Foster and R. S. Engelbrecht	

SESSION IV

VEGETATION RESPONSES

Vegetation Responses to Irrigation with Treated Municipal Wastewater.....	242
William E. Sopper and Louis T. Kardos	
Anatomical and Physical Properties of Red Oak and Red Pine Irrigated with Municipal Wastewater.....	270
W. K. Murphey, R. L. Brisbin, N. J. Young and B. E. Cutter	

OTHER ECOSYSTEM RESPONSES

Deer and Rabbit Response to the Spray Irrigation of Chlorinated Sewage Effluent on Wild Land.....	286
Gene W. Wood, D. W. Simpson, and R. L. Dressler	

SYSTEMS DESIGN, OPERATION, AND ECONOMICS

Sprinkler Irrigation Systems: Design and Operation Criteria....	299
Earl A. Myers	

Cost of Spray Irrigation for Wastewater Renovation.....	309
John B. Nesbitt	
Financing Municipal Waste Water Treatment Facilities, Including Land Utilization Systems.....	315
Belford L. Seabrook	

SESSION V

EXAMPLES OF OPERATING AND PROPOSED SYSTEMS

Large Wastewater Irrigation Systems: Muskegon County, Michigan and Chicago Metropolitan Region.....	322
W. J. Bauer and D. E. Matschke	
Implementing the Chicago Prairie Plan.....	342
Frank L. Kudrna and George T. Kelly	
Mt. Sunapee State Park, New Hampshire Spray Irrigation Project..	348
Terrence P. Frost, Ronald E. Towne, and Harry J. Turner	
Utilization of Spray Irrigation for Wastewater Disposal in Small Residential Developments.....	362
T. C. Williams	
Ecological and Physiological Implications of Greenbelt Irrigation With Reclaimed Wastewater.....	375
V. B. Youngner, W. D. Kesner, A. R. Berg, and L. R. Green	

SESSION VI

EXAMPLES OF OPERATING AND PROPOSED SYSTEMS

Municipal Wastewater Disposal on the Land as an Alternate to Ocean Outfall.....	387
W. A. Cowlshaw and F. J. Roland	
The Role of Land Treatment of Wastewater in the Crops of Engineers Wastewater Management Program.....	400
James F. Johnson	

PRESENT STATUS OF GUIDELINES FOR LAND DISPOSAL OF WASTEWATER

Michigan's Experience with Utilizing the Ten State Guideline for Land Disposal of Wastewater.....	410
Donald M. Pierce	

Forest Service Policy Related to the Use of National Forest Lands for Disposal of Wastewater and Sludges.....	414
Olaf C. Olson and Edward A. Johnson	

Spray Irrigation -- the Regulatory Agency View.....	420
Richard C. Rhindress	

RESEARCH NEEDS

Research Needs -- Land Disposal of Municipal Sewage Wastes.....	435
James O. Evans	

APPENDIX

List of Participants.....	443
---------------------------	-----

NEEDED DIRECTIONS IN LAND DISPOSAL

Maurice K. Goddard
Secretary
Department of Environmental Resources
Harrisburg, Pennsylvania

I am pleased to appear today at this "state of the art" symposium on land disposal of municipal wastewater and sludge and to make a pitch for increased research and development on this fascinating area with its potential for dramatically improving the quality of our nation's waterways.

Land disposal is far from a new idea in this country and around the world but it is only recently that it has received the interest and the beginnings of support which are so vital to its success. The interest in land irrigation with waste waters comes from the recognition of severe damage done to the aquatic ecosystems due to discharge of various liquid wastes directly into streams, rivers or other bodies of water. Land disposal can serve not only to recharge the ground water supplies but also to return nutrients to the soil. The concept is not new and has been practiced for thousands of years in many European and Asian countries.

As all of you are undoubtedly aware, and as the listing of speakers for this symposium makes clear, much of the recent definitive research work on land disposal was done here at Penn State by the men who have organized this conference. Our concern now should be to build upon this research and push for new studies and demonstration projects to determine the parameters in which land disposal can be a useful tool in waste water management.

One impetus for increased examination of systems for land disposal came from the recent work in Washington on the water pollution control bills. Had the Senate version of the legislation prevailed, it appeared that the land disposal of effluents would almost have been mandated or at least made the subject of an evaluation as an alternative in every case. This might not have been that bad a result since it would have required us to face the issue squarely with time, talent and money rather than limping along on a piecemeal basis. Although this requirement was not in the final bill, the debate over it and the legislative interest in it may still lead to expansion of the work now underway in this field.

I do not propose today to engage in a technical discussion on the question of land disposal. There are many others on this program far more capable than I to give you the latest scientific insights. Rather, I would like to address myself, speaking as an administrator of an environmental agency, to the need for serious consideration of this and other alternatives to our waste problem. I have often been critical of some environmentalists who want to have things their own way without examining all the issues and alternatives involved in a particular problem. But this is one instance where the environmentalists have come closer to being on the right side.

One of the goals of the science of ecology is to maintain a balance as much as possible in the whole life-support system of the earth. Treating waste products so they are somewhat improved and then discharging them into our waterways does not really meet this goal. Taking water from underground supplies, using it and then dumping it into the streams continually depletes groundwater. Groundwater loss can be even more serious when wastewater is not treated and recycled locally but piped to large distant treatment plants for waste removal. Hence the interest of many ecologists in using wastewater to reclaim and fertilize land and using land as a filter. . . a living filter if you will. . . to purify the water. In the process, the water returns to the underground stores from which it came.

But while ecologists have been calling for this circular approach, engineers have been designing bigger and better treatment plants and they are the ones who have been getting all the attention. Unfortunately, they have been aided in their quest for more and better hardware by environmental regulatory agencies which have been more interested in specifying higher degrees of treatment necessary than they have been in forcing an investigation of the alternatives to the entire treatment and discharge method of disposing of wastes. I believe a Department such as mine must become much more involved in the question of land disposal as a plausible alternative not only from a regulatory standpoint but also from an advocacy and supportive point of view.

We have at the present time about 75 land disposal operations in the Commonwealth. Some of these land disposal facilities have been in operation for various periods of time. Most are relatively small projects and in their early stages were installed without a great deal of surveillance from the Department. No permit was necessary because there was no discharge. All this has changed now, however. We require permits for spray irrigation systems, just as we do for discharges, because experience has shown that some of the effluent finally ends up in the water courses anyway. So you have to consider them as an alternative in a total waste management system.

The Department now has in the final stages of preparation a manual which we call our Spray Irrigation Manual. It will establish the primary factors for consideration in the review of the design and the submission of necessary reports and data for State approval. Later in this conference you will hear from one of our water quality people who I am sure will tell you more of our plans in this regard. I mention it only to indicate the increasing seriousness with which we are approaching the question of land disposal and our role as a regulatory agency. Our manual will provide a set of guidelines for use by the consulting engineers, geologists and soil scientists in locating and evaluating the area needed for spray irrigation and in designing the system for distribution of the wastewater to the land surface.

While we and other government environmental agencies are getting more into the business of regulation of land disposal operations, and this is good, we should also be getting more into the business of promoting the examination of this technique in wider applications. Despite the apparent success of the Penn State project, started several years ago, a more sophisticated and ambitious plan for Muskegon County, Michigan, was greeted with yawns and a notable lack of interest among politicians and, even worse, among pollution control officials. The elements of the Muskegon plan--lagoons and spray irrigation--are not new. What is new and exciting, however, is the application of these concepts to an entire county of some 13 communities with a combined population of 170,000 and five industries--paper, chemical, engine manufacturing and metal casting and plating.

Some of the project officials have been quoted as saying the liquid effluent after just intermediate stages of treatment will be superior to that taken from a conventional secondary treatment plant. There are also claims that the final stage of the Muskegon County project--the so-called living filter of the earth--will outperform any technology now in existence. Experiments reportedly have shown that virtually all the phosphates in domestic sewage are removed by the time the water has moved only 12 inches downward through the soil. The "living filter" also intercepts what are probably the most persistent and dangerous pollutants in domestic wastes, viruses. While conventional secondary treatment does little if anything to remove viruses and chlorination and municipal drinking water treatment also do not touch them, there are indications that using the earth as a "living filter" may provide 100 per cent removal of viruses.

As attractive as the plan sounds, it met with stiff opposition from the Michigan Water Resources Commission. Much of their opposition reportedly was based on economic grounds although the project's backers believe long-term cost will actually be lower than conventional treatment and also expect increased tourism due to the cleaner waters as well as profits from crops grown on

the irrigated lands. The state agency's objections spread to the Federal Water Quality Administration which was needed to help with financing. What finally broke the deadlock was the intervention by Michigan Congressman Guy Vander Jagt who took on the Muskegon County proposal as a special project. The Federal agency, after a lot of prodding from sources all the way up to the White House, awarded Muskegon County a research and development grant and a construction grant. Vander Jagt and other congressmen led the fight recently to have the House water pollution control bill amended to equal the Senate version which was based on the Muskegon project. As summed up by the Muskegon County Planning Director, Roderick T. Dittmer, the whole thing sounds deceptively simple. "Pollutants, like phosphates, are simply natural resources out of place," Dittmer has said. "We are putting them back in place." The time when governmental agencies concerned with the environment can ignore something which seems to be so environmentally sound has long since passed.

Few agencies are proving this more today than the U. S. Army Corps of Engineers. While environmentalists have had many targets over the past few years in which the citizen ecological movement has grown, none has been more in the line of fire than the Corps of Engineers. And, to be fair about it, the Corps has deserved some of the criticism it has received as have many other agencies. To its credit now, however, the Corps is working to be more in tune with the times and to be more aware of environmental concerns in its actions. And one of the moves it is making is to become involved in the entire question of land disposal systems. Having enticed into a Corps job one of the men who had a great deal to do with developing the Muskegon County plan, the Corps has embarked on an effort to use its planning ability to design regional land disposal systems like Muskegon's. The Corps will do the planning in various areas around the country, calculate costs and benefits of alternative strategies for waste disposal both on land and in water and then let the communities make the final decisions and proceed with what they want to do. The Corps has begun its work with studies in five major cities--Cleveland, San Francisco, Chicago, Detroit and Boston-- as well as the Codorus Creek Watershed near Harrisburg. The Corps investigation of alternative sites will be useful as part of the massive research effort needed on this question.

It cannot be said now whether a natural waste recycling system is as attractive an alternative for all areas of the country, for all sizes of population and for all types of waste as it seems to be for Muskegon County. The answers to questions concerning locale, soils and other variables involved in the successful operation of land disposal system must be sought and found in the months and years ahead. If land disposal is found to be a feasible solution in many instances, one of the problems will be availability of land for this purpose. At present there is little evidence of over-

whelming public acceptance of the idea, much less demand for it. Farmers have been rather skeptical about committing themselves to continued use of the treated effluents. But you cannot go ahead with such a project if people will only say they might be willing to try it for a month or two. There must be a long-term commitment to stick with it if it is to succeed. Except for self-contained, on-site agribusiness industries which can irrigate their own lands, the concept is not being widely applied. For spray irrigation of municipal wastes it appears it will be necessary for municipalities to purchase and maintain their own lands. It seems to me, therefore, that a tremendous amount of public information and public relations work will have to be done to convince the farmers that the effluent is valuable and can be accepted.

Another problem we have seen thus far with spray irrigation is management--or better the lack of management. Many sites have been operated with reasonable care but on others reasonable care is generally not given. I think it is fair to say that management has been uniformly quite poor. Maintenance personnel rarely visit the works, piping gets broken, sprinklers clog or stop up, field areas get flooded, the mosquito population builds up and soils get completely waterlogged and then the field goes anaerobic. This is one problem which may be amenable to a solution as regulatory agencies become more involved with the permitting and supervising of land disposal projects.

The other problem--that of obtaining public acceptance and willingness to put it into practice--is not so easily solvable. This, I think, is one of the biggest things which should come from this symposium. After hearing all the experts these next few days tell you all they can about the "state of the art" of this exciting field, you should be ready to go home and convince politicians, environmental agencies, ecologically-minded citizens and everyone else that land disposal is worthy of their interest and support for future projects on even larger scales until we find out just how helpful this ultimate recycling idea may be.

If we all do this, the time may come in the not-too-distant future when not only is water cleaner but crops are better and economies are growing, all because we followed nature and its desire for balance.

319D

CHEMICAL AND BIOLOGICAL QUALITY OF SEWAGE EFFLUENTS

Joseph V. Hunter and Theresa A. Kotalik
Department of Environmental Sciences
Rutgers University

Once the water carriage system for human wastes disposal became established, the unfortunate consequences of the discharge of such wastewaters to the environment became unpleasantly evident. These problems were due to constituents of the wastewaters, and the classical ones may be briefly outlined as follows:

<u>Constituent</u>	<u>Problem</u>
Microorganisms	Disease
Particulates	Sludge banks in streams
Organics	Odors, color, toxicity
	Low stream dissolved oxygen

Wastewater treatment processes such as primary treatment as outlined in Figure 1 were designed to remove easily settleable particulates and part of the organics by primary sedimentation, and the pathogenic microorganisms by disinfection. Secondary treatment represents the addition of biological oxidation and adsorption to primary treatment for the purpose of further reducing the organic matter in effluents.

It is interesting to note from Figure 1 that those processes that are employed to reduce the quantities of particulates and organics in turn give rise to problems of primary sludge and waste biomass disposal. These are problems of the utmost importance, as the disposal methodologies available represent one of the major stresses on secondary wastewater treatment.

Even after secondary treatment, wastewater effluents can have significant effects on the environment. Such effluents still contain organics, salts, nutrients, particulates and varying amounts of microorganisms depending on the degree of disinfection. It is the purpose of this paper to delineate the physical, chemical and biological composition of effluents so that the implications involved by their disposal on, or recycling through, agricultural and forested lands can be better understood.




Fig. 1. Flow Diagram for a Wastewater Treatment Plant

CHEMICAL COMPOSITION

Organic Composition

In 1963, it was estimated that the BOD contributed by the sewered population of this country was 7.3 billion pounds. Assuming a removal efficiency of 90% for secondary treatment, 730 million pounds of BOD entered the environment that year that had its origins in domestic wastewater treatment plant effluents. Another way of expressing this is that each use of water, even after secondary treatment, added 25 mg/l BOD (equivalent to 52 mg/l organic matter (American Chemical Society, 1969).

As water supplies rarely contain large quantities of organic matter, almost all the organics in effluents either entered during the use of the water or were formed during secondary treatment. As is true for wastewater itself, effluent organic matter is both soluble and particulate in nature. Usual sanitary analyses find it sufficient to divide wastewater organics into suspended matter and soluble matter on the basis of filtration (Standard Methods for the Analysis of Water and Wastewater, 1971) (through an asbestos mat, glass fiber mat or membrane filter) or centrifugation (Rebhan and Manka, 1971).

Other investigators (Rickert and Hunter, 1967; Painter et al, 1961) have divided these organics into a settleable portion (obtained by sedimentation), a colloidal fraction (obtained by centrifugation), a colloidal fraction (obtained by candle filtration or high speed centrifugation and a soluble fraction (what remains

when the three particulate fractions are removed). Rarely are the particulate and soluble organics analyzed together as their natures are sufficiently different to warrant different analytical schemes.

The general distribution of organic matter in effluents is shown in Tables 1 and 2. Although better than half of the effluent

Table 1. Volatile Solids Distributions in an Activated Sludge Effluent

Effluent Fractions	Winter, 1965-66 ^a		Spring, 1967 ^b	
	mg/l	%	mg/l	%
Soluble	71 ^c	79	62	67
Colloidal	2	2	6	7
Supra colloidal	16	18	24	26
Settleable	1	1	0	0
Total	90	-	92	-

^aFrom Rickert and Hunter (1967).

^bFrom Rickert and Hunter (1971).

^cAll values are averages from triplicate sets.

Table 2. Comparison of Organic Carbon Distributions in Effluents Expressed as a Percentage of the Total

Type	Activated Sludge ^a (American)	Trickling Filter ^b (British)
Soluble	69	52
Fine suspended ^c	6	9
Coarse suspended ^d	25	39

^aFrom Rickert and Hunter (1971).

^bFrom Painter *et al* (1961).

^cEquivalent to colloidal in Table 1.

^dEquivalent to the sum of settleable and supracolloidal in Table 1.

organics are soluble, a considerable amount of the organics are particulate. Nevertheless, most of the analyses have ignored particulate composition. There have been three extensive investigations of the nature of the organic constituents in effluents. The first, shown in Table 3, identified about 35% of the "soluble" organic constituents. The next study, shown in Table 4, identified only about 25% of the soluble organics and 40% of the particulate organics. The analytical schemes used by these investigators was one that would have identified (and have been used to identify) at least two thirds to three quarters of the organics found in the original wastewaters. Part of this mystery (for the soluble constituents) was solved by the investigators whose data is shown in Table 5. Much of the organic matter not detected by previous investigators was found to be Fulvic, Humic and Hymathomelanic Acids. These results were obtained for a strong highly colored Israeli effluent, and how widely applicable they are is unknown at present. It is obvious, however, that at least part of the organics not determined by the first two investigations were such materials.

There have been few analyses of effluent particulates more detailed than those shown in Table 4. Analyses of the Amino acid constituents of effluent particulates are shown in Table 6 and those of the fatty acid contents in Table 7.

A number of the miscellaneous soluble organics found in effluents are shown in Table 8. In addition to these, organic acids and as gallic, citric, and lactic have been detected. It is evident from the results presented in this section that the general distribution of effluent organics and the major groups of effluent organics have been fairly well delineated. The molecular nature of many of the organics still remains to be delineated.

Inorganic

The inorganic constituents of wastewater effluents are largely soluble, as can be observed from Table 9. Little has been done on the nature of the particulate inorganics, but the soluble inorganics (especially nutrients) have been of considerable interest and considerable research has been involved in their detection and estimation.

Unlike organic constituents, which are almost wholly added to the initial water during use, the inorganic composition of a wastewater reflects the inorganic composition of the water supply. As the inorganic composition of water supplies are highly variable, it is difficult to generalize on the soluble inorganic constituents of wastewaters.

Table 3. Composition of an American Activated Sludge Effluent^a

Constituent	Percent of Total COD
Ether extractables	10
Proteins	10
Carbohydrates and polysaccharides	5
Tannins and lignins	5
MBAS ^b	
Unidentified	65

^aFor a filtered sample from Bunch *et al* (1961).

^bEquivalent to anionic detergents.

Table 4. Composition of a British Trickling Filter Effluent^a
(as mg/l organic carbon)

Constituent	Concentration	
	Particulate	Soluble
	mg/l	mg/l
Fatty acids	0.12	0
Fatty acid esters	0.12	0
Proteins	2.74	0.25
Amino acids	0.00	0.00
Carbohydrates	1.39	0.24
Soluble acids	0.13	1.65
MBAS ^b	0.05	1.40
Amino sugars	0.38	0.00
Muramic acid	0.05	0.00
Total	5.0	2.6
Total carbon	12.90	14.00
Recovery (%)	38.80	25.70

^aFrom Painter *et al* (1961).

^bEquivalent to anionic detergents.

Table 5. Composition of an Israeli Trickling Filter Effluent with a COD of 185 mg/l^a

Constituent	Percent of Total COD		
	Sample 1	Sample 2	Sample 3
Ether extractables	10.6	6.6	7.8
Anionic detergents	12.8	13.3	15.6
Carbohydrates	10.9	12.7	11.0
Tannins	1.5	1.4	2.2
Proteins	21.0	22.0	24.1
Fulvic acid	22.5	18.8	28.8
Humic acid	10.4	11.0	11.9
Hymathomelanic acid	7.4	9.5	7.5
Total	97.1	95.3	105.9

^aFor a centrifuged sample from Rebhan and Manka (1971)

Table 6. Amino Acid Contents of an Indian Effluent Particulates^a

Amino acid	Dry weight content
	mg/g
Cystine	14.8
Lysine, histidine	26.9
Arginine	18.1
Serine, glycine, aspartic acid	36.4
Threonine, glutamic acid	34.3
Alanine	22.1
Proline	Trace
Tyrosine	12.8
Methionine, valine	31.7
Phenyl alanine	27.5
Leucine, isoleucine	29.9

^aFrom Subrahanyam et al (1969).

Table 7. Fatty Acid Contents of an Indian Effluent^a

Fatty acid	Concentration
	mg/l
Lauric	0.11
Myristic	0.13
Palmitic	1.3
Stearic	0.93
Oleic	1.1
Linoleic	2.1
Linolenic	0.06

^aFrom Viswanathan *et al* (1962).

Table 8. Miscellaneous Soluble Effluent Organics

Constituent	Concentration	Reference
Formic acid	91.0 g/l	Murtaugh and Bunch (1967)
Acetic acid	130.0 g/l	Murtaugh and Bunch (1967)
Propionic acid	13.7 g/l	Murtaugh and Bunch (1967)
Isobutyric acid	26.5 g/l	Murtaugh and Bunch (1967)
Butyric acid	30.7 g/l	Murtaugh and Bunch (1967)
Isovaleric acid	73.4 g/l	Murtaugh and Bunch (1967)
Valeric acid	8.1 g/l	Murtaugh and Bunch (1967)
Caproic acid	47.9 g/l	Murtaugh and Bunch (1967)
Pyrene	0.4-1.0 g/l	Wedgewood (1952)
Nonionic surfactants	0.5-1.0 mg/l	Ministry of Technology (1966)
Cholesterol	15-57 g/l	Murtaugh and Bunch (1967)
Coprostanol	8-102 g/l	Murtaugh and Bunch (1967)
Uric acid	5-12 g/l	O'Shea and Bunch (1965)
Anionic surfactants	5.6 mg/l ^a	Hunter (1971)
	1.6 mg/l ^b	Hunter (1971)
Leucine	5 mg/l	Kahn and Wayman (1964)
Valine	5 mg/l	Kahn and Wayman (1964)

^a1963 value (before conversion to biodegradable ABS).

^b1967 value (after conversion to biodegradable ABS).

Table 9. Fixed Solids Distributions for an Activated Sludge Plant Effluent

Effluent Fraction	Winter, 1965-66 ^a		Spring, 1967 ^b	
	mg/l	%	mg/l	%
Soluble	223 ^c	99	250	97
Colloidal	1	0	2	1
Supra colloidal	3	1	4	2
Settleable	0	0	0	0
Total	227	-	256	-

^aFrom Rickert and Hunter (1967).

^bFrom Richkert and Hunter (1971).

^cAll values are averages from triplicate sets.

The most successful approach to this problem has been to indicate the quantity of inorganics added to the initial supply during domestic use. An example of this approach is presented in Table 10. Although these are generalizations only, it is apparent that one use of water adds to the water a considerable amount of dissolved inorganic salts. Most of these represent the initial amounts added to the water during use, as little or none of the salts in Group I are removed during treatment. The inorganics listed in Group II of Table 10 have been subjected to considerable alteration. The phosphates found in effluents are largely orthophosphate, and a significant amount of this is formed by the hydrolysis of the wastewater condensed (poly) phosphates during treatment (Bunch *et al*, 1961). In addition, varying amounts of this nutrient are removed during secondary treatment.

Ammonia is formed by the hydrolysis of urea and the biological decomposition of compounds containing organic nitrogen. Its concentration is reduced by assimilation, volatilization, and conversion to nitrite and nitrate. Like ammonia and phosphate, nitrate and nitrite are either absent from the original water supply or present in only small amounts. Unlike ammonia and phosphate, nitrite and nitrate are not added in substantial amounts to water during its use (i.e. conversion to wastewater), but are formed by the microbial oxidation of ammonia.

Although it is not completely a function of the inorganic constituents, the pH of effluents should also be noted here. In general, the pH of domestic wastewater will be close to seven,

Table 10. Inorganic Constituents Added to Effluents Through Domestic Use

Constituent	Average Increment Added ^a
	mg/l
Group I	
Sodium	70
Potassium	10
Calcium	15
Magnesium	7
Chloride	75
Bicarbonate	100
Sulfate	30
Silica	15
Hardness (as CaCO_3)	70
Alkalinity (as CaCO_3)	85
Group II	
Phosphate	25
Ammonium	20
Nitrate	10
Nitrite	1

^aFrom American Chemical Society (1969).

somewhat higher when fresh, lower when stale, and does not change too radically during secondary treatment. For example, the pH of raw Bernardsville sewage has a median figure of about 7.4, while the effluent from the activated sludge plant has a median figure of 7.2. Thus, even though much organic matter is converted to carbon dioxide, most of this is lost to the atmosphere or enters the bicarbonate buffer and therefore does not have a substantial effect on pH.

BIOLOGICAL COMPOSITION

The organisms present in the effluents from secondary wastewater treatment plants originate in the sewage entering the plant, the atmosphere, and the population growth in response to the chemical constituents utilized.

Effluents, therefore, would be expected to contain representatives from almost all the major biological groups. Although a considerable number have been identified, the major stress here has been on pathogens or organisms indicative of the possible presence

of pathogens. Considering the potential population, those organisms presently identified probably represent only a small part of the total, and it is difficult to state with any assurance of accuracy what the dominant organisms are. Those which have been studied fall into the following categories:

Viruses

Although infectious hepatitis is the only viral disease proven to have been transmitted by water contaminated with sewage (Clarke and Kabler, 1964), there is little or no information as to its presence in secondary treatment plant effluents. On the other hand, Coxsackie, Polio and ECHO virus have all been detected in effluents (Clarke et al, 1961; Lamb et al, 1964; Primavesi and Weistenberg, 1965). In addition, Coliphage has also been detected in effluents (Gilcreas and Kelly, 1954), not too surprising when the number of coliform organisms is considered. Due to the fact that the present methods are essentially only semi-quantitative, the exact numbers of virus units in effluents is unknown. However, it has been estimated that there are about 500 virus units/100 ml of summer sewage (Kollins, 1966). If up to 98% of those can be removed by activated sludge treatment (Clarke and Kabler, 1964) (found for Coxsackie virus), then there could be as low as 10 virus units/100 ml of effluent.

Bacteria

As with the viruses, the major attention to the bacterial populations of effluents has been directed towards those of sanitary significance. Salmonella have been detected in effluents in numbers up to 1 /100 ml (Keil, 1964). Among the various species found were:

<u>Salmonella typhi</u>	Kapsenberg (1958)
	Coetzie and Pretorius (1965)
<u>Salmonella paratyphi</u>	Kapsenberg (1958)
<u>Salmonella typhimurium</u>	Kapsenberg (1958)
<u>Salmonella bareilly</u>	Kapsenberg (1958)
<u>Salmonella sarcon</u>	Kapsenberg (1958)
<u>Salmonella schottmuelleri</u>	Buss and Inal (1957)

In addition to the Salmonella, clostridia can be detected in effluents (Nussbaumer, 1963), and Mycobacteria have been detected in treated Tuberculosis sanitari effluents (Coin et al, 1965; Bhaskaran et al, 1960).

A considerable amount of research has been directed towards the removals achieved during secondary treatment, and some of this is shown in Table 11. A detailed review of the removal of pathogens during treatment has been made by Kabler (1959). In addition to the pathogens and indicator organisms noted above, other studies

Table 11. Bacterial Removals Obtained by Secondary Treatment

Bacteria	Sewage Population	Reference	Biological Treatment Reduction	Reference
Coliform	No./ml 0.5-1-x10 ⁶	Tomlinson (1962) Burm and Vaughn (1966) Benzie and Courchain (1966)	90-99	Allen et al (1949)
Fecal streptococci	5-20 x 10 ³	Benzie and Courchain (1966) Allen et al (1949)	84-94	Allen and Brooks (1949)
<u>Shigella</u>	present	Holt (1960)	90-99	Kabler (1962)
<u>Salmonella</u>	4 - 12	Coetzie and Pretorius (1965) McCoy (1957)	70	Kabler (1962)
Total Count	3-18 x 10 ⁶	Tomlinson et al (1962)	90-99	Tomlinson et al (1962)
<u>Pseudomonas</u>	102	Coetzie and Fourie (1965)	none, pop. incr.	Coetzie and Fourie (1965)
<u>Aeruginosa</u>	7 x 10 ³	Hoadley (1967)	99	Hoadley (1967)
<u>Clostridium</u>	507	Coetzie and Fourie (1965)	90-99	Coetzie and Fourie (1965)
<u>Perfringens</u>				
<u>Mycobacterium</u>	present	Kapsenberg (1958) Coetzie and Pretorius (1965) Buss and Inal (1957)	66-88	Kabler (1962)
<u>Tuberculosis</u>			95	Bhaskaran et al (1960)

have indicated the presence of Proteus sp. (City of Johannesburg, 1963) in biologically treated effluents, and a 9×10^3 nitrite reducing organisms and 17×10^5 nitrate reducing organisms (van Gylswyk, 1961). It should be remembered that the microbial populations of wastewater (Dias, 1963; Farquhar and Boyle, 1971) and activated sludge (Farquhar and Boyle, 1971; Unz, 1965) have also been studied, and unquestionably most of these bacteria might also be expected to be present in effluents.

Fungi

Three main fungi groups were found in both influents to and effluents from biological treatment plants (Sladka and Otlova, 1968). These were as follows:

Phycomycetes
Ascomycetes
 Rhodotorula species
 Saccharomycetes
Deuteromycetes
 Fusarium aquaeductum
 Fusarium roseum
 Fusarium oxysporum

Yeasts were also found in effluents by another investigator, ranging from 10 - 80 cells/ml, and included the following (Cook, 1965):

<u>Cryptococcus</u>	<u>Saccharomyces</u>
<u>Rhodotorula</u>	<u>Alternaria</u>
<u>Trichosporons</u>	<u>Asperquillus</u>
<u>Candida</u>	<u>Aureobasidium</u>
<u>Torulopsis</u>	<u>Fusarium</u>
<u>Kloeckera</u>	<u>Geotrichum</u>
<u>Trichoderma</u>	<u>Mucor</u>
<u>Hansenula</u>	<u>Penicillium</u>

In addition, effluents may also contain many of the filamentous organisms found in activated sludge (Farquhar and Boyle, 1971).

Protozoa

A significant amount of attention has been paid to the pathogenic Endamoeba histolytica. It has been detected in the same effluent from which two other intestinal parasites were isolated, Trichomonas and Chilomastix mesnili (Metzler et al, 1958). Eudamoeba cysts have also been detected (Dunlop and Wang, 1961), and the following relationships were found for an Israeli effluent (Kott and Kott,

1967):

<u>Endamoeba</u>	<u>histolytica</u>	:	7/10 liters
<u>Eudamoeba</u>	<u>coli</u>	:	22/10 liters

In addition to these, the amoeba Centropyxes aculeata has also been detected, as well as the ciliates Stylonychia, Stentor, Paramecium, and Carchesium (Murad and Bazer, 1970).

Effluents may also contain those protozoa known to be present in the wastewater treatment plants (Barker, 1943; Curds and Cockburn, 1970) in numbers of about 100/ml. Effluents could also contain the following protozoan inhabitants of tertiary lagoons (Evans and Beuscher, 1970):

<u>Protozoa</u>	<u>Form</u>
<u>Amoeba sp.</u>	Rhizopod
<u>Euplotes patella</u>	Ciliate
<u>Loxophyllum helus</u>	Ciliate
<u>Oikomonas sp.</u>	Flagellate
<u>Pelodinium reniforme</u>	Ciliate
<u>Phyllomitus anylophagus</u>	Flagellate
<u>Trigonomonas compressar</u>	Flagellate
<u>Vorticella campanula</u>	Ciliate
<u>Epistylis pliciatilis</u>	Ciliate

Nematodes:

Nematodes in effluents have been reasonably well investigated since they have been shown to be able to injest pathogens. (Chang, 1961). The major groups detected in effluents have been:

<u>Family</u>	<u>Reference</u>
<u>Rhabditidae and</u>	Murad and Bazar (1970)
<u>Diplogasteridae</u>	Chang (1961)
	Chang and Kabler (1962)
	Calaway (1963)
<u>Diplogasteroides</u>	Chaudhuri et al (1964)
	Chang and Kabler (1962)
<u>Dorylaimidae</u>	Chaudhuri et al (1964)
	Chang (1961)
	Chang and Kabler (1962)
<u>Monochidae</u>	Calaway (1963)
	Chang and Kabler (1962)
	Calaway (1963)

A more detailed description of the nematodes from trickling filter effluents and their intestinal bacteria is shown in Table 12. Their numbers have been estimated as 200-2,000/g (Chang, 1961) and 2,000-2,500/g (Chang and Kabler, 1962) and that trickling filter effluents contribute a major portion of the free living nematode population in receiving waters.

Miscellaneous

A number of investigators have concerned themselves with organisms causing schistosomiasis. It has been estimated that either activated sludge or trickling filters can remove 99.7% of the eggs of Shistosoma mansoni (Rowan, 1964a) but both the eggs and miracidia have been detected in effluents (Rowan, 1964b). In addition, algae such as Oscillatoria (Evans and Beuscher, 1970) Euglena and Ankistrodesmus have been detected, as well as the larva of the trickling filter fly, Psychoda.

DISINFECTION

In the United States, disinfection is practically synonymous with chlorination. This is not true, however, in other areas, since ozone is widely used for disinfection in Europe and chemical disinfection of wastewater treatment plant effluents is not a general practice in Britain.

For these reasons, and as chlorination would affect the effluent characteristics previously mentioned, physical, chemical and biological characteristics of effluents are frequently studied prior to chlorination, so that the information produced would have the widest applicability. The major exception to this generality is for biological effluent constituents with public health implications.

As chlorination of effluents is widely practiced in the United States, it is necessary to indicate what effects it should have on the effluent characteristics previously described. The exact role this process has on colloidal and fine particulates is not too clear, but slight accumulation of sludges in chlorination tanks could indicate some improvements in settling characteristics.


In addition to the fact that chlorination always adds chlorides, the effect of chlorination of the inorganic constituents of effluents falls into two categories. The first involves the form in which the chlorine is added. Chlorine gas is rarely added directly to effluents. Instead, a concentrated "solution" of the gas in water (or effluent) is prepared, and this is added.

Table 12. Nematodes Found in Trickling Filter Effluents and their Intestinal Bacteria^a

Trickling Filter	Nematode		Bacteria		Genera or Species
	<u>Common</u>	<u>Uncommon</u>	<u>Count/nematode</u>	<u>Coli/nematode</u>	
1. Diplogasteroides Rhabditis	Rhabditolaimus		105	9.3	<u>Pseudomonas</u>
	Diplogaster				<u>Proteus</u>
		Tilobus			<u>A. aerogenes</u>
		Ironus			<u>E. Coli</u>
2. Diplogasteroides Diplogaster	Myolaimus		92	4.5	<u>Pseudomonas</u>
	Mononchus				<u>Proteus</u>
	Plectus				<u>A. aerogenes</u>
	Rhabditis				<u>E. Coli</u>
	Dorylaimus				<u>Streptococcus</u>


^aFrom Chang and Kabler (1962).

When this addition occurs, the following reaction takes place,



forming hydrochloric acid. Thus, this practice could only tend to lower the pH, decrease the alkalinity, and increase the acidity. Another chlorination procedure involves the use of sodium hypochlorite solutions, which have the opposite effect since it is highly alkaline. Wastewater effluents, however, are usually reasonably well buffered, and large changes in these values are not to be expected unless exceptionally large concentrations of disinfectants are employed.

The second involves the reactions that chlorine or rather hypochlorite has with ammonia. These are:




and result in the formation of monochloramine, dichloramine, and nitrogen trichloride. With sufficient chlorination, (a molar ratio of chlorine/ammonia of 2/1), ammonia can be almost completely removed from solution (Fair et al, 1968).

In reactions with organic compounds in dilute aqueous solutions such as effluents, chlorine (i.e. hypochlorite) can act in either of two ways. It can oxidize functional groups or even molecules in a manner analogous to any other oxidant. Thus, hypochlorite can oxidize aldehydes to organic acids, but will not in general, oxidize aliphatic alcohols (Manufacturing Chemists Association, 1972).



In addition, hydroquinones can be oxidized readily to quinones:



Of even greater interest is the fact that in addition to simple oxidation, the reaction of hypochlorites and organic materials can actually introduce chlorine groups into the molecule. For example, reactions can occur with nitrogenous materials as follows:



Of even greater significance are the reaction products with aromatic compounds. Here, the usual course of events is to substitute chlorine for hydrogen on the benzene ring. In general, alkyl

benzenes, aromatic carboxylic acids and aromatic nitro compounds do not react. On the other hand, aromatic amines, phenols, and poly hydroxy phenols do form substitution products with hypochlorite. The paths of these reactions are complex. With increasing chlorination, up to three chlorine groups can be added. Chlorination past this point acts like simple oxidation, resulting in rupture of the benzene ring and the production of oxidized fragments (Manufacturing Chemists Association, 1972). The general approximation for sewage is that about 2 mg/l BOD reduction is achieved per mg/l chlorine added (Imhoff et al, 1971). In all probability, as effluents are already partially oxidized, the oxidation efficiency would not be as good.

As interesting as the reactions of chlorine with organic and nitrogenous materials happens to be, the goal of chlorination is sufficient to render water acceptable according to the prevailing standards (which may attempt to achieve complete pathogen elimination). This seems relatively simple, and the general law of disinfection was evaluated in 1908 by Harriet Chick, which stated:

$$C^n t = K$$

where C is the concentration of disinfectant, t is the time required to achieve a stated percentage kill, k is a constant for a given disinfectant-organism system, and n is a coefficient of dilution or reaction order (Fair et al, 1968).

Using this equation, comparisons of the degree of sensitivity of organisms to be disinfection can be made, and an example of this is shown in Table 13. Not all results are so neatly defined, however, and there seems to be considerable variation in the literature on the question of the chlorine dosage and/or residual required to yield a stated effect. This is not too surprising, as the effectiveness of disinfection by chlorine will not only be influenced by time and chlorine concentration, but also whether or not the chlorine residual is free or combined (hypochlorite or chloramine), how well it is distributed, whether or not there are particulates present, temperature, pH, the concentration, condition, and nature of the organism, etc. In addition, the results reported will also be a function of the sensitivity, precision and accuracy of the test procedures. Keeping these limitations in mind, Table 14 gives some idea of the relative resistances of organisms to disinfection by chlorine. There is little question but that virus inactivation is one of the more difficult tasks of chlorination, but as in any disinfection process, required kills can be achieved by lengthening the time or increasing the concentration. Within its limits, and despite all of the problems involved, it has been a successful disinfectant, and for domestic sewage and effluents it will probably remain the disinfectant of choice for the near future.

Table 13. Chick's Law Constants for Chlorination to 99% Kill or Inactivation

Organism	n ^a	K ^a	Reference
Adenovirus 3	0.86	0.098	Clarke et al (1956)
<u>E. coli</u>	0.86	0.24	Butterfield and Wattie (1946)
Poliovirus Type 1	0.86	1.2	Weidenkopf (1958)
Coxsackie A2 Virus	0.86	6.3	Chang et al (1960)

^aConstants according to Fair et al with time in minutes and concentration of HOCl in mg/l.

SUMMARY

The chemical and biological composition of effluents reflects the quality of the wastewater entering the plant and the changes that occur during the physical, chemical, and biological processes in the plant. The chemical changes that occur during treatment reflect the biological removal of 80-90% of the organic matter and the production of more oxidized organics. Thus, effluents will contain such materials as proteins, carbohydrates and soluble organic acids which either persist through the plant or are formed in it, such organics as Alkyl Benzene Sulfonates which have persisted through it, or such organics as Fulvic, Humic and Hyathomelanic Acids which are probably formed during treatment.

Interest in the removals of microorganisms during treatment lies mainly in the area involving the efficiency of pathogen removal. Sedimentation and biological oxidation do markedly reduce pathogens, but as removals will depend (among other things) on the concentration of the pathogen in the wastewater, their presence in the effluent from biological treatment units can be expected and demonstrated. In addition to wastewater bacteria, viruses, etc. that have persisted through the plant, large numbers of protozoa and nematodes can be developed during biological treatment. Interest here has centered on the nematodes, which can ingest pathogens and thus have public health significance.

Effluent chlorination is largely for disinfection. There is little question but that the correct combinations of time and concentration (residual) can be achieved to obtain effective disinfection. However, actual practice may not always achieve this end, and excessive chlorination without dechlorination may lead to toxicity problems in receiving waters. Although chlorine can remove nitrogen (as ammonia) from solution, it also reacts with as

Table 14. Effect of Chlorination of Various Organisms

Group	Organism	Chlorine Residual	Time	Efficiency	Reference
Virus	Infectious Hepatitis	mg/l	min.		
		1	30	Survived	Kabler (1959)
	Coxsackie	15	30	Inactivated	Kabler (1959)
	Echo	5	2.5	Survived	Kabler (1959)
	Poliovirus I	1.0	3	99.6% Kill	Kollins (1966)
	Coliphage B	1.95	6.5	Survived	Kabler (1959)
	Theiler Phage	0.53	14	Survived	Kabler (1959)
		0.03	10	20% Survival	Gilcreas and Kelly (1954)
		0.03	10	Killed	Gilcreas and Kelly (1954)
	<u>M. tuberculosis</u>	1-5	120	99% Kill	Kabler (1959)
Bacteria		2	30	99% Kill	Kabler (1959)
	<u>E. coli</u>	1	30	Destroyed	Rhaskaran et al (1961)
	<u>Coliforms</u>	0.14	3	99.9% Kill	Kollins (1966)
		0.03	10	48% Survival	Gilcreas and Kelly (1954)
	Total Count	1-1.2	15	99% Kill	Kabler (1959)
		some	15	98-99% Kill	Kabler (1959)
	Diplogaster	2.5-3	120	Survived and	Chang et al (1960)
	Cheilobus	15-45	1	Mobile	Chang et al (1960)
	<u>S. mansoni</u>	0.2-0.6	30	Killed	Kabler (1959)
	(ova and Miracidia)	0.2-0.6	30	Killed	Kabler (1959)
Nematodes	<u>S. japonicum</u>				
	(ova and Miracidia)				
Others					

well as oxidizes organic materials. The significance of these chlorine containing organics in effluents has not yet been definitely established.

REFERENCES

- Allen, L., E. Brooks, and I. Williams. 1949. Jour. Hyg., 47.
Allen, L. and F. Brooks. 1949. Jour. Hyg., 47, 320.
American Chemical Society. 1969. Cleaning our environment, the chemical basis for action, a report of the Committee on Chemistry and Public Affairs, Washington, D.C.
Barker, A. 1943. The Naturalist, July Sept., 65.
Benzie, W. and R. Courchaine. 1966. Jour. Water Poll. Control Fed., 38, 410.
Bhaskaran, T., M. Lahiri and B. Roy. 1960. India Jour. Med. Res., 48, 790, Water Poll. Abstr., 34, 2097 (1961).
Bunch, R., E. Barth, and M. Ettinger. 1961. Jour. Water Poll. Control Fed., 33, 122.
Burn, R. and R. Vaughn. 1966. Jour. Water Poll. Control Fed., 38, 400.
Buss, W. and T. Inal. 1957. Berl. Munch tieraragt Nschr., 70, 311, Water Poll. Abstr., 31, 1609 (1958).
Butterfield, C. and E. Wattie. 1946. Pub. Health, Report, 61, 157.
Calaway, W. 1963. Jour. Water Poll. Control Fed., 35, 1006.
Chang, S., G. Berg, and N. Clarke. 1960. Amer. Jour. Trop. Med. Hyg., 9, 136.
Chang, S. 1961. Jour. Amer. Works. Assn., 53, 288.
Chang, S. and P. Kabler. 1962. Jour. Water Poll. Control Fed., 34, 1256.
Chaudhuri, N., R. Siddiqi, and R. Engelbrecht. 1964. Jour. Amer. Water Works Assn., 56, 73 (1964).
Chick, H. 1908. Jour. Hyg., 8, 92.
City of Johannesburg. 1963. City Eng. Dept. Tech. Rept., Johannesburg, So. Africa, Water Poll. Abstr., 39, 249 (1966).
Clarke, N. and P. Kabler. 1954. Amer. Jour. Hyg., 59, 119.
Clarke, N. and P. Kabler. 1964. Health Lab. Sci., 1, 44.
Clarke, N., R. Stevenson, and P. Kabler. 1956. Amer. Jour. Hyg., 64, 314.
Clarke, N., R. Stevenson, S. Chang, and P. Kabler. 1961. Amer. Jour. Pub. Health, 81, 1118.
Coetzle, O. and N. Fourie. 1965. Proc. resolutions and papers, conf. on problems assoc. with the purif., discharge and reuse of municipal and ind. effluents., Nat. Inst. for Water Res., C.S.I.R., Conf. No. 55, Pretoria, So. Africa, 93.
Coetzle, O. and T. Pretorius. 1965. Pub. Health, 415, Water Poll. Abstr. 40, 19 (1967).
Coin, L., M. Menetrier, J. Labonde, and M. Hannoun. 1965. Proc. 2nd Internat. Conf. Water. Poll. Res., Tokyo, 1, 1.

- Cooke, W. 1965. Mycologia, 57, 696.
- Curds, C. and A. Cockburn. 1970. Water Research, 4, 237.
- Dias, F. 1963. Jour. Ind. Inst. Sci., 45, 36.
- Dunlop, S. and W. Wang. 1961. Jour. Milk, Tech., 24, 44, Water Poll. Abstr., 35, 137 (1962).
- Evans, R. and D. Beuscher. 1970. Water and Sew. Works, 117, 35.
- Fair, G., J. Geyer, and D. Okun. 1968. Water and wastewater engineering, vol. 2, John Wiley and Sons, Inc. N. Y.
- Farquhar, G., and W. Boyle. 1971. Jour. Water Poll. Control Fed., 43, 779.
- Finsteln, M. and J. Hunter. 1967. Water Research, 1, 274.
- Gilcreas, F. and S. Kelly. 1954. New England Water Works Assn. Jour., 68, 268.
- Hoadley, A. 1967. Thesis, Univ. Wisconsin, 1965, Dis. Abstr. 28, B, 459.
- Holt, H. 1960. Monthly Bull. Min. Health Lab. Service, 19, 29.
- Hunter, J. V. 1971. Origin of organics from artificial contamination in organic compounds in aquatic environments, S. D. Faust and J. V. Hunter, Eds. Marcel Dekker, Inc., N. Y.
- Imhoff, K., W. Muller, and D. Thistlethwayte. 1971. Disposal of sewage and other water-borne wastes, Ann Arbor Science Publ. Inc., Ann Arbor, Mich.
- Kabler, P. 1959. Sew. and Indust. Wastes, 31, 1373.
- Kabler, P. 1962. Environ. Health; India, 4, 258.
- Kahn, L. and C. Wayman. 1964. Jour. Water Poll. Control Fed. 36, 1368.
- Kapsenberg, J. 1958. Ned Tijdschr. Geneesk, 102, 836, Water Poll. Abstr. 32, 498 (1959).
- Keil, R. 1964. Arch. Hyg. Bakt., 148, 74, Water Poll. Abstr., 38, 40 (1965).
- Kollins, S. A. 1966. Adv. Appl. Microbiol., 8, 145.
- Kott, H. and Y. Kott. 1967. Water and Sew. Works, 114, 177.
- Lamb, G., J. Chen, and L. Scarce. 1964. Amer. Jour. Hyg., 80, 320.
- Manufacturing Chemists Association. 1972. The effect of chlorination on selected organic chemicals, Office of Research and Monitoring, Environmental Protection Agency Project #12020EXg.
- McCoy, J. 1957. Proc. Soc. Water Treatment Exm., 6, 81.
- Metzler, D., R. Culp, H. Stoltenberg, R. Woodward, G. Walton, S. Chang, N. Clarke, C. Palmer, and F. Middleton. 1958. Jour. Amer. Water Works Assn., 50, 1021.
- Ministry of Technology (Brit.). 1966. Notes on water pollution, No. 34.
- Murad, J. and G. Bazer. 1970. Jour. Water Poll. Control Fed., 42, 106.
- Murtaugh, J. and R. Bunch. 1967. Jour. Water Poll. Control Fed., 39, 404.
- Nussbaumer, N. 1963. Water Works Engr., 116, 722, Water Poll. Abstr. 38, 18 (1965).

- O'Shea, J. and R. Bunch. 1965. Jour. Water Poll. Control Fed., 37, 1444.
- Painter, H., M. Viney, and A. Bywaters. 1961. Jour. Inst. Sew. Purif., 302.
- Primavesi, C. and J. Weistenberg. 1965. Arch. Hyg. Bact., 149, 336, Water Poll. Abstr., 39, 1038 (1966).
- Rebhan, M. and J. Manka. 1971. Environ. Sci. Tech., 5, 606.
- Rickert, D. and J. Hunter. 1967. Jour. Water Poll. Control Fed., 37, 1475.
- Rickert, D. and J. Hunter. 1971. Water Research, 5, 421.
- Rowan, W. 1964a. Amer. Jour. Trop. Med. Hyg., 13, 572.
- Rowan, W. 1964b. Amer. Jour. Trop. Med. Hyg., 13, 577.
- Russel, E., E. Munro, and J. Peacol. 1962. Water Waste Treat. Jour., 8, 575.
- Sladka, A. and V. Otlova. 1968. Hydrobiologica, 31, 350.
- Standard methods for the analysis of water and wastewater. 1971. Amer. Pub. Health Assn., N. Y., N.Y., 13th ed.
- Subrahanyam, P., C. Sastry, A. Rao, and S. Pillai. 1969. Jour. Water Poll. Control Fed., 32, 344.
- Tomlinson, T., J. Loveless and L. Sear. 1962. Jour. Hyg. 60, 365.
- Unz, R. 1965. Doctoral thesis, Rutgers University, New Brunswick, N. J.
- van Gylswyk, N. 1961. Jour. Biochem. Microbiol. Tech. and Engr. 3, 115.
- Viswanathan, C., B. Bai, and S. Pillai. 1962. Jour. Water Poll. Control Fed., 34, 189.
- Wedgewood, P. 1952. Jour. Proc. Inst. Sew. Purif., 20.
- Weidenkopf, S. 1958. Virology, 5, 56.

CHEMICAL AND BIOLOGICAL QUALITY OF MUNICIPAL SLUDGE

J. R. Peterson, C. Lue-Hing and D. R. Zenz
The Metropolitan Sanitary District of Greater Chicago

320D

Sewage sludge is derived from the organic and inorganic matter removed from wastewater at sewage treatment plants. The nature of sludges depends on the wastewater sources and the method of wastewater treatment. If waste solids are to be evaluated as a soil amendment or as a fertilizer, it is important to understand their chemical and biological properties. A comparison of sludge analyses from various treatment plants would be confounded by the individual treatment processes; therefore, some of the more common wastewater treatment methods will be described.

CHEMICAL QUALITIES

The first treatment process is usually gravity separation of solids from wastewater. This process is commonly known as primary settling or primary treatment. Secondary sewage treatment may be accomplished by physical-chemical or biological processes. The physical-chemical processes include chemical precipitation using lime, alum, or ferric chloride. Biological secondary treatment includes trickling filters or some modification of the activated sludge process in an aerobic suspended growth system which consists of contacting primary treated with previously treated sludge. These processes result in nutrient consumption by micro-organisms and the formation of biological flocs which are later settled out and subsequently pumped to concentration chambers for reuse (as activated sludge) or ultimate disposal.

The wastewater solids separated by these primary and secondary water treatment processes may then be dried for marketing as a low analysis dry fertilizer, or subjected to various stabilization treatments. Some current sludge stabilization processes include: the Zimpro process, a high temperature and high pressure, wet oxidation treatment which produces an aqueous suspension having a granular ash; extended aeration in tanks or lagoons; and anaerobic meso- or thermophilic digestion.

Following any of these latter processes the stabilized sludge may be further concentrated by drying beds, vacuum filtration, pressing, centrifuging, or lagooning with supernatant drawoff. The liquid fraction is high in soluble constituents. Malina and Di-Fillippo (1971) reported that 57 percent of the nitrogen in the waste-activated sludge digester feed was removed in the digester

supernatant. The advantages of this further concentration is to save lagoon storage space, reduce handling costs, or to remove soluble chemical constituents which are usually returned to the treatment plant. The reduction in soluble chemical constituents has an advantage if the sludge is to be disposed of on land at high sludge application rates.

Land application of liquid sewage sludge requires high capital investment and is best done on a large scale. Therefore, to have a competitive disposal system on land, the area should be capable of safely accepting high application rates and provide some marketable crop which will remove nutrients and protect the soil from rapid weathering. Nitrate accumulations in groundwater have been reported with high application rates of dairy manure (Adriano, Pratt, and Bishop, 1971) and digested sewage sludge (Hinesly, Braids, and Molina, 1971). Therefore, any reduction in the nitrogen content of the sludge will permit a higher application rate of sludge without endangering groundwater quality.

The chemical properties of sludge at various steps in the waste-activated sludge treatment process at the Metropolitan Sanitary District of Greater Chicago (MSDGC) West-Southwest Sewage Treatment Plant are presented in Table 1. The sewage at this plant includes domestic and industrial wastewater at an approximate ratio of 3:2 plus stormwater from the Chicago area. Primary sludge properties are not included with these data (Table 1) except for lagoon sludge (Column 6) with supernatant removal. Part of the waste-activated sludge is treated with FeCl_3 and vacuum filtered. This is blended at a ratio of 1:3 with waste-activated sludge for thickening and fed to the digesters which are completely mixed. The digester drawoff (Column 4) at this plant does not have supernatant separation which may partly explain the very high total and NH_4 nitrogen concentration compared to what Anderson (1956) reported. The lower nitrogen concentration from anaerobically digested sludge reported by Anderson (1.3-3.1%) was due to the use of primary sludge only while Table 1 represents waste-activated anaerobically digested sludge. Anaerobic digestion at MSDGC averages ca 30% reduction in volatile solids. This solids reduction continues, to a much lesser degree, in the lagooned sludge because of further anaerobic degradation of the organic materials present.

Analyses of the lagooned sludge which had no supernatant draw-off was done by sampling three points in a 20 ha (50 acres) lagoon eight months after the start of the filling operation. The filling was done on a daily basis during these eight months after which time the total sludge volume was $1.5 \times 10^6 \text{ m}^3$ when sampled. At each point five samples from the surface to the lagoon bottom were taken; these samples were from the surface, 2.7, 5.5, and 9.1 m below surface, and a bottom sample (ca 15 m). A Kemmerer sampler was used in the cover water (0-4.6 m depth) while in the thickened

Table 1. Chemical Properties of Various Sludges Formed in the Waste-Activated Sludge Treatment Processes at MSDGC West-Southwest Treatment Plant, Chicago, Illinois

	State of Sludge Treatment					
	Activated (1)	Vacuum filtered & heat dried (2)	Digested feed ¹ / (3)	Digester drawoff ² / (4)	Lagooned without supernatant drawoff ³ / (5)	Lagooned with supernatant drawoff ⁴ / (6)
Number of analysis	7	7	7	230	15	30
Total solids (%)	1.43	99.5	5.41	3.99	3.99	--
Volatile solids (% total solids)	66.2	67.3	65.2	57	55.6	35.5
pH	6.7	--	6.2	7.4	7.5	7.2
Total nitrogen ⁵ / (% oven dry basis)	6.65	6.4	5.63	7.27	7.20	2.60
NH ₄ -N (% oven dry basis)	0.47	trace	1.15	3.26	3.60	1.20

¹/The digester feed consists of a blend of activated sludge and vacuum filtered activated sludge (3:1). The latter contains 10% FeCl₃ by dry weight.

²/Digested 14 days at 29-32°C without digester supernatant withdrawal.

³/Analyses estimated after 8 months of filling a lagoon with digester drawoff.

⁴/Earlier sludge produced at the same treatment plant which may be up to 20 years in age and has had supernatant removed from the lagoon (Peterson et al, 1971).

⁵/Total N analysis by Kjeldahl and NH₄-N by distillation with sludge buffered to pH 10.5.

underlying slurry an Ekman dredge sampler was used. The total solids for the whole lagoon were estimated to be equal to what was added (3.99%). The cover water-slurry partition was estimated as 1:1 (v/v basis). Laboratory columns confirmed this partition ratio. The lagooned sludge concentration was calculated for the whole lagoon by averaging the concentration of the cover water and the slurry with the assumption of a 1:1 volume ratio and a total solids of 3.99% in the lagoon if it were remixed. The estimated analyses of this sludge is presented in column 5 of Table 1. Only volatile solids showed any reduction, although NH_3 gas was sometimes detectable in the area.

A comparison of the two lagooned sludges in Table 1 (Columns 5 and 6) shows the great reduction in volatile solids and nitrogen compounds that can be expected with up to twenty years of lagooning and periodic supernatant drawoff. The inputs to this lagoon included Zimpro wet ash, waste-activated sludge, primary sludge, and digested waste-activated sludge.

A comparison of sewage sludge from various parts of the United States is presented in Table 2. The sludge types include: primary only at Georgia and primary plus waste-activated at Minnesota, Colorado, and Illinois. Sludge treatment included are: none at St. Paul, Minn., addition of FeCl_3 vacuum filtration, and heat-drying of waste-activated sludge MSDGC West-Southwest Plant; and anaerobic digestion of primary plus waste-activated sludges without supernatant drawoff at MSDGC, Hanover and Calumet Plants. The Hanover sewage is primarily from domestic sources and the Calumet and West-Southwest sewage is a blend of domestic and industrial at an approximate ratio of 3:2.

A comparison of Hastings and Hanover Park, two sewage treatment plants with the least industrial waste and the same sewage treatment processes indicates that Hanover Park (Column 3) has more Ca, Mg, and Fe in its wastewater, whereas Hastings (Column 1) has more Cr and Cu, in fact the most of any reported in Table 2. An industrial source at Hastings is discharging Cr into the sewage treatment plant.

A comparison of the three undigested sludges from St. Paul (Column 2), MSDGC, West-Southwest (Column 5), and Denver (Column 6) would be valid except for changes relating to the chemical additions in the latter two plants. From these three plants, Chicago heat-dried sludge had the highest concentration of total N, P, An, and Cu, and Denver had the least total N, P, B, and Cu.

At the MSDGC, West-Southwest Sewage Treatment Plant a daily composite of waste-activated anaerobically digested sewage sludge was collected for 281 days between August 19, 1971 and May 31, 1972

Table 2. Chemical Analyses of Sewage Sludges from Various Wastewater Treatment Plants

Source:	Hastings, Minn.1/	St. Paul, Minn.1/	-----M.S.D.G.C. Chicago Ill.2/-- Hanover, Calumet West-Southwest	Denver, Colo.3/	Athens, Ga.4/		
Treatment Process:	Primary & waste activated: anaerobic digestion with-out supernatant draw-off	Primary & waste activated (1:2): undigested	Primary & waste activated: anaerobic digestion with-out supernatant digester drawoff	Waste-activated FeCl3 addition: vac. filtered: heat-dried	Primary & anaerobic digestion activated: bic di-FeCl3 and lime: vac. filtered: undigested		
Analyses	(1)	(2)	(3)	(4)	(5)	(6)	(7)
N-Total	5.84	4.69	5.57	5.20	6.37	4.57	3.5
NH4-N	2.34	1.33	3.63	2.40	trace	---	---
P	2.61	2.20	2.59	3.90	2.49	1.75	0.75
K	0.27	0.24	0.68	0.55	0.41	---	0.22
Ca	2.97	2.52	5.05	4.20	1.4	7.38	1.21
Mg	0.26	0.40	1.64	0.60	0.75	0.45	0.09
Zn	0.075	0.14	0.069	0.35	---	0.172	0.252
B	0.0013	0.002	---	---	0.002-0.04	0.00022	0.00199
Fe	0.45	0.76	2.22	3.68	5.32	1.48	---
Mn	0.015	0.039	0.07	0.14	0.012	0.0253	0.0199
Al	0.65	0.74	---	1.21	---	---	---
Cd	0.00079	0.036	0.0089	0.0125	0.028	---	---
Cl	---	---	0.12	0.74	---	---	---
Cr	0.390	0.067	0.019	0.112	0.362	---	---

Table 2. Continued

Analyses	‡ of dry wt. basis					
	(1)	(2)	(3)	(4)	(5)	(6) (7)
Cu	0.12	0.065	0.062	0.088	0.11	0.0324 0.046
Ni	<0.001	0.015	0.032	0.020	0.034	0.0026
Pb	0.039	0.070	0.083	0.18	0.141	---

^{1/}Unpublished data from C. E. Clapp, R. H. Dowdy, and W. E. Larson, ARS, USDA, St. Paul, Minn.

^{2/}Unpublished data, MSDGC.

^{3/}Parza (1969).

for chemical analyses. Other properties of this material were determined on a less frequent basis. The analytical methods used were: total N by Kjeldahl; $\text{NH}_4\text{-N}$ by distillation at pH 10.5; total P by Technicon Auto-Analyzer method of Stanley and Richardson (1970); S by Leco induction furnace; metals were done by digestion of 10 ml of the liquid sludge in 10 ml of a mixture of concentrated H_2SO_4 and HNO_3 at a ratio of 1:1, dilution to 200 ml and determination by atomic absorption except for Hg which was by the absorption technique; Cl, pH, electrical conductivity (E.C.), total and volatile solids, COD, BOD₅, volatile acids and the hexane soluble constituents were done by standard methods (USPHS 1971); inorganic carbon by the Bundy and Bremner (1972) method; neutralizing power was done by repeated heating of the liquid sludge for 1 hour on a steam bath and repeated acid titrations to a pH 6.5 end point (Martens, 1971); alkalinity by the USPHS (1971) method of titration to pH 4.5 end point; particle size was done by using a Coulter Counter with 3 and 9 orifices; and cation exchange capacity (CEC) by the H. D. Chapman (1965) method as used for soils. The same analytical methods were used for MSDGC sludge analyses presented in Table 1 and 2.

A detailed analytical description of anaerobically digested waste-activated sewage sludge from the MSDGC West-Southwest Sewage Treatment Plant is presented in Table 3. The total N concentration is very high (7.27%) compared to other sludge sources. The soluble nitrogen ($\text{NH}_4\text{-N}$) content is 3.26%. This nitrogen is available to a growing crop or may be adsorbed by the colloidal fraction of the soil. The rate of organic nitrogen mineralization for digested sludge is less than for fresh organic wastes, e.g. animal manures or waste-activated sludges. In addition to nitrogen, this sludge is a source of P, Ca, Zn, Fe, and S for plants. Many other essential and non-essential elements exist in sewage sludge. The solubility of compounds of these elements varies with the nature of the sewage and the chemistry of the soil following sludge application. Jenkins and Cooper (1964) found that the dominant metal forms in industrial sludge were hydroxides. Parsa (1970) postulated chelation as an important mechanism of Zn release from sludge in soil. In a reduced environment, such as a digester, metal-sulfides, sulfites, -phosphates, -carbonates, -bicarbonates, -oxides, and -hydroxides are all possible in organic compounds that might be present. Following sludge application to soil the solubilities of these compounds are a function of soil pH. The 4.56% Fe content of MSDGC sludge may be advantageous according to Lagerwerff's (1967) data. He reported that metals are competitive with Fe in biological systems. The general order of decreasing competition seems to be: $\text{Cu} > \text{Co} > \text{Ni} > \text{Cr} > \text{Zn} > \text{Mn} > \text{Pb}$.

The continued application of sewage sludge on non-calcareous soil has been reported to cause a soil pH reduction (Hinesly, Braids and Molina, 1972; and Lunt, 1959), although digested sludge

Table 3. Properties of Anaerobically Digested Waste-Activated Sewage Sludge from MSDGC West-Southwest Sewage Treatment Plant between August 19, 1971 and May 31, 1972

Element ^{1/}	Avg Concentration ^{2/}	Element ^{1/}	Avg Concentration ^{2/}
	% dry basis		% dry basis
Total N (221)	7.27	Cd (43)	0.034
NH ₄ -N (221)	3.26	Cl (78)	1.17
Total P (238)	2.46	Cr (42)	0.341
K (40)	0.44	Cu (43)	0.136
Ca (43)	2.02	Hg (46)	0.000038
Mg (43)	0.99	Na (43)	0.38
S (6)	0.65	Ni (43)	0.08
Zn (43)	0.39	Pb (39)	0.106
Fe (43)	4.56	Al (40)	1.04
Mn (43)	0.02		
pH (136)			7.4
Electrical conductivity (221)			5 mmho/cm
Total solids (281)			3.99%
Volatile solids (281)			57% of TS
Volatile acids as HAc (136)			247 mg/l
Hexane soluble (7)			12% dry basis
COD			5400 mg/l
BOD ₅			1140 mg/l
Particle size (14)			99% < 9
Particle size (14)			60% < 3
Neutralizing power (3)			27 meq H ⁺ /100g solids
Neutralizing power as CaCO ₃ (3)			2.76% dry basis
Alkalinity as CaCO ₃ (75)			10.69% dry basis
Carbon, inorganic (6)			19.3% dry basis
Cation exchange capacity (6)			74 meq/100g solids

^{1/}Number of analysis in parenthesis. Methods of analyses presented in text.

^{2/}Percent dry basis x 10 = kg/metric ton.

has some neutralizing power (Table 3). The alkalinity determination in Table 3 was done by a cold acid titration in which protein and NH₄OH added to the true value for alkalinity. The determination of neutralizing power after heating the sludge suggests that only

about one fourth of the reported alkalinity was due to carbonates, bicarbonates and hydroxides. However, the inorganic carbon (19.3%) as released by 2N HCl indicate the very slight solubility of the inorganic carbon compounds which exist in this sludge. Even with heat, titration with 0.01N HCl over a 24-hour period released only a small fraction of the inorganic carbon present. The colloidal nature of sludge solids is reflected in a cation exchange capacity of 74 meq/100g solids in a matrix which has 60% of the particles with less than 3 micron diameter. These exchangeable cations may be considered as available to plants.

The chemical complexity of liquid sewage sludge continues in the soil because of the high volatile-acids and -solids which exist in the fresh sludge. These biodegradable constituents, when applied on soil, are subject to a vigorous change in their rate of degradation. Thin applications of liquid sludge on the soil surface have not resulted in reductions in water infiltration if the sludge dried between application (Hinesly, et al. 1971). Organic carbon does accumulate in sludge-treated soils (Peterson, et al. 1971).

BIOLOGICAL QUALITIES

Well-stabilized sewage sludges are generally free of odors and pathogens. This stabilization may be accomplished by anaerobic digestion, by extended aeration, or extended lagooning of the sludge. Poorly digested (less than 30% reduction in volatile solids) or acidic sludge may produce odors. Well-stabilized sludge may safely be left on the soil surface without worry of odor or vermins. This is advantageous in that sludge can be used on a growing crop for its nutrient and water benefits. Braids et al. (1970) reported a 99% decrease of fecal coliform in 30 days of dessication on the soil surface. Burd (1966) reported 99.8% bacterial reduction after 30 days of mesophilic anaerobic digestion and further that pathogenic organisms die within 7 to 10 days of digestion. Krone (1968) reported the density of non-spore forming bacteria outside their hosts decreased exponentially with time. Deliberate contamination of tomato plants with feces, Salmonella cerro, and Shigella alkaescens indicated that these pathogens did not survive the dessication and the sun for more than 35 days (Rudolfs et al. 1951). Rudolfs also reported that Emdamoeba histolytica and Ascaris eggs died upon dessication.

The aerobic bacteria population was reduced by two to three logs when wet sludge (4.9% total solids) was dewatered on a vacuum filter with Fe₂SO₄ and lime (1:6) addition to yield a product with 65.3% total solids (Kampelmacher and Van Noorle Jansen, 1972). They reported a 2 to 4 log reduction in enterobacteriaceae with the drying of this same sludge.

Molina et al, (1972) observed bactericidal properties in the liquid phase of anaerobically digested sludge. Heat sterilization did not eliminate bactericidal properties; therefore, parasitic relationships, protein, antibiotics, or nutrient competition were ruled out as the toxic agent. Escherichia coli isolated from the sludge had a lower mortality rate than did E coli from stock culture.

Soil nitrification was found to be stimulated by moderate additions of sewage sludge (≤ 114 kg $\text{NH}_4\text{-N/ha}$ equivalent in sludge) while higher dosing rates (≥ 228 kg $\text{NH}_4\text{-N/ha}$ equivalent in sludge) resulted in a lag in nitrification and an increase in denitrification of up to 13% of the sludge N (Premi and Cornfield, 1969). King (1971) reported that 22 to 36% of the applied nitrogen in liquid sludge was lost with surface application. This was by NH_3 volatilization and apparent denitrification.

ACKNOWLEDGMENTS

The authors wish to thank all the personnel of the Research and Development Department of the Metropolitan Sanitary District of Greater Chicago for their assistance in collecting data for this manuscript, and the Metropolitan Sanitary District of Greater Chicago for permission to use unpublished data.

REFERENCES

- Adriano, D. C., P. E. Pratt and S. E. Bishop. 1971. Nitrate and salt in soil and groundwaters from land disposal of dairy manure. Soil Sci. Soc. Amer. Proc. 35, 759-762.
- Amer. Public Health Assoc. 1971. Standard methods for the examination of water and wastewater. 13th Edition, APHA, New York.
- Anderson, M. S. 1956. Comparative analyses of sewage sludge. Sew. and Industrial Wastes. 28, 132-135.
- Bundy, L. G. and J. M. Bremner. 1972. A simple titrimetric method for determination of inorganic carbon in soils. Soil Sci. Soc. Amer. Proc. 36, 273-275.
- Hinesly, T. D., O. C. Braids, and J. E. Molina. 1971. Agricultural benefits and environmental changes resulting from the use of digested sewage sludge on field crops. U.S. Environmental Protection Agency Reports SW-30d.
- Jenkins, S. H., and J. S. Cooper. 1964. The solubility of heavy metals present in digested sewage sludge. International Jour. Air Water Poll. 8, 695-703.
- Kampelmacher, E. H., and L. M. Van Noorle Jensen. 1972. Reduction of bacteria in sludge treatment, Jour. Water Poll. Control Fed. 44, 309-313.

- King, L. D. 1970. The effect of land disposal of liquid sewage sludge on growth and chemical composition of coastal bermuda-grass and rye and on soil properties, ammonia volatilization and nitrate leaching. Ph.D. thesis, Univ. of Georgia, Univ. Microfilm, Ann Arbor, Mich. (Dissertation Abstr. 72-10, 989).
- Lagerwerff, J. V. 1967. Heavy metal contamination of soil, p 343-359 in Agriculture and The Quality of Our Environment, Plimpton Press, Norwood, Mass.
- Lunt, H. A. 1959. Digested sewage sludge for soil improvement, Conn. Agric. Expt. Sta. Bull., 622.
- Malina, J. F. and J. DiFillippo. 1971. Treatment of supernatant and liquids associated with sludge treatment, Water and Sew. Works, 118, R30-R38.
- Martens, D. C. 1971. Availability of plant nutrients in fly ash, Compost Science, Nov-Dec, p 15-18.
- Molina, A. J. E., O. C. Braids, and T. D. Hinesly. 1972. Observations on bactericidal properties of digested sewage sludge, Environ. Sci. and Tech. 6, 448-450.
- Premi, P. R. and A. H. Cornfield. 1969. Incubation study of nitrification of digested sewage sludge added to soil, Soil Bio. and Biochem. 1, 1-4.
- Rudolfs, W., L. L. Falk, and R. A. Ragotzkie. 1951. Contamination of vegetables grown in polluted soil, Sew. and Industrial Wastes, 23, 253-268.
- Stanley, G. H. and G. R. Richardson. 1970. The automation of a single reagent method for total phosphorus, p 305-311 in Advances in Automated Analysis, vol. II, Industrial Analysis, Technician Instrument Corporation, Tarrytown, New York.

DISCUSSION

- Miller: I was interested in volatile acid content, isn't this unusually high for digested sewage sludge, 247 mg/l?
- Peterson: No, it's what we've been getting at the Chicago West-Southwest treatment plant.
- Miller: It seemed a little high.
- Peterson: It's a high rate digestion.
- Stevenson: Have you monitored the effect of this sludge application to the soil on the groundwater?
- Peterson: Yes, we have and there'll be other speakers who will cover this.
- Ludington: Both speakers have used terms like soluble and suspended, I was wondering if they could define what those terms are and how they were analyzed. Were conventional standard methods of procedure used or some other method?

Peterson: Standard methods of wastewater and water tailings were used.

Hunter: It depends on what results I've had with the method I'm dealing with, but in general the sizing I was dealing with there is sedimentation for an hour for settleable solids; supercolloidal being that which will not settle out but which can be removed say, by centrifugation at about 50,000 rpm, in a Sharples supercentrifuge or the equivalent of this. A couple of different authors have done this. Oil being the most variable one and here people have defined it by chemical traces, to name one, by extremely high speed centrifugation or by cellulose membrane filtration. The soluble is what goes through all of these.

THE SOIL AS A PHYSICAL FILTER

060H
Richard E. Thomas
Robert S. Kerr Water Research Center
Environmental Protection Agency

The word "soil" has many definitions, but it is generally accepted that the soil is the upper portion of the loose material covering the surface of the earth. As such the soil is a mixture of mineral particles, organic material, air, and water. The pore space occupied by air or water may be as much as 50 percent of the total volume, and the pathway of movement through these pores is a maze of varying sized channels. It is the size distribution and the nature of this maze which control the capability of the soil to filter out suspended solids that are found in treatment plant effluents or industrial wastewaters. In most soils, the pore size distribution and the nature of the water movement channels are such that suspended solids are completely removed after short travel distances in the soil. Man has devised several approaches to utilize this filtering capability of the soil for disposal or renovation of municipal effluents and industrial wastewaters. These approaches include septic tank-soil absorption systems, cropland irrigation systems, surface disposal systems, and groundwater recharge systems.

Each of these approaches that man has devised for utilizing the soil to receive wastewaters is dependent on maintaining a balance between the filtering capability of the soil and the rate of water movement through the soil--the objective being to filter out the suspended solids while maintaining the water movement at a relatively high rate. The following discussion will cover some of the research study results and practical operating experiences that have helped to identify factors which influence the balance between filtering capability and the rate of water movement.

Septic tank-soil absorption systems are the most widely used of the approaches devised by man for wastewater disposal to the soil, and there are about 15 million homes in the United States utilizing this approach. The basic concept of the approach is to provide sufficient subsurface filtering areas to achieve long-term service without maintenance. Failure to achieve the desired longevity and other problems with the millions of septic tank systems installed in the late 1940's and early 1950's stimulated a surge of research interest to determine what caused the failure of these soil systems.

Water movement through the soil is essential to successful use of septic tank systems, and much of the research effort has been

directed to studies on soil clogging. These research efforts have not identified the specific causal agents of soil clogging, but they have elucidated several factors which influence the rate and degree of clogging. The results of several research studies have shown that clogging occurs at or near the surface of the soil (Jones and Taylor, 1965; Thomas et al, 1966; and Winneberger et al, 1960). The depth of the zone of clogging may be somewhat greater for coarse textured soils, but for most practical applications the predominant zone of clogging is confined to a depth of less than one inch. The most troublesome clogging usually occurs when the soil surface becomes inundated and remains submerged for an extended period of time. This clogging occurs as an impervious mat which forms at the surface of the soil and from a practical point of view plugs the ends of the channels through which water moves. The actual clogging is a physical blocking of the soil pores, but it is apparent that formation of the surface mat is the combined effects of physical, chemical, and biochemical interactions in the soil (McGauhey and Krone, 1967). This surface clogging mat has two characteristics which are very important from the practical point of view. One is the fact that the mat is formed in conjunction with the development of anaerobic conditions during extended periods of submergence. The other is the fact that restoration of aerobic conditions and drying of the mat removes most of the soil clogging directly associated with the formation of the mat.

In summary, the research efforts directed to identifying the causes of soil clogging elucidated three important factors to consider in selecting management practices for applying wastewater to the land. These three factors are (1) the zone of clogging which reduces the water intake rate is at or near the soil surface; (2) the most severe clogging develops in an anaerobic environment; and (3) the severe clogging developed under anaerobic conditions can be removed by drying the clogged surface layer of soil. Further studies of these three factors under practical operating conditions have verified the results of the small scale research studies.

Looking at crop irrigation systems, we find that good operating practices preclude the development of anaerobic conditions leading to formation of the troublesome clogging mat. Physical clogging of the filter for the irrigation approach should be limited to deposition of small amounts of suspended mineral particles and slowly degradable organic particles. The effects of these additions appear to go unnoticed at locations where wastewater irrigation has been practiced for up to 80 years (Hutchins, 1939; Hyde, 1950; and Segel, 1950). Quantitative information on differences in soil properties after 14 years of wastewater irrigation versus a fresh water irrigation source led to the conclusion that wastewater irrigation did not result in adverse effects that could not

be corrected with minor changes in cultural practices (Day et al, 1972). The adverse differences in soil properties observed in this study were associated with chemical interactions rather than physical clogging by deposition.

The situation is entirely different when one considers spray disposal and groundwater recharge approaches where the desire for high rates of hydraulic loading frequently lead to moisture conditions which promote development of anaerobic conditions and the consequent severe clogging of the soil filter. This situation has been counteracted by developing a routine management practice of alternating wetting periods and drying periods to take advantage of the fact that drying of the clogged surface results in recovery of the capacity to move water. The periodicity of the wetting and drying cycle can vary from a few days to a few weeks (Amramy, 1965; Bouwer, 1970) depending on local conditions and the overall objectives of a given project. Much remains to be learned in this area for improvement of techniques but we can make practical use of current knowledge, and some recharge operations have been in operation for several decades.

This brief discussion of the soil as a physical filter has been directed to factors which lead to clogging of the filter and management practices which can be used to extend the life of the filter. These aspects of the behavior of the filter are closely related to the chemical, biological, and hydrogeological interactions which are covered in companion papers presented during the symposium. Reference to these companion papers will strengthen and broaden ones understanding of the function of the soil as a filter for receiving municipal effluents or industrial wastewaters.

REFERENCES

- Amramy, A. 1965. Waste treatment for groundwater recharge, Jour. Air Water Poll. 9, 605-619.
- Bouwer, H. 1970. Water quality aspects of intermittent systems using secondary sewage effluent, Artificial Groundwater Recharge Conference, University of Reading, England, Paper 8.
- Day, A. D., J. L. Stroehlein, and T. C. Tucker. 1972. Effects of treatment plant effluent on soil properties, Jour. Water Poll. Control Fed. 44(3), 372-375.
- Hutchins, W. A. 1939. Sewage irrigation as practiced in the western United States, U.S. Dept. of Agriculture, Washington, Technical Bull. No. 675, 60 p.
- Hyde, C. G. 1950. Sewage reclamation of Melbourne, Australia, Sew. and Industrial Wastes 22(8), 1013-1015.
- Jones, J. H., and G. S. Taylor. 1965. Septic tank effluent percolation through sands under laboratory conditions, Soil Sci. 99, 301-309.

- McGauhey, P. H., and R. B. Krone. 1967. Soil mantle as a wastewater treatment system - Final Report, School of Public Health, University of California, Berkeley, SERL Rept. No. 67-11.
- Segel, A. 1950. Sewage reclamation at Fresno, California, Sew. and Industrial Wastes 22(8), 1011-1012.
- Thomas, R. E., W. A. Schwartz, and T. W. Bendixen. 1966. Soil chemical changes and infiltration rate reduction under sewage spreading, Soil Sci. Soc. of Amer. Proc. 30(5), 641-646.
- Winneberger, J. H., L. Francis, S. A. Klein, and P. H. McGauhey. 1960. Biological aspects of failure of septic-tank percolation systems, (Final Report) School of Public Health, University of California, Berkeley.

DISCUSSION

- Solomon: I'd like to know what is going to happen to many of the streams in the area if we implement this type of a wastewater procedure. For many streams in industrial areas and municipal areas, the flow consists of between 50 to 75% wastewater. If we channel this wastewater into the soil, undoubtedly we will raise the soil water table, but what will happen to the dependable flows in the streams in the area?
- Kardos: Well, actually you're just delaying the return flow to the streams. It's going to go back into the stream eventually as base flow, in other words, all you're doing is delaying slightly the return to the stream. You can't pile up water indefinitely in the soil, it's got to go somewhere and eventually it ends up in the streams.
- Anderson: I have a comment or two and then a question. It seems to me that part of the clogging might be due to case hardening that you get because of the coagulation of some of the larger molecular weight fragments, proteins, etc. Do you find that you have any kinds of tests that would anticipate this so that you could alter your schedule of treatment accordingly?
- Thomas: Not that I am aware of, this is a pretty uncertain art, and so far the management technique has been developed on pretty gross values. It depends basically on the hydraulic acceptance as measured by some device on the site.
- Burge: Have you looked at the nature of that mat? Is it particulate material or is it composed mainly of micro-organisms?

Thomas:

Both. There isn't a whole lot of work being done on the mat itself. There are micro-biological cells present and it also looks like there are materials that were in the wastewater to start with so that I'd say, really it is both.

Rhindress:

Assuming a field has developed an impermeable layer at the surface by clogging, how long or what treatment would you take to regenerate that field? Can you just plow that mat under and resume spraying or must you let it restructure in the soil?

Thomas:

Where you're working with fairly coarse textured soils, if you have a mat like I was showing here you can recover a lot of the original conductivity by just stopping applications for a period of time. The resting period depends on the weather conditions but usually in the order of magnitude of a week up to 3 weeks. In the long run you may get clogging that you would have to go in and do physical manipulation, plowing or some kind of disturbance of the surface to restore the hydraulic conductivity.

Parizek:

I think you were showing mats developed in a flooding or infiltration lagoon type of experiment. Are you likely to get such mats with a spray irrigation system?

Thomas:

Yes, the mats that I showed were obtained under flooding conditions. However, you could get the first mats in an irrigation type approach, if you had restricted water movement. With the irrigation approach, if you have good site selection and you're working with a very well treated effluent, the clogging would be a very minimal problem.

Parizek:

Because we need to maintain infiltration and good drain characteristics, it seems like this plugging problem can be alleviated by just not going to this flooding condition.

Schulze:

You mentioned that anaerobic mats, the mat that is produced under anaerobic conditions can be a very fine layer and it usually has a black color and I assume that it consists of fine suspended solids. Now I recall that probably these conditions are always very conducive to the forming of ferrous sulphide. Usually there is some iron available under anaerobic conditions and you can have hydrogen sulphide formation and so ferrous sulphide could also very well be formed and be the plugging agent. Are there any analytical data supporting this kind of idea?

- Thomas: Ferrous sulphide is there. This is the agent that causes most of the black color. My colleagues and I had heated arguments many times as to whether ferrous sulphide contributed to the clogging or whether it was just there because of the anaerobic conditions and is not one of the primary causes of clogging. We do have some data published on this. I have a publication in the Soil Science Society Proceedings.
- Schulze: And what is the result now?
- Thomas: The ferrous sulphide is there because of the anaerobic conditions but it is not one of the primary causes of the clogging.
- Schulze: If ferrous sulfide is not. Well, what is it then?
- Thomas: It's an organic matter mat of suspended material and biological cells. That's about as close as we came to really identifying it.
- Hart: Have you any feeling for what the effect on the soil would be if this is actually mixed within the soil rather than placed on the surface and allowed to form there as far as the transmissibility characteristics that would result?
- Thomas: I'm not sure I understand what you mean.
- Hart: Well, you're talking about putting the material directly on the soil surface, now what if we mix it with the soil?
- Thomas: You're talking about mixing a liquid or a solid like a sludge or something like this with the soil? I haven't any experience in this area at all. The area I've worked in is where we were working with the liquid waste and applying them at the surface.
- Walker, John: Following up a comment that was made earlier, can you only irrigate pretty clean effluent and do you have to go to a flooding system to put down more dirty effluent? Is there a criterion on that or is this a point of argument?
- Thomas: I would say it's a point of argument, but from the standpoint of the soil as a physical filter the dirtier the effluent or the more solids that it carries will limit the hydraulic load that you can put on and keep the system going for a long period of time. You can use a high quality effluent and go to the infiltration approach if it's advantageous for your area. In certain climatic regions you can manage to

go as high as 300 ft. per year, using the soil as a treatment media. This is opposed to the irrigation approach where you may go in the range of a few feet up to as much as 6 or 7 ft. a year.

Kotyk:

I'm wondering if you were able to determine the distribution of water? Such as infiltration into the soil and evaporation and evapotranspiration. Were you able to determine this at all?

Thomas:

We did it on one type of system, which we haven't even talked about and I guess we won't during this meeting, that's the spray run off system on a heavy soil. The particular system that we studied was located in northeast Texas, with an annual rainfall of about 45 inches, and a potential evaporation something slightly more than that. In this particular case, the distribution was about 20% percolating down through the soil, about 20% loss by evaporation and about 60% coming as a direct runoff to the surface stream. Now this balance will be directly dependent on the geographical location and the type of system that you are designing or using.

Kotyk:

Are there many systems where evaporation is the prime mode of disposal of water?

Thomas:

I would say in general that with the irrigation systems in the south-western United States the amount of the water that is lost through evaporation is pretty substantial.

Vhora:

What depth of water did you put on the surface and what was the depth of the filter. I mean physical soil filter?

Thomas:

These details will be covered in a later paper by Dr. Bouwer.

Tarquin:

Given that you need a drying period if you want to dispose of one inch of water, do you have any idea whether it would be better to put it on in one minute and dry it for 24 hours or put it on in 3 hours and dry for 21 or put it on for 12 and dry for 12?

Thomas:

There's no general set rule on this. It depends on the strength of the waste and the soil and the site. Generally we would recommend at least several hours for application time. At the state of the art where we are now you'd have to do a feasibility study concerning the best management.

THE SOIL AS A CHEMICAL FILTER

Boyd G. Ellis
Department of Crop and Soil Sciences
Michigan State University

061H

The soil has many times been referred to as "the living filter." But it serves as a chemical filter as well through the many organic and inorganic chemical reactions which occur when wastewater passes through the soil profile. In addition, the soil may chemically alter many of the materials which have been introduced into the profile by the addition of either wastewater or sludge. These alterations may lessen the environmental impact (for example, through conversion of organic materials to carbon dioxide thereby reducing the biological oxygen demand carried in the water) or may increase the environmental hazard (for example, through the conversion of organic nitrogen to nitrate, a much more hazardous material). Therefore, it is imperative that the soil chemistry be thoroughly understood and the various reactions used to optimize the "system" when applying waste to land so that environmental hazards will be at an absolute minimum.

In addition to purification of the wastewater passing through the soil profile, the accumulation of ions or compounds in the soil must not leave a residue which is harmful to either plant growth or to the animal or human consuming the crop. Our soil is a very precious resource. It must not be sacrificed in an effort to clean up our water resources.

The areas of soil chemistry which are of most importance for the soil to act as a chemical filter are: (1) ion exchange, (2) adsorption and precipitation, and (3) chemical alteration. The following discussion will include the theory of each process and the importance of each process to waste disposal systems.

ION EXCHANGE

The process that we now refer to as "ion exchange" was discovered in England in 1852 by a Yorkshire farmer, Thomas Way, when he found that the addition of soil to manure reduced the loss of ammonia (Tisdale and Nelson, 1956). Thus, the science of using the ion exchange properties of the soil for improving the environment had an early beginning. We now define ion exchange as the reversible process by which cations and anions are exchanged between solid and liquid phases and between solid phases if in close contact with each other (Wiklander, 1964). It is more common

to differentiate between cation and anion exchange since cation exchange is the dominant process in soils.

Several forms of chemical bonding may occur between ions and the solid phase of the soil during the process of ion exchange. They range from electrostatic to covalent in nature. When the bonding between ions and the solid phase is largely covalent in nature, the binding is generally more specific for the ion involved and not reversible to other ions of similar charge. Consequently, this type of binding is not truly exchangeable and will be covered as an adsorption reaction. Generally, the ion exchange reactions that we will consider here will be electrostatic and influenced by the valence and hydration of the ion involved and the location and density of the charge on the solid component of the soil.

The charge on the solid phase of the soil system may arise from several sources. First, isomorphous substitution occurs in many of the layer silicate minerals. Substitutions of aluminum for silicon or one of several divalent ions (Fe^{++} and Mg^{++} , for example) for aluminum will give rise to a negative charge site in the mineral. The strength of charge will also depend upon the location; i.e. if isomorphous substitution occurs in the tetrahedral layer, the attraction to exchangeable ions will be stronger than if the substitution occurs in the octahedral layer. For a more complete discussion of clay mineral structure, the reader is referred to Clay Mineralogy by Grim (1953) or The X-ray Identification and Crystal Structures of Clay Minerals edited by Brown (1961). Secondly, SiOH and AlOH groups from exposed surfaces (generally edges) of clay minerals and hydroxides of iron, aluminum and magnesium either as coatings or gels are capable of yielding exchange sites upon dissociation. Thirdly, soil organic matter constituents were very early recognized as having a high cation exchange capacity (McGeorge, 1930; Mitchell, 1932). Organic exchange sites develop from dissociation of acidic functional groups, of which carboxyl is quantitatively most important. In addition, a broad spectrum of acidic hydroxyls (phenolic, enolic) and tautomeric pseudo-acids involving nitrogen in appropriate structural configurations is likely involved (Broadbent and Bradford, 1952; Stevenson and Butler, 1969).

A portion of the cation exchange sites is known to vary with pH. Normally the SiOH groups will give rise to negative sites; but AlOH and FeOH can yield positive sites at low pH values (Freid and Broeshart, 1967). Thus, the decrease in net negative charge below pH 6.0 may not be an actual decrease of the negative charge but an increase in the positive charge (Wiklander, 1964). All sites originating from organic materials are expected to be pH dependent. The pK value of carboxyl groups is such that complete dissociation is expected by pH 7.0. Most other organic acidic groups would require higher pH values for complete dissociation.

Soil clays containing pedogenically chloritized 2:1 layer silicates were shown to develop a proportionately large increment of cation exchange capacity after brief contact with 2% sodium carbonate (pH 11) according to de Villiers and Jackson (1967a, 1967b). They suggested that the mechanism accounting for the pH dependent, hysteretic cation exchange charge of the mineral portion of many soils was deprotonation of the positive hydroxy alumina in aluminated soils, clays and allophane.

The ions adsorbed by exchange sites may form a diffuse double layer where the concentration of the ions will decrease exponentially with the distance from the clay surface. Fried and Broeshart (1967) state that it is unlikely that the adsorption of anions to soil constituents will have the nature of a double layer. Although solutions for cation distribution with distance from the clay surface may be obtained by combination of Boltzman's law with Poisson's equation, the complex nature of the cation exchange system in natural soils makes this solution little more than a rough approximation. The thickness of the double layer for a given soil will be a function of valence of the exchangeable cation and total ionic strength of the solution. In addition, Shainberg and Kemper (1966) have shown that the hydration status of the exchangeable cation also affects the double layer.

Giesekeing and Jenny (1936) showed experimentally that soil clays attract individual cations with different binding strengths. In general, the greater the valence the more strongly the cation was bound. But, in addition, rather large differences were found within cations of the same valence. For example, potassium was bound much more strongly than sodium. They also found considerable hysteresis (reported earlier by Vanselow, 1932) particularly in reactions involving monovalent-divalent exchange. Several methods of accounting for unequal bonding energies have evolved and are adequately summarized by Marshall (1964).

By far, the most studied exchange reaction has been that of sodium for calcium. This reaction has been particularly important in irrigation of soils because of the unfavorable soil structure which will develop if the cation exchange complex becomes sufficiently saturated with sodium so that dispersion of the soil occurs. Sodium-adsorption ratios $SAR = Na^+ (Ca^{++} + Mg^{++}) / 2$ have been used for a long time to evaluate the possible hazards of irrigation water (Richards, 1954). Anions which may precipitate either calcium or magnesium will also influence the sodium-adsorption ratios. Eaton (1950) introduced terms to correct the soluble-sodium percentage in soils for the precipitation of calcium and magnesium by carbonate and bicarbonate. Longenecker (1960) reported that sulfate reacted differently than either nitrate or chloride in soil systems. Thus, sodium sulfate salts replaced appreciably more magnesium than did the sodium salt of either nitrate or chloride.

These observations have been confirmed by later work (Pratt, Branson and Chapman, 1960; Babcock and Schulz, 1963; Bower and Wilcox, 1965; Bower, et al., 1965; Arshad and Carson, 1967; Rao, Page and Coleman, 1968; Bower, Ogata and Tucker, 1968; and Pratt and Bair, 1969). It is, therefore, necessary to consider both the anions and cations involved in cation exchange reactions for accurate evaluations.

Ideally, equations could be developed which would predict accurately the exchange which would occur when a given set of parameters is involved through the addition of wastewater. The first attempt was made by Kerr (1928) who introduced equations based on the law of mass action. A summary of this and other equations which have been developed since then is given in Table 1 (adapted from Fried and Broeshart, 1967). Generally speaking, no one equation has been successful if applied to widely varying conditions. All have been found to vary with soil series and most vary appreciably with the particular ion pair involved in the exchange. But, nevertheless, they do serve an important function since the particular K may be experimentally determined in the laboratory for a given region and set of parameters. This concept has been very successfully applied to predicting the effects of applying irrigation waters to soils.

Effect of Wastewater Applications on Exchangeable Cations in Soils

For the purposes of illustration, an example will be considered for two effluents with the following composition: (1) Na = 152 ppm, Ca = 36 ppm, and Mg = 16 ppm; (2) Na = 47 ppm, Ca = 33 ppm, and Mg = 19 ppm. It will also be assumed that they will be applied to a Conover loam soil. Initially, a Michigan Conover loam contained 15.8 me Ca/100 g, 2.1 me Mg/100 g and 0.14 me Na/100 g. The SAR for effluent number 1 is 5.3 and for effluent number 2 it is 1.62. Using the USDA salinity handbook, the estimated equilibrium exchangeable-sodium percentage would be 6.0 and 1.0, respectively. Thus, after prolonged irrigation with effluent number 1, this Conover soil would be expected to increase in exchangeable sodium percentage from 0.8 to 6% or from 0.14 me Na/100 g to 1.08. With effluent number 2 it would increase from 0.8 to 1% or from 0.14 to 0.18 me Na/100 g. As previously pointed out, the exact exchange constants would have to be determined for the soil and effluent under consideration to yield precise values. But it would appear that normal effluents would not lead to excessive levels of exchangeable sodium in most soils.

Generally, exchangeable sodium percentages greater than 15% would be considered very serious. Even lower values may seriously impede infiltration rates and percolation rates of water particularly in fine textured soils. It is calculated that effluent number 1 above could not tolerate more than 430 ppm sodium, and effluent

Table 1. Summary of Ion Exchange Equations Used in Soil Science Laboratories (from Fried and Broeshart, 1967)

Common Name	Equation	Reference
Donnan	$\frac{\frac{A^+ \text{ Soil}}{C^{++} \text{ Soil}}}{\frac{C^{++}}{A^+}} = 1$	Vageler and Woltersdorf (1930)
Mass action	$\frac{\frac{A^+ \text{ Soil}}{C^{++} \text{ Soil}}}{\frac{C^{++}}{A^+}} = K$	Kerr (1928)
Gapon-Schofield-Eriksson-Bolt	$\frac{\frac{A^+ \text{ Soil}}{C^{++} \text{ Soil}}}{\frac{C^{++}}{A^+}} = K_1$	Gapon (1933); Eriksson (1952); Schofield (1947); Bolt and Peech (1953)
Langmuir	$\frac{\frac{A^+ \text{ Soil}}{2C^{++} \text{ Soil}}}{\frac{C^{++}}{A^+}} = b_1/b_{-2} = K_4$	Boyd et al. (1947)
Vanselow	$\frac{\frac{A^+ \text{ Soil}}{C^{++} \text{ Soil} (C^{++} \text{ soil} + A^+ \text{ soil})}}{\frac{C^{++}}{A^+}} = K_2$	Vanselow (1932); Krishnamoorthy and Overstreet (1950)
Statistical	$\frac{\frac{A^+ \text{ Soil}}{C^{++} \text{ Soil} (1 - \frac{1}{2} C^{++} \text{ soil} + A^+ \text{ soil})}}{\frac{C^{++}}{A^+}} = K_2$	Krishnamoorthy et al. (1948); Krishnamoorthy and Overstreet (1950)

number 2 more than 390 ppm sodium before the soil structure would degrade to the point of restricting water movement. Although considerably higher than normally found in effluents, these values could easily be attained under certain circumstances.

The effect of SAR and clay content of soils on hydraulic conductivity is shown by data from McNeal and Coleman (1966) and McNeal et al. (1968). At salt concentrations of 12.5 me/l and lower, the relative soil hydraulic conductivity dropped to near zero for all soils having clay contents greater than 25% if the SAR was greater than 50. Sandy soils with less than 5% clay showed only about 25% reduction in hydraulic conductivity even at these extreme sodium contents. Although less drastic in the effect on soil structure than sodium, other monovalent ions such as potassium or lithium will also lead to reduced infiltration rates and hydraulic conductivities.

Although they did not report SAR values or exchangeable sodium, data by Day, Stroehlein and Tucker (1972) do show the effects of irrigation with wastewater on infiltration rate. After 14 years of irrigation with wastewater at a rate recommended by agriculturalists for crop production, the infiltration rate for the areas irrigated with wastewater was 1.52 cm/hr compared with 1.91 for other areas irrigated with well water and fertilized with inorganic fertilizers. The soluble salt was $1.77 \text{ mmhos/cm} \times 10^3$ compared with 0.88 for the comparable treatments suggesting that this reduced infiltration rate was the result of accumulation of soluble salts, presumably sodium. Their data for the sodium, calcium and magnesium contents of sewage effluent were used previously for my example calculation number one of SAR values from effluents which indicated that only 6% exchangeable sodium should result from use of this effluent. But even this amount was sufficient to significantly reduce the infiltration rate. Secondly, it must be remembered that they applied the wastewater at a rate recommended for crop irrigation and not the maximum quantity that could be applied to soils. This reduction in infiltration rate could be attained much more quickly if higher application rates are used.

ADSORPTION AND PRECIPITATION REACTIONS

Adsorption

Although theoretically adsorption and precipitation reactions differ, they have sufficient similarities to merit their consideration under the same general topic. Adsorption is defined as the adhesion, in an extremely thin layer, of gas molecules, dissolved substances or liquids to the surface of solids with which they are in contact. Precipitation is a term used to denote a rapid crystallization of a product of chemical reaction which is only slightly soluble in the medium in which it is formed. Adsorption differs from precipitation in that one component of the chemical reaction which is only slightly soluble in the medium in

which it is formed. Adsorption differs from precipitation in that one component of the chemical reaction is already a solid. Although adsorption of gases may be an asset in spreading wastewater onto soils since the soil will eliminate many odors by this mechanism, the remaining discussion will be restricted to adsorption of ions and/or molecules from solution onto solids and the precipitation of certain chemicals in the soil. The ions of particular interest will be phosphorus, boron, sulfate and certain of the heavy metals. This does not imply that other ions or compounds may not be removed from wastewater by a similar mechanism.

Two commonly used adsorption isotherms to quantitatively describe adsorption of ions from solution onto solids are the Freundlich isotherm ($x/m = kC^{1/n}$; where x/m = the quantity of ions adsorbed per unit weight of adsorber, C = the equilibrium concentration of the adsorbate after adsorption has occurred, k = a constant, and n = a constant) and the Langmuir adsorption isotherm $\frac{(M)}{x/m} = \frac{1}{Kb} + \frac{(M)}{b}$ where M = the activity of the ion in

moles per liter, x/m = meq of ion M adsorbed per 100 g of adsorber, K = a constant related to bonding energy, and b = the maximum amount of ion M in meq/100 g that will be adsorbed by a given adsorber. There have been many reports concerning the applicability of both isotherms to adsorption in soils. These are summarized by Ellis and Knezek (1972).

Using the Langmuir adsorption isotherm in studying the soil's ability to adsorb ions from wastewater has several distinct advantages. First, from laboratory measurements that are easily made an adsorption maximum can be predicted. When both the adsorption maximum and K are determined, predictions can be made of the quantity of the particular ion that will be adsorbed for any input level. One disadvantage of the use of adsorption isotherms is that they give little information concerning the mechanisms of adsorption of the ions being studied.

Considerable attention has been given to the necessity to introduce some corrections into experimental data from adsorption isotherms (See Fried and Broeshart, 1967, for a summary). If appreciable quantities of the ion under study are already adsorbed on the surface, this will cause an underestimation of x/m which leads to underestimation of both the adsorption maximum and the constant K . The amount initially adsorbed on the surface has been shown to be accurately estimated by radioisotopic exchange techniques; thus, a separate determination of the already surface adsorbed ion can be made and added to the quantity of x/m determined for the adsorption isotherm. The fact that the correction has made relatively small differences in many instances (i.e. less than 10% correction in the adsorption maximum for the data of Olsen and Watanabe, 1957) has led many researchers to the use

of uncorrected data. This should only be done if it is known that the correction is small. Otherwise, serious errors will occur especially in the low range of the adsorption isotherm.

The determination of the adsorption of an anion should contain a correction for negative adsorption (anion repulsion). A discussion of this correction is given by de Hann and Bolt (1963). In general, it has been ignored in determining adsorption isotherms but this may lead to serious errors.

Phosphate Adsorption

The Langmuir adsorption isotherm has been applied to phosphorus adsorption in soils by Fried and Shapiro (1956), Olsen and Watanabe (1957), and Ellis and Erickson (1969). Values determined for adsorption maxima were generally similar. The data given in Table 2 were extracted from the report by Ellis and Erickson as examples of the effect of soil series and horizon on the constants from the Langmuir adsorption isotherm. Since the maximum quantity of adsorption would not be reached except for very high levels of phosphorus in solution, the percentage of the adsorption maximum that will be saturated at 10 ppm phosphorus in solution was calculated and the total pounds of phosphorus that could be adsorbed per acre foot for each horizon were calculated assuming that the bulk density of A horizons would be 1.33 g/cm^3 and that of B and C horizons would be 1.5 g/cm^3 . The minimum adsorption was found in the dune sand which would adsorb only 77 pounds of phosphorus per acre foot and the maximum was for the Warsaw loam which would adsorb on the average over 900 pounds of phosphorus per acre foot. The effect of horizon is very great and is perhaps best illustrated by the data for the Rubicon sand. The A horizons adsorb a little more than 100 pounds phosphorus per acre foot. But the B horizon will adsorb more than 700 pounds of phosphorus per acre foot. The C horizon is intermediate. This correlated well with the quantity of iron in the profile in that iron has moved from the A horizon to the B horizon during the soil development making the B horizon the zone of iron accumulation. This increased iron content then accounts for the increased phosphorus adsorption by the B horizon. The high values for adsorption of the Warsaw loam are apparently accounted for by a high aluminum content of this particular soil.

It is of particular interest to note that the adsorption capacity of a soil may be recovered once saturated. Ellis and Erickson (1969) found that most soils recovered in about three months once they were saturated. The number of times this saturation and recovery cycle can be completed in a soil is unknown. However, Blanchar and Kao (1972) reported that the adsorption capacity of a Mexico soil changed little after 82 years of phosphate

Table 2. Phosphorus Adsorption by Soils as Predicted by Langmuir Adsorption Isotherms (Data from Ellis and Erickson, 1969).

Soil Series	Texture	Horizon	K	Adsorption Maximum	Adsorption at 10 ppm P % of Maximum	Adsorption at 10 ppm P Amount
			$K \times 10^{-4}$	g P/100 g	%	lbs/acre-ft
Dune Sand	Sand	--	4.5	1.89	94	77
Rubicon	Sand	A ₁	.77	4.23	71	108
	Sand	A ₂	1.98	3.87	86	120
	Sand	B	3.99	19.27	93	731
	Sand	C	5.78	10.75	95	416
Warsaw	Loam	A ₁	2.96	18.5	90	602
	Loam	B ₁	3.73	40.6	92	1,523
	Clay Loam	B ₂₁	5.83	49.0	95	1,898
	Clay Loam	B ₂₂	5.20	22.4	94	858
	Gravelly Clay Loam	B ₂₃	5.92	11.0	95	426
	Sand and Gravel	D	5.45	4.6	95	178

fertilization on the Sanborn field at Columbia, Missouri.

Shapiro and Fried (1959) derived an equation describing phosphate adsorption as primarily a mass action equation by assuming that phosphate adsorption was primarily an exchange with another ion such as hydroxyl. Their data indicated that their equation was valid but that two distinct regions of adsorption occurred, one corresponding to low levels of phosphorus (i.e. less than 1 ppm P in solution) and the other describing adsorption at much higher levels. Their equation is:
$$P(\text{solid}) = K_p P(\text{solid}) / p + P(\text{solid})_{\text{max.}}$$

This equation reduces to the Langmuir adsorption equation if the following identities are made: $P(\text{solid}) = x/m$; $K_p = 1/K_{\text{Langmuir}}$; $p = (M)$; and $P(\text{solid})_{\text{max.}} = b$.

Sulfate Adsorption

The adsorption of sulfate by soils is of less interest in applying wastewaters so it will be only briefly reviewed here. Chao, Harward and Fang (1962 and 1963) reported that sulfate adsorption by soils could be described by the Freundlich isotherm. The sulfate retained was in kinetic equilibrium with sulfate in solution. Several factors affected the adsorption including the cation accompanying the sulfate and the cation that was the exchangeable cation. As neutrality was approached, sulfate adsorption decreased considerably regardless of the type of saturating cation. Bornemisza and Llanos (1967) reported that the presence of phosphates enhanced slightly the movement of sulfate. They found no adsorption maxima even at high applications of sulfate. Aylmore, Karim and Quirk (1967) found that sulfate adsorption conformed to a Langmuir-type equation but that more than one region of adsorption existed. Barrow (1967) also found that sulfate adsorption did not always fit a Langmuir isotherm. Hasan, Fox and Boyd (1970) found adsorption maxima for several surface soils developed from volcanic ash varied from 80 to 1,500 mg S/1000 g soil. Barrow (1970) reported that the ratio of sulfate:phosphate adsorbed by soils increased 3-fold as the soil pH decreased from 6 to 4. It would be concluded from this that sulfate adsorption would not be at its maximum at the pH of most wastewater.

Boron Adsorption

The adsorption of boron by soils has been recently reviewed by Ellis and Knezek (1972). Boron adsorption has been described by the Langmuir adsorption equation (Biggar and Fireman, 1960; Hingston, 1964; Hatcher and Bower, 1958). But the Langmuir adsorption equation appears to be valid only over certain limited concentrations. A development of particular interest to applica-

tion of wastewater was made when several researchers (Thomas, 1944; Hiester and Vermeulen, 1952; and Vermeulen and Hiester, 1954) developed equations describing adsorption and desorption of boron during the flow of solutions through columns of exchangers where the adsorption equilibrium can be expressed by Langmuir's adsorption equation. Application of these equations to predict boron removal from soils by leaching was made by Hatcher and Bower (1958). It has been reported by Rhoades, Ingvalson, and Hatcher (1970a) that the Langmuir desorption theory underestimated the quantity of leaching required to elute toxic levels of soluble boron from soils. But, on the other hand, Tanji (1970) found good agreement and found that the chromatographic equations together with the Langmuir isotherm were adequate.

Soil chemically filter boron from solution by four mechanisms. First, iron and aluminum hydroxy compounds present in soils as coatings on or associated with clay minerals adsorb boron (Hatcher, Bower, and Clark, 1967; Sims and Bingham, 1968a,b). Secondly, iron or aluminum oxides will adsorb large quantities of boron (Scharrer, Kühn, and Lüttmer, 1956). Third, clay minerals, and particularly micaceous-type clay minerals, will absorb boron into their lattice (Couch and Grim, 1968; Fleet, 1965; and Sims and Bingham, 1967). This absorption is suggested to begin with chemical adsorption of $B(OH)_4^-$ at the tetrahedral portion of the edge of an illite flake. The anion gains stability by forming a weak ionic bond with the net positive charge expected at the mineral's edge. The second step is solid diffusion of boron into the interior of the crystal through crystal defects. Finally, magnesium-hydroxy clusters or coatings that exist on the weathering surfaces of ferromagnesium minerals have recently been shown to adsorb boron by bonding through the hydroxyl groups paralleling the bonding by iron and aluminum hydroxides (Rhoades, Ingvalson, and Hatcher, 1970b).


Heavy Metal Adsorption

The adsorption of zinc, copper, iron and manganese by soils was reviewed by Ellis and Knezek (1972). In addition, many other heavy metals, for example, nickel, chromium, cadmium, lead, mercury and cobalt, may enter into wastewater as a discharge from industry. The effects of these heavy metals are largely unknown. For those metals studied, a small fraction of the metal added appears to be bound very tightly to specific sites in the soils. These reactions for cobalt have been reported by Hodgson (1960); Hodgson and Tiller (1961); Hodgson, Geering and Fellows (1964); and Hodgson, Tiller and Fellows (1960). Zinc adsorption has been shown to be related to silicic acid by Tiller (1967). Sharpless, Wallihan and Peterson (1969) found that large quantities of zinc were rapidly adsorbed as an exchangeable cation. This

was followed by a slow conversion to a non-exchangeable acid soluble form of zinc but the rate of conversion varied greatly from soil to soil. Zinc adsorption was described by the Langmuir adsorption equation by Udo, Bohn, and Tucker (1970). At moderately high levels to zinc they found that zinc was precipitated as zinc hydroxide, a subject to be discussed later in this paper. Although it was shown that adsorption of zinc was described by a Langmuir adsorption isotherm, insufficient data are now present to warrant the conclusion that the Langmuir isotherm can be used to describe adsorption of heavy metals by a wide range of soils.

Precipitation Reactions in Soils

Many of the ion species introduced in wastewater may combine with other ions in the soil solution to produce an insoluble product. If a stable, solid phase is formed, the levels of ions left in solution may be described by a solubility product. Consider the following general reaction:



If the law of mass action is obeyed, the rate of the forward and reverse reactions will be given by:

$$\text{Rate forward} = k_f(A)^a(B)^b \dots\dots \text{and}$$

$$\text{Rate reverse} = k_r(L)^1(M)^m \dots\dots$$

The activities of each component in equations above are given by (A), (B), (L), and (M). The rate of the forward and the reverse reaction must be equal at equilibrium; therefore:

$$k_f(A)^a(B)^b \dots\dots = k_r(L)^1(M)^m \dots\dots$$

The equilibrium constant is then given by:

$$K_{eq} = k_f/k_r = \frac{(L)^1(M)^m}{(A)^a(B)^b}$$

For the specific case of the solubility product, the activity of the solid phase is assumed to be one (or not to change) and the equation reduced to:

$$K_{so} = (L)^1(M)^m \dots\dots$$

Solubility products have been applied to studies of soil phosphorus in many different ways. Schofield (1955) and Aslyng (1954) have suggested that soil phosphorus could be characterized by the use of "lime phosphate potentials" or the chemical potential

of monocalcium phosphate. Utilizing this principle, a plot of $1/2pCa + pH_2PO_4$ as determined in a 0.01 N $CaCl_2$ solution against $pH - 1/2pCa$ should define the values of phosphorus in solution for any soil. These potentials have been measured and reported by many investigators (Henze, 1963; Ulrich, 1961; Mattingly et al., 1963; Gough and Beaton, 1963; Scheffer and Ulrich, 1960; and White and Beckett, 1964). It can be easily shown that the lime-phosphate potentials are really a rearrangement of solubility products.

Lindsay and Moreno (1960) prepared a solubility phase diagram relating pH and pH_2PO_4 to the solubility of the common phosphate minerals found in soils. While their diagram does show the points of maximum H_2PO_4 in solution under the conditions of their assumptions and point out vividly the effects of soil pH on phosphate solubility, it is also quite similar to the lime-phosphate potentials since both originate from the same solubility products.

In acid soils, points for phosphate potentials many times do not fall on solubility lines for calcium phosphates. Clark and Peech (1955) suggested the use of aluminum phosphate solubility diagrams (or iron phosphate) for acid soils and show that experimental data fit these rather well.

Many of the heavy metals have quite insoluble hydroxides. It would be expected that heavy applications of these metals would result in saturation of adsorption sites and rapidly lead to precipitation. Table 3 gives solubility products from some of the compounds which might be expected to form in soils. Even though these hydroxides are very insoluble, other even more insoluble compounds may exist in soils. For example, zinc hydroxide would give 3.2 ppm zinc in solution at a pH of 8.0. But Lindsay and Norvell (1969) reported that less than 0.01 ppb Zn was actually found. The form of zinc that is controlling this low solubility is not known (Norvell and Lindsay, 1970).

CHEMICAL ALTERATION OF WASTE

The soil not only chemically filters but chemically alters components of wastewater and sludge which it contacts. Thus, to effectively understand the chemical filtration which will occur, one must also consider the changes in chemical compounds which will occur.

Wastewater and sludge materials contain many organic compounds. These organic compounds may be adsorbed by clay materials in the soil which will retard their microbiological breakdown. The nature of clay-organic complexes and reactions has been reviewed by

Table 3. Solubility Product Constants for Selected Compounds.

Chemical Formula	Solubility Expression	Solubility Product Constant
CdCO_3	$\text{CdCO}_3 = \text{Cd}^{++} + \text{CO}_3^{--}$	5.2×10^{-12}
CaCO_3	$\text{CaCO}_3 = \text{Ca}^{++} + \text{CO}_3^{--}$	6.9×10^{-5}
CoCO_3	$\text{CoCO}_3 = \text{Co}^{++} + \text{CO}_3^{--}$	8×10^{-13}
CuCO_3	$\text{CuCO}_3 = \text{Cu}^{++} + \text{CO}_3^{--}$	2.5×10^{-10}
PbCO_3	$\text{PbCO}_3 = \text{Pb}^{++} + \text{CO}_3^{--}$	1.5×10^{-13}
Hg_2Cl_2	$\text{Hg}_2\text{Cl}_2 = \text{Hg}_2^{+} + 2\text{Cl}^{-}$	1.1×10^{-14}
$\text{Al}(\text{OH})_3$	$\text{Al}(\text{OH})_3 = \text{Al}^{+++} + 3\text{OH}^{-}$	5×10^{-33}
$\text{Cd}(\text{OH})_2$	$\text{Cd}(\text{OH})_2 = \text{Cd}^{++} + 2\text{OH}^{-}$	2.0×10^{-14}
$\text{Cr}(\text{OH})_3$	$\text{Cr}(\text{OH})_3 = \text{Cr}^{+++} + 3\text{OH}^{-}$	7×10^{-31}
$\text{Co}(\text{OH})_2$	$\text{Co}(\text{OH})_2 = \text{Co}^{++} + 2\text{OH}^{-}$	2.5×10^{-16}
$\text{Cu}(\text{OH})_2$	$\text{Cu}(\text{OH})_2 = \text{Cu}^{++} + 2\text{OH}^{-}$	1.6×10^{-19}
$\text{Fe}(\text{OH})_3$	$\text{Fe}(\text{OH})_3 = \text{Fe}^{+++} + 3\text{OH}^{-}$	6×10^{-35}
$\text{Fe}(\text{OH})_2$	$\text{Fe}(\text{OH})_2 = \text{Fe}^{++} + 2\text{OH}^{-}$	2×10^{-15}
$\text{Pb}(\text{OH})_2$	$\text{Pb}(\text{OH})_2 = \text{Pb}^{++} + 2\text{OH}^{-}$	4×10^{-15}
$\text{Mg}(\text{OH})_2$	$\text{Mg}(\text{OH})_2 = \text{Mg}^{++} + 2\text{OH}^{-}$	8.9×10^{-12}
$\text{Hg}(\text{OH})_2$	$\text{Hg}(\text{OH})_2 = \text{Hg}^{++} + 2\text{OH}^{-}$	3×10^{-26}
$\text{Ni}(\text{OH})_2$	$\text{Ni}(\text{OH})_2 = \text{Ni}^{++} + 2\text{OH}^{-}$	1.6×10^{-16}
$\text{Mn}(\text{OH})_2$	$\text{Mn}(\text{OH})_2 = \text{Mn}^{++} + 2\text{OH}^{-}$	2×10^{-13}
$\text{Zn}(\text{OH})_2$	$\text{Zn}(\text{OH})_2 = \text{Zn}^{++} + 2\text{OH}^{-}$	5×10^{-17}
CaSO_4	$\text{CaSO}_4 = \text{Ca}^{++} + \text{SO}_4^{--}$	2.4×10^{-6}
CdS	$\text{CdS} = \text{Cd}^{++} + \text{S}^{--}$	6×10^{-27}
CoS	$\text{CoS} = \text{Co}^{++} + \text{S}^{--}$	5×10^{-22}
CuS	$\text{CuS} = \text{Cu}^{++} + \text{S}^{--}$	4×10^{-36}
PbS	$\text{PbS} = \text{Pb}^{++} + \text{S}^{--}$	4×10^{-26}
MnS	$\text{MnS} = \text{Mn}^{++} + \text{S}^{--}$	8×10^{-14}
HgS	$\text{HgS} = \text{Hg}^{++} + \text{S}^{--}$	1×10^{-60}
NiS	$\text{NiS} = \text{Ni}^{++} + \text{S}^{--}$	1×10^{-22}
ZnS	$\text{ZnS} = \text{Zn}^{++} + \text{S}^{--}$	1×10^{-20}
$\text{AlPO}_4 \cdot \text{H}_2\text{O}$	$\text{AlPO}_4 = \text{Al}^{+3} + \text{PO}_4^{-3}$	3×10^{-23}
$\text{FePO}_4 \cdot \text{H}_2\text{O}$	$\text{FePO}_4 = \text{Fe}^{+3} + \text{PO}_4^{-3}$	1×10^{-26}
$\text{Ca}_4\text{H}(\text{PO}_4)_3$	$\text{Ca}_4\text{H}(\text{PO}_4)_3 = 4\text{Ca}^{2+} + \text{H}^{+} + 3\text{PO}_4^{3-}$	1×10^{-47}
$\text{Ca}_{10}(\text{PO}_4)_6(\text{FH})_2$	$\text{Ca}_{10}(\text{PO}_4)_6(\text{FH})_2 = 10\text{Ca}^{2+} + 6\text{PO}_4^{3-} + 2\text{F}^{-}$	4×10^{-119}
$\text{Ca}_{10}(\text{PO}_4)_6(\text{OH})_2$	$\text{Ca}_{10}(\text{PO}_4)_6(\text{OH})_2 = 10\text{Ca}^{2+} + 6\text{PO}_4^{3-} + 2\text{OH}^{-}$	2×10^{-114}

Mortland (1970) and will not be covered here. Microorganisms will decompose the organic materials with the release of carbon dioxide and other simple compounds or ions. Organic nitrogen is released during this process as ammonia or ammonium ions. Under well-aerated conditions, this ammonia will be rapidly oxidized by microorganisms to nitrate nitrogen. Both organic nitrogen and ammonium will be retained in the soil to a large extent. But nitrate nitrogen is susceptible to rapid leaching and would be expected to rapidly move into groundwater or surface drainage, whichever the case may be. Under proper conditions, nitrate nitrogen will be denitrified and released back to the atmosphere in a gaseous form. This requires that the nitrate nitrogen move into an anaerobic zone with sufficient carbon as an energy source and the correct microbial population. Although this occurs occasionally in nature--in fact, denitrification is quite common in nature but only occasionally are conditions correct for nearly total denitrification of the nitrate present--the soil can be modified to favor this reaction. Thus, Erickson *et al.* (1971, 1972) produced a barriered landscape water renovation system designed to optimize this reaction. They reported more than 95% removal of nitrogen during the initial stages of operation.

It should be pointed out that the total nitrogen content of wastewater is usually sufficiently low that it is not likely to exceed drinking water standards for nitrate content after passing through a soil profile unless there is an input of nitrogen from another source.

Oxidation-Reduction

Oxidation is defined as the loss of electrons and reduction as the gain of electrons. When both oxidizing and reducing agents are present in the same solution, the reaction will proceed until the rate of oxidation is equal to the rate of reduction and no further net change occurs.

If the following general reaction



occurs in a reversible cell with e.m.f. equal to E, the free energy change is $G_r = NFE$ for the passage of N faradays. Making substitutions into the general form for the standard free energy of a reaction yields:

$$E = E^0 - \frac{RT}{nF} \ln \frac{(L)^1 (M)^m}{(A)^a (B)^b} \dots\dots$$

Although theoretically the redox potential can be measured and then the quantity of any species in solution as a function of pH and redox calculated, in practice with soils and soil solution this has not proven very successful. Bohn (1968) examined the emf of gold, graphite, and platinum electrodes in soil suspensions and concluded that gold and graphite were not useful. The platinum electrodes responded to aeration conditions, but he could not deduce a quantitative significance of his measurements to the Nernstian distribution of oxidized and reduced species.

The oxidation-reduction status of many soils will likely change under conditions of heavy application of wastewater and/or sludge materials. Reducing conditions can occur rapidly and high loading with organic materials will intensify reducing conditions.

Many chemical constituents will undergo chemical alteration because of the change in oxidation status. The reduction of nitrate nitrogen has already been discussed. Patrick (1960), in controlled redox experiments, found that nitrate nitrogen began to disappear from his soil system for redox potentials less than 300 mv. The rate of disappearance increased with decreasing redox potential so that 50 ppm nitrate nitrogen disappeared when the redox was -100 mv as compared to 20 ppm loss for a redox of 250 mv and no change for a redox of 300 mv.

Phosphorus will also respond to changes in redox. Patrick (1964) reported that below 200 mv redox potential the extractable phosphorus increased greatly. More than threefold increases in extractable phosphorus were found when the redox was -200 mv as compared to 200 mv. The sharp break in the phosphate release curve at 200 mv, the same point at which ferric iron begins to be reduced, indicates that the conversion of phosphorus to an extractable form is dependent upon the reduction of ferric compounds in the soil. Although limited data are available, it is expected that soil under reducing conditions would not adsorb as much phosphorus as the same soil in a well-aerated condition nor would the level of phosphorus in solution be maintained at as low a level.

In addition to iron mentioned above, manganese will reduce from plus four to plus two in soils with a low redox potential. Bricker (1965) developed phase diagrams to predict manganous ion levels as a function of pH and redox potential. But Bohn (1970) found that soils with pH values less than 7.0 did not contain sufficient manganese to yield the levels of manganese in solution that were predicted.

Effect of Wastewater Applications on Phosphorus

Most wastewater is expected to contain approximately 10 ppm of total phosphorus. It is probably present in wastewater as orthophosphate, condensed phosphates and organic forms. The latter forms of phosphorus should degrade to orthophosphate rapidly in soils if not in the preliminary wastewater treatment (Murrmann and Koutz, 1972). Soils should rapidly adsorb phosphorus until their adsorbing capacity is reached. Actually, as pointed out in Table 2, not all of the adsorption capacity is expected to be used at the levels of phosphorus in wastewater.

Phosphorus compounds can precipitate in the soil. Figure 1 illustrates the levels of phosphorus left in solution as a function of pH. These values were arrived at by using solubility product data from Table 3 and calculating total phosphate in solution by use of the Debye-Hückel equation for estimating the activity of the individual ion species in an ionic strength of 0.01 molar calcium chloride solution. The activity of the calcium ion was assumed to be $10^{-2.5}$, and it was assumed that gibbsite controlled the aluminum solubility in soils (Lindsay and Moreno, 1960). It can be readily seen that the concentration of phosphorus in solution in soils with a pH less than 6.0 is limited to low levels. But the pH of most wastewaters will be above 7.0 which will cause the soil pH to rise after continued application. For pH values above 7.0, the solubility will be limited by a calcium phosphate. Two compounds are shown in Figure 1, dicalcium phosphate and octacalcium phosphate. It is expected that dicalcium phosphate will form rapidly but it will limit phosphorus in solution to only 4 ppm at pH 9.0 and 8.0 ppm at pH 7.0. This would effect a low percentage removal from wastewaters. Octacalcium phosphates are slower to form. They have been found to form in soils from a few weeks to several months. However, if they form in the system they will limit the solubility of phosphates to levels between .3 ppm at pH 8.0 and 2.7 ppm at pH 7.0. Other calcium phosphates are much less soluble (i.e. hydroxapatite) but form so slowly in soils that they are not expected to have any effect on the precipitation of phosphorus from wastewater.

Effect of Wastewater Applications on Heavy Metals

If the soil pH is greater than 7.0, a condition expected after prolonged wastewater application, most of the heavy metals will precipitate as a hydroxide or a carbonate. Levels remaining in solution are expected to be quite low.

Either natural or organic chelators would increase the level of many of the heavy metals in solution. This can increase the total concentration of heavy metals in solution by many fold.




Fig. 1. Quantity of Total Phosphorus in Solution as a Function of pH.

Although most of the heavy metals are expected to be retained in the soil by adsorption onto clay surfaces or organic matter or by precipitation, little is known about the effect of these heavy metals on crop growth or quality. Melton, Doll and Ellis (1971) found that even small applications of zinc to acid soils led to excessive accumulation of zinc by bean plants and markedly reduced yield. This would suggest that the effect of heavy metals on plant growth should be carefully evaluated in wastewater disposal systems. Sludge materials are many times extremely high in heavy metals (Berrow and Webber, 1972). And, in addition, they may contain

organic materials capable of chelating these heavy metals which will result in increased uptake by plants and increased leaching through the soil profile. Again, these factors must be carefully considered.

REFERENCES

- Arshad, M. A. and J. A. Carson. 1967. Ionic exchange behavior in a loam soil as indicated by movement of radio-calcium. *Soil Sci. Soc. Amer. Proc.* 31, 321-324.
- Aslying, H. C. 1954. The lime and phosphate potentials of soils, the solubility and availability of phosphates. *Royal Vet. Agric. College Copenhagen, Yearbook*, 1954, p. 1-50.
- Aylmore, L. A. G., Mesbahul Karim, and J. P. Quirk. 1967. Adsorption and desorption of sulfate ions by soil constituents. *Soil Sci.* 103, 10-15.
- Babcock, K. L. and R. K. Schulz. 1963. Effect of anions on the sodium-calcium exchange in soils. *Soil Sci. Soc. Amer. Proc.* 27, 630-632.
- Barrow, N. J. 1967. Studies on the adsorption of sulfate by soils. *Soil Sci.* 104, 342-349.
- Barrow, N. J. 1970. Comparison of the adsorption of molybdate, sulfate and phosphate by soils. *Soil Sci.* 109, 282-288.
- Berrow, M. L. and J. Webber. 1972. Trace elements in sewage sludges. *Jour. Sci. Food Agric.* 23, 93-100.
- Biggar, J. W. and Milton Fireman. 1960. Boron adsorption and release by soils. *Soil Sci. Soc. Amer. Proc.* 24, 115-120.
- Blanchar, R. W. and Chun Wei Kao. 1972. Distribution and chemistry of phosphorus in a Mexico soil after 82 years of phosphorus fertilization. From M.S. Thesis of Chun Wei Kao (1971), University of Missouri.
- Bohn, H. L. 1968. Electromotive force of inert electrodes in soil suspensions. *Soil Sci. Soc. Amer. Proc.* 32, 211-215.
- Bohn, H. L. 1970. Comparisons of measured and theoretical Mn^{2+} concentrations in soil suspensions. *Soil Sci. Soc. Amer. Proc.* 34, 195-197.
- Bolt, G. H. and M. Peech. 1953. The application of the Gouy theory to soil water systems. *Soil Sci. Soc. Amer. Proc.* 17, 210-213.
- Bornemisza, E. and R. Llanos. 1967. Sulfate movement, adsorption, and desorption in three Costa Rican soils. *Soil Sci. Soc. Amer. Proc.* 31, 356-360.
- Bower, C. A., G. Ogata, and J. M. Tucker. 1968. Sodium hazard of irrigation waters as influenced by leaching fraction and by precipitation or solution of calcium carbonate. *Soil Sci.* 106, 29-34.
- Bower, C. A. and L. V. Wilcox. 1965. Precipitation and solution of calcium carbonate in irrigation operations. *Soil Sci. Soc. Amer. Proc.* 29, 93-94.

- Bower, C. A., L. V. Wilcox, G. W. Akin, and Mary G. Keyes. 1965. An index of the tendency of CaCO_3 to precipitate from irrigation waters. *Soil Sci. Soc. Amer. Proc.* 29, 91-92.
- Boyd, G. E., J. Schubert, and A. W. Adamson. 1947. The exchange adsorption of ions from aqueous solutions by organic zeolites. I. Ion exchange equilibria. *Jour. Amer. Chem. Soc.* 69, 2818-2829.
- Bricker, O. 1965. Some stability relations in the system $\text{Mn-O}_2\text{-H}_2\text{O}$ at 25° and one atmosphere total pressure. *Amer. Mineralogist* 50, 1296-1354.
- Broadbent, F. E., and G. R. Bradford. 1952. Cation exchange groups in soil organic fraction. *Soil Sci.* 74, 447-457.
- Brown, G. 1961. The X-ray identification and crystal structures of clay minerals. Jarrold and Sons, Ltd. Norwich.
- Chao, Tsun Tien, M. E. Harward, and S. C. Fang. 1962. Adsorption and desorption phenomena of sulfate ions in soils. *Soil Sci. Soc. Amer. Proc.* 26, 234-237.
- Chao, Tsun Tien, M. E. Harward, and S. C. Fang. 1963. Cationic effects on sulfate adsorption by soils. *Soil Sci. Soc. Amer. Proc.* 27, 35-38.
- Clark, J. S. and M. Peech. 1955. Solubility criteria for the existence of calcium and aluminum phosphates in soils. *Soil Sci. Soc. Amer. Proc.* 19, 171-174.
- Couch, Elton L. and Ralph E. Grim. 1968. Boron fixation by illites. *Clays and Clay Minerals* 16, 249-256.
- Day, A. D., J. L. Stroehlein, and T. C. Tucker. 1972. Effects of treatment plant effluent on soil properties. *Jour. Water Poll. Control Fed.* 44, 372-375.
- de Haan, F. A. M. and G. H. Bolt. 1963. Determination of anion adsorption by clays. *Soil Sci. Soc. Amer. Proc.* 27, 636-640.
- de Villiers, J. M. and M. L. Jackson. 1967a. Cation exchange capacity variations with pH in soil clays. *Soil Sci. Soc. Amer. Proc.* 31, 473-476.
- de Villiers, J. M. and M. L. Jackson. 1967b. Aluminous chlorite origin of pH-dependent cation exchange capacity variations. *Soil Sci. Soc. Amer. Proc.* 31, 614-619.
- Eaton, F. M. 1950. Significance of carbonates in irrigation waters. *Soil Sci.* 69, 123-133.
- Ellis, B. G. and A. E. Erickson. 1969. Movement and transformation of various phosphorus compounds in soils. Report to Michigan Water Resource Commission.
- Ellis, Boyd G. and Bernard D. Knezek. 1972. Adsorption reactions of micronutrients in soils. Chapt. 4 in *Micronutrients in Agriculture*. Ed. J. J. Mortvedt, P. M. Giordano, and W. L. Lindsay. *Soil Sci. Soc. Amer., Inc. Madison, Wisconsin.*
- Erickson, A. E., J. M. Tiedje, B. G. Ellis, and C. M. Hansen. 1971. A barriered landscape water renovation system for removing phosphate and nitrogen liquid feedlot waste. *Proc. of the International Symp. on Livestock Wastes.* p. 232-234.

- Erickson, A. E., J. M. Tiedje, B. G. Ellis and C. M. Hansen. 1972. Initial observations of several medium-sized barriered landscape water renovation systems for animal waste. Proc. of the 1972 Cornell Agric. Waste Management Conf. p. 405-410.
- Eriksson, E. 1952. Cation-exchange equilibria on clay minerals. Soil Sci. 74, 103-113.
- Fleet, M. E. L. 1965. Preliminary investigations into the sorption of boron by clay minerals. Clay Minerals Bull. 6, 3-16.
- Fried, Maurice and Hans Broeshart. 1967. The soil-plant system in relation to inorganic nutrition. Academic Press. New York.
- Fried, M. and R. E. Shapiro. 1956. Phosphate supply pattern of various soils. Soil Sci. Soc. Amer. Proc. 20, 471-475.
- Gapon, E. N. 1933. On the theory of exchange adsorption in soils. Jour. Gen. Chem. (USSR) 3, 144-163.
- Giesecking, J. E. and Hans Jenny. 1936. Behavior of polyvalent cations in base exchange. Soil Sci. 42, 273-280.
- Gough, N. A. and J. D. Beaton. 1963. Influence of phosphorus source and soil moisture on the solubility of phosphorus. Jour. Sci. Food Agric. 14, 224-266.
- Grim, Ralph E. 1953. Clay mineralogy. McGraw-Hill Book Co., Inc. New York.
- Hasan, S. M., R. L. Fox, and C. C. Boyd. 1970. Solubility and availability of sorbed sulfate in Hawaiian soils. Soil Sci. Soc. Amer. Proc. 34, 897-901.
- Hatcher, John T., C. A. Bower. 1958. Equilibria and dynamics of boron adsorption by soils. Soil Sci. 85, 319-323.
- Hatcher, John T., C. A. Bower, and Myron Clark. 1967. Adsorption of boron by soils as influenced by hydroxy aluminum and surface area. Soil Sci. 104, 422-426.
- Henze, R. 1963. Comparison of yields from the Göttingen E-fields and the nutrient potential and supply of the soil. I. Pflanzenbau Dtsch. Bodenk. 103, 9-21.
- Hiester, N. K. and T. Vermeulen. 1952. Saturation performance of ion-exchange and adsorption columns. Chem. Engr. Prog. 48, 505-516.
- Hingston, F. J. 1964. Reactions between boron and clays. Australian J. Soil Res. 2, 83-95.
- Hodgson, J. F. 1960. Cobalt reactions with montmorillonite. Soil Sci. Soc. Amer. Proc. 24, 165-168.
- Hodgson, J. F., H. R. Geering and Martha Fellows. 1964. The influence of fluoride, temperature, calcium and alcohol on the reaction of cobalt with montmorillonite. Soil Sci. Soc. Amer. Proc. 28, 39-42.
- Hodgson, J. F. and K. G. Tillier. 1961. The location of bound cobalt on 2:1 layer silicates. Clays and Clay Minerals. Proc. of the 9th National Conf., p. 404-411.
- Hodgson, J. F., Kevin G. Tillier and Martha Fellows. 1969. Effect of iron removal on cobalt sorption by clays. Soil Sci. 108, 391-396.

- Kerr, H. W. 1928. The nature of base exchange and soil acidity. Jour. Amer. Soc. Agron. 20, 309-335.
- Krishnamoorthy, C., L. E. Davis, and R. Overstreet. 1948. Ionic exchange equations derived from statistical thermodynamics. Science 108, 439-440.
- Krishnamoorthy, C. and R. Overstreet. 1950. An experimental evaluation of ion-exchange relationships. Soil Sci. 69, 41-53.
- Lindsay, W. L. and E. C. Moreno. 1960. Phosphate phase equilibria in soils. Soil Sci. Soc. Amer. Proc. 24, 177-182.
- Lindsay, W. L. and W. A. Norvell. 1969. Equilibrium relationships of Zn^{2+} , Fe^{3+} , Ca^{2+} , and H^+ with EDTA and DTPA in soils. Soil Sci. Soc. Amer. Proc. 33, 62-68.
- Longenecker, D. E. 1960. Influence of soluble anions on some physical and physico-chemical properties of soils. Soil Sci. 90, 185-191.
- Marshall, C. E. 1964. The physical chemistry and mineralogy of soils. Vol. I. Soil Materials. John Wiley & Sons, Inc. New York.
- Mattingly, G. E. G., R. D. Russell, and B. M. Jephcott. 1963. Experiments on cumulative dressings of fertilizers on calcareous soils in southwest England. II. Phosphorus uptake by ryegrass in the greenhouse. Jour. Sci. Food Agric. 14, 629-637.
- McGeorge, W. T. 1930. The base exchange property of organic matter in soils. Arizona Agric. Expt. Sta. Tech. Bull. 30, 181-213.
- McNeal, B. L. and N. T. Coleman. 1966. Effect of solution composition on soil hydraulic conductivity. Soil Sci. Soc. Amer. Proc. 30, 308-312.
- McNeal, B. L., D. A. Lafield, W. A. Norvell, and J. D. Rhoades. 1968. Factors influencing hydraulic conductivity of soils in the presence of mixed-salts solutions. Soil Sci. Soc. Amer. Proc. 32, 187-190.
- Melton, J. R., B. G. Ellis, and E. C. Doll. 1970. Zinc, phosphorus, and lime interactions with yield and zinc uptake by *Phaseolus Vulgaris*. Soil Sci. Soc. Amer. Proc. 34, 91-93.
- Mitchell, J. 1932. The origin, nature, and importance of soil organic constituents having base exchange properties. Jour. Amer. Soc. Agron. 24, 256-275.
- Mortland, M. M. 1970. Clay-organic complexes and interactions. Adv. in Agron. 22, 75-117.
- Murmann, R. P. and F. R. Koutz. 1972. Role of soil chemical processes in reclamation of wastewater applied to land. Chapt. 4 in: Wastewater Management by Disposal on the Land. Crops of Engineers. U.S. Army. Cold Regions Research and Engineering Laboratory. Hanover, N. H.
- Norvell, W. A. and W. L. Lindsay. 1970. Lack of evidence for $ZnSiO_3$ in soils. Soil Sci. Soc. Amer. Proc. 34, 360-361.

- Olsen, Sterling R. and Frank S. Watanabe. 1957. A method to determine a phosphorus adsorption maximum of soils as measured by the Langmuir isotherm. *Soil Sci. Soc. Amer. Proc.* 21, 144-149.
- Patrick, W. M., Jr. 1960. Nitrate reduction rates in a submerged soil as affected by redox potential. *Trans. International Congress Soil Sci.*, 7th Madison, Wisconsin. 2, 494-500.
- Patrick, W. M., Jr. 1964. Extractable iron and phosphorus in a submerged soil at controlled redox potentials. *8th International Congress of Soil Sci.* Bucharest, Rumania. IV. p. 605-609.
- Pratt, P. F. and F. L. Bair. 1969. Sodium hazard of bicarbonate irrigation waters. *Soil Sci. Soc. Amer. Proc.* 33, 880-883.
- Pratt, P. F., R. L. Branson, and H. D. Chapman. 1960. Effect of crop fertilizer and leaching on carbonate precipitation and sodium accumulation in soil. *International Congress Soil Sci. Trans.* 7th Madison, Wisconsin. 2, 185-192.
- Rao, Talur S., A. L. Page, and N. T. Coleman. 1968. The influence of ionic strength and ion-pair formation between alkaline-earth metals and sulfate on Na-divalent cation-exchange equilibria. *Soil Sci. Soc. Amer. Proc.* 32, 639-643.
- Rhoades, J. D., R. D. Ingvalson, and J. T. Hatcher. 1970a. Laboratory determination of leachable soil boron. *Soil Sci. Soc. Amer. Proc.* 34, 871-875.
- Rhoades, J. D., R. D. Ingvalson, and J. T. Hatcher. 1970b. Adsorption of boron by ferromagnesian minerals and magnesium hydroxide. *Soil Sci. Soc. Amer. Proc.* 34, 938-941.
- Richards, L. A. (ed.). 1954. Diagnosis and improvement of saline and alkali soils. *USDA Agricultural Handbook No. 60.*
- Scharrer, K., H. Kühn, and J. Lüttmer. 1956. Investigations of the fixation of boron by inorganic constituents of the soil. *Z. Pflernähr Düng.* 73, 40-48. (*Soils and Fertilizers*, 1956, 19, 1501).
- Scheffer, F. and B. Ulrich. 1960. Physical-chemical basis of nutrient dynamics in the soil. *Acad. Rep. Populare Romine Probl. Act. Biol. Stunte Agr.* p. 663-670.
- Schofield, R. K. 1947. A ratio law governing the equilibrium of cations in the soil solution. *Proc. 11th International Congress Pure and Appl. Chem.* (London), 3, 257-261.
- Schofield, R. K. 1955. Can a precise meaning be given to "available" soil phosphorus? *Soils and Fertilizers* 18, 373-375.
- Shainberg, I. and W. D. Kemper. 1966. Hydration status of adsorbed cations. *Soil Sci. Soc. Amer. Proc.* 30, 707-713.
- Shapiro, Raymond E. and Maurice Fried. 1959. Relative release and retentiveness of soil phosphates. *Soil Sci. Soc. Amer. Proc.* 23, 195-198.
- Sharpless, R. G., E. F. Wallihan, and F. F. Peterson. 1969. Retention of zinc by some arid zone soil materials treated with zinc sulfate. *Soil Sci. Soc. Amer. Proc.* 33, 901-904.
- Sims, J. R. and F. T. Bingham. 1967. Retention of boron by layer silicates, sesquioxides, and soil materials. I. Layer

- silicates. Soil Sci. Soc. Amer. Proc. 31, 728-732.
- Sims, J. R. and F. T. Bingham. 1968a. Retention of boron by layer silicates, sesquioxides, and soil materials. II. Sesquioxides. Soil Sci. Soc. Amer. Proc. 32, 364-369.
- Sims, J. R. and F. T. Bingham. 1968b. Retention of boron by layer silicates, sesquioxides, and soil materials. III. Iron- and aluminum-coated layer silicates and soil materials. Soil Sci. Soc. Amer. Proc. 32, 369-373.
- Stevenson, F. J., and J. H. A. Butler. 1969. Chemistry of humic acids and related pigments. Chapt. 22. In Organic Geochemistry Methods and Results. Ed. G. Eglington and M. T. J. Murphy. Springer-Verlag. New York · Heidelberg · Berlin.
- Tanji, Kenneth K. 1970. A computer analysis on the leaching of boron from stratified soil columns. Soil Sci. 110, 44-51.
- Thomas, H. C. 1944. Heterogeneous ion exchange in a flowing system. Jour. Amer. Chem. Soc. 66, 1664-1666.
- Tiller, K. G. 1967. Silicic acid and the reactions of zinc with clays. Nature 214, 852.
- Tisdale, Samuel L. and Werner L. Nelson. 1956. Soil fertility and fertilizers. The MacMillan Co., New York.
- Udo, E. J., H. L. Bohn and T. C. Tucker. 1970. Zinc adsorption by calcareous soils. Soil Sci. Soc. Amer. Proc. 34, 405-407.
- Ulrich, B. 1961. Soil and plants: Their interrelationships--physical-chemical view, Ferd. Enke Verlag, Stutthart, p. 1-114.
- Vangeleern, von P. and J. Woltersdorf. 1930. Beiträge zur Frage des Basenaustausches and der Aziditäten. Z. Pflanzenernähr. Düng. Bodenk 15, 329-342.
- Vanselow, A. P. 1932. Equilibria of the base-exchange reactions of bentonites, permutites, soil colloids, and zeolites. Soil Sci. 33, 95-113.
- Vermeulen, T. and N. K. Hiester. 1959. Ion-exchange and adsorption column kinetics with uniform partial presaturation. Jour. Chem. Phys. 22, 96-101.
- White, R. E. and P. H. T. Beckett. 1964. Studies on the phosphate potentials of soils. Part I. The measurement of phosphate potential. Plant Soil 20, 1-16.
- Wiklander, Lambert. 1964. Cation and anion exchange phenomena. Chapt. 4. In Chemistry of the Soil. Ed. Firman E. Bear. Reinhold Publishing Corp., New York.

DISCUSSION

- Hunt: I wanted to ask a question on your anaerobic denitrification. Have you had any problems in this particular system with the clogging under anaerobic conditions, and do you think that this concept has any applicability to field conditions?
- Ellis: In answer to your first question, yes, there has been some trouble. Dick Thomas's slides fit exactly what we

discovered. The trouble is in a very thin layer on the surface. But you can manage this. You may have difficulty in growing a crop on it. We're considering quack grass since it seems to grow about everywhere. But it does give us some difficulty. You can get away from some of this by resting and it will go back into receiving material. Secondly, you asked do I think it has any applicability in the field, yes I do. The one we have built is a very detailed system where we have it all enclosed in plastics. We don't lose anything and we can analyze all the materials. Dr. Erickson in our department says we can go about and build one of these in the field very easily by using an asphalt barrier to provide the anaerobic zone. We won't worry about recycling all the water back through the swine barn to flush it a second time, we'll just let it go off into the ground water after it's all purified. The one thing I expect trouble on though is the high levels of salt, particularly potassium may give us difficulties and perhaps also chloride.

McKernan: I'm interested to know in your last experiment with the swine barn waste whether the burms that you have constructed are characterized by certain kinds of vegetative cover and whether the evaporation characteristics of the cover has affected your experiment?

Ellis: We have operated these with grass covers and bare soils. I would suppose that there has been some evapotranspiration. I realize that in Michigan, our evapotranspiration rates are not extremely high and we were putting on more than 1 inch per day, so evapotranspiration should not be a large part of this.

Goydan: What method are you referring to when you mention ion adsorption tests in the laboratory?

Ellis: We've been using the Langmuir adsorption isotherm for this. It's very simple to perform. You add increasing increments of phosphorus to a series of 5 gram samples, let them come to equilibrium...24 hours is sufficient to do this, determine the amount of phosphorus adsorbed, plug it back into the Langmuir equation and you can predict the adsorption maximum plus the constant K. This is what we're doing in the laboratory. There are other isotherms that can be used, but I think more work has been done with the Langmuir than anything else and it at least appears to me to give us some hope of a ballpark estimate. I certainly wouldn't want to stake my reputation or life on the fact that these are accurate but I think we're going with the best estimation

we have right now without going out into the field and measuring.

Sutherland: In your incubation treatment of soils with phosphate, did you permit the soils to dry during that 3 month period of time or were they allowed to remain moist?

Ellis: We maintained them relatively moist but we were doing this in polyethylene bags and brought them back up to field capacity about once a week during the 3 month period, which meant there was some drying in the system. This is something I haven't pursued as much as I should have. It could be very critical to design criteria to know how many times you could go through a cycle and then give it 3 months in a field to recover. We know nothing except that we were able to recover the original absorption capacity in the laboratory once in a 3 month period.

Kraft: I have a question concerning the hog waste renovation system. How long have you researched this and also what was the type of soil? With the apparent nitrogen removals that you got, are you sure that actual nitrification and denitrification occurs or is it possible that the ammonia is being absorbed by the soil and you haven't saturated the absorption complex?

Ellis: We measured the ammonia on the soil and this will not account for it. This is Erickson's experiment principally. I'm the chemist involved in it and we do the analysis work on it. I threw it in just as an illustration here, but let me say this. Yes, I think we're getting rid of it by denitrification because when we overloaded the system by accident one time, a switch blew out and we dumped a weeks load in one night, immediately the nitrate values went very high and we no longer could handle it, so I think we are denitrifying the system. We've been running it off and on a little over a year now. How long we can go with it I don't know. Our soil microbiologist says indefinitely providing we maintain the carbon there that we need for the denitrification. If we lose the carbon it won't work. As far as phosphate removal, we're on borrowed time there and my calculations indicate that we should go about 18 months before we start to leak phosphorus.

THE SOIL AS A BIOLOGICAL FILTER

R. H. Miller
Department of Agronomy
The Ohio State University

062 H

Renewed interest in land disposal of secondary effluents and liquid sewage sludges has stimulated the scientific community to examine in more detail than ever before the physical, chemical, and biological processes in soil which influence waste renovation. In this symposium the useful analogy of "soil as a filter" has been employed to simplify the discussion of the renovative capacity of soil for waste materials. Previous papers by R. E. Thomas, "Soil as a Physical Filter" and B. G. Ellis, "Soil as a Chemical Filter" have covered the soil physical and chemical properties which influence the "soil filter". This paper will address itself to a third component of the soil filter, the biological component.

The groups of organisms comprising the soil biological filter are bacteria actinomycete, fungi, protozoa, algae, soil micro- and macro-animals and higher plants. The significance of higher plants to the successful renovation of liquid wastes on land has been well documented previously (Kardos, 1967, 1970; Sopper, 1971) and in this symposium. This discussion will therefore focus on the contributions of the soil microbial population to the selectivity and success of the soil filter.

THE MICROBIAL POPULATION OF THE SOIL FILTER

Individual groups of soil microorganisms in the plow layer of agricultural soils often reach high numerical populations. Estimates of 10^7 bacteria, 10^6 actinomycetes, and 10^5 fungi per gram of soil are typical values obtained by plate counts on various artificial media. Direct microscopic counts for soil bacteria are usually higher with about 10^9 cells per gram of soil, a common figure (Clark, 1967). Soil fungi become the dominant numerical group of soil microorganisms in the litter layer (Ao) and A₁ horizons of acidic forest profiles. In both agricultural and forest soils the microbial population is concentrated primarily in the surface 15 cm organic matter rich region of the soil, and numbers decrease rapidly with depth.

Addition of organic waste materials to soil should be expected to and does increase microbial numbers (Glathe and Makawi, 1963; Miller, 1972). Representative data for changes in various groups

of microorganisms during the decomposition of an aerobically digested sewage sludge are shown in Table 1 and 2.

Table 1. Plate Counts^a of Bacteria and Actinomycetes in Soils Amended with Anaerobically Digested Sewage Sludge after 1-Month Incubation

Soil	Soil Moisture ^b	Organisms/g dry soil x10 ⁻⁶		
		Control	90 ton/ha	224 ton/ha
Ottokee sand	FC	7.5	33.0	46.0
	Sat	7.0	472	857
Celina silt loam	FC	15.5	268	88.0
	Sat	30.5	864	521
Paulding clay	FC	28.6	484	842
	Sat	13.7	37.9	96.2

^aOn soil extract-sludge extract agar.

^bFC = field capacity Sat = water saturation.

Table 2. Plate Counts^a of Fungi in Soils Amended with Anaerobically Digested Sewage Sludge after 1-Month Incubation

Soil	Moisture ^b	Organisms/g dry soil x10 ⁻⁴		
		Control	90 ton/ha	224 ton/ha
Ottokee sand	FC	17.5	752	576
	Sat	17.5	95	303
Celina silt loam	FC	12.5	50	48
	Sat	14.0	9.0	46
Paulding clay	FC	11.0	419	826
	Sat	11.0	7.5	6.0

^aOn rose-bengal-streptomycin agar.

^bFC = field capacity Sat = water saturation.

No data is presently available on population changes induced by

irrigation with secondary effluent. Presumably the increase in agricultural soils would be minimal because of the low organic loading associated with secondary effluent. The changes which might occur in the microbial population of forest soils remains an unanswered question, but would probably be more dramatic than in agricultural soils.

Numerous estimates of bacterial biomass and a few estimates of fungal biomass have been calculated and representative data are shown in Table 3. In most arable soils, the amount of bacterial

Table 3. Estimates of Microbial Biomass in Soils^a

Reference	Bacterial Biomass		
	g/m ²	lbs/Acre	% of Soil Mass
Alexander (1961)	33-330	300-3000	0.015-0.15
Jensen (1963)	100-1000	900-9000	0.045-0.45
Russell (1950)	170-390	1500-3600	0.077-0.18
Krasil'nikov (1944)	67-720	600-6400	0.031-0.33
Latter & Cragg (1967)	21-135	190-1200	0.010-0.06
Stockli (1956)	160-380	1500-3500	0.075-0.17
Clark (1967)	450	4100	0.22
Mean	300	2800	0.14
	Fungal Biomass		
	g/m ²	lbs/Acre	% of Soil Mass
Jackson (1965)	190	1700	0.09
Clark & Paul (1970)	260 ^b	2400	0.19
Alexander (1961)	55-550	500-5000	.025-0.25

^aValues are calculated on live weight basis for 15 cm depth.

^bg/m²/10 cm depth.

biomass is commonly estimated to be somewhat less than that of fungi, but to exceed that of the algae, protozoa and nematodes combined (Clark, 1967). Comparative data for the biomass of actinomycetes are not available but is generally considered to be equal to that of the true bacteria. Jenkinson (1966) used the distribution of

^{14}C in soil after decomposition of ^{14}C labeled ryegrass to estimate that the soil biomass contained 2.3 to 3.5 percent of the soil carbon.

In summary, the microbial component of the "soil filter" occupies the upper portion of the soil profile (plow layer or litter layer and A₁ horizon of a forest soil). Its mass makes up only a relatively small part of the total soil mass. The contribution of this small but significant component to waste recycling and renovation will be discussed in more detail in the paragraphs which follow.

SIGNIFICANCE OF THE BIOLOGICAL FILTER IN RECYCLING MUNICIPAL WASTEWATER AND SLUDGE

Microbial Decomposition of Organic Wastes

One of the most significant functions of the microbial component of the soil filter is the degradation of organic compounds contained in the waste materials applied to soils. Indeed, one of the primary advantages attributed to recycling of secondary effluent through soil is that soil provides an alternative to stream discharge or expensive tertiary treatments for reducing BOD and improving water quality.


Disposal of liquid sewage sludges on land presents a somewhat different problem since soil application is considered an economical method for ultimate disposal of these high organic wastes. Proper design and management of soils systems for sludge disposal by either high rate single application or repeated lower rate applications depends to a large part on the rate at which sludge organic matter is decomposed. A less rapid decomposition of sewage sludges would be advantageous for the reclamation of sandy soils or strip-mine spoil. These soils would benefit from the improved physical and chemical properties associated with organic matter accumulation. In contrast, proper management of sludge disposal on finer textured agricultural soils would require a more rapid rate of decomposition of sludge carbon. Experience at both the Paris and Berlin sewage farms indicate that organic matter accumulation was associated with "exhausted" soils (Rohde, 1962). The primary reason cited for poorer plant growth in these soils was an accumulation of toxic levels of Cu and Zn associated with the organic matter. Excessive accumulation of sludge organic matter might also reduce soil aeration and the associated problems of odor, reduced root development, and mobility of Fe and Mn.

Those of us in agriculture are well aware of the enzymatic versatility of the heterotrophic microbial population of soil and its


significance in decomposing a wide host of natural and synthetic organic compounds (Alexander, 1961; McLaren and Peterson, 1967). Soil microorganisms are actually too efficient in their catabolic activity and it has been found almost impossible to maintain the organic matter of both mineral and organic soils when used for agriculture, Hallam and Bartholomew (1953) concluded that annual additions of organic carbon of 2 to 5 tons per acre were needed just to maintain the organic carbon content of temperate region soils.

The products of microbial metabolism of organic compounds in soil under aerobic and anaerobic conditions are shown in the generalized formulae below.

Aerobic



Anaerobic



* The percentage values are estimates of the distribution of the carbon of the original organic compound(s) after metabolism by the microbial population.

While the main products of aerobic metabolism are CO_2 , H_2O and cells; in the absence of O_2 intermediate substances such as organic acids, alcohols, amines, and mercaptans accumulate. Because the energy yield during anaerobic fermentation is small, fewer microbial cells accumulate per unit of organic carbon degraded. Note also that while NO_3^- and SO_4^{2-} are the end products of organic nitrogen and sulfur compounds under aerobic conditions, H_2S and NH_4^+ are formed under anaerobic conditions.

Secondary effluent from properly operating treatment plants contains relatively low levels of organic compounds. A BOD of 25 mg/l and a COD of 70 mg/l was considered typical for secondary effluent (Reed, 1972). Very little information is available on the chemical analysis of the organic compounds of secondary effluent (Painter et al., 1961; Hunter, 1973). A portion of the readily decomposable organic materials (measurable by BOD) are derived from sludge particles carried over from the treatment system. These particulates should have a chemical composition similar to that of microbial tissue. The data of Painter et al. (1961) although accounting for less than 50 percent of the effluent carbon, would seem to verify this assumption. Part of the BOD of wastewater effluent is also in the colloidal and soluble states and would probably differ little from the analysis given for particulate organic compounds. The protein, carbohydrates, nucleic acids, fatty acids, amino sugars and other organic materials found within microbial cells will be readily degradable by the common biochemical pathways of glycolysis, the tricarboxylic acid cycle, B-oxidation, etc.

The remainder of the organic compounds of secondary effluent are commonly called refractory organics. Refractory organics are estimated by the difference between the values of COD and BOD. As the name implies, these organic compounds are those which are considered more slowly degradable eg. phenols, detergents, fats and waxes, hydrocarbons, cellulose, lignin, tannin, plant and bile pigments, pesticides, and humic compounds. Physical entrapment and chemical adsorption of these compounds in the soil matrix should provide the necessary retention time for effective microbial degradation of most of these compounds. Since some of these refractory organics are considered toxic or problematic to different sectors of our environment their elimination from the soil by biodegradation will be discussed in greater detail in the next section.

Very little information is currently available on the rate at which the organic compounds of wastewater effluents are actually decomposed in soil. Thomas and Bendixen (1969) studied the rate of degradation of septic tank effluent in sand lysimeters and secondary effluent in lysimeters of sand and a silt loam soil. About 80 percent of the organic carbon from septic tank effluent was digested during 82-425 day dosing cycles with little difference due to duration of dosing, temperature or loading rates. Only 68% of the organics of secondary effluent was degraded in the sand lysimeters during 513 and 760 day dosing periods which 89% was degraded during a 513 day dosing of a single lysimeter containing a silt loam soil. One other aspect of these data is of significance. An average of 14% of the applied organic carbon was found in the percolate from the sand lysimeters (3 ft depth). These values are very large and represent a potential problem with the renovating

capability of the soil filter of coarse textured soils. These high percolation rates of soluble organics may only reflect the influence of continuous dosing and do not seem to reflect data from field studies.

Application of secondary effluent to soil at a rate of 2" per week for a 40-week period (March-November) should not place any stress on the soil filter and the microorganisms of the "living filter" should effectively remove and decompose most of the organic material of the effluent. At a COD of 70 mg/l the 80" addition of effluent will add only 728 Kg (1600 lbs) of organic matter per acre. This is far below the maintenance level of 2 to 5 tons of organic matter per acre per year noted by Hallam and Bartholomew (1953) and there should be no accumulation of organic matter in the soil. Higher and more frequent applications of secondary effluent could cause waterlogging with concomitant anaerobic conditions and slower rates of decomposition.

Anaerobically digested sewage sludges contain about 25% organic carbon on a dry weight basis (Burd, 1968). During the process of anaerobic digestion the waste organic solids are stabilized by the almost complete microbial fermentation of carbohydrates (the exception is cellulose) resulting in a 60 to 75% reduction in volatile solids. Although data on the organic analysis of anaerobically digested sludge is difficult to obtain the residual organic material consists of a mixture of microbial tissue, lignin, cellulose, lipids, organic nitrogen compounds, and humic acid like materials (McCoy, 1971).

As might be expected, anaerobically digested sludge is not degraded rapidly in soil. A maximum of only 17 to 18 percent of the sludge carbon was evolved as CO_2 during a 6-month period at soil temperatures equivalent to spring-summer or summer-autumn in Columbus, Ohio. It was apparent that the rate of sludge decomposition was more rapid during the initial month than during the subsequent months following addition. These data certainly suggest that addition of anaerobically digested sewage sludge to soils will result in the accumulation of organic matter.

The above discussion dealt with the rate of degradation of anaerobically digested sewage sludge. Undigested primary sludge or activated sludge will contain organic residues which are much more readily degradable. Additions of the latter two sludges to soil, at comparably high rates as anaerobically digested sewage sludge, would exert a greater demand on the oxygen supplying power of soil. Anaerobic conditions, odor and reducing conditions would probably result.

Elimination of Environmental Toxins

Municipal waste effluents and sewage sludges contain a number of organic and inorganic substances which are considered potential environmental toxins. Listed in this category are phenolic compounds, the chlorinated hydrocarbon pesticides and chlorinated biphenyls, detergent residues like ABS and NTA, petroleum products and heavy metals.

One of the important questions which must be asked when considering the feasibility of applying municipal wastes to land is the fate of these chemicals after they reach the soil. The primary environmental impact of these chemicals would occur if they would move through or off the soil surface and reach ground and surface water supplies. In this section we will discuss the participation of the microbial component of the soil filter in removing or detoxifying the organic toxins discussed above. The microbially mediated reactions which influence the mobility or plant availability of heavy metals will be discussed in the next section.

Phenols often reach sewage systems as wastes from oil refineries, steel mills, and chemical companies (Reed, 1972; Lake Erie Report, 1968). Secondary treatment is reported to reduce the concentration of phenolic compounds from 65 to 99 percent, the reduction being due to biological activity. The quantity of phenolic compounds in secondary effluent used for land disposal can be expected to vary greatly. Data for a typical analysis of a secondary effluent gives a value of 0.3 mg/l of phenol (Reed, 1972). Assuming a 40-week period of irrigation (March-November) at 2 inches per week only 6.2 lbs/acre (6.9 Kg/ha of phenol) would reach the soil. Even though the phenolic compounds are considered rather stable to biological degradation considerable evidence indicates that phenolic compounds should be decomposed in soils. The enzymatic cleavage of the aromatic ring occurs by mixed function oxidases followed by subsequent metabolism of the ring carbon (Dagley, 1967; Gibson, 1968). A recent review by Horvath (1972) points out that co-metabolism might be involved in the biological metabolism of many organic compounds including some substituted phenolic compounds. Regardless of the metabolism scheme, it is doubtful if phenolic compounds will accumulate in soil when applied at or near the normal rates. The microbial portion of the soil filter should readily eliminate the phenolic compounds as long as physical and chemical adsorption provide sufficient retention time for microbial activity to proceed.

Pesticides, particularly the chlorinated hydrocarbon insecticides, DDT, aldrin, dieldrin, etc. and polychloroaromatic herbicides such as 2,3,6-TBA and 2,4,5-T have received considerable publicity as potential carcinogens or teratogenic agents. These same compounds have acquired a reputation as being recalcitrant i.e. nonbio-degradable (Alexander, 1965a). Recent reports that these same

pesticides may be metabolized to nontoxic intermediates under laboratory conditions by the process of co-metabolism offers a possible approach to accelerating microbial detoxication (Horvath, 1972). It has also been suggested that "analog enrichment" which involves the addition of a biodegradable analog at the same time as the recalcitrant compound might result in a more rapid oxidation and detoxication (Horvath, 1972). Data from a lysimeter study by Robeck *et al.* (1963) would seem to support the idea that co-metabolism is indeed involved in the biodegradation of 2,4,5-T. Although 2,4,5-T is normally considered to persist in soils for periods of at least 6 months (Alexander, 1965b) data from this study showed that 2,4,5-T added to septic tank effluent and percolated through lysimeters was metabolized after a 14-day lag period. The more rapid degradation of 2,4,5-T in the lysimeters may be due to the organic materials of the effluent providing energy for the microbial co-metabolism of this "recalcitrant" herbicide. All of the pesticides discussed will normally be present in wastewaters in significant quantity only as a result of industrial operations. Initial low levels of pesticides coupled with strong adsorption on soil particles and eventual biodegradation make it doubtful if any environmental problems will occur.

Hydrocarbons in sewage effluents are derived from various industrial sources and oil spills. An estimate of the maximum quantity of hydrocarbons that will be present in secondary effluent can be calculated on the assumption that more than 10 to 20 mg/liter of petroleum in sewage will inhibit the microorganisms of the activated sludge system (Reed, 1972). The activated sludge process will remove between 50-70 percent of these hydrocarbons leaving a maximum 6 to 10 mg/liter petroleum hydrocarbons in the effluent. Hydrocarbons which reach the soil surface can be degraded slowly by a large number of soil microorganisms (Ellis and Adams, 1961). In general, the low molecular weight hydrocarbons decompose more rapidly than those of higher molecular weight and straight chained compounds at a rate branch chained aromatics. -oxidation is the mechanism proposed for the microbial degradation of aliphatic hydrocarbons and the involvement of mixed function oxidases for metabolism of the aromatic hydrocarbons (McKenna and Kallio, 1965). Strong adsorption on soil particles with slow biodegradation should eliminate any problems with hydrocarbon residues in soil.

The last group of organic environmental toxins which will be discussed and which have caused some concern when present in effluents are detergent residues. One infamous group of surface active agents, the alkylbenzene sulfonates, (ABS) have been eliminated from use in detergents since 1965 because of their slow biodegradability. Although ABS has been largely removed from detergent mixtures, its biodegradability in sewage systems and soils is still of considerable interest. Studies by Robeck *et al.* (1963) with sand

and soil lysimeters and the Penn State group with field soils (Kardos, 1967; Kardos et al, 1968) have shown that ABS can be effectively removed from waste effluents by the soil filter. Both studies have shown that adsorption in the soil surface is extremely important in providing the necessary retention time for microbial activity to occur. The Penn State experiments recorded 70% reduction in ABS in the top few inches of the forest floor with a 97% removal at the 4-foot depth. Cropland was even more effective in removing ABS residues. Robeck et al. (1963) found that passage of effluent through 3-foot lysimeters of sand were 85 to 96 percent effective in removing ABS. The importance of soil adsorption can be seen by their observation that a 21-day lag period occurred before ABS was degraded by sewage and soil microorganisms. The use of ^{35}S ABS demonstrated that ABS was degraded to $^{35}\text{SO}_4^{2-}$ (76%) and short chain sulfonates (21%). Studies by Benarde et al. (1965) and Horvath (1972) suggest that ABS may be degraded by co-metabolism. This would certainly indicate the significance of an organic matter rich soil or surface horizon for the rapid decomposition of ABS.

The recent indictment of detergent phosphates as biostimulants in aquatic systems has resulted in the use of alternative compounds. Nitrilotriacetate (NTA) was one such alternative until it too was removed from detergents pending further testing to assure its safety in the environment. One aspect on which to base the approval of NTA for detergent use is the ability of sewage and soil microorganisms to degrade NTA. A recent study by Tiedje and Mason (1971) using mono-carboxyl labeled NTA has shown that the soil microflora can degrade NTA after a 2-4 day lag period. The pattern and rate of degradation of NTA was variable among different soils with no apparent correlation between degradation and soil texture, drainage, plant cover, or pH. Degradation was, however, dependent on aerobic conditions being maintained. Rapid degradation of the Hg, Ni, Mn, Co, Na, Cd, Pb, Cu, Fe, and Zn chelates of NTA occurred in soils which previously had been exposed to NTA.

Elimination of Pathogenic Microorganisms

Land application of sewage, primary and secondary effluent or liquid sewage sludges may present a potential health hazard because of the human and animal pathogens which these wastes contain. Among the common pathogens found in these waste materials are the bacterial pathogens Salmonella, Shigella, Mycobacterium and Vibrio comma; the hepatitis viruses, enteroviruses and adenoviruses; and the protozoan, Endamoeba histolytica (Engelbrecht and Foster, 1973). The potential health hazards associated with land disposal of sanitary wastes without disinfection are associated with the

pollution of groundwater by movement pathogenic microorganisms through the soil filter, surface runoff carrying pathogens into surface water supplied, contamination of leafy vegetables and root crops with pathogens formed during irrigation. Of the four areas listed above, the microbial component of the soil filter will be of particular significance in the first two. Both the chance of pathogens moving through the soil column into groundwater and movement off the soil surface by runoff will depend in part on their survival time in soil.

The initial soil reactions influencing the removal of pathogens from liquid wastes are physical entrapment and chemical adsorption by the soil, primarily at the soil surface (McGauhey and Krone, 1968). Once the microorganisms are retained the primary consideration is the length of survival of these organisms in the soil matrix.

An extensive compilation of scientific literature has addressed itself to the survival of pathogenic microorganisms in natural environments including the soil (Van Donsel et al, 1967; Law, 1968). Fortunately, most studies indicate a rather rapid die back of coliforms and bacterial pathogens reaching the soil so that the long term hazard to groundwater or surface waters are considered minimal under normal conditions (McGauhey and Krone, 1967; Van Donsel et al, 1967). A review by Rudolfs et al. (1950) cites reports of the survival of *Salmonella* for periods as long as 6 months to one year. Fecal streptococci from digested sewage sludge have been found to survive up to 6 months in a clay soil but not in a silt loam or sandy soil (Miller, 1972). *Escherichia coli* and *Aerobacter aerogenes* have been reported to survive up to four years in soil (Mallman and Mack, 1961).

Attempts have been made to ascertain the mechanisms by which pathogenic and coliform microorganisms are eliminated from the soil. Both abiotic and biotic factors have been considered significant. Abiotic factors considered important to the persistence of pathogenic microorganisms in soil are texture, moisture, pH, aeration, temperature and organic matter content. This paper will not review any of these aspects in detail, and readers are referred to the following references for more information (Van Donsel et al, 1967; Law, 1968, Rudolfs et al, (1950). The participation of the soil microorganisms of the living filter in these processes would be only indirect as microbial activity would alter soil pH, aeration, and organic matter content. More important to our discussion are the mechanisms by which soil microorganisms directly participate in the elimination of pathogenic microorganisms from the soil. Rapid die back of pathogenic microorganisms in soil would seem to be an example of a "homeostatic" reaction of the soil microbial community which maintains the constancy of the community (Alexander, 1971a). An ecological explanation of this phenomenon is that all of the potential niches are occupied in the complex environment of

the soil so that the potential invaders find it difficult to gain a foothold. The exact mechanisms involved in the elimination of the foreign microorganisms eg. pathogenic bacteria, viruses and protozoa from the soil environment are difficult to ascertain. The possibilities included the production of microbial toxins; enzymatic lysis; predatory protozoa; parasitic bacteria, fungi, and phage; and the inability of the aleins to compete effectively with the indigenous community for nutrients.

In summary, it seems likely that the soil filter will effectively eliminate the pathogenic bacteria and protozoa reaching the soil from applications of secondary effluent or sewage sludge. Survival of viruses is still an open question because of the paucity of information on this topic. The limiting factor in the elimination of all pathogens may be the effectiveness of the physical and chemical processes of the soil filter in retaining the pathogens long enough for their elimination by the soil microbial population. Movement through coarse texture soils or surface cracks of fine textured soils could certainly provide a means to circumvent the effectiveness of the biological portion of the soil filter.

MICROBIAL REACTIONS WHICH INFLUENCE THE MOBILITY AND PLANT AVAILABILITY OF IONS IN SOIL

Of the many problems which would limit the usefulness of land disposal of municipal wastewaters and sludges, those involving the accumulation and movement of N, P and various heavy metal ions are potentially the most serious. For instance, movement of N or P through soil or off the soil might accelerate the processes of eutrophication in streams and lakes; accumulation of NO_3^- -N at a concentration greater than 10 mg/liter in ground or surface water supplies may cause methemoglobinemia in children or nitrate toxicity in animals; movement of potentially toxic or nuisance levels of metal ions into groundwater may cause a deterioration of water quality; and accumulation and increased solubility of heavy metal ions in soil may cause phytotoxic effects and reduce the renovation capacity of the plant component of the soil filter. The magnitude of the above problems should normally be greater with liquid sewage sludges than with the more dilute secondary effluents. It is the purpose of this section to discuss the influence of the soil microbial population on the mobility and solubility of nutrient and heavy metal ions in soil. The biochemical reactions of interest are mineralization, immobilization, oxidation, reduction, chelation, volatilization, and precipitation.

Nitrogen - The microbial reactions involving nitrogen which are of significance to the functioning of the "soil filter" are mineralization, nitrification, and denitrification. Secondary effluent contains rather modest concentrations of both NH_4^+ -N (9.8 mg/l) and NO_3^- -N (8.2 mg/l) with a small amount of organic N primarily

as protein (2.0 mg/l). The values given are typical values (Reed, 1972) and may differ considerably depending upon the efficiency and retention time of the treatment system.

Because secondary effluent has a low C:N ration of <10:1, a net mineralization of nitrogen will occur in the soil. This mineralized ammonium nitrogen as well as the ammonium nitrogen in the effluent will be held by the soil exchange sites until nitrified by the activity of the chemosynthetic autotrophs, Nitrosomonas and Nitrobacter. Nitrification should proceed at a rapid rate in all agricultural soils irrigated with secondary effluent at rates which maintain aerobic conditions. The obvious exception will be in those climatic regions where low winter temperatures will reduce microbial activity. Nitrification of ammonium nitrogen reaching acid forest soils may be limited by the absence of nitrifying bacteria. It is possible that irrigation with waste effluents may provide conditions which would allow a population of nitrifying bacteria to develop.

Once formed, NO_3^- is very mobile and will be leached from the soil as water moves through the profile. The factors affecting nitrate movement in soils have recently received a great deal of attention and will not be covered in this paper (Viets and Hageman, 1971). However, of considerable importance to the efficiency of the total "soil filter" will be the adsorption and utilization of NO_3^- by the actively growing agronomic crop or forest vegetation. Studies at Penn State University (Kardos, 1967; Kardos et al, 1968) have demonstrated the effectiveness of vegetation in removing effluent nitrogen from soil and maintaining the integrity of the soil filter.

Activated sludge (avg 5.6% N) and digested sewage sludge (avg 2.4% N) contain a considerable quantity of nitrogen (Burd, 1968) half of which is in the ammonium form. When sewage sludge is applied to land for the purpose of disposal, there is a tendency to apply as large a quantity of sludge as possible. A recent U.S. Dept. of Interior report has recommended sludge application rates of 10 to 40 tons of dry solids per acre which would contain 480 to 1920 lbs of N per acre (Burd, 1968). Hinesly et al. (1971) have proposed that no more than 2 inches of anaerobically digested sewage sludge be added to supply the nitrogen needs of a non-leguminous crop. Even this rate of application supplies over 600 lbs of N per acre. It is apparent from these reports that one potential problem associated with disposal of liquid sludges on land will be an excess of nitrogen above that which the growing crop can assimilate. If nitrification of the excess ammonium nitrogen originally present or subsequently mineralized occurs and NO_3^- moves through the soil profile considerable nitrate enrichment of groundwater or surface waters may occur. Lysimeter studies (Hinesly et al, 1971) conducted on light silt loam soils by the

University of Illinois have shown that nitrification does occur in soil amended with from 5 to 10 inches (1650-3000 lbs of N/acre) of liquid digested sewage sludge. Nitrate nitrogen found in the leachate was considerably higher than unfertilized check plots or control plots receiving 200 lbs of N per acre as commercial fertilizer. The significance of the plant cover in nitrogen renovation was shown by the fact that no water and accompanying nitrate moved through the 4-foot lysimeters during the summer months. It should be readily apparent from these studies that the soil filter is permeable to high applications of nitrogen in liquid wastes.

The preceding discussion has emphasized one of the more critical problems associated with the microbial component of the soil filter, namely nitrification. It is perhaps fortunate that a second microbial reaction associated with nitrogen, biological denitrification is potentially useful in alleviating the potential pollution hazard associated with the formation and movement of NO_3^- .

Biological denitrification involves the loss of N_2 and N_2O during anaerobic respiration in which NO_3^- is used as an electron acceptor. The microorganisms involved are primarily facultative anaerobic heterotrophic bacteria. Conditions which favor biological denitrification would include a near neutral pH, a readily available source of carbonaceous substrate, and anaerobic conditions ($E_h \sim +200\text{mV}$).

The significance of biological denitrification during disposal of wastes on land is difficult to evaluate. Undoubtedly applications of secondary effluents to agricultural land, regardless of the mode of application, should provide at least temporary periods of anaerobiosis and sufficient substrate for some loss of nitrogen to the atmosphere. This will be true even though proper management of soils for wastewater disposal require that aerobic conditions are maintained. The reason for this apparent anomaly is anaerobic microsites can occur in soils considered aerobic (Broadbent, 1973).

Denitrification losses from soils which have been amended with liquid sewage sludges should exceed that from secondary effluents because of the organic matter supplied. This author is not familiar, however, with any quantitative evaluation of denitrification from sludge amended soils.

In conclusion, it seems apparent that biological denitrification will remove some NO_3^- from soils during waste renovation on agriculture soils. If the pH of forest soils will allow a build-up of nitrifying bacteria with subsequent nitrification, it is also likely that the heterotrophic denitrifying bacteria will also be present. It is doubtful that much can be done to increase biological denitrification on spray irrigation sites where growing crops are being maintained. Rapid infiltration systems such as that at Flushing

Meadows (Bouwer, 1973) and the overland flow systems for waste disposal should be able to take greater advantage of denitrification for NO_3^- removal.

Phosphorus - Phosphorus will be present in secondary effluent (10 mg/l) primarily as orthophosphate; as the condensed phosphates, meta and polyphosphates; and as organic phosphate (Reed, 1972). Sewage sludges contain high concentrations of phosphorus (0.7 - 3.9%) (Burd, 1968). Although the chemical identity of sludge phosphorus has not been determined, it probably corresponds closely to that of secondary effluent.

Chemical fixation of orthophosphate by Fe, Al, Ca, and clay minerals in soil and plant removal provide the primary mechanisms for the renovation of waste phosphorus by the soil filter. Soil microorganisms influence the effectiveness of soil renovation primarily by mineralizing orthophosphorus from the more mobile organic and condensed phosphates so that the fixation reactions can occur. The significance of the microbial reduction of ortho P to volatile PH_3 and the synthesis of inorganic poly P in soils (Ghonsikar and Miller, 1973) has presently not been evaluated.

Sulfur - The primary chemical forms of sulfur in secondary effluent will be SO_4^{2-} with small amounts as organic sulfur. Sewage sludges will be higher in organic sulfur but will also contain some insoluble metal sulfides and hydrogen sulfide. If aerobic conditions are maintained in the soil during waste disposal the microbial reactions of primary interest are the oxidation of metal sulfides and H_2S to SO_4^{2-} which is both mobile and available to higher plants. Mineralization of organic sulfur will probably be of greater significance than immobilization when waste materials are added to soils with the result that the pool of soluble SO_4^{2-} will increase.

Improper management of liquid waste disposal on land which creates anaerobic soil conditions will result in SO_4^{2-} reduction to H_2S . Hydrogen sulfide can in turn react with various metal ions to form insoluble sulfides. Ferrous sulfide has been implicated as one of the chemical components responsible for intensifying soil clogging during wastewater irrigation (Reed, 1972).

Inorganic ions - Waste effluents contain relatively low concentrations and sewage sludges high concentrations of metallic and non-metallic cations and anions (Ewing and Dick, 1970; Lagerwerff, 1967). The exact composition of these waste with regards to inorganic constituents is extremely variable and dependent upon the industrial sources which contribute wastes to the sanitary treatment system as well as the treatment processes itself.

When secondary effluents are applied to soils most of the heavy metals are retained within the surface horizon by interactions with soil organic matter and colloidal clay minerals; or by precipitation as insoluble oxides, hydroxides, phosphates, or sulfides. In the case of applied sewage sludge, the sludge solids will retain most of the metal ions until released by the microbial decomposition of the sludge organic matter.

Addition of these inorganic constituents to soils in liquid wastes presents a potential problem because of their movement into groundwater, destroying water quality; or by their accumulation to phytotoxic levels in the soil. The latter effect would reduce the efficiency of the higher plant component of the "soil filter" for waste renovation. In addition a particular element may be taken up in such concentration that the intended use of the harvested plant material for human or animal consumption may be curtailed.

Soil reactions of iron and manganese are similar in many ways and thus will be discussed together. A detailed discussion of the relative significance of each reaction to the mobility of Fe and Mn is beyond the scope of this paper, but a few salient remarks will be made about each. The readers are referred to an excellent symposium Mortvedt et al. (1972) for further information on the soil reactions of these and other micronutrient ions. Unfortunately, much of this information is based on soil reactions at low concentrations of inorganic ions. Considerably more information is needed on the interactions of inorganic ions in soils at the high concentrations likely to be encountered after prolonged applications of waste effluents and sewage sludges.

The iron and manganese in well aerated soils and at near neutral pH's will be primarily found in the oxidized state as insoluble organic matter complexes and insoluble oxides, hydroxides, and phosphates. The concentration of these individual ions in the aqueous phase is normally very low, often in the parts per billion range. The ions which are found are considered to be primarily in organic combination as soluble metal-organic matter complexes (Lindsay, 1972; Geering et al, 1969). Organic compounds capable of forming chelates are continuously being produced in soil by microbial activity. Most of these compounds can in turn be decomposed so the amount present in the soil solution represents a balance between synthesis and destruction. Since chelating agents have the ability to transform solid phase forms of Fe and Mn (hydroxides, phosphates, etc.) into soluble metal complexes, their production during decay of organic waste materials are likely to increase the availability of these ions to plants, and their mobility through the profile. The degradation of the soluble organic matter-metal complexes, as well as the insoluble organic matter complexes will again release Fe and MN ions which will again be precipitated or recomplexed. Some microorganisms can also form mineral acids (nitric and sulfuric) which would solubilize some of the oxides, hydroxides, or phosphates).

Another microbial process of considerable significance to the mobility of Fe and Mn is that of reduction. If a soil becomes waterlogged during irrigation with liquid wastes the Fe^{2+} and Mn^{2+} level in soil rises rapidly. Ferrous and manganous ions are highly mobile in soil and may, under prolonged anaerobic condition, move through the soil profile into water supplies or form a water impermeable layer in the B horizon (Döring, 1960; Bocho, J., 1965). The presence of available organic substrates enhances the reduction of both ions. The reduction of Fe^{3+} has been shown to be entirely a result of microbial activity, while Mn^{4+} reduction is almost exclusively microbial at a pH >6.0 (Alexander, 1961). The reduction of both ions may occur as an indirect result of microbial activity in lowering soil pH, or of the E_h by depletion of O_2 ; or by direct reduction with both Fe^{3+} and Mn^{4+} serving as electron acceptors in cell respiration. Biological reoxidation of both Fe^{2+} and Mn^{2+} has been shown to occur in soils (Aristovskaya and Zavarazin, 1971; Ehrlich, 1971) although chemical oxidation of Fe^{2+} can occur at a near neutral pH, and Mn^{2+} at a pH >8.0.

Under anaerobic conditions and in the presence of high concentrations of H_2S , insoluble sulfides of both Fe and Mn can be formed in soil (see section on sulfur). The effect of sulfide formation will be to reduce the mobility of Fe and Mn.

The microbial reactions which influence various heavy metals ions are like those of Fe and Mn but do not include oxidation-reduction reactions. As with Fe and Mn a very large percentage of the ion present in solution probably occurs as soluble organic complexes (Lindsay, 1972). The quantity of all of these heavy metals which will be retained by the "soil filter" after repeated application of metal containing wastes will be largely related to the organic matter content of the soil. Unfortunately very little is known concerning the relative amounts of the various metal ions which will occur as organic-metal complexes or of the factors affecting the availability of the organically bound nutrients to plants. Experiences at the Paris and Berlin sewage farms have indicated that "exhausted" soils high in organic matter retained a larger total amount as well as soluble Cu and Zn (Rohde, 1962). Studies at the University of Illinois by Hinesly et al. (1971) have shown that plants grown in soil amended with liquid digested sewage sludge contained a greater concentration of Zn, Mn and Fe but not Ni and Cu. They attributed the enhanced uptake in part to the addition of the elements in the sludge as well as the indirect effect of sludge on increasing the availability of the metal ions.

A third group of inorganic ions K^+ , Mg^{2+} , Ca^{2+} , and Na^+ are also found in waste effluents and sewage sludges. None of these cations are complexed strongly by soil organic matter and their retention in soil is related to normal exchange reactions on clay minerals and organic colloids. The microbial population of soils has little effect on the reactions of these ions except indirectly in the formation and degradation of soil organic matter.

A couple of other microbial reactions could possibly influence the mobility of metal ions in soils. One involves the alkylation of certain metals to volatile derivatives. Thus far, the microbial alkylation of Hg, Se, Te, and As has been demonstrated to occur (Alexander, 1971b; Ehrlich, 1971). Whether these laboratory phenomena have any significance in the soil environment remains to be evaluated. A second reaction would be the immobilization of metal ions within microbial cells. Although there are some examples of very large accumulations of metal ions within microbial cells in culture, it is doubtful if this reaction will be of any significance in the soil reactions of metal ions.

CONCLUSIONS

The preceding discussion has reviewed in moderate detail the various microbial reactions which influence the success of soil as a filter for renovating municipal wastewater and sludge. The majority of these activities are beneficial, actually essential, for maintaining the integrity and effectiveness of the soil filter. Only one reaction, nitrification, can be considered detrimental to the success of the soil filter when the disposal method maintains adequate soil aeration.

It should also be emphasized that prolonged periods of anaerobiosis must be avoided for the proper functioning of the microbial component of the soil filter. Proper management of land disposal systems for liquid waste regardless of the mode of application must provide for periods of adequate aeration. Failure to do so will result in reduced decomposition of organic wastes, odors, reduction and mobilization of Fe and Mn, changes in the solubility of other inorganic ions, and inundation of vegetative cover. In addition, anaerobic conditions in the soil seem to intensify the clogging of the soil surface with microbial cells, polysaccharides, and ferrous and manganous sulfides which reduces water infiltration.

REFERENCES

- Alexander, M. 1961. Introduction to Soil Microbiology, John Wiley and Sons, Inc., N. Y.
- Alexander, M. 1965a. Biodegradation problems of molecular recalcitrance and microbial fallibility. *Adv. Appl. Microbiol.* 7, 35-80.
- Alexander, M. 1965b. Persistence and biological reactions of pesticides in soils. *Soil Sci. Soc. Amer. Proc.* 29, 1-7.
- Alexander, M. 1971a. Microbial Ecology. John Wiley and Sons, Inc., N. Y.
- Alexander, M. 1971b. Biochemical ecology of microorganisms. *Ann. Rev. Microbiol.* 25, 361-392.
- Aristovskaya, T. V. and G. A. Zavarzin. 1971. Biochemistry of iron in soil. Ch. 13, In Soil Biochemistry, vol. 2, A.D. McLaren and J. Skujins (ed.) Marcel Dekker, Inc., N. Y.
- Benarde, M. A., B. W. Doft, R. Horvath, and L. Shaulis. 1965. Microbial degradation of the sulfonate of dodecyl benzene sulfonate. *Appl. Microbiol.* 13, 103-105.
- Bouwer, H. 1973. Renovating secondary sewage effluent by groundwater recharge with infiltration basins. Recycling treated municipal wastewater and sludge through forest and cropland. The Pennsylvania State University Press.
- Bocko, J. 1965. Displacement of iron in soil irrigated with sewage. *Zesz. nauk. Wyzsz. Szk. roln. Wrocl. Melior.* 10: 61, 209-217. Abstract only, *Soils and Fertilizers* 29, 527.
- Broadbent, F. E. 1973. Factors affecting nitrification-denitrification in soils. Recycling treated municipal wastewater and sludge through forest and cropland. The Pennsylvania State University Press.
- Burd, R. S. 1968. A study of sludge handling and disposal. Water Pollution Control Research Series Publication WP-20-4, U.S. Dept. of the Interior.
- Clark, F. E. 1967. Bacteria in soil. In Soil Biology, A. Burges and F. Raw (ed.) Academic Press, N. Y.
- Clark, F. E. and E. A. Paul. 1970. The microflora of grassland. *Adv. Agronomy* 22, 375-435.
- Dagley, S. 1967. The microbial metabolism of phenolics. In Soil Biochemistry, vol. 1, McLaren, A. D. and G. H. Peterson (ed.) p 287-318. Marcel Dekker, Inc., N. Y.
- Döring, H. 1960. Chemical causes of soil fatigue following irrigation with sewage water in Berlin, and possibilities of preventing the decrease in crop yields. *Dtsch. Landw.* 11, 342-345.
- Ehrlich, H. L. 1971. Biogeochemistry of the minor elements in soil. Ch. 12, In Soil Biochemistry, vol. 2, A. D. McLaren and J. Skujins (ed.) Marcel Dekker, Inc., N. Y.
- Ellis, R., Jr. and R. S. Adams, Jr. 1961. Contamination of soils by petroleum hydrocarbons. *Adv. Agronomy* 13, 197-216.

- Ewing, B. B. and R. I. Dick. 1970. Disposal of sludge on land. In Water Quality Improvement by Physical and Chemical Processes. University of Texas, Austin.
- Foster, D. H. and R. S. Engelbrecht. 1973. Microbial hazards in disposing of wastewater on soil. Recycling treated municipal wastewater and sludge through forest and cropland. The Pennsylvania State University Press.
- Geering, H. R., J. F. Hodgson, and C. Sdano. 1969. Micronutrient cation complexes in soil solution: IV. The chemical state of manganese in soil solution. *Soil Sci. Soc. Amer. Proc.* 33, 81-85.
- Ghonsikar, C. P. and R. H. Miller. 1973. Naturally occurring inorganic polyphosphates in soil. *Soil Sci.* (In Press).
- Gibson, D. T. 1968. Microbial degradation of aromatic compounds. *Sci.* 161, 1093-1097.
- Glathe, H. and A. A. M. Makawi. 1963. Über die Wirkung von Klarschlamm auf Boden und Mikroorganismen. *Z Pfl Ernähr Düng.* 101, 109-121.
- Hallam, M. J. and W. V. Bartholomew. 1953. Influence of rate of plant residue addition in accelerating the decomposition of soil organic matter. *Soil Sci. Soc. Amer. Proc.* 17, 365-368.
- Hinesly, T. D., O. C. Braids, and J. E. Molina. 1971. Agricultural benefits and environmental changes resulting from the use of digested sewage sludge on field crops. Report SW-30d, U.S. Environmental Protection Agency.
- Horvath, R. S. 1972. Microbial co-metabolism and the degradation of organic compounds in nature. *Bacteriol. Rev.* 36, 146-155.
- Hunter, J. V. and T. A. Kotalik. 1973. Chemical and biological quality of treated sewage effluent. Recycling treated municipal wastewater and sludge through forest and cropland. The Pennsylvania State University Press.
- Jackson, R. M. 1965. Studies on fungi in pasture soils. 2. Fungi associated with plant debris and fungal hyphae in soil. *New Zealand Jour. Agric. Res.* 8, 865-877.
- Jenkinson, D. S. 1966. Studies on the decomposition of plant material in soil II. Partial sterilization of soil and soil biomass. *Jour. Soil Sci.* 17, 280-302.
- Jensen, H. L. 1963. Recent advances in soil microbiology. *Sci. Hort.* 15-21.
- Kardos, L. T. 1967. Wastewater renovation by the land - a living filter. In Agriculture and the Quality of Our Environment. N. C. Brady (ed.) AAAS Publication 85, Washington, D. C.
- Kardos, L. T. 1970. A new prospect. *Environment* 12, 20-21, 27.
- Kardos, L. T., W. E. Sopper, and E. A. Myers. 1968. A living filter for sewage, In Science for Better Living, p 197-201 U.S. Dept. of Agriculture. Yearbook of Agriculture, Washington, D.C.
- Krasilnikov, N. A. 1944. The bacterial mass of the rhizosphere of plants. *Mikrobiologia* 13, 144-146.

- Lagerwerff, J. V. 1967. Heavy-metal contamination of soils. In Agriculture and the Quality of Our Environment. N. C. Brady (ed.) AAAS Publication 85, Washington, D.C.
- Latter, P. M. and J. B. Cragg. 1967. The decomposition of Juncus squarrosus leaves and microbiological changes in the profile of Juncus moor. Jour. Ecol. 55, 465-482.
- Lake Erie report - A plan for water pollution control. U.S. Dept. of Interior, Fed. Water Poll. Control Admin. 1968.
- Law, J. R., Jr. 1968. Agricultural utilization of sewage effluent and sludge. An annotated bibliography. Fed. Water Poll. Control Admin. U.S. Dept. of Interior.
- Lindsay, W. L. 1972. Role of chelation in micronutrient availability, Ch. 17. In E. W. Carson (ed.) The Plant Root and Its Environment. University of Virginia Press, Charlottesville.
- Mallman, W. L. and W. N. Mack. 1961. Biological contamination of groundwater. Groundwater Contamination, U.S. Public Health Service Tech. Rept. W61-5, p 35-43.
- McCoy, J. H. 1971. Sewage pollution of natural waters. In Microbial Aspects of Pollution, G. Sykes and F. A. Skinner, (ed.) Academic Press, N. Y.
- McGauhey, P. H. and R. G. Krone. 1967. Soil mantle as a wastewater treatment system. Engineering Research Laboratory Report 67-11, Univ. of Calif., Berkeley.
- McKenna, E. J. and R. E. Kallio. 1965. The biology of hydrocarbons. Ann. Rev. Microbiol. 19, 183-208.
- McLaren, A. D. and G. H. Peterson. 1967. Soil Biochemistry, vol. 1, Marcel Dekker, Inc. N. Y.
- Miller, R. H. 1972. The microbiology of sewage sludge decomposition in soil. Unpublished report. Dept. of Agronomy, The Ohio State University.
- Mortvedt, J. J., P. M. Giordano and W. L. Lindsay. (ed.) 1972. Micronutrients in Agriculture. Soil Sci. Soc. Amer., Inc. Madison, Wisc.
- Painter, H. A., M. Viney, and A. Bywaters. 1961. Composition of sewage and sewage effluents. Jour. Inst. Sew. Purif. Pt. 4, 302.
- Reed, S. C. 1972. Wastewater management by disposal on the land. Special Report 171, Cold Regions Research and Engineering Laboratory, Hanover, N. H.
- Robeck, G. G., J. M. Cohen, W. T. Sayers, and R. L. Woodward. 1963. Degradation of ABS and other organics in unsaturated soils. Jour. Water Poll. Control Fed. 35, 1225-1236.
- Rohde, G. 1962. The effects of trace elements on the exhaustion of sewage irrigated land. Jour. Inst. Sew. Purif. Pt. 6, 581-585.
- Rudolfs, W., L. L. Falk and R. A. Ragotzkie. 1950. Literature review of the occurrence and survival of enteric, pathogenic and relative organisms in soil, water, sewage, sludges and on vegetation. Sewage Ind. Waste 22, 1261-1281.

- Russell, E. J. 1950. Soil Conditions and Plant Growth, 8th Ed., Longmans, Green and Co., London.
- Sopper, W. E. 1971. Effects of trees and forests in neutralizing waste. Institute for Research on Land and Water Resources, The Pennsylvania State University, University Park, Pa. Reprint Series 23.
- Stockli, A. 1956. Mitt. Schveiz. Landwirt. 8, 125-130. In F. E. Clark and E. A. Paul. 1970. The Microflora of Grassland Adv. in Agronomy 22: 404.
- Tiedje, J. M. and B. B. Mason. 1971. Biodegradation of nitrilotriacetic acid (NTA) in soils. Bacteriol. Proc. p 1.
- Thomas, R. E. and T. W. Bendixen. 1969. Degradation of wastewater organics in soil. Jour. Water Poll. Control Fed. 41, 808-813.
- Van Donsel, D. J., E. E. Geldreich and N. A. Clarke. 1967. Seasonal variations in survival of indicator bacteria in soil and their contribution to storm-water pollution. Appl. Microbiol. 15, 1362-1370.
- Viets, F. G., Jr. and R. H. Hageman. 1971. Factors affecting the accumulation of nitrate in soil, water, and plants. Agriculture Handbook No. 413, ARS, USDA Washington, D.C.

SITE SELECTION CRITERIA FOR WASTEWATER
DISPOSAL -- SOILS AND HYDROGEOLOGIC CONSIDERATIONS

321 D

Richard R. Parizek
Department of Geosciences and The Mineral Conservation Section
The Pennsylvania State University

Site selection criteria for sewage effluent spray irrigation sites are discussed. Soils, geology, hydrology, topography, project management and other factors are considered to maximize the chances for achieving a high degree of renovation of waste constituents while at the same time minimizing secondary environmental problems that can result such as -- degradation of groundwater quality, water logging of soils, surface runoff and erosion, and local flooding. Site conditions suitable and unsuitable for groundwater recharge and reuse are pointed out as are factors to be considered when designing monitoring programs necessary to prove the degree of treatment being achieved, hence the success or failure of a particular irrigation operation. Finally, the importance of the hydrogeologic-soil condition is discussed for the benefit of administrators who are responsible for defining environmental policy and preparing guidelines for design, regulation and enforcement procedures to be used for wastewater irrigation projects.

Comments are not based solely on experiences gained with the Penn State Wastewater Project. Rather, basic principles are considered which should apply when selecting irrigation sites or designing and operating irrigation systems in many areas. Experiences from our own project as well as other successful and unsuccessful projects in Pennsylvania and elsewhere are used for illustration.

SIGNIFICANCE OF THE SOILS, GEOLOGIC, AND HYDROLOGIC CONDITIONS

Significance of various physical and geochemical factors to be considered when selecting irrigation sites vary depending on the quality of wastewater to be applied, acreage required, amount and duration of wastewater application, water quality standards to be met for the receiving body of water, climate, other uses to be made of the irrigation site, seasons of year water is to be applied, attention that is likely to be given to managing the irrigation project, and a number of other factors.

For example, where effluent is being used primarily as a source of irrigation water and is being applied solely as a benefit to crops, the amount and quality of water best suited to plant growth and the intended use of the crop may be the limiting factors. How

often and how much water should be applied and by what method to achieve the best growth response at least cost? Almost any soil and cover crop condition can benefit from sewage effluent when application rates are equal to or less than evapotranspiration rates because under these conditions little if any effluent moves through the soil. The soil moisture reservoir becomes a physical barrier to water movement whenever the soil-water content drops below field capacity. The residence time of effluent in the biologically active zone is prolonged in such a climatic setting and effluent is depleted mainly by evapotranspiration rather than deep percolation. In more humid regions this procedure would be impractical because water could be applied only from time to time as weather conditions dictate. More frequent applications would be possible in arid to semi-arid regions.

Prolonged use of this practice in more arid regions, balancing application rates with evapotranspiration rates, however, would result in a salt or total dissolved solids build-up in shallow soils, an increase in the salinity of return flow and occasional groundwater recharge of poor quality. This normally would not be a problem in humid regions because precipitation is available to provide dilution.

When planning to apply wastewater in arid to semi-arid regions, considerable attention must be given to site selection and land management to be assured that the irrigation area will not be chemically degraded and the agricultural productivity destroyed. A considerable experience has been gained in applying waters with a high total dissolved solids content in arid and semi-arid regions with both favorable and devastating results. This general problem has been studied by others and is well documented in the literature. For example, Fireman and Heywood (1955). Several points are obvious. Application rates combined with precipitation must exceed evapotranspiration rates to insure that soluble salts are leached from the soil. Good subsurface drainage is desirable as is a rather deep water table to minimize groundwater evapotranspiration losses and a resulting salinity build-up. There is a limit particularly for large projects to how many times reclaimed effluent should be recycled from the community to the treatment site to avoid a long term increase in total dissolved solids. It is desirable to have thorough drainage of return flow or an open rather than a closed geochemical system. In the latter, the total dissolved solids will accumulate and ultimately may cause problems.

Most wastewater irrigation projects will not be operated only when irrigation water is required. Rather, to be feasible, they must operate during periods when soil moisture is in excess of plant requirements, and the moisture content is at or above field capacity. The more irrigation rates exceed evapotranspiration rates the more important topography, soils, geologic, hydrologic and other factors

become in the selection of irrigation sites to insure sufficient and long-termed renovation of waste constituents. No one of a number of factors to be considered under these circumstances needs to be limiting or controlling but rather these factors must be considered together.

Other authors in these proceedings have stressed the role and importance of biological, chemical and physical processes in wastewater renovation which must work in tandem to provide a maximum degree of renovation. The basic processes involved are summarized in Table 1. These processes operate primarily within the biologically active zone of shallow soils and in deeper soils and rock above and below the water table. The soil and rock substrate and the soil-water and groundwater they contain serve more than just as a substrate for the biological community--the living filter which accounts for most of the renovation achieved. Rather they exert an active physical and geochemical role as well which helps to increase the efficiency of the treatment system and provide protection or a factor of safety against the premature or eventual breakthrough of waste constituents to the groundwater or surface water reservoir. This can occur during prolonged use of irrigation sites, during periods of excessive application accompanying pipe line breaks or leaks, where runoff and local ponding at the surface and in the subsurface redistributes effluent and causes heavy loadings, during heavy precipitation, during winter irrigation, and melting of snow and ice packs.

It is desirable, therefore, in site selection studies to consider those aspects of the soils, geologic and hydrologic condition that will help to maximize and prolong the renovation process, hopefully, indefinitely.

Characteristics of an Ideal Site

There is little point in defining site characteristics so specifically and rigidly that they can rarely be met under the great variety of conditions likely to be encountered in the field. It is desirable to outline conditions that should be strived for when selecting wastewater renovation sites. The very best and most conservative sites should always be selected when choices are available. In this manner secondary environmental problems can be minimized or eliminated and the life of the renovation system, hence the project, prolonged indefinitely. Fewer choices are available for small projects where effluent must be treated close to its source. If site conditions are poor at these locations, land application may not be the answer. For larger projects where millions to tens of millions of gallons of effluent a day are involved, proximity to the source is far less important than obtaining a suitable site.

TABLE 1. Summary of Physical, Geochemical and Biochemical Processes that Contribute to the Renovation of Solid and Liquid Waste Materials (After Farizek and Langmuir, 1971)

Physical Processes
Filtration
Dispersion
Dilution
Adsorption-desorption
Gas transfer
Geochemical Processes
Complex ion pair formation
Acid-base reactions
Inorganic redox reactions
Ion exchange
Precipitation-solution
Biochemical Processes
Solute uptake in biosynthesis
Solubilization of cellulose, etc.
Mineralization of organics
Catalysis of inorganic redox reactions

It is equally important that regulatory officials responsible for adopting policy guidelines for irrigation projects or for reviewing, approving and policing irrigation projects maintain a flexible viewpoint as well because many sites that may appear to depart drastically from the ideal may in fact be found to be suitable under actual use. For example, poorly drained soils may actually provide a higher degree of nitrate removal when compared to better drained soils. Control of nitrate concentrations in groundwater at irrigation sites is one of the main challenges that users of the irrigation system face. Nitrate removal can be one of the weakest links in the irrigation concept.

It is possible to engineer some sites to improve infiltration and drainage, improve renovation, control groundwater levels, prevent trespass of wastewater by overland or subsurface flow, control wind drift of effluent, etc. Regulatory officials should encourage innovation and originality among those designing and operating irrigation projects because each project must be designed as a separate unit and each will have its own special problems and challenges that must be worked out. There is no single fixed blue print for wastewater irrigation systems that can be used under all field circumstances.

Infiltration and Drainage

Sewage effluent must infiltrate into soil and be retained for a sufficient period within the biologically active zone to be acted upon by renovation agents. Some renovation may be achieved during overland flow but this is not as effective as when effluent enters and is retained within the soil. Reduction in BOD, removal or reduction of suspended solids and bacteria, etc. can be expected during overland flow. After infiltrating into the soil, some of the effluent may be withdrawn and consumed by evapotranspiration, some may percolate to the water table or move laterally as interflow and be returned to surface. Lateral flow need not be bad at irrigation sites provided that the effluent has been renovated prior to being discharged to the surface and provided that other wastewater is not being applied to these soil-water discharge areas, particularly the larger ones. Some lateral flow is inevitable particularly when effluent is being applied in humid regions, on sloping ground or on soils where the B-horizon, caliche layers, plow soles and stratification within or below the C-horizon help promote lateral movement. Effluent has been sampled at the Penn State research facility after having moved laterally through soil for 25 to more than 250 feet before being discharged to the surface or intercepted in a 17-foot deep trench lysimeter. Water was found to be of favorable quality wherever it had entered the soil and had a residence time sufficiently long to permit renovation.

Natural soil or at least fine-grained unconsolidated material is always preferred at irrigation sites over mechanically weathered bedrock, quarry wastes, artificial fills containing a wide variety of waste materials and grain sizes. The latter can have high or excessive infiltration capacities and may be too well drained to favor renovation when compared to most natural soils. A moderately well drained to well drained soil would appear to meet both infiltration and drainage requirements for an irrigation area. However, even less well drained soils can be considered provided that effluent is not being applied during prolonged rainy periods, periods of heavy rainfall or freezing weather.

Values of hydraulic conductivity of different soils have been reported by O'Neil (1949), and Smith and Browning (1946). These may serve as a guide when considering soils for irrigation projects (Table 2).

Soils in the extremely slow to very slow class are bound to create water logging and runoff problems at irrigation sites and neither can be drained effectively to control the water table position. Soils in the slow class may require artificial drainage to control water levels, and improve on aeration conditions. These soils may prove to afford better nitrate removal when compared with

TABLE 2. Classes of Permeability or Percolation Rates for Saturated Sub-soils (Expanded from Smith and Browning, 1946)

Class	Hydraulic Conductivity or Percolation Rate inches/hour	Comments
Extremely slow	<0.001	So nearly impervious that leaching process is insignificant. Unsuitable for wastewater renovation under most circumstances.
Very slow	0.001- 0.01	Poor drainage results in staining; too slow for artificial drainage. Wastewater renovation possible under restricted conditions.
Slow	0.01 - 0.1	Too slow for favorable air-water relations and for deep root development. Usable under controlled conditions; drainage facilities may be required; runoff likely to be a problem. Good nitrate removal possible.
Moderate	0.01 - 1.0	Adequate permeability (conductivity) Ideal for most irrigation systems.
Rapid	1 -10	Excellent waterholding relations as well as excellent permeability (conductivity). Ideal for most irrigation systems. Application rates may have to be reduced to insure renovation.
Very rapid	>10	Associated with poor waterholding conditions. Infiltration and drainage may be too rapid to achieve complete renovation. Extreme caution required.

better drained soils. Soils in the moderate to rapid class should be ideal. For soils in the very rapid class, flow rates may be excessive thus precluding a high degree of renovation. Effluent must be retained within the soil profile and subsoil for a sufficient period to allow the renovation processes to be effective. This is measured in days, not hours and will vary with climate, season of year, crop cover, etc.

At our winter irrigation site, for example, a 6-inch per week application rate (water applied during a single day) was not excessive from an infiltration standpoint. However, nitrates and MBAS were rapidly driven to depths of 17 feet in the soil after six months of winter irrigation and were below the biological zone and could not be renovated during the following growing season by biological processes. These constituents were free to migrate to the water table after adsorption requirements were met.

Where highly permeable sand and gravel, mechanically weathered bedrock, fractured bedrock, conduits and cavity systems are present beneath the soil, little if any additional treatment except dilution and dispersion should be anticipated. Renovation must be achieved within the overlying soil.

Irrigation techniques and equipment are so well advanced today that it is possible to select and achieve a 1/4-, 1/6-, 1/8-inch or even lower application rate per hour. Where, for example, a 2-inch per week amount is called for, it is possible to apply the water at a low rate over a one to two day period or at a higher rate for briefer periods but on two separate days following one or two days of rest. Many sites with poorly drained soils could be considered suitable for irrigation provided that application rates are lower than for well drained soils assuming all other factors were equal.

The infiltration capacity can be maintained or improved by adopting good farm management practices at the irrigation site. If effluent is to be applied in winter or on soils with low infiltration rates, plowed ground should be avoided. Rather, forested areas or hay fields with well established cover crops should be used. Even under favorable site conditions, local runoff is possible from time to time particularly in the winter, early spring or late fall when evapotranspiration requirements are low, soil-water contents are high, water temperatures are low, and effluent is applied during periods of precipitation.

When winter irrigation is required in northern latitudes, careful attention must be given to selecting irrigation sites that have good infiltration capacities and subsurface drainage. Forested areas are desirable. Root holes, animal burrows and thick organic litter on the forest floor tend to provide higher infiltration capacities when compared to the same soil type in adjacent grasslands or cultivated areas. Also it has been shown that a honeycomb-type frost structure or more open structure tends to form in forested areas compared to the less permeable concrete-type frost that develops in plowed ground (Storey, 1955).

At the Penn State site runoff from melting snow and ice packs composed of effluent is more pronounced in open fields than from ice packs in woodlands having the same soil type. Runoff may be traced

across sloping hayfields for 100 to more than 500 feet to where it enters forest border lands that surround our fields. Here it is lost by infiltration within 500 to 1,000 feet from the irrigation plots even during periods of quick thaw.

Runoff from the Penn State irrigation plots is less than might be expected for other facilities because closed surface sags and depressions reflecting the differential solution of underlying dolomite bedrock provide surface detention storage in fields and forests alike. These depressions trap surface water, minimize runoff, and help to promote infiltration.

Measurement of Infiltration

The infiltration process is complex and influenced by a number of variables. The problem is to assess the infiltration rate not at isolated test plots, within the area of interest, but rather for the entire project area. This is a difficult task in advance of irrigation because test plots that have adequate infiltration characteristics when tested by themselves may in fact prove to be soil-water or even groundwater discharge areas or become waterlogged after water is applied to a more general area for prolonged periods. It is as important to know how the proposed site behaves in the presence of excess water in advance of irrigation - as in the Spring - as it is to know the infiltration capacity at a number of test plots. Potential drainage problem areas need not be obvious when observing soil characteristics or type of vegetation present. Frequently problem areas can be isolated by field study following spring thaws, prolonged periods of heavy rainfall and recharge. Runoff, standing water and near saturation conditions may be observed for brief periods at sites where drainage problems are likely to occur after extensive irrigation begins.

Even experiences gained with normal agricultural irrigation practices may not prove to be foolproof in selecting irrigation sites and isolating problem areas. Normally, water is applied when there is a moisture deficit, hence, potential drainage problem areas are not as likely to be revealed. Wastewater treatment by irrigation normally requires that water be supplied in excess of evapotranspiration requirements and during periods of excess water even if winter storage is planned. Infiltration and drainage problems are maximized under these circumstances.

Infiltrimeters either of the flooding or sprinkler type may be used to evaluate infiltration rates at test plots with the reservations mentioned. Methods involved have been described by Chow (1964), Gray, Norum and Wigham (1970) and others. Parizek and Myer (1968) pointed out that preliminary estimates of drainage problems can be

obtained from experience or by conducting trial irrigation operations on site using potable water. Areas with poorest drainage might be tested at rates in excess of what is planned during normal operation to determine the worst possible drainage conditions that might result. Problem areas can be avoided in the final design of the distribution lines, receive less water on a weekly basis, be used only seasonally, or drained artificially. Even then, it may be difficult to anticipate subsurface drainage conditions that may develop in the long term within deeper soil or rock both above or below the water table.

For these reasons, all irrigation projects should undergo a shakedown period when they are first put into operation. During this time problem areas can be isolated and necessary adjustments made in the irrigation system. This may require changing the application schedule. Spray heads may have to be removed, or even segments of distribution lines discontinued at troublesome areas. If corrective action is taken, many of the drainage problems usually observed at irrigation sites can be minimized or eliminated. Unfortunately, irrigation systems are often viewed as rigid systems that once designed and constructed, no longer need to be altered. Economic and poor enforcement considerations dictate this to be so.

At our Gamelands site for example, effluent was applied on hill slopes underlain by stratified soils comprised of interbedded clay, silt and sand. Lateral flow and surface discharge was excessive at 4-inch and 6-inch per week winter application rates when effluent was applied from line to line in sequence going from top to bottom or bottom to top of a particular slope. Surface discharge and runoff were reduced when lower application amounts were used (decreasing from 6 inches to 4 inches per week) and when effluent was applied in a staggered manner, i.e., first using a line on one slope, then a line on an adjacent slope before returning to the initial slope. This procedure allowed more time for subsoil drainage between applications, hence, lateral surges of soil-water movement were reduced. This simple management procedure can be adopted for manually operated or automated systems even after the project has been initiated.

Factors Commonly Ignored

Infiltration and drainage rates are influenced by water temperature and water quality among many other important factors. Infiltration rates determined in advance of irrigation may bear little resemblance to those encountered when effluent is applied. The hydraulic conductivity, K , of a soil varies with the physical properties of the soil together with the density and viscosity of water applied. This is expressed by the equation

$$K = k_{pg}/n \quad (1)$$

where ρ = density of water in gm/cm³
 n = viscosity of water in dyne-sec/cm²
 k = intrinsic permeability of soil or rock in cm²
 g = acceleration due to gravity in cm/sec²
 K = hydraulic conductivity of soil or rock in cm/sec.

This equation has been applied to soil water flow in unsaturated and saturated conditions.

The rate of flow is determined by Darcy's law

$$V = -Ki \quad (2)$$

where V = volume of flux of water per unit cross-sectional area
 K = hydraulic conductivity in cm/sec
 i = hydraulic gradient.

Frequently K is treated as a constant in field studies despite the fact that it varies with the properties of the soil as well as of the intrained water as noted above. Also intrinsic permeability of soil or rock commonly is assumed to be constant unless there is a change in soil characteristics. The fact that significant changes in trinsic permeability can occur is frequently ignored when evaluating infiltration and drainage characteristics of soils at proposed irrigation sites. The mineralogy of soils together with quality of effluent to be disposed of must be considered because clay soils can expand in the presence of increased volumes of water or with changes in water quality. Also changes in cations and anions in soils resulting from exchange reactions can bring about dispersion reactions that break up soil aggregates and plug soil pores. Swelling and dispersion phenomenon both can drastically influence intrinsic permeability, hence the infiltration capacity of a soil and its drainage characteristics. Irrigation sites that initially had favorable drainage characteristics experienced serious runoff problems with use for these and other reasons.

Temperature has a drastic effect on infiltration and drainage. It influences the viscosity of water as well as its surface tension. Eisenberg and Kauzmann, (1969) have shown that the viscosity of water changes from 1.798 centipoises at 0°C to 0.8904 at 25°C. Equation 1 instructs us that the hydraulic conductivity responds to changes in temperature. Lowering the water temperature from 25°C to 0°C can decrease the hydraulic conductivity by one-half (Klock, 1972). The effect of changes in density accompanying water temperature changes is insignificant by comparison (equation 1). Weast (1968) has shown how surface tension is effected by temperature which influences both infiltration and drainage. Surface tension is 75.60 dynes per cm at 0°C and 71.97 dynes per cm at 25°C.

In his experiments, for example, he calculated from the capillary rise equation that 19 percent of the water in a soil column would remain after drainage at 0.3°C and observed 15.5 percent to remain in experiments. An additional 1.7 percent of total available water would be lost if the temperature increased from 0.3°C to 25°C. The water content of a soil greatly influences its water transmission properties which Bruce and Klute (1956) show to be a maximum when the moisture content approaches 75-80 percent of pore saturation.

The range in water temperatures likely to be encountered at irrigation sites must also be considered when evaluating proposed or potential irrigation sites and application rates.

Less well known are the infiltration characteristics of frozen soils which are important in year around irrigation projects in northern latitudes. At our winter irrigation site, 6 inches and 4 inches per week were applied the first winter partly in the belief that more water may be required to keep the ground from freezing. Also less land area and pipes were required to keep the system in continuous operation to prevent ice damage to the trunk and distribution lines. We observed that whenever effluent was applied at freezing to below freezing conditions (wet bulb temperatures near 32°F) ice began to develop first on twigs, tree trunks, needles, grass, etc., until more massive ice packs developed. As long as water was applied at below freezing temperatures, ice continued to build to the point that it encrusted tree trunks and branches and even began to encroach on spray heads. Where spray heads were close to trees, ice grew around and over an occasional head which continued to supply water. Snow trapped in ice packs added to the total amount of water in storage. Any day that effluent was applied at above 32°F, the ice pack began to melt and water was available for infiltration or runoff. Surprisingly, much of this melt water stayed in close proximity to the ice packs indicating that some of the water was stored in adjacent snow packs when snow was available and some infiltrated into the soil beneath and adjacent to the ice packs. Two points are clear. Ground frost development must be limited or poorly developed below ice packs near spray heads. Adjacent soils, although exposed and frozen, must retain some of their infiltration and permeability characteristics. The water content of soil near spray heads increases following the growing season and should be sufficient to produce a rather tight ground frost. However, the moment that an ice pack begins to accumulate an insulation layer is formed which helps to prevent the further development of frost. As the pack thickens and migrates laterally around the spray head, it serves as a more effective insulator. Water applied during thaws is available to permeate the ice pack and help break up what ground frost may be present.

Significant runoff may be observed particularly in the spring when effluent is being applied, during warm rainy periods when ice packs are still present. Adjacent soils, although frozen, cannot be impermeable during these periods. Runoff has been observed to enter forested border areas not receiving effluent and pond in shallow depressions where it later infiltrates the soil or it infiltrates during overland flow.

Most investigators interested in the infiltration phenomenon in frozen soils agree that the quantity and size of ice-free pores is important. Work by Larkin (1962), Kuznik and Bezmenov (1963), Post and Dreibelbis (1942) and others show that if a soil is frozen when its moisture content is greater than field capacity, its infiltration rate will be very low and if saturated, the intake rate may be virtually zero. Gray et al. (1970) reports that other experiments have shown that whenever an extremely wet layer within the soil profile is frozen, downward movement of water through the layer is impeded until the zone is thawed. Zavodchikov (1962) showed that the infiltration rate of frozen soil may be increased 6-8 times its initial rate during the melting period which implies that heat is added to the deeper frozen layers and helps to thaw this ice. At our own site, heat contained in the effluent may be sufficient to cause the repeated and early break-up of ground frost. Even in areas that are flooded from time to time, free from snow and later are exposed to below freezing temperatures, infiltration continues during the next period of runoff. Ground frost may be nearly impermeable at first in these areas, but it must thaw quickly during the next runoff-ponding cycle.

It is also possible that not all voids are occupied by ice but rather as the freezing process continues, the total dissolved solids content increases to the point that the final "brine" produced does not freeze. Small conductive channels may remain for this reason.

Recent studies by Jame and Norum (1972) support the conclusion that in a frozen soil, unfrozen liquid water can exist in equilibrium with ice over a large temperature range below 0°C. Equations developed by them using a concept of soil water potential helps to explain the freezing-point depression of pore water that is brought about in frozen soil. At a fixed value of soil water suction, or soil water potential, there is a corresponding freezing point depression which implies that for each moisture content there is a corresponding freezing point depression. They explain that as freezing occurs in the soil water system, water is transformed into ice lenses, the amount of water remaining in the pores thus comes under increasing suction or potential. This suction or potential is believed responsible for the reduction of the freezing-point of the remaining pore water. Presumably the remaining water is free liquid water which can account for soil conductivities observed below freezing temperatures.

Whatever the mechanisms are that help to maintain infiltration, excessive runoff should be anticipated at most project sites whenever irrigating in winter. Levees or small dams will have to be provided to prevent the trespass of these waters. Forest border lands, natural depressions, or engineered interception structures all can help infiltration and control runoff.

Ion Exchange Capacity

Physical-chemical processes operating in the soil that can add to the renovation process are discussed by others in this proceedings. It is sufficient to state that a high cation-anion exchange capacity is desirable. Clay minerals, sesquioxides, abundant organic matter, and other fine-grained mineral matter contribute to the exchange capacity. The exchange capacity is relied upon to retain and store exchangeable waste constituents within the shallow soil until they can be assimilated by the biologic system at a later date. Exchange and other physical-chemical reactions may also be relied upon to store nutrients within the soil indefinitely. Phosphorus removal by soil is a case in point. Even at the winter irrigation site where 6 inches per week of effluent were applied November through April, the first year on sandy soils, phosphorus was not detected above background concentrations even at shallow depths (3 to 17 feet). Kardos has indicated that given our phosphorus concentrations and 2-inch per week year around application rate, 100 years would be required to saturate even a 5-foot thick column of our soil with phosphorus. If phosphorus were our only concern, higher application rates could be used year around (>2 inches per week) successfully for a prolonged period.

A soil's ability to physically retain effluent within the biologically active zone is largely dependent upon its drainage characteristics and its water content. Once the water content is in excess of field capacity, water is free to move through the soil after each new increment of water is applied. This moisture condition is prevalent during the late fall, winter and early spring when the biologic system is less active and evaporation rates are low. During this time, the adsorption capacity of the soil must be relied upon to retain nutrients within the shallow soil. This is one of the principle roles of the soil system during winter irrigation and when applying effluent during periods of heavy rainfall. Swelling and dispersion characteristics of soils are related to the mineralogy and exchange capacity of soils and quality of water applied as has been pointed out.

Soil Thickness

Evidence provided by Sopper and Kardos in this proceedings support the conclusion that most renovation is achieved within the

upper 3 to 4 feet of land surface where biological activity is at a maximum. Some would debate, therefore, that a 3- to 4-foot thick soil column should be adequate to provide the degree of treatment required.

In carbonate terranes where bedrock is covered by thin residual or transported soils, shallow voids and cavities are common near the bedrock surface. Thin soils are especially prone to being washed or piped into these voids under natural conditions. The process is speeded up when additional water is added to the soil. Soil may be eroded away and the soil and renovation media eliminated. Sinkholes and piping voids become avenues for quick recharge that short circuit unrenovated water to the water table. Two large piping holes developed at our reed canarygrass plot where a 2-inch per week application rate has been maintained since 1965. Both occurred where soil was 40 to 60 feet thick. Similar but more numerous sink holes developed at the Morgan Paper Company spray field near Lititz, Pennsylvania where residual soils derived from carbonate bedrock average less than 10 feet in thickness. Sink holes can be backfilled as they develop and covered with soil. This adds to the management responsibilities where this problem applies. Subsurface erosion problems are not normally experienced in most other geologic settings.

More than 3 to 4 feet of soil is desirable at irrigation sites in humid regions located on other soil and rock types for other reasons as well. Any site found to contain only 3 to 4 feet of soil cover on the average is bound to contain a significant land area where soils are likely to be even thinner than 3 feet. Most designers of wastewater irrigation projects are likely to irrigate the entire site rather than try to isolate numerous thin soil areas unless required to do so. A detailed soil exploration program is required at any site to be used for wastewater renovation but this program can prove to be costly as test boring, test pits, seismic shot lines, etc. have to be closely spaced. Even then, many thin soil areas may be overlooked. I prefer to see 20 or more feet of soil (unconsolidated deposits) above bedrock or a thick cover of fine-grained soil above coarse-gravel or boulder gravel because animal burrows often extend to bedrock and provide open channels for surface runoff, application rates are always uneven in actual practice and surface ponding, runoff, and subsurface lateral flow stem and trunk flow, and pipeline leaks all help to redistribute effluent in an uneven manner at irrigation sites. Some parts of the soil system, therefore are called upon to handle application rates measured in feet of water per week rather than inches per week as intended. Operational problems also arise from time to time requiring that more water be applied than the designed amount. All of these conditions increase the likelihood of breakthroughs of incompletely treated effluent, hence, degradation of groundwater and ultimately surface water quality in the vicinity of irrigation projects.

At winter irrigation sites 3 to 4 feet of soil is totally inadequate in northern latitudes because the nutrient storage potential of thin soils is apt to be inadequate and nutrients (pollutants) will be flushed to the water table.

The thickness of the soil cover can be artificially increased using top soil or suitable subsoil materials. Some would argue that soil structure is important to the infiltration process, hence, artificial fills should not be considered for irrigation. However, even artificial fills can be designed to insure suitable infiltration and optimum drainage through careful selection and placement of cover materials. Research work with coal mine spoil restoration using sewage effluent and sludge show that it will not take long to develop a lush cover of trees or grass even when comparatively poor material (rock fragments) is being irrigated (Sopper and Kardos, 1972). A higher degree of renovation would be achieved the first year if fine-grained material were used as cover material.

Topographic Setting

Slope is related to soil characteristics and runoff. Steeper slopes will promote overland flow and subsurface lateral flow more so than gentle slopes all other factors being equal. However, so long as overland flow can be avoided, it should be possible to irrigate rather steep slopes successfully under some field circumstances. It depends upon the amount of slope to be irrigated, subsoil and water table conditions, design of laterals, application rates, land use, and other factors. Also some projects will provide for lagoon storage during winter and wet periods when slope begins to exert a dominant influence on runoff.

Slopes can be engineered to some extent to provide contour ditches, terraces, etc., to increase detention storage and infiltration. In addition to overland flow, subsurface seepage problems are more likely to develop on steep slopes where groundwater discharge areas begin to develop.

In more humid regions groundwater mounds tend to develop beneath topographic highs in response to groundwater recharge. Groundwater gradients are thereby increased during recharge periods with the result that a greater amount of water is induced to flow through an increased saturated thickness of soil or rock to regions of discharge. Irrigation projects located where there is some local relief and favorable permeability in the substrate can take advantage of the fact that there is space available for a water table build-up beneath topographic highs. Also as gradients increase, flow rates may be sufficient to transport recharge waters naturally to points of discharge.

In low relief to nearly flat areas water tables are commonly at or very near land surface and there is little if any space for additional recharge. Subsoil drainage must be provided artificially to insure adequate drainage and aerobic conditions in the biologically active zone.

Drainage ditches, tile fields, drainage wells or water supply wells may be used for this purpose but often at a considerable additional expense to the project. Tile fields and drainage ditches are preferable where they can be used because once they have been installed they operate by gravity. Drainage wells and water supply wells have pumping lift costs to contend with in addition to construction, operation, and maintenance costs, which can add significantly to total project costs. These factors should be considered when selecting irrigation sites in low relief and poorly drained areas.

Characteristics of the Groundwater Reservoir

Parizek and Myer (1968) stressed the importance of knowing the location of groundwater recharge and discharge areas when selecting wastewater renovation sites using land disposal methods. Irrigating natural groundwater discharge areas with the intent of achieving recharge should produce a negative result. Renovated water is soon rejected by the groundwater reservoir and lost by runoff and evapotranspiration. Still worse, poor drainage conditions and runoff result, and soils may become waterlogged. This could cause the biologically active zone to shift from an aerobic to anaerobic state, cause a destruction or alteration of the physical-chemical-biological treatment processes, and ultimately a degradation of soil-, ground-, and surface-water quality (Parizek and Myers, 1968). This basic concern is complicated by the fact that recharge-discharge relationships are not fixed. Rather, the boundary separating the two is transient. Significant increases in the rates of recharge accompanying irrigation can greatly expand discharge areas, particularly for large projects. Areas that were formerly well drained recharge areas may become poorly drained discharge areas. These areas can occur several hundred to thousands of feet beyond stream channels or appear as discontinuous upland patches remote from nearby streams.

Advantages of having relief on the water table have been discussed. In addition, there should be space available for a seasonal build-up of the water table beyond natural conditions. Permeability characteristics of saturated soil and rock should be sufficient to convey reclaimed effluent to groundwater discharge areas. Where both gradients and permeability are sufficient to facilitate lateral movement of reclaimed effluent and natural recharge, a considerable savings can be achieved when compared to sites where this must be done artificially.

The question frequently arises, how deep should the water table be at an irrigation site used for wastewater renovation? More importantly, what is the seasonal range in water table position and how will this be modified by additional recharge accompanying irrigation? The latter questions can be answered only by examining soils at the site to see if they formed under conditions of a seasonally high water table, by observing water table fluctuations on site or similar adjacent sites at least a year in advance of irrigation and by computing water table changes likely to be brought about by irrigation. Soils are one of the most important and reliable indices to the natural drainage (Table 3). As they formed they integrated and thus reflect the results of years of favorable or unfavorable drainage conditions. Soil properties are related to both the depth of the water table and number of months during the year that water is in contact with the soil profile. Schneider and Erickson (1972) stress that even in dry months of the year the natural soil drainage can be predicted by observing the color and color pattern of each soil horizon, natural vegetation - whether it is water-tolerant or water-loving, and position on the landscape. This is important because water tables may fail to rise to their maximum level during a particular series of dry years or during the brief period of field study when irrigation sites are being selected.

The decision to artificially drain a site using wells, tile fields, or ditches immediately limits the concern for the position of water table because its position will be controlled or engineered as required. Even when one is willing to do so, this does not mean that artificial drainage can always be achieved at a reasonable expense. Soils, for example, that are in the "extremely slow" to "very slow" permeability class (Table 2) may be so nearly impervious that leaching and artificial drainage are impossible using conventional artificial means. Sites must be examined carefully with this point in mind.

It would not be rational for regulatory agencies to arbitrarily set a depth of water table position for example, at 6 or 10 feet, as a requisite condition of irrigation sites. If this were done vast areas in the United States with water tables less than this would be eliminated from consideration. This would involve great expenses of the mid west with little or no relief that had to be drained to be farmed, and a significant percentage of areas covered by glacial till. Farm land now being drained by tiles need not be suitable in their present form, however, because a closer spacing and even a deeper tile setting may be required to control both rainfall and reclaimed effluent. On the other hand, where enforcement personnel responsible for environmental protection are few in number and overtaxed with work, more stringent site requirements are justified.

Sites can be selected with wastewater renovation as the sole purpose. Under these circumstances renovation is to be achieved in

TABLE 3. Soil Class by Drainage, Color Appearance, and Water Table Position (From Schenider and Erickson, 1972)

Soil class	Color	Water table conditions
Well-drained	Bright red, yellow, and brown. Free of mottles to a depth of 36 to 42 inches or more.	Water table commonly greater than 60 inches during most months.
Moderately well-drained	Uniform red, yellow or brown colors in the surface and upper subsoil horizons. Mottles present in the lower subsoil and parent or underlying materials.	---
Somewhat poorly drained (imperfectly drained)	Generally mottled directly below surface horizon. Color matrix below surface layer is dominantly yellow and brown with gray, rust brown, and orange mottles.	Mottled conditions indicate the presence of a high water table during some parts of the year, usually spring, late fall and winter months. Seasonally, water table ranges from 24 to 120 inches in depth.
Poorly drained	Dark-colored surface layer high in organic matter. Horizon below the surface layer predominantly gray with orange, brown, rust brown or yellow mottles.	High water table at or within 30 inches of surface most of the year unless artificially drained.

advance of a more distant present or possible future water use. Parizek and Myers (1968) indicated that site selection criteria for a renovation system favoring distant reuse will depart from those favoring local reuse as groundwater. Shallow penetration of renovated effluent and rapid return to the surface may be acceptable. This can be achieved by irrigating side hill slopes and local uplands that favor the surface return of waters after a sufficient degree of treatment has been achieved. Irrigation on local uplands surrounded by nearby valleys and on stratified deposits favoring the development and lateral movement of perched groundwater are common settings where this can be achieved. Loess overlying glacial till, shale or siltstone bedrock, lake clay, lake silts and sands, fluvatile silts and sands, dune sand, residual and other transported soils that overlie deposits with low permeability characteristics are cases in point. The percentage of land area that would favor renovation but unimportant groundwater recharge is greater for many states than is land that would favor significant increases in groundwater recharge for local reuse.

Groundwater recharge for local reuse may be an important objective at some project sites. Examples have been cited above where infiltration, renovation, and quick return to land surface can be achieved. In these cases, reclaimed effluent may be available for reuse off-site as surface water, it may be recaptured by wells located downstream by induced streambed infiltration, or used for recreational purposes or wildlife propagation (Parizek and Myers, 1968).

Water supply wells may be located beneath or adjacent to irrigation sites to derive benefits of reclaimed water. Wells may be planned to improve drainage as well as to supply water. In both instances, the number and spacing of wells required to provide the necessary amount of water will depend upon aquifer characteristics--storage, transmission properties, boundary conditions, recharge rates--and degree of treatment anticipated, amount of land to be irrigated, application rates and evapotranspiration requirements.

The number and spacing of onsite wells necessary to insure drainage may depend upon the volume of water required from the well field, depth and extent of pumping cones of depression developed for each well, economic considerations, and aquifer hydrologic characteristics.

Parizek and Myers (1968) point out that pumping cones of depression within the free-water surface or water table are ideal for dewatering some unconfined soil and rock aquifers and for deriving direct benefit from artificial recharge. Five plans of action are possible: (1) a wastewater renovation facility can be located adjacent to an existing well field where site conditions are suitable

for irrigation, and effluent used is free of toxic or harmful non-degradable substances that otherwise are not likely to be removed in the renovation media, (2) a well field can be placed in close proximity of the site after it has been established that adequate renovation is being achieved, (3) reclaimed water discharged to surface can be re-collected in wells relying upon induced stream-bed infiltration, or (4) drainage wells can be placed within the irrigation area with no beneficial use planned for the water except to insure adequate drainage. Where there is doubt that adequate renovation can be achieved without relying upon dilution as well, the irrigation site should be located remote from areas of existing or potential groundwater development.

For cases 1 through 4, to be effective, unconfined aquifers, or at least, semi-unconfined aquifers should underlie the irrigation site (Parizek and Myers, 1968). These may be of diverse origin and be composed of fractured bedrock--sandstones, siltstones, carbonate rocks, gneisses and schists--sedimentary rocks containing favorable intergranular or primary permeability--sandstone, siltstone, carbonate rocks--or of permeable unconsolidated sediments such as sand and gravel.

Where confining beds are thick or relatively low in permeability, confined aquifers may derive little additional recharge than was being achieved under natural conditions. Once the maximum hydraulic gradient has been developed between the source bed and confined aquifer in response to recharge and pumpage, vertical leakage rates are fixed. Where recharge rates to source beds are in excess of the vertical leakage rate to the confined aquifer, water is rejected from the shallow system and no additional recharge benefits are achieved.

Selected vertical hydraulic conductivities for soil and rock units are presented in Table 4 as a guide.

One point cannot be overstressed. A large volume of recharge should be expected when irrigating in humid regions even when only a 2-inch per week rate is used during the growing season. Even more recharge is achieved with year around irrigation.

Over 78 feet of effluent has been applied at the Penn State facility to plots irrigated at a rate of 2 inches per week, 12 months a year starting in 1964. Based on calculated evapotranspiration losses, between 59 to 100 percent of the applied water was potentially available for recharge depending upon the rate of application used, length of irrigation period and weather conditions experienced that year. The lesser amount occurred when effluent was applied April through November during a drought year, whereas, the 100 percent value was for a year when rainfall exceeded evapotranspiration by 6.01 inches (Table 5).

TABLE 4. Vertical Hydraulic Conductivities for Soil and Rock Units Determined from Field Testing Procedures

Vertical Hydraulic Conductivity in gpd/ft ²			Material Examined	Source
Range	Average			
1.02 -1.60	1.31	Glacial drift in Illinois; sand and gravel, some clay and silt	Walton (1965)	
0.10 -0.63	0.25	Glacial drift in Illinois; clay and silt with considerable sand and gravel	"	
0.01 -0.08	0.03	Glacial drift in Illinois; clay and silt with some sand and gravel	"	
0.005 -0.011	0.008	Glacial drift in Illinois; clay and silt with some sand and gravel and dolomite	"	
0.005 -	0.005	Glacial drift in Illinois; clay and silt with some sand and gravel and shaley dolomite	"	
0.00005-.00007	--	Dolomite, with shale	Norris (1962)	
0.00005-.0007	--	Maquoketa shale, northern Illinois	"	
0.0008 -0.9	--	Glacial till in northeastern Ohio	"	
0.01 -0.5	--	Surficial till, Montgomery Co. Ohio	"	
0.03 -0.16	--	Buried till, Montgomery Co. Ohio	"	
0.08 -0.02	--	Glacial till, southern Illinois	"	
0.0003 -0.5	--	Glacial till, South Dakota	"	
Hydraulic Conductivity in gpd/ft ²			Walton (1970)	
0.001 -2.0		Clay, silt		
100 -3,000		Sand		
1,000 -15,000		Gravel		
200 -5,000		Sand and gravel		
0.1 -50		Sandstone		
0.00001 -0.1		Shale		

TABLE 5. Recharge by Sewage Effluent for 1-Inch and 2-Inch Application Rates by Year at the Pennsylvania State University Project Site

Year	Application Rate Inches per Week (April through November)	Percent Potential Recovery	Remarks	Recharge (g/acre/yr)
1963	1	65.5	Agronomic crops: Glaney-Criddle method.	427,000
1963	2	82.7		1,078,000
1964	1	59.8		
1964	2	79.9		
1965	2			1,493,000
Inches of Recharge				
1963	1	18	Forestry plots: Thornthwaite method	488,700
1963	2	41		1,113,000
1964	1	26		706,000
1964	2	59		1,602,000
1965	2	--		1,493,000
1967	2	--		1,859,000

(After Parizek et al., 1967, and Kardos, 1970; and Sopper, 1971)

Recharge rates were higher at all plots irrigated on a 12 month per year basis and during years of normal to above normal precipitation. As evapotranspiration rates diminish during the late fall, winter and spring, nearly all applied effluent and precipitation are available for recharge at our site. Losses by runoff are negligible.

Annual recharge rates might approximate 2.9 million gallons per year where 2 inches per week are applied on a year around basis to 135 acres, 1.5 billion gallons for a 600-acre project, etc. For projects involving thousands of acres (Muskegon County, Michigan, various projects proposed by the U.S. Army Corps of Engineers) vast amounts of recharge would be involved. These projects will and have required detailed hydrogeologic investigations of proposed irrigation sites and a hydrogeologic systems analysis to determine what effect irrigation waters are likely to have on recharge and regional water table configurations. Such analyses will help to delineate areas likely to be flooded both on and adjacent to irrigation plots, the need for and density and distribution of drainage facilities, and their effect on water tables during irrigation. For some projects, potential problem areas will be delineated that may or may not cause problems once the project has been placed into operation. Contingency plans to eliminate potential drainage problems can be

included at the time irrigation projects are designed and submitted for approval to regulatory agencies. Control measures, in turn, would be added to the system only after it has been shown that they are required through actual experience.

Large irrigation projects involving hundreds or thousands of acres of land are more difficult to analyze because as the land requirement increases the soils, geologic and hydrologic diversity and complexity are more likely to increase. Water table level responses at these sites will require analyses using electrical analog or digital modeling techniques rather than conventional analytical methods which assumes more nearly ideal conditions. Data requirements for modeling soil-water and groundwater flow under complex field conditions also become more demanding because all elements required in the models must be accounted for during field studies either through actual measurement or "educated" guesswork. Fortunately, computers are now available that allow solution of large sets of simultaneous equations that can predict cause and effect phenomenon in heterogeneous aquifer and confining bed systems under a wide variety of recharge and no flow boundary conditions. Generalized digital computer programs have been written to simulate one-, two- and three-dimensional steady and nonsteady flow of groundwater in heterogeneous deposits under water table, nonleaky and leaky artesian conditions. Programming techniques allow for varying pumpage from wells, varying natural or artificial recharge rates, relationship between exchange between surface waters and the groundwater reservoir, influence of drainage facilities on water table level, groundwater evapotranspiration and similar other complexities frequently encountered in the field (Douglas and Rachford, 1956; Zienkiewicz and Cheung, 1965; Zienkiewicz, Mayer and Cheung, 1966; Pinder and Bredehoeft, 1968; Bittinger, Duke and Longenbaugh, 1967; Bredehoeft, 1970; Cooley and Peters, 1970; Cooley, 1970; Prickett and Lonnquist, 1971; and Pinder, 1971).

These analytical procedures make it possible to determine the water table configuration that will develop in response to natural recharge and various schemes of groundwater development. The problem is identical for sewage effluent irrigation projects with the exception that recharge rates are greatly increased. However, basic data requirements must be met through detailed hydrogeologic investigations frequently involving geologic mapping, test drilling programs, control pumping tests, etc. Most project areas will require definition of the following variables:

1. Coefficient of vertical and horizontal permeability distributions for aquifers and confining beds.
2. Specific yield of deposits saturated or dewatered by water table fluctuations, and coefficients of storage for confined aquifers.

3. Thickness and distribution of aquifer and confining units.
4. Location and character of hydraulic boundary conditions, including recharge and nonflow boundaries.
5. Water table and potentiometric surface configurations for unconfined and confined aquifers with seasonal changes.
6. Location and amount of natural recharge and artificial recharge expected from the applied effluent.
7. Location of groundwater withdrawal points and annual pumping schedule.
8. Estimated groundwater evapotranspiration losses for the area where water tables are within 10 or less feet of land surface.

Analyses of groundwater systems can now be made for rather complex field situations. These analyses should be demanded by regulatory agencies responsible for evaluating proposals for large scale irrigation projects. These same analysis procedures may be used to determine drawdowns likely to be brought about by drainage ditches, tile fields, water supply and relief wells proposed to control water levels.

Hydrologic Isolation, Dilution and Dispersion

The groundwater reservoir can serve other roles as well. Some waste constituents are likely to be contained in sewage effluent that cannot be renovated by biological or biochemical processes or physical chemical processes operating within the soil. Ultimately these will find their way to the groundwater reservoir. Difficult or impossible to renovate trace elements and other substances that are likely to pass through the renovation system unaltered or little altered can be isolated within groundwater flow systems. These remaining substances, in turn, can be diluted to acceptable concentrations within nearby streams and lakes. A groundwater hydrologic isolation system will work only as long as groundwater flow systems are more or less in a steady state condition. Any change in the nearby groundwater recharge-discharge regimen, change in hydrologic boundary conditions brought about by new groundwater development, excavations, or mining can cause a shift in the flow regimen, therefore a change in the system being relied upon to achieve isolation. It should be remembered that these waste constituents may survive for years to tens of years within the groundwater reservoir once they have been introduced and a procedure of "controlled contamination" or controlled pollution is being adopted.

A more detailed hydrologic analysis is justified where such a system is to be used compared to a system where renovation is likely to be more complete.

Aside from a hydrological isolation role, the soil-water and groundwater reservoirs may be relied upon to provide dilution and dispersion of waste materials.

All nonbiodegradable substances and wastes not involved in physical-chemical reactions within the soil-water and groundwater reservoirs must be accounted for in this manner whether intended or not. A basic question arises. If waste substances cannot be removed within the renovation media by any of a combination of processes involved, should they be allowed in sewage or other effluents applied to the land and if so in what concentrations? Trace elements, heavy metals, and other more difficult to handle wastes derived from industrial processes may have to be excluded from irrigation systems or at least strictly controlled and monitored. Many of these same wastes do not belong in our rivers or lakes either.

Toxic wastes pose a problem. They may poison biological systems responsible for key renovation processes. They may cause slow, but long term and difficult to correct damage to groundwater quality. They may be concentrated within plants used for agricultural production and cause related difficulties when used as food or feed. Spectacular irrigation project failures may be cited where oil field brine or chemical wastes have been applied to the land.

Where potentially harmful substances are included in sewage effluent, that will be applied to the land, an analysis should be made to determine the concentration that may result as a function of volume and quality of water applied, time since application and distance of travel within the soil-water and groundwater reservoirs beneath and adjacent to the irrigation site. Conservative estimates can be made for design purposes by assuming that only dilution and dispersion is being relied upon to reduce the concentration of a particular substance. A more complete and representative analysis of the real complexities involved is the subject of ongoing study by various people. Ultimately it will be possible to include biochemical and geochemical reactions in addition to physical processes now being used in these analyses to study flow in saturated and unsaturated systems.

It is first necessary to determine the seepage velocity within all reference elements of the groundwater reservoir that influence groundwater flow in the vicinity of an irrigation site. All of the basic data requirements specified earlier that are required in groundwater systems analyses must be met. In addition, the porosity

of saturated soil and rock must be known to determine the average seepage velocity for the deposits in question. Also the waste concentration, total waste load applied with time and area of application must be known. Horizontal and longitudinal dispersion coefficients must be known for all saturated soil and rock encountered. These hydrologic parameters are essentially unknown for most naturally occurring soil and rock which further complicate these analyses.

The theoretical basis and derivations of dispersion equations are presented by Bear, Zaslavsky and Irmay (1968), Reddell and Sunada (1970), Ogata (1970) and Bredehoeft and Pinder (1972).

If no chemical reactions occur between the water and the aquifer or soil materials which affect the dissolved-solids concentration, then equation 3 describes the mass transport and dispersion of dissolved chemical constituents in a saturated porous media.

$$n \frac{\partial C}{\partial t} = \frac{\partial}{\partial x_i} \left(D_{ij} \frac{\partial C}{\partial x_j} \right) - \frac{\partial (q_i C)}{\partial x_i} + C_p Q \quad (3)$$

where C is the mass concentration of dissolved solids (m/L^3),

D_{ij} is the coefficient of hydrodynamic dispersion (L^2/T)

C_p is the mass concentration of dissolved solids at a source or sink (m/L^3)

and Q is the rate of production of a source (L^3/T).

The first term on the right hand represents movement of dissolved solids due to hydrodynamic dispersion, and is assumed to be proportional to the concentration gradient. The second term represents convective transport, which is proportional to the seepage velocity. The third term is a fluid source or sink.

Bear, Zaslavsky, and Irmay (1968) conclude that two processes account for hydrodynamic dispersion. One is mechanical dispersion, which depends upon both the flow of the fluid and the nature of the pore system through which flow takes place. The second is molecular diffusion which is time dependent and becomes significant at low flow velocities. In two recent field studies, Bredehoeft and Pinder (1972) and Konikow (1973) showed diffusion to be of little consequence.

Scheidegger (1961) expressed the relationship between the dispersion coefficient, fluid flow, and the pore system as

$$D_{ij} = -\epsilon_{ijmn} \frac{V_m V_n}{V} \quad (4)$$

where ϵ_{ijmn} is the dispersivity of the porous medium (L),

$V_m V_n$ are the components of velocity in the m and n directions (L/T), and

V is the magnitude of velocity (L/T).

Further, for isotropic porous medium the dispersivity tensor is defined by the constant α_I , the longitudinal dispersivity of the medium, and α_{II} , the transverse dispersivity. These are related to the longitudinal and transverse dispersion coefficients by

$$D_L = \alpha_I V \quad (5)$$

$$D_T = \alpha_{II} V \quad (6)$$

The method of characteristics is used to solve equation (3) Pinder and Cooper (1970), Reddell and Sunada (1970), and Bredehoeft and Pinder (1972).

Konikow (1973) presented the most complete field study that demonstrated the applicability of the theory in predicting shallow groundwater quality changes resulting from irrigation practice in a semi-arid region.

Digital solution of complex groundwater flow and chemical transport equations involved will provide a conservative estimate of the waste concentration that will result if no other renovation processes are involved.

These analyses should be demanded of designers of wastewater irrigation projects where there is doubt about the water quality conditions that may result in response to prolonged irrigation. These analyses will provide some estimate of how much of a buffer zone should be allowed between spray fields and wells and springs used as water supplies.

Design of Monitoring Facilities

All wastewater irrigation projects must contain appropriate monitoring facilities so that the designers' claims and expectations can be verified through actual experience. Wastewaters, soils, geologic and hydrologic settings, operating and management procedures are so varied that it is not safe to assume that if the irrigation method worked in one area it will automatically work in an adjacent area with a similar setting. Operator and management variations alone can cause the demise of a particular project. Cases can be cited where the recommended total annual application amount was applied to a plot within a two- or three-week period rather than on a weekly year around basis. Groundwater pollution, vegetation kills, water logging of soils, surface runoff and soil erosion resulted at these sites. The simple act of irrigating wastewaters is not sufficient to insure renovation. A missapplication of the technique can do a disservice to the living filter-irrigation concept.

Regulatory agencies should demand the installation of monitoring facilities at all wastewater irrigation projects and require routine performance reports of the operator. Some would argue that since

only one sample point is required to evaluate the performance of sewage treatment plants, the effluent outflow line, only one point should be required at irrigation project sites. This is absurd in view of the field complexities involved. A question arises. How many monitoring points are necessary, how should they be constructed, where should they be located, how frequently should samples be taken, what waste constituents should be examined for, for how long should sampling continue, what analyses techniques should be applied, etc.? For example, soil water samples collected from 6 feet below an irrigation site will produce different results when compared to samples taken from monitoring wells completed in the water table below irrigation plots or when compared to samples collected from wells located in the direction of groundwater flow but adjacent to irrigated areas. It is also necessary to determine how representative a sample station is when compared to the general conditions encountered at the site. Regulatory agencies must determine what water quality standards should be met for each of the sampling regimes--on site soil-water and groundwater, and groundwater adjacent to the site.

Only several hydrogeologic factors are considered here to illustrate the caution that must be exercised. A variety of monitoring devices and sampling stations were designed and installed at the Penn State Waste Water Renovation and Research Facility, (Parizek et al., 1967). These were intended for research purposes, hence the number and diversity of stations and frequency of sampling was considerably greater than would be required for routine projects.

Sampling water within the soil-moisture reservoir - above the water table - poses special problems because water is normally under tension and will not enter bore holes unless perched groundwater lenses develop. Shallow and deep pan and pressure-vacuum lysimeters were used to collect soil-water samples at the Penn State facility as well as sand-point wells, and soil samples. The advantages and disadvantages of pan and pressure-vacuum lysimeters design and construction procedures used are described by Parizek and Lane (1968). Pressure-vacuum lysimeters represent the single best approach to sampling soil water or water under tension. They are inexpensive, easy to install, provide samples long after other sampling devices fail as the moisture content is reduced and can be used at depths of 6 inches to more than 60 feet. Commercial lysimeters are available and can be modified to provide water samples below 20 or more feet (Parizek and Lane, 1968). These can be stacked within individual bore holes and provide soil-water samples at any interval within soil. It is possible, therefore, to determine the degree of renovation being achieved with time and depth on a systematic basis below irrigation plots.

Sampling water within unsaturated bedrock poses other problems where deep water tables are encountered within bedrock. A variety of well types and pumps can be used to obtain effluent samples from

the groundwater reservoir. Ideally, monitoring wells should be pumped long enough to induce flow from adjacent soil or rock deposits, thereby increasing the chance of providing a more representative sample of groundwater within the vicinity of the well. Hand bailing a few gallons from a 6-inch diameter well, for example, might represent only a 1/4,000,000 or less part or sample of water recharged at a 100-acre irrigation site.

Groundwater flow systems must also be considered when designing monitoring wells. Wells may be located above or below flow channels containing effluent hence, fail to provide samples of effluent recharged to the groundwater reservoir. Depending upon the hydrogeologic setting involved, pumping may increase the chance of obtaining representative samples or have little effect. Chances of bypassing are greatly increased where monitoring wells are completed in fractured rocks. Fractures greatly increase the permeability of rock over that of the more massive blocks of rock they enclose. The number, distribution, orientation and aperture size of rock fractures or joints and bedding plane separations rarely can be determined for irrigation sites because these sites should contain a soil cover even to be considered for irrigation. Hence, there is risk that unclaimed effluent may escape the site undetected.

Zones of fracture concentration revealed by fracture traces, on the other hand, can be routinely mapped on areal photographs. These delineated zones of intensive jointing and physical and chemical weathering hence increased permeability and porosity that may be 10 to 1,000 times more permeable than adjacent rock. (Lattman and Parizek, 1964; Parizek and Voight, 1970; Siddiqui and Parizek, 1971; Parizek, 1971 a, b).

Monitoring wells located on fracture traces can greatly increase the chances of obtaining a representative sample of groundwater beneath and adjacent to irrigation sites because they concentrate flow and serve as conduit-like systems that are interconnected on a regional basis. Monitoring wells located remote from these zones may fail to reveal pollution problems developing on site, either because they channel effluent away from irrigation sites or provide dilution where adjacent groundwater enters the site.

Zones of fracture concentration can serve another important function where well dewatering or groundwater reuse is planned in areas underlain by fractured rocks. These zones serve as efficient groundwater collector channels when tapped by wells. Fewer dewatering wells would be required to control groundwater levels in fractured rocks where wells are placed at fracture trace intersections compared with cases where wells would be drilled without knowledge of these zones. Zones of fracture concentration are

narrow, hence are not often penetrated by chance. This would be of vital importance in large projects where dozens of dewatering wells might be involved. Dewatering using zones of fracture concentrations can be achieved with a fraction of the total number of wells that otherwise might be required.

These same zones greatly increase the yield potential of water supply wells. Siddiqui and Parizek (1971) showed the percent of fracture trace wells whose yield values equalled or exceeded specific values when compared with wells located remote from fracture traces. Data presented are for wells completed in shale, shaley limestone, limestone, dolomites, with various textures and sandy dolomites located in central Pennsylvania. Similar relationships are being found for other rock types in Pennsylvania and elsewhere as well. Fracture trace and fracture-trace intersection wells in all cases are among the most productive wells being drilled within various rock types when compared to wells drilled off these zones in the same terrane.

Administrative Considerations

A wealth of experience is available on applying irrigation water to crops. However, data are still scant on the use of sewage effluent as irrigation water to determine the degree of renovation that may be achieved under varied crop and climatic conditions. Many have irrigated with sewage effluent but with little concern of the pollution potential involved. A number of questions become obvious when one considers land disposal and treatment of wastewaters. Many of these were considered in the design of the Penn State research project and must be considered by others who are seeking alternative solutions to wastewater treatment and disposal problems. Some of these have been listed and discussed by Parizek *et al* (1967), Parizek and Myers, (1968), and Parizek (1971c).

Regulatory agencies charged with the responsibility of reviewing waste treatment and disposal applications and with enforcement are or will be forced to decide often with scanty data whether to grant operating permits for wastewater irrigation systems. Some states may grant one-year experimental or provisional permits until they are assured projects are performing up to expectation.

Soil-water and groundwater flow rates frequently are so slow that months or even years may be required before applied effluent reaches a particular monitoring station. For instance, on the Penn State Project soil water was being sampled from a perched groundwater lens within a loamy soil. The monitoring point is located at a depth of 33 feet below surface where effluent is applied April through November. Chlorides, which serve as our best tracer, did not begin

to increase above background concentrations until 13 months after irrigation began.

Nearly two years were required before detectable changes in chloride and nitrate were noted in groundwater monitoring wells located 275 feet below irrigation sites containing nearly 60 to 100 feet of clay to sandy clay soil and 100 to 200 feet of unsaturated cavernous dolomite bedrock. Monitoring wells in each case were open to the top of the water table and equipped with pumps.

Monitoring installations must be planned to allow an early evaluation of irrigation projects as well as the long term response of these systems. Both were allowed for in the Penn State project with the result that water quality changes within the deep groundwater reservoir have been noted after nine years of irrigation but the quality changes are entirely acceptable. In fact it is of better quality than the average groundwater supply being used for domestic and farm purposes within the adjacent valley area.

Other problems arise when attempting to evaluate monitoring results. Seasonal changes in land use, weather, recharge, rates of physical, chemical and biological processes produce erratic graphical plots of water quality when a given constituent is considered. It is difficult to establish meaningful trends in such data even after two or more years of irrigation let alone account for the possible sources and reasons for the variability observed. In short, the success or ultimate failure of a particular project cannot be judged in the short term. Monitoring must be continued for the life of the project even if to a limited extent once initial success has been established.

CONCLUSIONS

1. Knowledge of the soils, geology and hydrology can help when selecting sites for wastewater renovation to insure that a high degree of renovation is achieved for a prolonged period, to insure that groundwater recharge and/or reuse can be achieved and to minimize secondary environmental problems that can result from wastewater irrigation projects.
2. This same knowledge must be applied to the design of monitoring systems used to evaluate these projects.
3. Regulatory agencies responsible for the evaluation of irrigation proposals and policing and enforcement work need diversified personnel to deal with wastewater irrigation projects. Aside from sanitarians, soil scientists, groundwater geologists and related personnel are required. Regulation and enforcement are mandatory to insure the success of irrigation projects.

4. As the size of irrigation projects increase, the likelihood for major failures will increase. Numerous small scale projects have already failed due to poor design, improper site selection and poor management. More attention will have to be given to details of site selection, use of a conservative design, and continued project management. Management is the key to achieving a high degree of renovation over the long term at good sites and of making the best of poor sites.
5. Wastewater irrigation projects are different from normal fresh water irrigation projects. Many sites are entirely unsuited for wastewater treatment using the irrigation method.
6. Many sites that may appear to be unsuited for wastewater irrigation may in fact be made suitable through the use of imaginative engineering practices.
7. The concentrations of harmful trace elements and toxic substances not likely to be removed in the renovation media may well have to be controlled in irrigation waters or reduced or eliminated in advance of land disposal. Extensive soil-water and groundwater pollution and pollutants can persist for generations within the subsurface.
8. Recent theoretical developments and increased size of computers make it possible to evaluate regional water level changes likely to be brought about by large irrigation projects under complex field sites as well as to estimate quality changes likely to result from dilution, dispersion and other mechanisms operating within the soil-water and groundwater reservoirs. This capability should be exploited when designing large projects as our total documented experience with wastewater irrigation projects is still limited despite the number of irrigation projects in use.
9. Regulatory agencies should not be shortsighted in the levels of treatment they require of spray irrigation projects. If only phosphorous is to be removed, high application volumes--2,6 or more inches per week--might be used on a variety of soils with success. However, pollution may result from other points of view, MBAS, nitrates, etc. The physical-chemical-biological processes operating in the soil can be relied upon to provide a high degree of renovation of a number of constituents from the outset if allowed to do so.
10. Land ownership will greatly increase the cost of spray irrigation projects when compared to other methods of treatment particularly where real estate values are high. It would appear reasonable that long term lease agreements would be a suitable basis for state and federal funding of irrigation projects. Arrangements might be possible where land owners are paid for the use of their

land where water and nutrients are in excess of their needs but pay for these when they need them.

11. Hopefully the idea that irrigation projects are only suitable for small towns, trailer courts, and small industries is dead. The concept is applicable to major metropolitan centers as well. Public water supplies for these major centers are rarely derived from within city limits. Rather, water may be imported from sources 50 or more miles away. By contrast, wastewater treatment facilities have traditionally been located in the topographically low end of town for economic reasons. Large scale projects being planned or dreamed about show that these waters can be returned to their region of origin so that they might be renovated and made available for reuse. The problems involved are more apt to be political than technical or economical.

ACKNOWLEDGEMENT

Portions of this research were supported by funds from Demonstration Project Grant WPD 95-01 received initially from the Division of Water Supply and Pollution Control of the Department of Health, Education, and Welfare and subsequently from the Federal Water Pollution Control Administration, Department of the Interior. Partial support was also provided by the Office of Water Resources Research, USDI, as authorized under the Water Resources Research Act of 1964, Public Law 88-379.

REFERENCES

- Bear, J., D. Zaslavsky and S. Irmay, 1968. Physical principles of water percolation and seepage, UNESCO, 465p.
- Bittinger, M. W., H. R. Duke, and R. A. Longenbaugh, 1967. Mathematical simulations for better aquifer managements, International Assoc. Scientific Hydrology, Symposium of Haifa, publ. 72.
- Bredehoeft, A. D., 1970. Digital analysis of areal flow in multi-aquifer ground water system, a quasi three-dimensional model, Water Resources Research, Vol 6(30): 883-888.
- Bredehoeft, J. D. and G. F. Pinder, 1972. The application of the transport equations to a ground water system, 24th International Geol. Congress, Montreal Canada, Section 2, Hydrogeology, p.255-263.
- Bruce, R. R. and A. Klute, 1956. The measurement of soil moisture diffusivity, Proc. Soil Sci. Soc. Amer., Vol. 20: 458-462.
- Chow, V. T., 1964. Handbook of Applied Hydrology, McGraw-Hill Book Co., New York, N. Y.

- Cooley, R. L. 1970. A finite difference method for analyzing liquid flow in variably saturated porous media, Tech. Paper 22, The Hydrologic Engineering Center, Corps of Engineers, Sacramento, California, 44p.
- Cooley, R. L. and J. Peters, 1970. Finite element solutions of steady state potential flow problems, Hydrologic Engineering Center, U. S. Army Corps of Engineers, Publ. 723-440.
- Douglas, J. and H. H. Rachford, Jr., 1956. On the numerical solution of head conduction problems in two and three space variables, Trans. Amer. Math. Soc. 82: 421-439.
- Eisenberg, D. and W. Kauzmann, 1969. The structure and properties of water, Oxford Univ. Press, New York, N. Y., 296p.
- Fireman, M., and H. E. Haywood, 1955. Irrigation water and saline and alkali soils, p. 321-327, 1955 Yearbook of Agriculture, U. S. Dept. of Agriculture, 751p.
- Gray, D. M., D. I. Norum, and J. M. Wigham, 1970. Infiltration and the Physics of Flow of Water Through Porous Media, Section V, in Handbook on the Principles of Hydrology, Edited by D. M. Gray, National Research Council of Canada, p. 5.1-5.58.
- Jame, Y. W. and D. I. Norm, 1972. Phase composition of a partly frozen soil, Research Paper No. 11, Div. Hydrol. College of Eng. Univ. of Sask. Saskatoon, Saskatchewan.
- Kardos, L. T., 1970. A new prospect: preventing eutrophication of our lakes and streams; Environment, Vol. 12 (2): 10-27.
- Klock, G. O., 1972. Snowmelt temperature influence on infiltration and soil water retention, Jour. of Soil and Water Conservation, Vol. 27 (1): 12-14.
- Konikow, L. F., 1973. Simulation of hydrologic and chemical-quality variations in an irrigated stream aquifer system, Arkansas River Valley Colorado, PhD dissertation, The Penn. State University, University Park, Pa., 79p.
- Kuznik, I. A. and A. I. Bezmenov, 1963. Infiltration of melt water in frozen soils, Soviet Soil Sci., No. 7, p 665-670, Translation Scripta Technica, Inc.
- Larkin, P. A., 1962. Permeability of frozen soils as a function of their moisture content and fall tillage, Soviet Hydrol. Selected Papers, No. 4: 445-460, Amer. Geophys. Union Publishers.
- Lattman, L. H. and R. R. Parizek, 1964. Relationship between fracture traces and the occurrence of ground-water in carbonate rocks, Jour. of Hydrology, Vol. 2: 73-91.
- Norris, S. E., 1962. Permeability of glacial till, U. S. Geol. Survey Research.
- Ogata, A., 1970. Theory of dispersion in a granular medium, U. S. Geol. Survey Prof. Paper 411-I, 34p.
- O'Neal, A. M., 1949. Soil characteristics significant in evaluating permeability, Soil Sci., Vol. 67: 403-409.
- Parizek, R. R., L. T. Kardos, W. E. Sopper, et al, 1967. Waste water renovation and conservation, Penn State Studies No. 23, The Penn State University, University Park, Pennsylvania, 71p.

- Parizek, R. R. and E. A. Myers, 1968. Recharge of ground water from renovated sewage effluent by spray irrigation, Proc. of 4th American Water Resources Conference, New York, p. 426-443.
- Parizek, R. R. and B. E. Lane, 1970. Soil-water sampling using pan and deep pressure-vacuum lysimeters, Jour. Hydrology, Vol. 11: 1-21.
- Parizek, R. R. and B. Voight, 1970. Question 37: on remote sensing investigations for dam and reservoir construction in karst-terraces, Commission Internationale des Grands Barrages, Montreal, G. R. Q. 37, Vol. 6: 538-541.
- Parizek, R. R., 1971a. Prevention of coal mine drainage formation by well dewatering, Special Res. Report, Coal Research Section, The Pennsylvania State University, University Park, Pennsylvania
- Parizek, R. R., 1971b. Hydrogeologic framework of folded and faulted carbonates-influence of structure, p. 28-34, in hydrogeology and geochemistry of folded and faulted carbonate rocks of the central Appalachian type and related land use problems, Parizek, R. R., W. B. White and D. Langmuir, Guidebook, The Geological Society of America, 184p.
- Parizek, R. R., 1971c. Land use problem in carbonate terranes - waste water renovation and conservation, p. 153-170, in hydrogeology and geochemistry of folded and faulted carbonate rocks of the central Appalachian type and related land use problems, Parizek, R. R., W. B. White and D. Langmuir, Guidebook, The Geological Society of America, 184p.
- Parizek, R. R. and D. Langmuir, 1971. Management of leachates from sanitary landfills, Penna. Geol. Survey Bull. (in Press).
- Pinder, G. F. and J. D. Bredehoeft, 1968. Application of the digital computer for aquifer evaluation, Water Resources Res., Vol 4 (5): 1069-1093.
- Pinder, G. F. and H. H. Cooper, 1970. A numerical technique for calculating the transient position of the salt water front, Water Resources Res., Vol. 6 (3): 875-882.
- Pinder, G. F., 1971. An iterative digital model for aquifer evaluation, U. S. Geol. Survey, Open File Report, 44p.
- Post, F. A. and F. R. Dreibelbis, 1942. Some influences of frost penetration and micro-climate on the water relationships of woodland pasture and cultivated soils, Proc. Soil Sci. Soc. Amer., Vol 7: 95-104.
- Prickett, T. A. and C. G. Lonnquist, 1971. Selected digital computer techniques for ground water resource evaluation, Illinois State Water Survey, Bull. 55, Urbana, Illinois, 62p.
- Reddell, D. L. and D. K. Sunada, 1970. Numerical simulation of dispersion in groundwater aquifers, hydrology paper, Colorado State University, No. 41, 79p.
- Scheidegger, A. E., 1961. General theory of dispersion in porous media, Jour. Geophys. Res., Vol. 66 (10): 3273-3278.

- Schneider, I. F. and A. E. Erickson, 1972. Soil limitations for disposal of municipal waste water, Research Rept. 195, Farm Science, Michigan State University, Agric. Expt. Station, East Lansing, Michigan, 54p.
- Siddiqui, S. H. and R. R. Parizek, 1971. Hydrogeologic factors influencing well yields in folded and faulted carbonate rocks in central Pennsylvania, Water Resources Res., Vol. 7 (5): 1295-1312.
- Smith, R. M. and D. R. Browning, 1946. Some suggested laboratory standards of subsoil permeability, Proc. Soil Sci. Soc. Amer., Vol. 11: p. 21-26.
- Sopper, W. E. and L. T. Kardos, 1972. Effects of municipal waste-water disposal on the forest ecosystem. Jour. of Forestry 70(9): 540-545.
- Storey, H. C., 1955. Frozen soil and spring and winter floods, p. 179-184, Water, Yearbook of Agriculture, U. S. Dept. of Agriculture, 751p.
- Walton, W. C., 1965. Ground water recharge and runoff in Illinois, Illinois State Water Survey Rept. of Investigation 48, Urbana, Ill., 55p.
- Walton, W. C., 1970. Groundwater Resource Evaluation, McGraw-Hill, Inc. 664p.
- Weast, R. C., 1968. Handbook of chemistry and physics (49th edition) Chem. Rubber Co., Cleveland, Ohio, 2120p.
- Zavodchikov, A. B., 1962. Snowmelt losses to infiltration and retention on drainage basins during snow melting period in Northern Kazakhstan, Soviet Hydrol. Selected Papers, No. 1, p. 37-42, Amer. Geophys. Union.
- Zienkiewicz, O. C. and Y. K. Cheung, 1965. Finite elements in the solution of field problems, The Engineer, Vol. 220 (5722): 507-510.
- Zienkiewicz, O. C., P. Mayer, and Y. K. Cheung, 1966. Solution of anisotropic seepage by finite elements, Amer. Soc. Civil Engineers, Engin. Mech. Div. Jour., Vol. 92, No. EM1, p. 111-120.

RENOVATION OF MUNICIPAL WASTEWATER THROUGH LAND
DISPOSAL BY SPRAY IRRIGATION

322 D

Louis T. Kardos and William E. Sopper
Department of Agronomy and School of Forest Resources
The Pennsylvania State University

Diversion of treated municipal wastewater from its usual disposal medium, surface waters, to the land means that the diverted wastewater with all its constituents must ultimately reside in the soil or be removed from the soil in harvested vegetation, by vapor loss to the atmosphere or by movement in the soil solution to the groundwater. The latter in turn may cycle as base flow to the surface waters or be re-used as a pumped water supply. It is imperative therefore that the quality changes in the wastewater as it passes through the living filter, the soil and its associated biosystems, be documented and evaluated.

In the Penn State project this was accomplished by extracting soil solution samples with suction lysimeters installed at various depths in the soil profile. Soil water samplers were obtained from Soil Moisture Equipment Co., Santa Barbara, California. Details concerning the method of installation and operation of these other monitoring systems are given in Penn State Studies No. 23 (Parizek et al., 1967). The chemical quality of the chlorinated secondary treated wastewater was monitored by obtaining a composite of the wastewater being applied through the sprinklers during each irrigation sequence. Irrigation application rates were 0.25 inches per hour and amounts applied were 0, 1, 2, or 4 inches at weekly intervals. Various sites received irrigation ranging from 16 to 32 weeks (Apr.-Nov.) on the corn rotation area, 40 to 50 weeks (Jan.-Dec.) on the reed canarygrass area and 23 to 52 weeks (either Apr.-Nov. or Jan.-Dec.) on forested areas. The irrigation programs and soil types for these areas are shown in Table 1. Detailed descriptions of the soil types are given in Parizek et al. (1967). Average annual concentration of various constituents in the applied wastewater are shown for the corn rotation area for 1963-70 in Table 2 and are representative of the concentrations in wastewater applied to the other areas.

The extent of renovation of the applied wastewater may be expressed as the change in mean annual concentration of a particular constituent in the applied wastewater when compared with that found in the soil solution in the suction lysimeters. However this computation is not applicable to the nitrogen components since they are biologically changed from one form to another. Because nitrate-N is a widely used limiting parameter for drinking water, the overall

Table 1. Irrigation Programs for Agronomy and Forestry Areas

Vegetative Cover	Soil ^{1/}	Weekly Application in Inches	Seasonal Irrigation Amounts in Inches								Total
			1963 June- Dec.	1964 March- Nov.	1965 April- Nov.	1966 April- Nov.	1967 April- Nov.	1968 April- Oct.	1969 April- Oct.	1970 April- Oct.	
Rotation-Corn	H	1	24	33	29	32	26	20	16	16	196
Rotation-Corn	H	2	48	66	58	64	52	40	32	32	392
Hardwoods	H	1	23	33	30	32	28	31	28	25	230
Red Pine	H	1	23	33	30	32	28	31	28	25	230
Red Pine	H	2	46	66	60	64	56	62	56	50	460
Old Field	H	2	46	66	60	64	56	62	56	50	460
Reed canarygrass	H	2	--	July- Nov.	Apr.- Dec.	Jan.- Dec.	Jan.- Dec.	Jan.- Dec.	Jan.- Dec.	Jan.- Dec.	572
Hardwoods	M	2	--	--	Nov.23- Dec.	Jan.- Dec.	Jan.- Dec.	Jan.- Dec.	Jan.- Dec.	Jan.- Dec.	516

^{1/} H = Hublersburg silt loam or clay loam
M = Morrison sandy loam

Table 2. Average Concentration of Various Constituents in Wastewater Applied to the Corn Rotation Area at Rates of One and Two Inches Per Week During 1963 to 1970.

Constituent	1963		1964		1965		1966		1967	
	1	2	1	2	1	2	1	2	1	2
	Concentration (mg/l)									
Phosphorus	9.680	9.720	8.620	8.545	6.310	6.935	5.970	5.370	4.930	6.725
NRAS	3.17	3.20	1.47	1.54	1.09	0.98	0.33	0.36	0.26	0.30
Nitrate-N	5.7	5.8	14.9	13.8	6.3	5.9	8.1	8.0	5.4	5.2
Organic-N _L	7.3	7.3	3.7	2.8	2.9	2.5	6.5	4.6	4.0	4.0
Potassium	17.1	16.8	16.4	15.3	19.9	20.6	20.6	19.2	18.4	18.6
Calcium	32.4	32.3	35.6	35.0	24.8	25.3	30.1	28.9	22.6	22.6
Magnesium	18.5	19.0	19.2	19.1	13.4	14.0	19.8	18.4	11.3	12.2
Sodium	46.0	46.9	32.2	34.2	36.0	35.7	41.4	38.6	39.5	40.0
Manganese	†	†	†	†	†	†	0.08	0.08	0.16	0.12
Chloride	43.4	43.9	40.0	38.9	42.7	43.8	54.4	51.4	48.9	45.0
Boron	†	†	0.40	0.40	0.32	0.32	0.36	0.36	0.42	0.41
pH	7.3	7.3	7.2	7.3	7.5	7.6	7.6	7.7	7.6	7.8

1/ Values included ammoniacal nitrogen. For the period 1965-1967, values are underestimated due to loss of undetermined amounts of ammoniacal nitrogen during analysis. Method of analysis changed in 1968.

† Values not determined.

Table 2. Continued.

Constituent	1968		1969		1970	
	1	2	1	2	1	2
	Concentration (mg/l)					
Phosphorus	5.345	7.105	4.675	6.560	4.265	4.135
MBAS	0.50	0.57	0.57	0.54	0.44	0.44
Nitrate-N	4.7	4.2	5.8	5.1	5.8	4.9
Organic-N	2.9	3.8	7.8	4.8	3.3	4.1
Ammoniacal-N	15.7	14.6	11.4	12.8	5.3	6.3
Potassium	16.7	17.1	15.2	13.8	13.5	13.7
Calcium	20.9	20.2	34.6	32.0	29.8	24.2
Magnesium	10.6	10.4	17.4	16.3	14.3	11.8
Sodium	37.4	40.8	51.5	52.8	34.3	32.7
Manganese	0.36	0.18	0.12	0.10	0.14	0.11
Chloride	50.6	41.2	60.6	44.4	48.1	45.0
Boron	0.38	0.40	0.34	0.38	0.29	0.29
pH	7.6	7.7	7.8	7.9	7.9	8.0

renovation for the nitrogen fractions will be discussed in terms of the limiting concentration of 10 mg. $\text{NO}_3\text{-N}$ per liter being exceeded or not.

Since phosphorus and nitrogen are the two key eutrophic elements most of the discussion in this paper will be focused on them. Table 3 shows the mean annual concentration of phosphorus in the applied effluent and at the 6, 24 and 48 inch depths in the corn rotation area from 1965 through 1970. The Duncan's separations shown are between treatments within years and within depths. The wastewater treatments began in 1963 but suction lysimeter samples for a complete season were not obtained until 1965. These results show that on the wastewater treated areas P concentration decreases drastically between the upper six inches and the 24-inch depth, remains essentially constant at the 24 and 48-inch depths, does not differ or is erratically different from the control area at the deeper positions but is significantly greater than the control ($P = 0.01$) at the six-inch depth on the two-inch per week wastewater area each year beginning in 1965. Differences between the control and 1-inch per week area were generally not significant at the 6-inch depth.

For the 2-inch treatment the minimum decrease in concentration at the 6-inch depth was 91 percent in 1967 and the maximum was 98 percent in 1965. On the 1-inch treatment area the minimum decrease at the 6-inch depth was 97.1 percent in 1967 and the maximum was 99.1 percent in 1965. In 1970 the decrease was 96.7 percent for the 2-inch treatment and 98.4 percent for the 1-inch treatment at the six-inch depth. At the 48-inch depth decrease in concentration ranged from 98.1 percent to 99.6 percent for the 2-inch treatment and from 98.6 to 99.8 percent for the 1-inch treatment. The data indicate that phosphorus is not leaking out of the soil profile into the groundwater at a higher concentration from the wastewater treated area than from the control and that excellent removals of phosphorus are continuing through the eighth year of treatment on the corn rotation area. A more detailed description of the phosphorus retention mechanisms is given in an unpublished Ph.D. thesis (Edwards, 1968) and in the chapter by Hook, Kardos and Sopper (1973).

The reed canarygrass area, which is on the same soil type and has been receiving two inches of effluent weekly, year around, since 1964, and hence almost twice as much phosphorus annually as the corn rotation area, is much more effective in removing phosphorus. Detailed phosphorus data for the reed canarygrass area are in Table 4. The mean annual phosphorus concentrations at each depth were not significantly different from year to year. Through 1970, the reed canarygrass area had received 180 inches more wastewater than the corn rotation area but lysimeter concentration at the six inch depth was only 0.186 mg/l compared to 0.557 mg/l in the corn area.

Table 3. Mean Annual Concentration (mg/l) of Phosphorus in Suction Lysimeter Samples at Three Depths in Corn Rotation Plots Receiving Various Levels of Wastewater. 1965-70.

Depth in Inches	1965			1966			1967		
	Wastewater Application - Inches Per Week								
	0	1	2	0	1	2	0	1	2
6	0.035a**	0.047a	0.118b	0.044a**	0.077a	0.269b	0.046a**	0.149a	0.571b
24	0.025a**	0.020a	0.044b	0.045N.S.	0.036	0.055	0.39a**	0.039a	0.086b
48	0.032b**	0.016a	0.022ab	0.045b*	0.028a	0.036ab	0.039a**	0.030a	0.054b
1968									
1969									
1970									
	Wastewater Application - Inches Per Week								
	0	1	2	0	1	2	0	1	2
6	0.035a**	0.160a	0.586b	0.022a**	0.073a	0.557b	0.042a**	0.060a	0.138b
24	0.048a*	0.063ab	0.078b	0.079N.S.	0.046	0.058	0.054N.S.	0.064	0.094
48	0.041N.S.	0.052	0.060	0.066N.S.	0.066	0.070	0.034a**	0.052ab	0.075b

1/ The Duncan's separations are between wastewater treatments within depths and within years.

** = P(0.01), * = P(0.05), N.S. = not significant

Table 4. Mean Annual Concentration of Phosphorus in Suction Lysimeter Samples at Three Depths and in the Applied Wastewater in the Reed Canarygrass Area Receiving Two Inches of Wastewater Weekly from 1966 to 1970.

Lysimeter Depth	1966	1967	1968	1969	1970
inches	concentration - mg/l				
6	0.164	0.128	0.218	0.186	0.161
24	0.091	0.110	0.120	0.089	0.067
48	0.055	0.053	0.052	0.035	0.038
Wastewater	7.690	7.695	8.450	4.185	3.490

Comparative data for phosphorus in the forest areas are given in Table 5. The irrigation programs and soil types for these areas are given in Table 1. Although there are variations in time of initiation of wastewater irrigation and total irrigation load on the various areas, in 1970 phosphorus concentration at the 48-inch depth on the Morrison sandy soil area is substantially higher than on the finer textured Hublersburg soil areas. The detailed data in Table 5 show some erratic fluctuations at any one depth from year to year but the grand average over years show the greatest effect of wastewater additions on the phosphorus concentration in the 6-inch zone, with diminishing effect in the deeper zones.

Although the concentrations of phosphorus in the percolating soil water was adequately small on all of the sites the same cannot be said for nitrate-nitrogen. Table 6 and 7 indicate that the corn rotation area held nitrate-nitrogen levels below the recommended Public Health Service limit for drinking water, 10 mg $\text{NO}_3\text{-N}$ per liter, on the control and 1-inch per week treatments quite well. However, at the 2-inch per week level the mean annual concentration remained below the limit only when grass-legume hays occupied from 28 to 68 percent of the site in 1965 through 1968. In 1969 and 1970 when the entire site was occupied by corn the mean annual concentration exceeded the Public Health Service limit. On the reed canarygrass area where more than twice as much nitrogen was added annually in the year-around 2-inch application the mean annual $\text{NO}_3\text{-N}$ concentration remained well below the Public Health Service limit.

The nitrate data for the forested areas are given in Table 8. It is clear that the forested areas can handle a 1-inch per week application without having the mean annual concentration of the 48-inch depth exceed the Public Health Service limit. However, when 2 inches were

Table 5. Mean Annual Concentration (mg/l) of Phosphorus in Suction Lysimeter Samples at Three Depths in Forest Areas Receiving Various Levels of Wastewater During the Period 1965 to 1970.

Red Pine - Hublersburg Soil									
Year	6-Inch Depth			24-Inch Depth			48-Inch Depth		
	inches per week			inches per week			inches per week		
	0	1	2	0	1	2	0	1	2
1965	0.450	0.178	0.335	--	0.190	0.517	0.040	0.300	0.400
1966	0.157	0.202	0.373	0.064	0.024	0.049	0.043	0.134	0.143
1967	0.065	0.149	0.242	0.040	0.108	0.072	0.053	0.092	0.031
1968	0.024	0.562	1.007	0.013	0.253	0.109	0.075	0.089	0.044
1969	0.020	0.056	0.261	0.040	0.068	0.040	0.010	0.064	0.037
1970	0.171	0.094	0.235	0.076	0.053	0.065	0.065	0.076	0.070
Ave.	0.148	0.207	0.409	0.047	0.116	0.142	0.048	0.126	0.121

Hardwood - Hublersburg Soil						
Year	6-Inch Depth		24-Inch Depth		48-Inch Depth	
	inches per week		inches per week		inches per week	
	0	1	0	1	0	1
1965	0.065	--	0.010	0.390	0.050	0.250
1966	0.048	0.429	0.034	0.077	0.037	0.043
1967	0.053	0.068	0.030	0.078	0.044	0.077
1968	0.064	0.166	0.044	0.388	0.106	0.222
1969	0.023	0.212	0.025	0.065	0.072	0.047
1970	0.047	0.244	0.046	0.087	0.033	0.143
Ave.	0.050	0.224	0.032	0.181	0.057	0.130

Table 5. Continued.

Old Field - Hublersburg Soil						
Year	6-Inch Depth		24-Inch Depth		48-Inch Depth	
	inches per week		inches per week		inches per week	
	0	2	0	2	0	2
1965	0.065	--	--	0.116	--	0.460
1966	0.038	0.091	0.030	0.069	0.030	0.140
1967	0.045	0.136	0.032	0.097	0.039	0.068
1968	--	0.275	0.122	0.125	0.040	0.053
1969	0.036	0.293	--	0.122	0.051	0.098
1970	0.035	0.342	0.102	0.119	0.042	0.114
Ave.	0.044	0.227	0.072	0.108	0.040	0.156

Hardwood - Morrison Soil						
Year	6-Inch Depth		24-Inch Depth		48-Inch Depth	
	inches per week		inches per week		inches per week	
	0	2	0	2	0	2
1966	0.076	0.255	0.091	0.030	0.059	0.042
1967	0.049	0.113	0.223	0.057	0.068	0.063
1968	0.020	0.452	0.050	0.129	0.071	0.116
1969	0.031	0.319	0.032	0.104	0.059	0.137
1970	0.052	0.277	0.026	0.119	0.051	0.209
Ave.	0.046	0.283	0.084	0.088	0.062	0.113

Table 6. Mean Annual Concentration (mg/l) of Nitrate-Nitrogen in Suction Lysimeter Samples at Three Depths in Corn Rotation Plots Receiving Various Levels of Wastewater During the Period 1965 to 1960.

Depth in Inches	1965				1966				1967			
	Wastewater Application - Inches Per Week				Wastewater Application - Inches Per Week				Wastewater Application - Inches Per Week			
	0	1	2		0	1	2		0	1	2	
6	6.8N.S.	4.2	4.7	4.6b** ^{1/}	1.7a	5.0b	1.1a**	2.4b	5.2c			
24	6.1N.S.	6.8	7.7	3.3b**	1.8a	4.0b	3.1b**	2.2a	6.6c			
48	5.2a**	8.2b	9.7c	4.7a**	4.9a	7.0b	3.4a**	3.8a	7.1b			
1968												
6	12.6N.S.	12.0	10.5	14.7N.S.	11.9	17.3	9.6N.S.	8.5	6.5			
24	2.6a**	4.5b	10.6c	10.0b**	5.3a	14.0c	7.3N.S.	6.0	8.1			
48	4.5a**	5.8b	9.5c	9.4b**	7.7a	13.5c	10.3N.S.	8.9	10.9			
1969												
1970												

^{1/} The Duncan's separations are between wastewater treatments within depths and within years.
 ** = P(0.01); N.S. = non-significant.

Table 7. Mean Annual Concentration of Nitrate-Nitrogen in Suction Lysimeter Samples at Three Depths in the Reed Canarygrass Area Receiving Two Inches of Wastewater Weekly During the Period 1966 to 1970.

Lysimeter Depth	1966	1967	1968	1969	1970
inches	concentration - mg/l				
6	0.8N.S.	0.6	0.7	0.6	1.2
24	2.2N.S.	1.5	1.8	1.1	0.8
48	3.7b* ^{1/}	3.3ab	3.1ab	2.5a	2.4a

^{1/} The Duncan's separations are between years within depths.
 * = P(0.05), N.S. = non-significant

applied per week either in the April-Nov. period with red pine on the Hublersburg soil or year-around with hardwoods on the Morrison soil the NO₃-N concentration at the 48-inch depth rapidly exceeded the Public Health Service limit. On the other hand, 2 inches of wastewater applied weekly on the old field area in the April-Nov. period did not result in excessive NO₃-N values at the 48-inch depth.

The difference between the 2-inch red pine and 2-inch old field areas on the same soil type probably resides in the difference in the recycling of the nitrogen through the two vegetative covers. In the red pine relatively less nitrogen is assimilated in the annual growth than in the herbaceous annuals and perennials in the old field and large amounts of readily decomposable organic residues are deposited annually in the old field. The larger quantities of carbonaceous material in the old field area may also promote a higher degree of denitrification in this fine textured soil. The sandiness of the soil on the 2-inch hardwood area would not be conducive to denitrification of the larger nitrogen load applied in a year-around irrigation period and the hardwood leaf litter although more decomposable than the red pine needle litter would not be as decomposable as the old field residues.

The explanation above was serendipitously corroborated when the 2-inch red pine area was clearcut after many of the trees were felled by a heavy wet snow and windstorm in November, 1968. After the clear-cutting in 1969 the area grew up to a dense cover of herbaceous vegetation similar to that on the irrigated old field area. A large mass of

carbonaceous material was deposited on the surface that fall and in 1970 another dense cover of herbaceous vegetation was produced and the mean annual concentration of $\text{NO}_3\text{-N}$ dropped from a value of 24.2 mg $\text{NO}_3\text{-N/l}$ in 1969 to a value of 8.3 mg $\text{NO}_3\text{-N/l}$ in 1970 and to 3.0 mg $\text{NO}_3\text{-N/l}$ in 1971.

Further support for the importance of denitrification in decreasing the inputs of nitrate to the groundwater was obtained in the data from the Hardwood area on the Hublersburg soil which received four inches of wastewater, weekly, in the April-Nov. period (Table 8). In spite of doubling the nitrogen load, the $\text{NO}_3\text{-N}$ concentration at 48 inches remained below 10 mg/l, probably because the larger hydraulic load encouraged more denitrification.

Changes in concentration of other chemical constituents in the wastewater have also been examined. For instance, on the corn rotation area during 1970 the concentration in the applied wastewater was greater than in the lysimeter samples at the 48-inch depth. By the time the percolate reached the 48-inch depth some degree of renovation was secured for all constituents. However, if one compares the concentrations in the control area with those in the wastewater treated areas the pattern is not consistent. For example concentrations of K, Ca and Mn were higher in the control area at 48 inches than in the wastewater treated areas, while the reverse was true for Mg, Na, Cl, B and total-N ($\text{NO}_3\text{-N} + \text{Org.-N} + \text{NH}_4\text{-N}$). It should be pointed out that the control area did receive substantial amounts of K and Ca in the commercial fertilizer that was applied to that area but not to the wastewater areas. The greatest increase in concentration as a result of the wastewater treatment occurred with Na and Cl. The sodium concentration increased almost 14-fold on the two-inch treatment compared to the control and the chloride concentration increased to a value almost 5 times that of the control. The largest relative decrease in concentration from that in the wastewater occurred with potassium as a 15-fold decrease from 13.7 mg/l in the wastewater to 0.9 mg/l at the 48-inch depth in the 2-inch wastewater area.

Boron and manganese were substantially decreased in concentration from that in the wastewater, boron decreasing from 0.29 to 0.09 mg/l and manganese decreasing from 0.11 to 0.03 mg/l. Both of these concentrations as well as those of the other constituents, except nitrate-nitrogen, are well below the recommended limits for drinking water. The nitrate-nitrogen, which constitutes about 83 percent of the total nitrogen in the percolate on the corn area can be substantially decreased below the $\text{NO}_3\text{-N}$ limit by using a perennial grass as the vegetative cover rather than an annual crop such as corn. These nitrogen relationships were discussed earlier and the problem of handling the excess nitrogen should not be an unsurmountable one.

Table 8. Mean Annual Concentration (mg/l) of Nitrate-Nitrogen in Suction Lysimeter Samples at Three Depths in Forest Areas Receiving Various Levels of Wastewater. 1965-1970

Red Pine - Hublersburg Soil									
Year	6-Inch Depth			24-Inch Depth			48-Inch Depth		
	inches per week			inches per week			inches per week		
	0	1	2	0	1	2	0	1	2
1965	0.2	1.7	9.2	--	0.4	10.7	0.9	2.2	3.9
1966	0.1	1.5	26.8	0.2	0.2	14.6	0.1	2.1	9.3
1967	0.9	6.9	9.6	0.4	5.1	10.6	0.9	1.7	13.8
1968	0.5	18.7	21.8	0.2	6.1	17.6	0.9	2.7	19.9
1969	0.1	17.6	10.5	0.2	9.0	19.6	0.2	4.2	24.2
1970	<1	11.0	4.8	1.7	5.5	3.3	<1	5.3	8.3
Ave.	0.3	9.6	13.8	0.5	4.4	12.7	0.6	3.0	13.2

Hardwood - Hublersburg Soil						
Year	6-Inch Depth		24-Inch Depth		48-Inch Depth	
	inches per week		inches per week		inches per week	
	0	1	0	1	0	1
1965	0.1	1.0	--	0.2	--	0.0
1966	0.1	3.3	0.1	2.1	0.1	0.2
1967	0.4	13.3	0.4	5.4	0.3	1.4
1968	0.4	10.9	0.2	10.0	0.1	8.0
1969	0.4	6.8	0.3	4.9	0.1	7.2
1970	<1	9.5	<1	4.7	<1	5.0
Ave.	0.3	7.5	0.3	4.6	0.2	3.6

Table 8. Continued.

Old Field - Hublersburg Soil						
Year	6-Inch Depth		24-Inch Depth		48-Inch Depth	
	inches per week		inches per week		inches per week	
	0	2	0	2	0	2
1965	0.1	5.1	0.1	8.4	0.3	8.0
1966	0.1	4.3	0.4	7.5	0.1	5.0
1967	0.4	4.6	0.4	12.0	0.3	6.1
1968	0.0	4.8	0.2	4.9	0.2	3.7
1969	0.4	7.3	0.4	8.3	0.2	2.3
1970	<1	5.2	1.0	2.4	<1	3.5
Ave.	0.3	5.2	0.4	7.3	0.2	4.8

Hardwood - Morrison Soil						
Year	6-Inch Depth		24-Inch Depth		48-Inch Depth	
	inches per week		inches per week		inches per week	
	0	2	0	2	0	2
1966	0.2	12.5	0.5	14.9	0.1	10.6
1967	--	16.9	0.5	20.4	1.4	19.2
1968	0.1	22.3	0.2	26.0	0.1	25.9
1969	0.4	17.0	0.1	24.4	0.3	23.7
1970	1.1	21.0	<1	34.8	1.0	42.8
Ave.	0.5	17.9	0.3	24.1	0.6	24.4

Hardwood - Hublersburg Soil								
Year	6-Inch Depth		24-Inch Depth		48-Inch Depth		72-Inch Depth	
	inches per week		inches per week		inches per week		inches per week	
	0	4	0	4	0	4	0	4
1965	0.1	7.3	--	4.2	--	2.3	--	5.2
1966	0.1	11.1	0.1	9.3	0.1	9.1	--	9.5
1967	0.4	8.6	0.4	5.1	0.3	3.4	--	8.3
1968	0.4	8.8	0.2	3.2	0.1	0.9	--	8.2
Ave.	0.3	9.0	0.2	5.5	0.2	3.9	--	7.8

The data allow one to conclude that with appropriate management of nitrogen loads to maximize utilization by the vegetation and with hydraulic loads adjusted to the soil site to maximize denitrification it should be possible to recharge water of drinking quality into the aquifer below a wastewater disposal site.

ACKNOWLEDGEMENT

Research reported here is part of the program of the Waste Water Renovation and Conservation Project of the Institute for Research on Land and Water Resources, and Hatch Projects No. 1481 and 1809 of the Agricultural Experiment Station, The Pennsylvania State University, University Park, Pennsylvania.

Portions of this research were supported by funds from Demonstration Project Grant WPD 95-01 received initially from the Division of Water Supply and Pollution Control of the United States Department of Health, Education, and Welfare and subsequently from the Federal Water Pollution Control Administration, United States Department of the Interior. Partial support was also provided by the Office of Water Resources Research, United States Department of the Interior, as authorized under the Water Resources Research Act of 1964, Public Law 88-379.

REFERENCES

- Edwards, Ivor K. The Renovation of Sewage Plant Effluent by the Soil and by Agronomic Crops. Ph.D. Thesis in Agronomy. 174pp. Sept. 1968.
- Hook, James E., L. T. Kardos and W. E. Sopper. 1973. Effect of Land Disposal of Wastewaters on Soil Phosphorus Relations. Proceedings of Symposium on Recycling Treated Municipal Wastewater and Sludge Through Forest and Cropland. The Pennsylvania State University Press.
- Parizek, R. R., L. T. Kardos, W. E. Sopper, E. A. Myers, D. E. Davis, M. A. Farrell and J. B. Nesbitt. 1967. Waste Water Renovation and Conservation. Penn State Studies No. 23, 71pp. The Pennsylvania State University, University Park, Pennsylvania.

RENOVATING SECONDARY EFFLUENT BY GROUNDWATER RECHARGE
WITH INFILTRATION BASINS

Herman Bouwer
U. S. Water Conservation Laboratory
Agriculture Research Service, USDA

063H

The Salt River Valley in Central Arizona is changing from a predominantly agricultural to a predominantly urban valley. Groundwater currently supplies about one-third of the municipal and agricultural water needs in the area of the Salt River Project, which is the main irrigation district in the Valley. The resulting depletion of the groundwater can be reduced if the sewage effluent produced by the increasing population (presently about one million) can be reused. The principal contenders for the sewage effluent would be irrigated agriculture and recreation (parks, golf courses, and lakes). Certain industrial applications may also be possible, but reuse for drinking water is still far off (Long and Bell, 1972).

Unrestricted use of sewage effluent for recreational lakes and irrigation requires tertiary treatment. A promising technique for such treatment in the Salt River Valley would be by groundwater recharge, with spreading basins in the Salt River bed. This normally dry bed traverses the Valley from east to west, attains a width of one-half to one mile, and consists mostly of a loamy sand top layer underlain by coarse sand and gravel strata. The groundwater table is at a depth of 10 to 50 feet in the western part of the Valley. A chain of infiltration basins could be constructed on each side of the river bed. After infiltration, the sewage water would move to the center of the river bed where it would be pumped from a series of wells.

Because the performance of a land-filtration system depends so much on the local conditions of climate, soil, and groundwater, a pilot system should precede any large-scale development. For the Salt River bed, such a system was installed in 1967. The study is in cooperation with the Salt River Project, which received a demonstration grant from the Environmental Protection Agency for partial support of the first three years of study. The findings obtained and their use in the design of a large-scale system will be presented in the following sections.

EXPERIMENTAL PROJECT

Description of System

The experimental system, called the Flushing Meadows Project, is located in the Salt River bed west of Phoenix, about 1.5 miles west of 91st Avenue. The project contains six parallel infiltration basins of 20 by 700 feet each and 20 feet apart, and a number of observation wells. Secondary effluent from the 91st Avenue sewage treatment plant (activated sludge process) is pumped into the basins from the effluent channel on the north side of the project.

The first 50 feet of each infiltration basin were made into a sedimentation pond by excavating the bottom of the basin and constructing a gravel dam 50 feet from the inlet. Constant water depth in each basin is maintained by an overflow structure at the lower end of the basin. Infiltration rates in the basins are calculated from the inflow at the upper end and the outflow at the lower end measured with critical depth flumes (Replogle, 1971).

The soil profile beneath the basins consists of about 3 feet of fine, loamy sand (saturated hydraulic conductivity about 4 feet/day) underlain by coarse sand and gravel layers to a depth of about 240 feet, where a clay layer begins. The profile has been described in detail (Bouwer, 1970). The static water table is at a depth of about 10 feet. The observation wells are 20 feet deep, with the exception of the East Center Well (ECW), which is 30 feet deep, and the West Center Well (WCW), which is 100 feet deep. All wells are cased with non-perforated steel pipe, open at the bottom.

Infiltration Rates and Flooding Schedules

The infiltration rates generally ranged between 2 and 3 feet per day at the beginning to between 1 and 2 feet per day at the end of an inundation period, at a water depth of 1 foot. The decrease in infiltration was due to clogging of the surface layer of the soil and it was essentially linear with time. Drying the basins restored the infiltration rate. The infiltration recovery during dry-up was S-shaped, and essentially complete recovery of the infiltration rate was generally obtained after 10 days of drying in the summer and 20 days in the winter.

Maximum long term "hydraulic loading" was obtained with flooding periods of 2 to 3 weeks, alternated with dry periods of about 10 days in summer and 20 days in winter. With this schedule, an annual infiltration of 400 feet has been obtained. Regular

drying of the basins was also necessary to provide oxygen in the soil for BOD removal and nitrification of ammonium.

Suspended solids had a significant effect on infiltration rates. In the summer and fall, the suspended solids content was generally in the 10 to 20 mg/l range, which was acceptable for infiltration. In the winter and spring, however, the suspended solids content was often in the 50 to 100 mg/l range. This caused a build-up of sludge in the basins, which was removed each year in late spring or early summer by "shaving" the basins with a front-end loader. Best infiltration results were obtained if the suspended solids content was less than 10 mg/l (Rice, 1972).

Infiltration rates in basins with an established grass cover (Bermudagrass) were about 25% higher, and those in a gravel-covered basin (2 inches of concrete sand topped by 4 inches of 3/8-inch rock) were about 50% lower, than those in a bare soil basin, when the soil variability between the basins was taken into account. In the spring, however, short flooding periods had to be used for the grassed basins to allow the grass to grow to a mature stand. During this sequence of short flooding periods, the infiltration amounts were less than those in the bare soil basin where flooding periods of 2 to 3 weeks could be used for the entire year. Moreover, the increased infiltration obtained for a complete grass cover could also have been obtained in the basins without vegetation by increasing the water depth. Thus, over a long period, non-vegetated basins can yield similar or even higher infiltration rates than vegetated basins.

Vegetation may be desirable where the wastewater is applied with sprinklers to protect the soil surface against the impact of the drops. Also, vegetated basins may remove more nitrogen from the effluent than non-vegetated basins (see section on Nitrogen). The low infiltration rates in the gravel-covered basin are attributed to accumulation of solids at the surface of the underlying soil, and to poor drying of this soil during dry periods caused by a mulching effect of the gravel layer.

Water Table Response

The static depth of the groundwater table was about 10 feet below the bottom of the infiltration basins. The water table beneath the basins rose during infiltration and reached a pseudo-equilibrium position which, in the center, was about 2 to 4 feet (depending on the infiltration rates) above the static water table level. During dry periods, the water table receded to its static level.

Based on the assumption that the sand and gravel layers of the aquifer formed a uniform anisotropic medium, the hydraulic conductivity of the aquifer was evaluated as 282 feet/day horizontally and 17.6 feet/day vertically. These values were obtained with an electrical resistance network analog from the response of the water levels in the East Center Well and the West Center Well to infiltration, and they agreed with directional hydraulic conductivity data obtained from permeability tests on the observation wells (Bouwer, 1970).

Water Quality Improvement

Quality parameters of the secondary effluent and the water pumped from the 30-foot-deep East Center Well (ECW), mostly obtained in 1971, are shown in Table 1. The effluent was sampled

Table 1. General Range of Quality Parameters of Secondary Sewage Effluent and Renovated Water from East Center Well

Constituent	Effluent	East Center Well
	mg/l	mg/l
BOD	10-20	0-1
COD	30-60	10-20
TOC	10-25	1-7
Org.-N	2-6	0.3-0.7
NO ₃ -N	0-1	0.1-50
NO ₂ -N	0-3	0-1
NH ₄ -N	20-40	5-20
PO ₄ -P	7-12	4-8
F	3-5	2-2.5
B	0.7-0.9	0.7-0.9
Cu	0.1	0.02
Zn	0.2	0.1
Cd	0.008	0.007
Pb	0.08	0.07
Total salts	1,000-1,200	1,000-1,200
pH	7.7-8.1	6.9-7.2
Fecal coliforms per 100 ml	10 ⁵ -10 ⁶	0-100

continuously for 24-hour periods. Grab samples were obtained almost daily from ECW. The water obtained from ECW is effluent water that infiltrated in basins 3 and 4, then moved through about

6 feet of unsaturated soil to the water table, after which it traveled about 30 feet below the water table to the intake of the well. The underground detention time of ECW-water was about 5 to 10 days, depending on the infiltration rate in the basins.

Oxygen demand. The BOD of the renovated water from ECW was essentially zero (Table 1). The COD of ECW-water was in the 10- to 20-mg/l range, which was about the same as the COD of the native groundwater in the area. The total organic carbon content (TOC) of the renovated water averaged about 4 mg/l, indicating some residual organic matter.

Nitrogen. The nitrogen in the effluent was mostly in the ammonium form (Table 1). Total nitrogen levels in the effluent ranged from around 25 mg/l in the summer to around 35 mg/l in the winter. The form and concentration of the nitrogen in the renovated water depended on the length of the inundation periods of the basins and on whether the basins were vegetated.

When short, frequent flooding periods were used for the basins (i.e. 2 days wet-2 days dry), the oxygen levels in the soil were sufficiently high for complete nitrification of the ammonium. In that case, the renovated water from the wells contained $\text{NH}_4\text{-N}$ levels of 1-5 mg/l and $\text{NO}_3\text{-N}$ levels of 20-30 mg/l.

If medium inundation periods were used (i.e. 2 weeks wet-2 weeks dry), $\text{NO}_3\text{-N}$ levels were close to zero in the renovated water, except for $\text{NO}_3\text{-N}$ peaks which occurred a few days after the start of each new inundation. These peaks were due to the arrival of effluent water that was held as capillary water in the soil during the preceding dry period. Because of the aerobic conditions in the upper layers of the soil during drying, ammonium adsorbed by the clay and organic matter during inundation, plus the ammonium in the capillary effluent water itself, could be converted to nitrate. When the basins were flooded again, this nitrate-rich effluent water was then pushed down by the newly infiltrated water, and when it arrived at a well caused a $\text{NO}_3\text{-peak}$ in the water samples from that well. The arrival time of the $\text{NO}_3\text{-peak}$ at ECW ranged between 5 and 10 days, depending on the infiltration rate in basins 3 and 4.

If very long inundation periods were used (i.e. several months), the nitrogen can be expected to remain in the ammonium form as the effluent moves through the soil. This has not been tested in the field system, but it was observed in parallel laboratory studies where columns filled with soil from the infiltration basins were flooded with the same secondary effluent (Lance and Whisler, 1972).

When sequences of medium inundation periods were first used in 1968, the $\text{NH}_4\text{-N}$ concentration in the renovated water was in the 2-3 mg/l range. Thus, after the passage of the $\text{NO}_3\text{-peak}$, the total nitrogen level in the renovated water was 90% less than that in the

sewage effluent. However, continued use of medium inundation periods caused a gradual increase in the $\text{NH}_4\text{-N}$ level in the renovated water. In 1969, for example, the $\text{NH}_4\text{-N}$ level in ECW water increased from 4 mg/l in January to about 10 mg/l in July. Then it gradually dropped to 4 mg/l in November, and increased again to reach about 15 mg/l in June 1970. After that, the $\text{NH}_4\text{-N}$ level in the water from ECW decreased to 7.5 mg/l in November 1970. In 1970, the total-N level in the renovated water after the passage of the $\text{NO}_3\text{-peak}$ was only 30% to 60% less than that in the sewage effluent.

The gradual increase in the $\text{NH}_4\text{-N}$ level was probably due to the application of more ammonium during flooding than could be nitrified during drying, causing the cation exchange complex in the soil to remain essentially saturated with NH_4 . The limiting factor is probably the amount of oxygen entering the soil during drying (Lance et al., 1972). During the summer months, higher temperatures and better drying of the soil may cause a temporary increase in the nitrifier activity. This could explain the decrease in the $\text{NH}_4\text{-N}$ concentration of the renovated water from May until December.

The tendency of the $\text{NH}_4\text{-level}$ in the renovated water to gradually increase with continued use of 2-3 week flooding periods was reversed by changing to a sequence of short, frequent floodings (i.e. 2 days wet-5 days dry). This was done in 1971 for basins 1, 2, 5, and 6, while basins 3 and 4 were continued to be flooded with 2-3 week periods. While the $\text{NH}_4\text{-N}$ level in the renovated water below basins 3 and 4 stayed at a plateau of about 18 mg/l for most of 1971, the $\text{NH}_4\text{-N}$ levels below basins 1, 2, 5, and 6 gradually decreased to about 5 mg/l at the end of 1971. During the first few months of 1971, when short inundation periods were used for basins 1, 2, 5, and 6, the renovated water below basins 1 and 2, which were not vegetated, contained much higher $\text{NO}_3\text{-N}$ levels than the renovated water below basins 5 and 6, which were covered by native grasses (mainly Mexican sprangletop and barnyard grass) and bermudagrass. This $\text{NO}_3\text{-N}$ was probably due to nitrification of ammonium stored in the soil during the preceding sequences of medium flooding periods. The lower $\text{NO}_3\text{-N}$ releases from the vegetated basins could be attributed to increased denitrification in the root zone, or to decreased nitrification which would cause the ammonium to remain adsorbed to the clay and organic matter.

With high-rate land disposal systems, such as the Flushing Meadows Project with loading rates of 300 to 400 feet per year, the nitrogen loading is so high (24,000 to 32,000 pounds per acre per year at Flushing Meadows), that crop uptake of nitrogen is insignificant as a removal process. Some nitrogen can be stored in the soil by adsorption of ammonium to clay and organic matter, fixation in microbial tissue, etc., but this is only temporary. Consistent nitrogen removal can be obtained mainly by denitrification. This requires the presence of nitrate and organic carbon

under anaerobic conditions. If nitrogen removal from the effluent water is desired, the system should be managed so as to create conditions that promote denitrification.

For example, the pattern of nitrogen removal with sequences of 2-3 week flooding periods is probably due to denitrification. During dry-up, and probably also during the initial stages of inundation, the upper 3 feet of soil are aerobic and the ammonium nitrogen in the capillary water and that adsorbed on the clay and organic matter can be nitrified. Some of the nitrate thus formed may move into micro-anaerobic pockets in the soil, where denitrification can occur. Also, when flooding is resumed, the nitrates may mix with the incoming sewage effluent and become denitrified in anaerobic zones. When all nitrates are flushed out and oxygen is depleted, the nitrogen in the effluent water will probably stay in the ammonium form and can be adsorbed by the clay and organic matter, after which it will be nitrified during the following dry-up period.

The overall nitrogen removal is difficult to predict because the volumes represented by the samples from ECW are not known. However, the N levels in the renovated water from the wells outside the basin area, where the NO_3 peaks are not as distinct indicate that total nitrogen removals of around 30% can be obtained with medium flooding periods (2 weeks wet-2 weeks dry). This agrees with results from laboratory studies using soil columns, where a complete nitrogen balance could be developed for the system (Lance and Whisler, 1972).

There is some evidence that vegetation had a beneficial effect on denitrification. For example, in 1968, the $\text{NO}_3\text{-N}$ levels after the passage of the NO_3 peaks were about 6 mg/l in the renovated water below the bare-soil basins, but less than 0.5 mg/l in the renovated water below the basins with a mature stand of bermudagrass. Also, the grassed basins released much less nitrate than bare-soil basins when, after 3 years of using primarily 2-3 week flooding periods, the schedule was changed to a sequence of 2 days flooding-5 days dry to lower the ammonium level in the renovated water. Direct uptake of N by the crop could not account for the difference in nitrate levels in the renovated water. The beneficial effects of vegetation on denitrification are probably due to the organic carbon exuded by live roots and that returned to the soil by decaying roots (which supplied energy for the denitrifying organisms) and to the more anaerobic environments due to oxygen uptake by the root system (Woldendorp et al., 1965). More research is needed on the effect of vegetation on denitrification and the system management needed to obtain maximum nitrogen removal.

Phosphate. The $\text{PO}_4\text{-P}$ levels in the secondary sewage effluent averaged about 10 mg/l in 1970 and 1971. The $\text{PO}_4\text{-P}$ concentrations

in the renovated water from ECW were low when the project was first started, but gradually increased to about the 5 mg/l level, where it has remained for the last 2 years. The renovated water yielded by the "outlying" wells 1 and 8 had lower $\text{PO}_4\text{-F}$ levels. The main mechanism for P-removal is probably precipitation of calcium-phosphate compounds, such as apatite, and precipitation of magnesium ammonium phosphate. Analysis of the top soil from the infiltration basins with an electron microprobe indicated phosphorus-rich clumps and coatings of soil particles. Phosphate-fixing materials, such as iron and aluminum oxides, are not present in large quantities in the sands and gravels of the Salt River bed.

Fluoride. The fluoride content was reduced from about 4 mg/l in the effluent to about 2 mg/l in the renovated water from ECW. Like the phosphates, the water from the outlying wells was lower in fluoride. The removal of fluoride paralleled that of phosphate, suggesting the formation of fluorapatites as a probable mechanism for its decrease.

Boron. The boron concentration in the effluent gradually increased from about 0.4 mg/l in 1968 to about 0.9 mg/l in 1971. Boron is not removed as the effluent moves through the sands and gravels of the Salt River bed (Table 1).

Metals. Metal analyses were carried out in the fall of 1971 on six samples taken bi-weekly over a 2-month period. The concentrations of copper and zinc in the renovated water from ECW were considerably less than those in the effluent, but the concentrations of lead and cadmium remained essentially unchanged (Table 1). A combination of high pH and aerobic environment apparently favors immobilization of metallic ions in the soil.

Total salts. The concentration of total dissolved salts in the effluent was generally in the 1000-1200 mg/l range in the effluent. The salt concentration in the renovated water was slightly higher, as a result of evaporation from the infiltration basins. The annual evaporation from a free water surface in central Arizona is about 6 feet. The evaporation at Flushing Meadows can be expected to be slightly less, because evaporation from the soil is reduced at the end of a dry period. When the annual evaporation is about 5 feet and the annual infiltration is 350 feet, the salt content of the renovated water can be expected to be about 1.4% higher than that of the effluent.

The concentrations of the more important ions in the effluent were as follows:

<u>Ion</u>	<u>Concentration</u>	<u>Ion</u>	<u>Concentration</u>
	mg/l		mg/l
Na+	200	HCO ₃ ⁻	381
Ca ⁺⁺	82	Cl ⁻	213
Mg ⁺⁺	36	SO ₄ ⁻⁻	107
K+	8	CO ₃ ⁻⁻	0

pH. The pH of the renovated water was about 7, which is one unit less than that of the sewage effluent (Table 1). This is probably due to bacterial action in the soil, which produces carbon dioxide and organic acids.

Fecal coliforms. Most of the reduction in fecal coliform density (Table 1) occurred in the first 3 feet of travel through the soil. This was determined by samples of effluent water taken at different depths in the soil profile with ceramic cups to which a vacuum was applied. For inundation periods of 2-3 weeks, the fecal coliform density in the renovated water from ECW increased after the start of a new flooding period, when newly infiltrated water reached the well. The fecal coliform density then decreased to low values (often zero) until the next flooding period. The fecal coliform density for the outlying wells was lower than for ECW, i.e. a general range of 0-10 per 100 ml for well 7, and a complete absence of fecal coliforms for well 8.

OPERATIONAL SYSTEM

The infiltration studies at the Flushing Meadows Project have shown that a full-scale operational system can be designed on the basis of a hydraulic loading of about 300 feet per year. Thus, one acre of infiltration basin can handle 300 acre-feet of sewage effluent per year, or about 0.27 mgd. To renovate the total present flow of around 80 mgd would thus require about 300 acres of basins. The projected sewage flow for the year 2000 is some 300,000 acre-feet per year, which would require about 1,000 acres of basins.

Because of the many existing wells in the Salt River Valley, the wastewater renovation system should be designed and operated in such a way as to prevent the renovated water from moving into the aquifer outside the system of infiltration basins and wells. This can be achieved by locating the infiltration basins along both edges of the river bed (which is about 0.5 mile wide) and placing the wells for pumping the renovated water in the center of the river bed. To insure that renovated water will not move into the aquifer outside the river bed, the system should be operated to

keep the water table below the outer edges of the basin areas at a level equal to, or slightly below, the water table in the rest of the aquifer. Thus, the renovated water should be pumped from the wells at the same or a slightly higher rate than the infiltration rates in the basins.

From the response of the water levels in the observation wells to infiltration at the Flushing Meadows Project, the effective transmissibility of the aquifer for recharge was evaluated by resistance network analog and horizontal flow theory (Bouwer, 1970). This transmissibility was then used in an analog study of the system to predict water table positions and underground detention times for various geometries. The results showed that the conditions in the Salt River bed enable a system with underground detention times of at least several weeks and underground travel distances of at least several hundred feet (Bouwer, 1970). The quality of the renovated water from the wells should be better than that shown in Table 1 for the water from ECW, for which the underground detention time was only about 1 week and the underground travel distance about 40 feet. Thus, the large-scale operational system should yield renovated water that can be used for unrestricted irrigation, primary contact recreations, and certain industrial applications (Environmental Protection Agency, 1968, and Arizona State Dept. of Health, 1972).

ECONOMIC ASPECTS

Preliminary estimates indicate that the total cost of putting the sewage effluent into the ground and pumping it up as renovated water with the system in the Salt River bed will be around \$5 per acre-foot (Buxton, 1969). The cost of in-plant tertiary treatment to obtain renovated water of similar quality will be an order of magnitude higher. Moreover, a significant part of the investment for a land treatment system is in land. Since land values tend to increase with time, an additional cost benefit can be obtained with the sale or different use of the land once the infiltration system has become obsolete. Wastewater renovation by groundwater recharge is aesthetically more attractive to the public than in-plant treatment. Also, land treatment systems are essentially 100% fail-safe.

ACKNOWLEDGMENTS

The author acknowledges the valuable contributions to this project by E. D. Escarcega, J. C. Lance, and R. C. Rice of the U.S. Water Conservation Laboratory. The cooperation of the Salt River Project and its support of M. S. Riggs, who performed the water analyses, are gratefully acknowledged. The metal analyses were done by J. V. Lagerwerff of the U.S. Soils Laboratory, ARS-USDA, in Beltsville, Md. P. R. Buseck of Arizona State University performed the electron microprobe analyses of the soil.

REFERENCES

- Arizona State Department of Health, Phoenix, Ariz. 1972. Rules and regulations for reclaimed wastes.
- Bouwer, Herman. 1970. Groundwater recharge design for renovating wastewater. Jour. Sanitary Engr. Div., ASCE, vol. 96 SA1, 59-74.
- Buxton, J. L. 1969. Determination of a cost for reclaiming sewage effluent by groundwater recharge in Phoenix, Ariz. M.S. thesis, Arizona State University, College of Engineering Science.
- Environmental Protection Agency, Washington, D.C. 1968. Water quality criteria. Report of Natl. Tech. Adv. Comm. to Secretary of Interior.
- Lance, J. C. and F. D. Whisler. 1972. Nitrogen balance in soil columns intermittently flooded with secondary sewage effluent. Jour. of Environmental Quality 1, 180-186.
- Lance, J. C., F. D. Whisler, and H. Bouwer. 1972. Oxygen utilization in soils flooded with sewage water. Unpublished report.
- Long, W. N., and F. A. Bell. 1972. Health factors and reused waters. Jour. Amer. Water Works Assoc. 64, 220-226.
- Replogle, J. A. 1971. Critical-depth flumes for determining flow in canals and natural channels. Amer. Soc. Agric. Engr. Trans. 14, 428-433.
- Rice, R. C. 1972. Soil clogging during infiltration with secondary sewage effluent. Paper presented at Annual Meeting Amer. Soc. Agric. Engr., Hot Springs, Ark.
- Woldendorp, J. W., K. Dilz, and G. J. Kolenbrander. 1965. The fate of fertilizer nitrogen on permanent grassland soils. Proc. 1st General Meeting European Grassland Fed., 53-76.

PHOSPHORUS AND NITRATE LEVELS IN GROUNDWATER AS RELATED
TO IRRIGATION OF JACK PINE WITH SEWAGE EFFLUENT

Dean H. Urie
North Central Forest Experiment Station
Forest Service, USDA

127 E

In response to requests from municipalities to use forest lands for sewage disposal sites, the North Central Forest Experiment Station has begun research on the effects of sewage effluent on groundwater nutrient levels. This report covers results from an initial test conducted near Cadillac, Michigan, under conditions similar to those found on a site that has been selected for sewage renovation near Traverse City, Michigan. The test was conducted on a sand soil with a shallow water table where groundwater contamination could be a serious hazard. The treatment area was covered with a pole-sized jack pine (Pinus banksiana Lamb.) stand having a sparse understory vegetation.

This exploratory test was conducted to gain background information on the methods which could be used to conduct field tests of sewage effluent renovation where only small volumes of effluent are available.

Little research on sewage renovation in forests has been done (Sopper, 1971). Reports by Rudolph and Dils (1955) and Rudolph (1957) are perhaps most applicable to the study reported here, as their tests of tree survival and growth under irrigation by cannery wastewater was conducted on sand soils at Fremont, Michigan. Groundwater under those tests was found to meet potable water standards after 3 years of irrigation.

Irrigation with secondary effluent has resulted in a high degree of phosphorus removal in loam and sandy loam soils under pine and hardwood forests at The Pennsylvania State University. Nitrate in soil water at 60-cm (24-inch) and 120-cm (48-inch) depths has increased during the study although no report of increases in groundwater nitrate concentrations has yet been found. Water table levels are approximately 60 m (200 feet) below the surface in contrast to the shallow water tables in the study reported here.

Pure red pine (Pinus resinosa Ait.) removed less nitrate in The Pennsylvania State University studies than hardwood and white spruce forests. The pine plantation used for the test described here was similarly expected to remove the smallest amount of nitrogen of all forest types on the Traverse City project area.

Despite the poor removal of nitrates on sand forest land, the availability, low cost, high infiltration, and remoteness of such soils have created a demand for them for sewage disposal with and without the forest cover (Shaeffer, 1970; Urie, 1971).

METHODS OF STUDY

Secondary-treated municipal sewage effluent from the Cadillac, Michigan, treatment plant was used to irrigate a small plot in a 35-year-old jack pine plantation. The plantation is located on a Kalkaska loamy sand soil which is a Typic Haplorthod developed on deep sand drift. During the test period, water table depth varied from 1.3 m (4 feet) to 3 m (10 feet), which is shallower than normal for Kalkaska sands on the proposed Traverse City disposal site. The test site is located on the Cadillac District, Manistee National Forest, NE 1/4, NW 1/4, Sec. 14, Selma Township, Wexford County, Michigan.

The plantation had been thinned by removing every fourth row in 1968. Slash from this cut was still present, with little decomposition of twigs over 5 cm (1/5-inch) diameter. The residual stand is about 10 m (40 feet) in height, with an average diameter of 16 cm (6.3 inches). Ground cover is sparse except in the cleared strips where a few hardwood seedlings have been established. *Lycopodium* covered about 12 percent of the surface of the plot prior to irrigation. Needle litter was 2.5 cm (1 inch) in depth before irrigation.

Observation wells were installed to depths of 1.5 m (5 feet) below the water table on the irrigation test site. Measurements of static water levels showed that the water table sloped toward Pleasant Lake. Three wells were then installed within the irrigated area. Two 1-1/4 inch diameter wells were driven to the level of the lowest annual water table fluctuation. Well No. 1 was located at the center of the irrigated plot and Well No. 2 was located on the edge of the plot in the direction of groundwater flow, as determined from the surrounding wells. A recorder was installed in a 6-inch diameter well near the center of the irrigated plot. Previous groundwater studies in the area have shown that the annual cycle of water table fluctuation experienced during the 1972 growing season were similar to those occurring in 2 previous years.

A standard rain gage was installed in a nearby forest opening. Water quality samples were removed from the two treatment wells (No. 1 and No. 2) and two control wells (No. 3 and No. 4) using a pitcher pump. All wells were capped during irrigation.

TREATMENT

Effluent Application

The effluent was trucked from the plant and temporarily stored during the irrigation period. Irrigation began immediately upon delivery. Sewage effluent was applied at an average rate of 64 mm (2.5 inches) over a 10-hour period 1 day per week to an area averaging 6.1 m (20 feet) in radius. Two applications were made during November 1970. Treatments were renewed April 26, 1971, when the ground was free of snow and frost, and continued until October 19, 1971. A total of 162 cm (64 inches) was applied during the 1971 growing season. Distribution of the single rotary sprinkler used was checked with temporary gages. Application was relatively uniform from 2 to 5 m (7 to 16 feet), except in tree shadows and splash zones.

Field Measurements

Water quality samples were removed from four wells about 12 hours after irrigation ended. This timing coincided with the recharge peak shown by the recording well.

A liter sample was collected from Wells 1, 2, 3, and 4 at each sampling date. The samples were preserved with HgCl (10 mg/l) and refrigerated. Storage did not exceed 30 days. Liter samples of irrigated effluent were drawn from the temporary storage tank during irrigation.

Rainfall during the week previous to each irrigation was measured in the open using a standard 8 inch gage. The pattern of water table levels in the center of the irrigated plot was determined from the water level recorder record.

Lab Analyses

Chemical analyses of nitrate-N and total phosphorus in water samples were performed by the Institute of Water Research, Michigan State University, using standard Environmental Protection Agency methods.

Additional measurements of ammonia-N and total Kjeldahl-N in the sewage effluent from the Cadillac treatment plant were made from samples collected during May and June 1972. These samples showed similar nitrate-N and phosphorus levels to those measured during the treatment period. The average level of total nitrogen was used to estimate the total nitrogen applied during the test period.

Soil samples were removed from 0- to 23-cm (0- to 9-inch) and 23- to 53-cm (9 to 21-inch) layers in the irrigated plot and from an equal number of points in the surrounding unirrigated control area. Analyses of phosphorus and nitrate, as well as other standard soil fertility tests were performed by the Michigan State University Soil Testing Laboratory.

Suction lysimeters were installed at 61- and 122-cm depths (24 and 48 inches) in September 1971. Samples of soil water were removed on seven dates and analyzed for nitrate-N, ammonia-N, and total phosphorus.

RESULTS

Phosphorus

The average concentration of phosphorus in the effluent was 7.52 mg/l for the first 24 weeks of the 25-week season in 1972. An excessively high value (58 mg/l) on the last treatment date was associated with a temporary failure in the sewage treatment process. This input boosted the average to 9.67 mg/l, a total phosphorus loading of 141 pounds per acre.

The mean total phosphorus level in the two treatment wells was 0.09 mg/l for 25 sampling dates (Table 1). The mean level in the control wells was 0.14 mg/l. There was no significant difference between the treatment and control wells. The two control wells were in shallower water table situations, which may have caused a small increase in average phosphorus content.

There was no evidence of phosphorus enrichment of the groundwater. High levels in two wells on August 31 may have been due to sampling errors as one treatment well and one control well were anomalously high (0.72 and 0.99 mg/l, respectively).

Phosphorus levels in soil water at 60-cm (24-inch) and 120-cm (48-inch) depths were sampled with tension lysimeters during September and October. Total phosphorus in the soil water was below 0.2 mg/l in all samples.

Soil analyses were made on a rather gross basis. An increase of 27 pounds per acre of total phosphorus was found in the 0- to 15-cm (0- to 6-inch) layer of the irrigated plot (Table 2). Phosphorus contents of litter and foliage were not determined.

Table 1. Total Phosphorus and Nitrate Levels in Groundwater Samples Collected in the Pleasant Lake Study, 1971

Date	Total Phosphorus		Nitrate-N	
	Treatment Mean	Control Mean	Treatment Mean	Control Mean
	mg/l	mg/l	mg/l	mg/l
11/10/70	0.04	0.07	0.16	0.63
11/11/70	.03	.13	.32	.63
11/18/70	.04	.08	.22	.57
4/27/71	.15	.18	.11	.12
4/29/71	.14	.26	.16	.08
5/ 4/71	.03	.24	.10	.18
5/11/71	.03	.20	.06	.28
5/18/71	.02	.20	.06	.18
5/25/71	.02	.08	.14	.18
6/ 2/71	.09	--	.12	--
6/ 8/71	.06	.12	.12	.24
6/15/71	.02	.22	.09	.28
6/22/71	.08	.12	.18	.17
6/29/71	.16	.17	.30	.40
7/ 7/71	.26	.29	.36	.14
7/13/71	.04	.04	.06	.10
7/19/71	.03	.08	.06	.06
7/26/71	.06	.03	.04	.02
8/ 2/71	.10	.04	.03	.06
8/10/71	.14	.07	.32	.11
8/17/71	.18	.10	.23	.14
8/31/71	.42	.56	.26	.26
9/14/71	.04	.04	.93	.04
9/28/71	.06	.06	.10	.05
10/20/71	.06	--	7.60	--
Mean	.09	.14	.48	.19

Nitrogen

Nitrate levels in the effluent were low, approximately the same as in the groundwater public water supply source, 0.3 mg/l. Most of the nitrogen was in ammonia and organic form, approximately 8.0 mg/l and 2.9 mg/l, respectively. The total nitrogen applied was about 170 pounds per acre.

Groundwater samples were tested for nitrate during the entire study. Tests for other forms of nitrogen were conducted only during the final weeks of treatment. Definite increases in mean nitrate levels appeared in September and continued through the end of the irrigation. The test well on the downslope edge of the treatment plot produced samples with the highest $\text{NO}_3\text{-N}$ levels. The highest $\text{NO}_3\text{-N}$ level of 14.3 mg/l was measured on October 20, 10 days after the last irrigation.

Tension lysimeters at 60-cm (24-inch) and 120-cm (48-inch) depths were used to collect samples during September and October in which nitrate-N levels ranged from 25 to 30 mg/l. By mid-November, nitrate levels at these depths in treatment and control areas were below 5 mg/l.

Soil analyses showed increases of approximately 6 pounds per acre of nitrate-N in the surface 6 inches (Table 2) on October 20, 1971. After 10 days, no changes were found in deeper

Table 2. Nitrate-N and Total P in the Soils on the Irrigated and Control Areas of the Pleasant Lake Study, October 20, 1971

Soil Depth	Total P		Nitrate-N	
	Irrigated	Control	Irrigated	Control
inches	lbs/a	lbs/a	lbs/a	lbs/a
0-6	36	9	8	2
6-12	12	8	2	2
12-21	21	18	4	4

soil layers despite the high soil-water nitrate level measured on this date from suction lysimeters.

Vegetation Response

A comparison of 1971 annual growth on the 15 irrigated and 15 control jack pine was made in November. Increment borings showed a mean annual radial growth of 0.14 cm (0.055 inch) on irrigated trees in comparison to 0.10 cm (0.040 inch) on control trees. Dominant trees showed greatest effects and the irrigated trees had nearly twice the annual ring width of controls. The 1971 growing season was rather dry (May-September precipitation was

95 mm (3.7 inches) below normal); thus, the supplemental water may have been the main cause for the growth increase.

Subordinate vegetation increased in frequency due to irrigation, mostly through survival of Prunus and Fraxinus seedlings. Several species of flowers and vegetables were introduced, apparently from seeds contained in the sewage effluent.

DISCUSSION AND CONCLUSIONS

The single plot test described here illustrated that the nitrates added in sewage effluent irrigation may reach shallow water tables under sand-soil, forest conditions. Phosphorus renovation was complete during the initial year. Public health considerations may limit the permissible dosage levels in such highly permeable soils. Further tests will be needed to determine whether hardwood forest types or shrub-herb cover conditions may be more satisfactory for sewage renovation purposes on sandy soils. Alternative methods of cropping or volatilization of nitrogen may be a necessary pretreatment before economic volumes of sewage effluents can be renovated satisfactorily. Dilution of nitrate levels during groundwater flow may be a satisfactory solution in remote areas, with small sewage irrigation loads, and where domestic water supplies are protected.

Experience with this single plot test has resulted in the adoption of a different type of field test in locations where sewage effluent must be trucked to the test site. Tests now in progress utilize plots about 0.001 hectare in area using gravity methods of application. Tension lysimeters (soil-water samplers) are being used instead of wells to test the degree of renovation under various treatments. These micro plots do not permit tests of response of large trees to sewage treatments. Replicated tests of renovation are possible with small volumes of effluent on a variety of soils and understory vegetation types.

REFERENCES

- Rudolph, V. J. 1957. Further observations on irrigating trees with cannery waste water. Mich. Agric. Expt. Sta. Q. Bull. 39, 416-423.
- Rudolph, V. J., and R. E. Dils. 1955. Irrigating trees with cannery waste water. Mich. Agric. Expt. Sta. Q. Bull. 37, 407-411.
- Shaeffer, J. R. 1970. Reviving the Great Lakes. Saturday Rev., Nov. 9, 1970, p. 62-65.
- Sopper, William E. 1971. Effects of trees and forests on neutralizing wastes. In Trees and Forests in an Urbanizing Environment,

Symposium on Urban Forestry, Amherst, Mass., p. 43-57.
Urie, Dean H. 1971. Opportunities and plans for sewage renovation on forest and wildlands in Michigan. Mich. Acad. IV (1), 115-124.

RESTORATION OF ACID SPOIL BANKS
WITH TREATED SEWAGE SLUDGE

Terrence R. Lejcher and Samuel H. Kunkle
Shawnee National Forest, Eastern Region
Forest Service, USDA

323D

In many areas where strip mining has occurred there is a critical need for land reclamation, both to return wasteland to productivity and to reduce water pollution problems. Strip mining of coal often causes a significant degradation of water quality, aquatic environment and riparian wildlife habitat (Udall, 1967). In some cases, traditional strip mine reclamation techniques are apparently ineffective for correcting water quality impacts (Anderson, et al, 1972); therefore, new land reclamation techniques are needed.

Studies at The Pennsylvania State University (Hunt, Sopper and Kardos, 1971), and at other locations (Peterson and Gschwind, 1971), indicate that the utilization of treated municipal wastes may offer a potential technique for land reclamation in strip mined areas. Simultaneously, many cities are faced with the question of sludge disposal from their treatment plants. For example, Chicago is producing over 900 metric tons per day (dry weight) of solids from its sewage treatment plants. Disposal of the digested solids or sludge includes the following alternatives and costs:

Dewatering and incineration	\$63/metric ton
Wet air oxidation	\$55/metric ton
Digestion and permanent lagoons	\$54/metric ton
Drying and sale as fertilizer	\$50/metric ton
Digestion, and reclamation of strip mines	\$18/metric ton
Digestion, and reclamation of farmlands	\$16/metric ton


In the case of Chicago, the sludge is disposed of primarily by the first four processes above. The disadvantages of these particular disposal methods include cost, air pollution, and the scarcity of storage space. Sludge storage costs for the Metropolitan Sanitary District of Greater Chicago are over 1.5 million dollars per year (Dalton, et al., 1968). On the other hand, sludge disposal on strip mined lands offers an opportunity to reduce disposal costs while making a beneficial use of the sludge.

Little information is available regarding the practicality or environmental consequences of sludge treatment of strip mined sites.



Therefore, the Shawnee National Forest in Illinois, in conjunction with the Metropolitan Sanitary District of Greater Chicago, established a demonstration site in 1970 to evaluate sludge treatment on strip mined land. The demonstration site, a 77 hectare stripped area, is known as the Palzo Tract. Within the Palzo Tract, four plots (500 square meters each) were set up to monitor water quality runoff and to observe plant growth following sludge treatment. Monitoring of the plots has continued since 1970. Land reshaping of the entire 77 hectares is underway in 1972 in preparation for sludge application to the entire tract. These efforts are in cooperation with Forest Service Research and university personnel. This paper presents the 1970-1972 water, vegetative, and soil observations from the small plots and considers the sampling design for the larger area and an adjacent stream which is affected by runoff from the tract.

THE CHEMICAL PROCESSES SPOIL


Chemical oxidation of pyrite in shales of stripped areas is somewhat complex and not completely understood. The general reactions, however, are described by Hill (1971) as follows:



Oxidation of the pyrite (equation 1) produces ferrous sulfate and sulfuric acid. The reaction continues as follows:



Oxidation of the ferrous iron proceeds slowly. However, the resultant ferric iron is reduced by the pyrite to release more acid and ferrous iron (equation 4).



Singer and Stumm (1968) and others also present evidence that microbes possibly play an important role in the oxidation process. Smith and Shumate (1971) indicate the reaction rates are a function of pH, temperature and oxygen concentration conditions at the pyrite surface. Erosion of stripped areas also continually exposes fresh pyrite for oxidation.

PLOT VEGETATIVE RESPONSE

The four 500 square meter plots on the demonstration tract were designed to sample subsurface flow. Each plot was treated with

sludge in November 1970 at treatment levels of 304, 178 and 78 dry metric tons of sludge per hectare. The fourth plot remained as a control. The following spring, the plots were seeded with K-31 tall fescue (*Festuca arundinacea*) and weeping lovegrass (*Eragrostis curvula*) at the rates of 22 and 8 kilograms per hectare, respectively. Within 30 days germination had occurred on all but the control plot. At the end of the first growing season, there was a ninety percent vegetative cover on the most heavily treated plot, whereas the plots with lower treatments were less than 50 percent covered. In the second growing season only the 304 ton per hectare treatment continued to support as much vegetation as in the first growing season.

PLOT RUNOFF RESPONSE

Water samples collected from subsurface drains in the plots have been analyzed for chemical and bacterial contamination since the study began. The average acidity levels and concentrations of various metals observed in runoff from the plots appear in Table 1. The heaviest treatment (304 metric tons per hectare) reduced acidity as well as aluminum and iron concentrations in the runoff by more than 60 percent and manganese concentrations by more than 50 percent. Slight increases in chromium, cadmium and zinc concentrations were observed, however, as shown in Table 1. (All of these elements also naturally appear in acid runoff from the tract.)

Within the period of observation, a cyclic trend in metal concentrations has been noted. From November 1970 through September 1971, a sharp decrease in metal concentrations was observed in the runoff. During the dormant season of 1971-1972, a slight rise in concentrations occurred. With the onset of the growing season during the spring of 1972, metal concentrations began decreasing again. This cyclical pattern of concentrations is perhaps associated with the seasonal availability of water and with plant uptake of metals. The dormant season in the area coincides with the period of higher rainfall and lower evapotranspiration rates. The initial decrease in metal concentrations in the runoff was likely due to neutralization of the spoil's acidity by the highly alkaline sludge. The sludge, which contains about 40 percent organic matter, also has a high cation exchange and buffering capacity which may complex many of the metal cations in the acid spoil. Also, uptake by plants during the growing season was indicated by analyses conducted on the weeping lovegrass. The observed increase in lead, chromium, cadmium and zinc, particularly noted in runoff from the 178 ton treatment, implies that the lower treatment rates are incapable of providing sufficient buffering to help tie up certain metals. These metals, whose solubility is pH dependent, probably passed through the

Table 1. Average Concentration of certain Parameters in Subsurface Runoff from the Sludge Treated Plo's before and after Treatment ("after" values based on 1970-1972 averages)

Element	Treatment (metric tons/hectare)						
	-304-		-178-		-78-		-0-
	Before	After	Before	After	Before	After	Average
Al	1,240	402	395	138	440	346	548
Cd	1.14	1.92	0.31	1.18	0.70	1.13	0.66
Cr	3.5	4.8	1.3	1.6	2.3	3.4	2.1
Cu	11.6	7.5	3.8	3.3	4.0	3.6	4.5
Fe	3,700	1,260	1,280	320	1,000	822	1,620
Mn	70	30	51	17	71	42	36
Pb	0.33	0.23	0.16	0.18	0.42	0.18	0.22
SO ₄	11,000	7,740	8,400	3,730	7,100	6,770	7,980
Zn	24.4	36.4	8.1	24.8	14.1	26.0	13.3
Acidity	22,940	8,900	7,310	3,320	7,040	5,900	9,770

inadequately neutralized spoil, to appear in the runoff. In summary, these initial results indicate that sludge treatment of acid spoils apparently must be at a high enough level to neutralize the spoil in order to prevent additional water pollution by metals and to maintain a vegetative cover. The heaviest treatment of 304 metric tons per hectare appeared to be most desirable.

NUTRIENTS

Although the sludge contains about 5 percent dry weight of nitrogen, only 1 to 2 percent are in the water soluble form of ammonia and nitrate. Merz (1959) indicates that as much as 80 percent of the nitrogen in sludge may remain in the organic form the first year. The slow availability of the nitrogen is highly desirable for plant growth and water quality considerations. Analysis for $\text{NO}_3\text{-N}$ and $\text{NO}_2\text{-N}$ in runoff from the test plots has shown no concentrations exceeding State water quality standards. Concentrations of $\text{NH}_3\text{-N}$ ranged from 54.0 mg/l 10 months after treatment on the most heavily treated plot. The high levels of $\text{NH}_3\text{-N}$ and O-N , in conjunction with no consistent increases of $\text{NO}_2\text{-N}$ and $\text{NO}_3\text{-N}$, indicate that the acidity of the spoil material and/or the heavy metal concentrations probably are preventing nitrification. Once a high enough pH is established, nitrification could be anticipated and $\text{NH}_3\text{-N}$ concentrations presumably would decrease. Establishment of sorghum and millet, both high nitrogen demanders, possibly would minimize nitrogen concentrations in the runoff.

BACTERIA

No fecal coliform bacteria were found in runoff from the sludge treated plots during the year immediately following application. A digestion period of 7-10 days during municipal treatment kills pathogenic organisms, according to Burd (1966). Also, lagooning of a sludge for 30 days after digestion further reduces fecal coliforms by 99 percent (Braids, 1970). The sludge used by Palzo has been lagooned for over two years. Exposure to ultraviolet radiation by spreading the sludge on the ground is detrimental to bacteria. Finally, fecal coliforms in contact with acid water with a pH of 2.5 for 24 hours exhibit a die-off of greater than 99 percent (Joseph and Shay, 1952). Considering all of these factors, it appears unlikely that pathogens would survive in the runoff.

SPOIL OBSERVATIONS

The maximum level sludge treatment effectively raised the pH of the acid spoil. As would be expected, the major difference

in pH between the treatment and control plot spoil is in the top 20-25 centimeters. The average pH based on nine observations per plot taken at various times during the first year following treatment showed the following:

<u>Treatment Rate</u> (dry metric tons/hectare)	<u>Plot Average</u> <u>Soil Surface pH</u>
304	6.2
178	5.2
78	4.7
0	2.3

Laboratory analyses of percolate from the spoil were made to supplement the field runoff and spoil pH observations. Columns of spoil approximately one meter by five centimeters were augered from the most heavily treated and the control plots in 1972. The spoil cores then were transported in two layers to the laboratory (0-50 centimeter and 50-100 centimeter layers) and leached with distilled water. About one-half year's equivalent of precipitation (1000 ml) was percolated through the individual columns during a ten-day period. The percolate was analyzed for the parameters shown in Tables 2 and 3, plus calcium and magnesium.

These preliminary percolate analyses of July 1972 indicate that mixing of the sludge into the spoil was apparently more effective than simple surface application in terms of water quality improvements. As shown in Tables 2 and 3, acidity was reduced in percolate from the treated plot's spoil when sludge was mixed into the spoil (note hydrogen ion concentration). Likewise, iron concentrations in the percolate were greatly reduced by the sludge incorporation. Less impressive reductions appeared for sulfur, manganese, aluminum, and copper.

Sludge application apparently increased zinc and sodium levels in the percolate water, as shown in Table 2. Hunt, et al. (1971) noted that zinc apparently was weathered out of spoil when treated effluent was applied by irrigation. Further observations are needed to assess the significance of any metal releases that are associated with sludge application.

If the zone of highest oxidation rates in the spoil can be effectively neutralized and stabilized, the acid production should be decreased. The zone of major oxidation in the spoil is recognized by Good, et al. (1970) to be in the top 25 centimeters. This zone has the clay removed by leaching and is most permeable to air and water.

Table 2. Concentrations of Chemical Constituents in the Percolate Collected from the 0-50 cm Column of Spoil Material

Treatment	Constituent										
	Zn	Pb	Fe	S	Mn	Cu	Na	Al	K	H	Ni
304 t/ha plot	mg/l	mg/l	mg/l	%	mg/l	mg/l	mg/l	mg/l	mg/l	meq/l	mg/l
	28.4	3.5	trace	0.058	2.0	0.5	7.1	105	28.0	1.38	0.2
Mixed	22.0	4.5	trace	0.060	1.0	--	5.8	155	16.0	1.92	0.1
	62.4	20	42	0.135	2.8	3.2	3.2	960	0.2	54.15	0.1
Unmixed	22.6	4.5	1.9	0.063	13.0	1.2	3.8	1300	0.5	11.35	0.2
Control	1.9	5.0	5400	0.082	3.3	0.6	0.9	210	0.1	36.96	0.5
Plot	1.4	5.0	11	0.071	2.2	0.2	1.8	1300	--	11.97	0.1

Table 3. Concentrations of Chemical Constituents in the Percolate Collected from the 50-100 cm Column of Spoil Material

Treatment	Constituent										
	Zn	Pb	Fe	S	Mn	Cu	Na	Al	K	H	Co
	mg/l	mg/l	mg/l	%	mg/l	mg/l	mg/l	mg/l	mg/l	meq/l	mg/l
304 t/ha plot	37.4	4.6	trace	0.077	3.0	0.4	9.9	370	78.0	4.49	0.2
Mixed	4.8	5.0	trace	0.045	0.5	--	4.3	250	22.0	2.11	0.2
	48.4	5.5	196	0.098	17.5	2.2	2.7	2500	0.2	30.92	0.2
Unmixed	29.6	4.7	14	0.055	4.0	1.0	4.5	920	0.4	11.70	0.4
Control	40.4	6.5	2600	0.229	12.8	1.2	8.7	12600	0.1	33.14	0.1
Plot	1.2	4.9	4600	0.069	2.8	0.6	0.8	1200	0.2	28.71	0.2
											0.5

Infiltration capacities averaging 7,400 cm/hr have been measured in the top 40 cm of Palzo spoil. The second zone, immediately below this highly permeable zone, has a lower permeability due to clay fines precipitated by rain. However, the permeability of the deeper zone is not strikingly lower in the samples studied at this site. Below 40 cm, permeability averages 6,200 cm/hr. A very wide range of permeability in these samples suggests more samples are needed to increase the precision of the estimate. A third zone suggested by Good, et al. (1970), is the deepest area where little, if any, oxidation occurs.

LARGE SCALE OPERATIONS

Following the results of the plot work discussed above and considering the results of researchers in the same subject area, the Forest Service has decided to apply sludge on the larger tract surrounding the test plot.

The entire 77 hectare acid producing watershed, where the spoil pH ranges from 1.9 to 4.0, will be treated with anaerobically digested sludge. The purpose of the demonstration is to test the practicality of sludge treatment on a large scale.

The sludge will probably be obtained from the Metropolitan Sanitary District of Greater Chicago. It will be shipped, by rail, unloaded in a receiving lagoon, and piped to a storage lagoon on the site, which will hold 1.020×10^5 cubic meters of sludge.

The 77 hectare area has been extensively leveled and reshaped in June-July 1972. Digested sludge will be applied to the site at a rate of 626 dry metric tons per hectare over a two or three year period. Either an irrigation sprinkler system or gated irrigation pipe will be used to apply the sludge. Before and during sludge application, the site will be disked to increase infiltration. Infiltration tests run on the most heavily treated test plot indicate that upon saturation, infiltration capacities average only about 25 cm/hr. Thus, successful irrigation must be intermittent to allow soil drainage.

The planned rate of application is twice that of the most heavily treated test plot. The 304 metric ton per hectare plot had sludge mixed to a depth of about 8.0 cm. However, since the upper 25 cm is reported to be the zone of most extensive oxidation by Good, et al. (1970), it seems desirable to mix the sludge to this depth, if possible. Complete disking on the entire tract will mix the sludge to the first 15 to 20 cm. Although the amount of sludge applied will be about twice that of the most heavily treated plot, it will be mixed to about twice the depth. This sludge-spoil

combination will contain about 20 percent sludge and should provide a good rooting zone for plant establishment.

The nutrient value of the sludge is high enough to support plant growth. Hinesly (1972) claims the N:P:K ratio to be 33:18:4. The nutrient loading rate for the suggested application rate will be: nitrogen-7,670 kilograms per hectare, phosphorus-4,180 kilograms per hectare and potassium-930 kilograms per hectare. As previously discussed, most of the nitrogen is in the organic form and thus, will be available to the plants over a long period of time. Supplemental potash may be required.

The immediate establishment of K-31 tall fescue (*Festuca arundinacea*), weeping lovegrass (*Eragrostis curvula*), and orchard grass (*Dactylis glomerata*) should provide erosion protection. The planting of shortleaf pine (*Pinus echinata*), Virginia Pine (*Pinus virginiana*), cottonwood (*Populus deltoides*) and black locust (*Robinia pseudoacacia*) should provide further stabilization. If vegetation can be well established and erosion controlled, acid production from the site should basically be reduced by a combination of the following factors:

1. Neutralization of the surface acid producing spoil (and chelation of the metals).
2. Erosion control to prevent exposure of fresh pyritic material.
3. A decrease of surface and subsurface water flow from the site, due to increased evapotranspiration losses.

THE RECEIVING STREAM

The acid water leaving the tract has a very low pH and high acidity concentration. Calculations based on sampling observations and average stream discharge data indicate that approximately 9,000 metric tons per year of acidity are contributed to the adjacent receiving stream. This acid runoff is generally considered to be one of the worst in the State of Illinois. Table 4 describes the impact of the Palzo runoff upon the chemistry of the stream.

In addition to stream sampling above and below the Palzo Tract, a water quality survey was made every 75 to 100 meters along the 1.5 kilometer section of the adjacent stream. The purpose of the stream survey was: (1) to identify apparent acid input points; (2) to describe patterns of stratification, mixing and assimilation of the acid into the stream; and (3) to determine the range of

water quality within individual cross sections of the stream. These survey data serve both as pretreatment information and as a basis for stream sampling design.

Table 4. Impact of Palzo Runoff on Sugar Creek as shown by the 1969 to 1971 Stream Samples

Pollutant	Sugar Creek Above Palzo ^{1/}	Palzo Runoff ^{2/}	Sugar Creek Below Palzo ^{1/}
	mg/l	mg/l	mg/l
Al	59	2,075	306
Fe	49	3,955	529
Mn	5.7	320.0	51.4
SO ₄	558	23,675	3,731
Acidity	338	20,100	3,232
Specific Conductance (umhos/cm)	825	14,885	3,329

^{1/} Upper 40 cm layer of stream only.

^{2/} Surface flow emerging from the tract.

Water quality changes along the stream (Sugar Creek) are most striking. For example, values of pH and conductivity change from around 6.0 pH units and 500 micromhos per centimeter upstream, to less than 3.0 pH units and over 11,000 micromhos per centimeter downstream.

The stream cross sections above the stripped tract are fairly uniform in water quality. However, once acid inputs occur, a distinct and stable stratification appears.

Inputs of acid water into upstream reaches of the creek by the Palzo Tract appear to be neutralized, presumably because of dilution and buffering effects. However, once the stream's moderate buffering capability is overwhelmed, stratification becomes continuous.

The extreme water quality stratification in the receiving stream emphasizes the need for integrated or layered sampling, if one is to correctly evaluate water quality changes occurring in the stream.

MONITORING DESIGN

A monitoring system will be initiated on the site to determine the large scale effect of treating the spoil banks with digested sewage sludge. Water, spoil and plant responses will be observed in a variety of ways.

Since the Palzo Tract is now causing severe pollution problems, as shown in Table 4, monitoring the water leaving the area will be most important. The following main sites will be monitored:

- a. Two Palzo surface runoff stations on the tract, with continuous pH, electrical conductance and flow measurements. Weekly samples will be analyzed for chemicals and bacteria.
- b. Two Sugar Creek stream stations, with continuous pH, electrical conductance and flow measurements. Weekly samples will be analyzed for chemicals and bacteria.
- c. Twenty-two shallow groundwater stations, spaced about 65 meters apart along the saturated zone. Bi-weekly samples will be taken after treatment begins and analyzed for selected parameters.
- d. Twenty soil moisture stations randomly located at 20 to 100 cm depths throughout tract. Monthly observations will be made for selected parameters.

The basic objectives of the above design are:

- a. To determine if runoff from the tract is in compliance with Federal and State water quality standards.
- b. To establish a good baseline record of water quality parameters before sludge treatment.
- c. To determine the pattern and relationship of individual elements entering Sugar Creek. This information should allow composite sampling and analysis of index parameters, in order to reduce the number of observations.

Monitoring in subwatersheds (within the tract) will be used to determine effects of particular treatments on selected areas. Important measurements in the subwatersheds will include observation of the hydrologic response of the area due to treatment, monitoring of fecal coliform counts during and after sludge application, and evaluation of chemical parameters in runoff following selected levels of treatment.

COOPERATIVE RESEARCH

In addition to the demonstration work, the North Central Forest Experiment Station will utilize a randomized block design to study the effects of various levels of sludge and limestone applications upon soil chemistry, water quality and plant growth.

The Forestry Department of Southern Illinois University, supported by the National Science Foundation, also is studying plant and soil response of sludge and limestone treatments upon acid spoil as it varies with depth of incorporation into the spoil. They are investigating vegetative response of 12 grasses and six tree species.

The Agronomy Department of the University of Illinois presently is studying pyrite and other forms of sulfur in the acid spoil. They will examine redox potential of the spoil at various depths to describe the rate of change in surface and subsurface spoil materials resulting from sludge treatments.

SUMMARY

This report details the preliminary results of a strip mined reclamation demonstration project in Southern Illinois. The initial observations indicate that treated municipal sludge, when applied to the spoil in sufficient amounts, improves spoil pH, allows establishment of vegetation and reduces acidity and concentrations of some of the chemicals in the runoff issuing from the tract.

The proposed application of sludge to a larger 77 hectare area should provide some insight into the practicality of sludge treatment on strip mined areas. If such treatment is practical, three main advantages could possibly result: (1) reclamation of useless stripped areas, (2) reduction of water pollution associated with these areas, and (3) the disposal of municipal sludge.

REFERENCES

- Anderson, D. A., S. H. Kunkle and R. Hedrich. 1972. Affluence, effluence, and new roles for forest hydrology in the East. Proc. Amer. Water Resources Assoc., Fort Collins, Colorado, June 1972, 14 p.
- Braids, O. C., M. Sobhan-Ardakani and J. A. E. Molina. 1970. Liquid digested sewage sludge gives field crop necessary nutrients. Illinois Res. 12(3), 6-7.
- Burd, R. S. 1966. A study of sludge handling and disposal. Publication WP-20-4. Federal Water Poll. Control Admin. USDI. Cincinnati, Ohio.

- Dalton, Frank E., J. E. Stein and B. T. Lynam. 1968. Land reclamation - A complete solution of the sludge and solids disposal problem. *Jour. Water Poll. Control*, 40, 5, 789-800.
- Good, D. M., U. T. Ricca and K. S. Shumate. 1970. The relation of refuse pile hydrology to acid production. *Third Symposium on Coal Mine Drainage Research*, 145-149.
- Hill, Ronald D. 1971. Restoration of the terrestrial environment - *The ASB Bulletin*, 16,3, 107-116.
- Hinesly, Thomas D. 1972. Personal contact. Department of Agronomy, University of Illinois.
- Hunt, Clifford F., W. E. Sopper and L. T. Kardos. 1971. Renovation of treated municipal sewage effluent and digested liquid sludge through irrigation of bituminous coal strip mine spoil. *The Pennsylvania State University, Technical Paper, Institute for Research on Land and Water Resource*, 118 p.
- Joseph, J. M. and D. E. Shay. 1952. Viability of *Escherichia coli* in acid mine waters. *Amer. Jour. of Pub. Health*, 42, 795-800.
- Merz, Robert C. 1959. Utilization of liquid sludge. *Water and Sewage Works*, 106, 489-493.
- Patterson, J. R. and J. Gschwind. 1971. Human and animal wastes as fertilizers. *Fertilizer Technology and Use*, 577-594.
- Singer, P. C. and W. Stumm. 1968. Kinetics of the oxidation of ferrous iron. *Second Symposium on Coal Mine Drainage Research. Mellon Institute*, 12-34.
- Smith, E. E. and K. S. Shumate. 1971. Rate of pyrite oxidation and acid production rate in the field. Presented at Acid Mine Drainage Workshop. Athens, Ohio, 11 p.
- Sopper, W. E. 1970. Revegetation of strip mine spoil banks through irrigation with municipal sewage effluent and sludge. *Compost Sciences*, 6-11.
- Udall, Stewart L. 1967. Surface mining and our environment. U.S. Department of the Interior, 124 p.

EFFECTS OF LAND DISPOSAL OF WASTEWATERS
ON SOIL PHOSPHORUS RELATIONS

324 D

J. E. Hook, L. T. Kardos and W. E. Sopper
Department of Agronomy and School of Forest Resources
The Pennsylvania State University

At present there is an increasing useage of soil and soil-plant systems as a final treatment and disposal system for municipal and industrial wastewaters. The success of a land disposal site depends upon the ability of the soil to temporarily fix and store effluent constituents for use by plants and microbes and to prevent the migration of contaminants to the groundwater (Kardos, 1970). The movement and the fixation of phosphorus, a major constituent of many wastewaters, are important considerations in these disposal systems. In the Wastewater Renovation and Conservation Research Project at The Pennsylvania State University, the fate of phosphorus has been monitored as treated municipal sewage effluent was applied to cropland and forested areas. Ten years of monitoring has indicated a high degree of efficiency of the soil-plant system to retain and use phosphorus. The purpose of this report is to describe the chemical forms in which the phosphorus was being retained and to what depth in the soil it was accumulating.

METHOD OF STUDY

To evaluate phosphorus, as well as other constituents, of the treated wastewater, an extensive monitoring network was established. Its purpose was to collect water samples in the soil and underlying substratum. This network is described in detail elsewhere (Parizek et al, 1967). Yields of harvested crops were measured and samples were analyzed for phosphorus content by the method reported by Baker et al (1964).

Soil samples from the various treatment and control areas were analyzed for pH, organic matter, free iron, free aluminum, and available phosphorus. Organic matter and pH were determined by the methods of Peech et al (1947). Available phosphorus was determined using the dilute hydrochloric acid, dilute NH_4F extractant of Bray as described by Jackson (1956). Phosphorus in the soil samples was fractionated according to the scheme of Chang and Jackson (1957) with modifications of Glenn et al (1959) and Peterson and Corey (1965). Free iron was determined in the citrate-dithionite extract of the phosphorus fractionation scheme. Basically it was the extractant described by Aguilera and Jackson (1953). Free aluminum

was the aluminum extracted by the NH_4F (pH 8.2) extract of the phosphorus fractionation scheme.

The areas which received effluent included two major soil series. The Morrison sandy loam and the Hublersburg clay loam. These series have quite different properties and represent two possible extremes of the range of deep well drained Pennsylvania soils. Several properties of these soils which affect movement and fixation of soluble phosphorus are presented in Table 1.

Treatments of these areas included variations of effluent levels, usually zero, one and two inches per week and variations of vegetative cover. Although as many as 42 plots have been studied, only four treatment and three control plots will be considered in this paper. Each of the treated areas considered here was irrigated with two inches of effluent per week.

The agronomy area, located on Hublersburg clay loam was divided into seven crop rotation strips. The crop sequence is presented in Table 2.

Treatment was two inches of effluent per week and a control which received fertilizer phosphorus. The amount of effluent applied, concentration of phosphorus in the effluent and the amount of phosphorus applied for the eight years of treatment are presented in Table 3. From the phosphorus content and yield data, the average removal of phosphorus on the treated site was calculated and is also presented in Table 3.

The net amount remaining - the total applied, 620.7, minus the removal by crops, 206.3, or about 414 pounds per acre per year - is a measure of the amount which is being held by the soil.

The reed canarygrass area, located on Hublersburg clay loam, was irrigated with effluent year round. The grass was established in 1964, and since 1965 three cuttings were made each year except in 1968 when only two cuttings were made. The amount of phosphorus removed yearly by the grass is shown in Table 4. Also presented in that Table are the amount of effluent applied, concentration of phosphorus in the effluent and amount of phosphorus applied.

The old field area, located on Hublersburg clay loam, was usually irrigated from May through November each year. This field, abandoned in the early 1930's, has received no commercial fertilizer. Growth responses of the vegetation have been measured (Sopper, 1971) but none of the vegetation has been removed. The area is covered with a variety of weeds and has a scattered stand of white spruce (*Picea glaucus* M.). The old field control plot is similar but has received no effluent.

TABLE 1. Some Properties of the Two Soils at the Areas Which Were Used in the Effluent Irrigation Project

Area	Soil Depth	pH	Organic Matter	Free Iron	Clay Content
	inches		%	% Fe ₂ O ₃	%
<u>Hublersburg clay loam</u>					
Agronomy Control	0-12	5.6	2.96	3.44	--
	12-24	5.1	0.86	4.54	--
	24-36	5.1	0.40	5.70	--
	36-48	5.0	0.20	6.15	--
	48-60	4.9	0.15	6.75	--
Reed Canarygrass Irrigated	0-12	6.4	3.01	3.62	43
	12-24	5.8	0.82	5.00	52
	24-36	5.4	0.34	5.25	49
	36-48	5.3	0.18	5.35	45
	48-60	5.1	0.09	5.42	41
Old Field Control	0-12	5.2	2.39	3.94	--
	12-24	5.2	0.54	5.30	--
	24-36	5.1	0.23	5.80	--
	36-48	5.1	0.21	5.80	--
	48-60	5.1	0.21	5.80	--
<u>Morrison sandy loam</u>					
Gamelands Forest Control	0-12	4.8	1.67	1.66	15
	12-24	4.9	0.31	2.14	28
	24-36	5.0	0.25	2.31	28
	36-48	5.0	0.19	2.22	16
	48-60	4.9	0.19	2.71	36
Gamelands Forest Irrigated	0-12	5.5	1.43	1.21	--
	12-24	5.2	0.30	2.08	--
	24-36	5.0	0.14	2.17	--
	36-48	4.7	0.12	2.32	--
	48-60	4.7	0.12	2.37	--

TABLE 2. Yearly Crop Sequence for the Seven Strips in the Agronomy Area

Strip Number	1963	1964	1965	Year 1966	1967	1968	1969	1970	1971
1	corn	oats	alfalfa	alfalfa	alfalfa	corn	corn	corn	corn
2	wheat	red clover	corn	corn	corn	corn	corn	corn	corn
3	red clover	corn	oats	alfalfa	alfalfa	corn	corn	corn	corn
4	wheat	red clover	corn	corn	corn	corn	corn	corn	corn
5	corn	oats	alfalfa	alfalfa	alfalfa	corn	corn	corn	corn
6	red clover	corn	oats	alfalfa	alfalfa	corn	corn	corn	corn
7	alfalfa	corn	oats	alfalfa	alfalfa	corn	corn	corn	corn

TABLE 3. Concentration of Phosphorus in the Effluent and Amounts of Phosphorus Added by Effluent Irrigation and Removed by Crop Harvest in the Agronomy Area Receiving Two Inches of Effluent at Weekly Intervals

	1963	1964	1965	1966	Year 1967	1968	1969	1970	Total
	Average concentration of P in effluent (mg/l)								
	9.70	8.55	6.95	5.35	6.75	7.10	6.55	4.15	--
	Amount of Effluent Applied (inches/year)								
	48	66	58	64	52	40	32	32	392
	Total Phosphorus Applied (lbs/acre/year)								
	105.7	127.8	91.1	77.9	76.2	64.4	47.6	30	620.7
	Average Amount of Phosphorus removed by all crops (lbs/acre/year)								
	26.3	18.5	27.1	31.8	24.8	<u>1/</u>	43.1	34.7	206.3

1/ No harvest

TABLE 4. Concentration of Phosphorus in the Effluent and Amounts of Phosphorus Added by Effluent Irrigation and Removed by Crop Harvest in the Reed Canarygrass Area

	Year							
	1964	1965	1966	1967	1968	1969	1970	Total
Average concentration of P in the effluent (mg/l)								
8.55		6.95	7.70	7.70	8.45	4.20	4.05	--
Amount of effluent applied (inches/year)								
66		80	78	94	98	100	86	602
Total phosphorus applied (lbs/acre/year)								
127.8		125.7	135.9	163.9	187.6	94.8	88.8	924.5
Average amount of phosphorus removed by reed canarygrass (lbs/acre/year)								
1/		40.0	33.4	55.9	47.2	47.2	56.0	279.7
1/ No harvest								

The gamelands area, located on Morrison sandy loam soil, has a mixed hardwood forest vegetation. The plot (New Gamelands) for which lysimeter data is presented has been irrigated on a year round basis since 1965. The control, adjacent to this plot has not been irrigated or fertilized. For analysis of total soil phosphorus (the fractionation data) a nearby plot (Old Gamelands) which has been irrigated since 1963 was used. This plot has received various levels of effluent irrigation since 1964 and prior to sampling in 1970 had received a total of 600 inches of effluent.

RESULTS

One of the first questions to be considered was that of how much phosphorus was leached through the soil. The concentration of phosphorus in the percolating soil water was derived from the suction lysimeter data. These lysimeters sampled water in and just below the plant root zone. The mean annual concentrations of phosphorus in the soil water of the treated and control areas is presented in Table 5.

In the agronomy area, mean annual concentration in samples from the control site at a depth of 48 inches varied within a range of 0.030 to 0.080 ppm. These concentrations represent the normal background phosphorus which is in equilibrium with the soil phosphorus. These concentrations are considered typical for this heavy textured soil. The mean annual concentration in samples from the old field control area also fell within this range.

When treated with effluent from 1963 to 1971 the percolate in the agronomy area has shown no increase in phosphorus concentration at the 48 inch depth. Only a slight inconsistent increase occurred at 24 inches. At 6 inches the percolate concentration in the treated area varied considerably but was consistently higher than in the control area. Since the effluent concentration was about 7 ppm and the highest percolate concentration was about 0.6 ppm a reduction of greater than 90% occurred after water percolated through only 6 inches of soil.

The reed canarygrass area was as effective as the agronomy area in reducing phosphorus concentrations in the soil percolate. The concentration at the 24 inch depth in the reed canarygrass area was only slightly higher than in either the agronomy control or the treated area, and has remained nearly constant. The increase which occurred in 1971 at the 6 inch depth was a result of a substantial increase in both concentration and amount of applied phosphorus. During most of that year effluent containing stabilized digester sludge (approximately one part of sludge slurry to eleven parts of effluent) was applied to that area. This effluent-sludge mixture

TABLE 5. Mean Annual Concentration of Phosphorus (mg/l) in Soil Percolate Samples Taken at Three Depths from Both Effluent Treated and Control Areas

Area	Effluent Amount	Soil	1965	1966	1967	Year 1968	1969	1970	1971
	in./wk								
6-Inch Depth									
Agronomy	0	clay loam	.035	.050	.045	.060	.025	.035	.045
Agronomy	2	clay loam	.145	.250	.600	.620	.500	.135	.120
Reed Canarygrass	2	clay loam	--	.165	.140	.190	.205	.135	.210
Old Field	0	clay loam	--	.040*	.045*	.000*	.035	.035	.030*
Old Field	2	clay loam	--	.090	.140	.260	.295	.340*	.995
New Gamelands	0	sandy loam	--	.050*	.050*	--	.045	.050	.090*
New Gamelands	2	sandy loam	--	.265	.115	.450	.320	.630	.965
24-Inch Depth									
Agronomy	0	clay loam	.055	.045	.045	.045	.070	.060	.040
Agronomy	2	clay loam	.040	.060	.090	.080	.060	.090	.065
Reed Canarygrass	2	clay loam	.025*	.085	.100	.105	.100	.075	.105
Old Field	0	clay loam	--	.030*	.032	.120*	.220*	.100*	.025*
Old Field	2	clay loam	--	.070	.095	.125*	.120*	.120*	.250*
New Gamelands	0	sandy loam	--	.090*	.225*	.035*	.030*	.025*	.040*
New Gamelands	2	sandy loam	--	.030	.050	.130	.105	.130	.090
48-Inch Depth									
Agronomy	0	clay loam	.030	.040	.040	.040	.080	.045	.035
Agronomy	2	clay loam	.025	.040	.070	.075	.095	.080	.060
Reed Canarygrass	2	clay loam	.010*	.055	.055	.060	.030	.045	.060
Old Field	0	clay loam	--	.030	.040	.040	.050	.040	.040*
Old Field	2	clay loam	--	.060	.070	.055	.100	.115*	.420*
New Gamelands	0	sandy loam	--	.060*	.070	.075*	.105*	.050*	.025
New Gamelands	2	sandy loam	--	.040	.055	.115	.140	.155	.265

* Indicates means computed from fewer than 10 samples.

had a total phosphorus level of 20 to 25 mg/l and an orthophosphate level of 15 to 15 mg/l.

In the old field treated area, though located on the Hublersburg clay loam soil, the percolate has increased in phosphorus concentration more than in the treated agronomy and reed canarygrass areas. This greater increase occurred to the 48 inch depth. The factor which may have contributed most to this increase was that phosphorus was not removed in a harvested crop. The phosphorus cycled through the soil rather than being removed. The old field was also treated with effluent each year for as many as ten weeks longer than the agronomy area.

At the gamelands treated area, located on the Morrison sandy loam soil, effluent irrigation has resulted in a substantially greater increase in phosphorus concentration in the soil percolate. While treated sites on the Hublersburg soil have concentrations about the same as the agronomy control, the gamelands treated area has shown a steady increase above that of the control area since the irrigation began in 1965. One reason for this greater increase is the recycling of phosphorus through the forest litter. A more important reason is the lower clay content and lower content of sesquioxides in the soil (Table 1). The effect of these properties will be discussed in greater detail later.

If a few assumptions are made concerning the movement of water, these concentrations of phosphorus in the soil water can be used to calculate the amount of phosphorus which may be leaching into the substratum. In 1970, for example, 86 inches of effluent were applied to the reed canarygrass area. The total rainfall that year was 47 inches. Of that, approximately 26 inches^{1/} were lost by evapotranspiration. Assuming that the total of effluent and recharge - 107 inches - percolates downward (no interflow or runoff) at the mean concentration of phosphorus found in the six-inch lysimeter - 0.135 mg/l - then a total of 3.3 lbs/acre/year would move downward. By the time this reaches four feet the concentration is reduced to 0.060 mg/l. From this depth only 1.4 lbs/acre/year would leave the irrigated area. This is only 1.7% of the 89 lbs/acre added that year.

^{1/}This value represents the potential evapotranspiration as calculated by the Thornthwaite equation. Taylor, S. A. and Ashcroft, G. L. 1972. Physical Edaphology. W. H. Freeman and Co; San Francisco. pp. 64-66.

Very little of the phosphorus added with effluent has been lost by leaching. The remainder, 98.3%, has been removed by crops, has been held by the soil and has been lost in runoff. The amount of runoff is not exactly known for each treated area, but it has not been excessive. The agronomy and old field areas were irrigated during the driest part of the year. Runoff occurred only during heavy rainstorms. The reed canarygrass area had a considerable amount of runoff during winter and spring. The amount of water lost as runoff from a sub-watershed of this area occasionally exceeded the amount applied as effluent (Myers, 1967). Ice covered ground, saturated soils, negligible evaporation and increased precipitation led to higher runoff during winter irrigation. Myers showed that the runoff which passed the weir below this sub-watershed of the reed canarygrass area had a lower phosphorus concentration than the applied effluent even when no precipitation was available to dilute the runoff. This was interpreted as indicating that a portion of the effluent had entered the soil, moved downslope as interflow and seeped back to the surface with a lowered phosphorus content.

Runoff losses of phosphorus from the irrigated areas on the sandy Morrison soil were probably very low. Even during winter a thick leaf mulch and sandy surface soil prevented runoff. Interflow on top of clay layers in the soil contributed most downslope movement of irrigated water. Rebuck (1967) intercepted runoff and shallow interflow from an effluent irrigated area located on this soil. He found an average 8% loss of irrigation water when application rates were between one and three inches per week. Since much of this water was from interflow, the effluent had contact with the soil for enough time to substantially lower the phosphorus concentration.

The amount of phosphorus removed by crops is a large and important part of the effluent treated sites. The data in Table 3 indicates that the crops removed from 14 to 115 percent of the phosphorus added annually to the agronomy area. The net phosphorus added since the beginning of effluent treatment increased until 1968 after which it has actually decreased. This was due to the decrease in added phosphorus and increase of phosphorus removed by the crop. Ideally, if the amount added would just equal the amount removed in harvest, phosphorus would not build up in the soil and the concentration of phosphorus in the percolate would be expected to remain constant or decrease.

In the reed canarygrass area (Table 4), higher phosphorus applications have resulted in a continued net increase in phosphorus not removed by the crop since irrigation began. Though the reed canarygrass removes slightly more phosphorus than the agronomic

crops (Table 2), it has removed only 30 to 60 percent of the total added. At this site it is expected that the gradual increase in net phosphorus, which represents primarily the amount which is building up in the soil, will result in a gradual increase in phosphorus in the percolating water.

In the old field and gamelands forest areas no harvest was made. Some of the added phosphorus is taken up by the plants and trees in these areas. Sopper (1971) reported higher concentrations of phosphorus in foliar material of irrigated hardwoods in the gamelands than in the control. Similarly ground vegetation in the irrigated old field area had a higher phosphorus content than in the control. The forest vegetation in these treated areas did take up phosphorus, but the extent to which this uptake contributes to renovation of the effluent is not certain. Most of the phosphorus taken up by the trees and ground vegetation is recycled in the litter. This must obviously result in buildup of phosphorus in the soil and an eventual increase of phosphorus in the percolating water. This was found to occur in both the old field and gameland areas as discussed earlier.

When phosphorus is added to soils it usually is in the form of orthophosphate anions. Even organic phosphates are mineralized to this soluble form before being taken up by plants or reacting with the soil. These anions bond chemically with surfaces of iron and aluminum oxyhydroxides and will form precipitates with iron and aluminum when these are in solution. The bonds formed from surface and precipitation reactions vary in strength. The most weakly bonded, that is the most soluble phosphates, readily equilibrate with the soil solution and, hence, would be considered available to plants. A good measure of the amount of this available phosphorus is the Bray dilute acid-dilute fluoride extraction. This test was carried out periodically with soils from the treatment plots.

Soil from the agronomy area showed an increase in Bray extractable phosphorus over the 9 years of treatment, although this increase occurred only in the upper one foot of soil. The control plot which received about 40 lbs P/acre/year as commercial fertilizer, showed a smaller increase. Below the top foot of soil no increase was observed. In the reed canarygrass area soils were analyzed only two years - 1969 and 1971. The amount of Bray extractable phosphorus in the upper foot was 29.8 and 42.3 $\mu\text{g P/gram}$ of soil for the two years, respectively. Again there was no increase below the upper foot of soil.

Bray phosphorus in the old field area increased approximately the same as in the agronomy area. The control plot of this area, which received no fertilizer, remained almost constant. In the second foot of both control and effluent treated plots, the Bray

phosphorus remained constant at less than 3.0 $\mu\text{g P/gram}$ of soil. These plots are all located on the Hublersburg clay loam. Effluent additions have not increased Bray extractable phosphorus significantly below the upper foot of this soil. As was pointed out earlier, the effluent has caused increases in water soluble phosphorus of percolate samples below the upper foot. This apparent discrepancy is due to the fact that the concentration in the percolate is measuring the equilibrium phosphorus in transit whereas the Bray extract measures both equilibrium and reserve phosphorus with the latter dominating in relative quantity.

In the old gamelands area on the Morrison sandy loam, however, there was evidence that an increase of Bray phosphorus has occurred to a depth of three feet. Samples were analyzed only in 1967 and 1971. In 1967, just 2½ years after effluent irrigation began, Bray phosphorus had reached 75.6, 4.9 and 2.2 $\mu\text{g P/gram}$ of soil for the 1st, 2nd, and 3rd feet, respectively. This compared to 16.5, 2.1 and 1.2 $\mu\text{g P/gram}$ of soil for the respective depths of the control plot. In 1971 the irrigated area had 143.8, 31.6 and 9.9 $\mu\text{g P/gram}$ of soil and the control had 6.3, 1.5 and 0.7 $\mu\text{g P/gram}$ of soil in the respective depths. The Morrison sandy loam soil on which this treatment area was located has shown a very large increase in Bray extractable phosphorus in response to year round effluent irrigation.

A difficulty with the Bray extractable phosphorus test is that this test does not measure all of the native or retained phosphorus. It does indicate changes in the amount of phosphorus which is available to plants, and this amount is affected by treatments. However, for many soils the Bray test measures less than 5% of the total soil phosphorus.

To evaluate changes in the phosphorus content more completely a fractionation of the soil phosphorus was carried out on soils from some of these treatment plots. The procedure was used to explain what has happened to the applied phosphorus and to relate this to other measured properties of the soils.

The fractionation procedure separates the soil phosphorus into four fractions: the NH_4F - soluble fraction, the NaOH - soluble fraction, the reductant soluble fraction and the H_2SO_4 soluble fraction. While these phosphorus fractions do not represent discrete chemical compounds, they do result from groups of related compounds. The NH_4F (pH 8.2) extracts phosphorus which is bound to aluminum and aluminum compounds. NaOH extracts phosphorus bound to the surfaces of iron compounds. The reductant solution dissolves phosphorus compounds enmeshed within iron oxyhydroxides, and the sulfuric acid extracts calcium and magnesium phosphates.

The phosphorus fractions were determined for the old field control plot. The fractions are expressed as percent of the total extracted. This total varied from 300 to 600 $\mu\text{g P/g soil}$. The NaOH plus the reductant fractions made up 80 to 90 percent of the total extracted soil phosphorus. These are the fractions associated with iron. This was not surprising since total iron oxides expressed as Fe_2O_3 made up 2 to 6 percent of those soils; whereas, aluminum oxyhydroxides made up less than one half of one percent. Calcium and magnesium in these soils exist primarily as exchangeable cations. Only a small portion, less than 6% of the total extracted soil phosphorus was associated with calcium and magnesium. It is, in fact, possible that this small percentage was actually related to aluminum which was released after the iron reduction treatment.

NH_4F - phosphorus made up less than five percent of the total extracted phosphorus for most untreated soils, particularly sub-soils. In the upper foot of the reed canarygrass effluent treated plot it constituted 13 percent. In the upper foot of the agronomy area control plot it was 16 percent. In the gamelands treated plot NH_4F phosphorus made up 43, 27, 17 and 11 percent of the total fractions of the first through fourth feet, respectively. This fraction, though not the most abundant, was probably the most important. This was demonstrated first by its relation to Bray extractable phosphorus. It was found to be highly correlated with this Bray test for plant available phosphorus. Its importance was further demonstrated by its relation to effluent and fertilizer treatments.

On the old field and agronomy control areas and the reed canarygrass irrigated area located on the Hublersburg clay loam, the greatest amounts of NH_4F - phosphorus occurred in the upper foot decreased sharply in the second foot and then remained relatively constant in the deeper layers. Statistically significant differences between the three areas were only present in the upper foot. The reed canarygrass area which had been treated with effluent had the greatest amount of NH_4F phosphorus in the upper foot and was followed in order by the agronomy area control plot which has been receiving commercial fertilizer, and by the old field control plot which has received neither effluent nor commercial fertilizer.

In the forested plots located on Morrison sandy loam effluent additions have significantly increased the amount of NH_4F phosphorus extracted when compared to the control. This increase occurred in the second and third as well as the first foot. This movement of applied phosphorus was similarly indicated by the Bray test.

There are several reasons why phosphorus has penetrated deeper in this hardwood area of the Morrison soil. First, there is no removal of harvested crops. As mentioned earlier phosphorus taken up by growing plants is later released as the leaf litter mineralizes. Secondly, the sandy soil of this area has a greater hydraulic conductivity; as a consequence the phosphorus in soil solution has less time to react with particle surfaces. Third, the mineral composition of the Morrison soil (Table 1) shows about one half as much free iron as the Hublersburg soil. Further it has less aluminum oxyhydroxides and has less clay which would result in less reactivity with phosphorus.

In addition to the noted effect of effluent treatments on the NH_4F fraction of the soils there was one other significant treatment effect. This was with respect to the NaOH fraction of the reed canarygrass plot. The effluent additions of phosphorus have resulted in a slight increase of NaOH phosphorus, though only in the upper foot. This should be expected. The fractions as separated are in equilibrium with each other. Aluminum phosphate compounds generally have a higher solubility than iron phosphates. As the aluminum phosphates try to maintain their solubility, phosphate in solution reacts with iron surfaces and iron in solution as these become available for phosphate reactions. The long range effect is to form the less soluble iron phosphates at the expense of the aluminum phosphates.

By calculating the amounts of phosphorus added to the reed canarygrass plot and by estimating the amounts lost by leaching, runoff and crop harvest, a mass balance indicated that 500 pounds of phosphorus per acre were retained by the plot in 6 years. This amount was equal to the amount of phosphorus extracted in the NH_4F and NaOH fractions of the reed canarygrass topsoil minus the amount extracted in these fractions from the untreated old field topsoil. This mass balance indicates that most of the added effluent phosphorus can be accounted for in the NH_4F and NaOH fractions.

CONCLUSIONS

Soils and soil plant systems may be effectively used to renovate wastewaters. Applications must be managed so that the constituents of the wastewater remain at the disposal site or leave in harmless or beneficial forms. The water which leaves the disposal site should have concentrations below USPHS recommended limits for drinking water and below stream standards where applicable. In the case of phosphorus, a major constituent of municipal wastewaters, the soil-plant system proves to be an excellent renovating media. When the system is properly managed most of the added phosphorus remains in the soil

at the disposal site or leaves as a nutrient in harvested crops. Soils differ in their ability to hold phosphorus. In a heavy textured soil high in sesquioxides, phosphorus from effluent irrigation did not increase in the soil below a depth of one foot after 7 years of irrigation. In a light textured soil with half as much sesquioxides phosphorus content of soils increased to a depth of 3 feet after 6 years of treatment. The Bray test for available phosphorus was suitable for determining zones of accumulation of added phosphorus. The fractionation of total soil phosphorus enabled a rough mass balance to be made for the phosphorus within the disposal system.

ACKNOWLEDGEMENT

Research reported here is part of the program of the Waste Water Renovation and Conservation Project of the Institute for Research on Land and Water Resources, and Hatch Projects No. 1481 and 1809 of the Agricultural Experiment Station, The Pennsylvania State University, University Park, Pennsylvania.

Portions of this research were supported by funds from Demonstration Project Grant WPD 95-01 received initially from the Division of Water Supply and Pollution Control of the United States Department of Health, Education, and Welfare and subsequently from the Federal Water Pollution Control Administration, United States Department of the Interior. Partial support was also provided by the Office of Water Resources Research, United States Department of the Interior, as authorized under the Water Resources Research Act of 1964, Public Law 88-379.

REFERENCES

- Aguilera, N.H. and M.L. Jackson. 1953. Iron oxide removal from soils and clays. *Soil Sci. Soc. Amer. Proc.* 17:359-364.
- Baker, D.E., G.W. Gorsline, C.B. Smith, W.I. Thomas, W.E. Grube, and J.L. Ragland. 1964. Technique for rapid analysis of corn leaves for eleven elements. *Agron. Jour.* 56:133-136.
- Chang, S.C. and M.L. Jackson. 1957. Fractionation of Soil Phosphorus. *Soil Sci.* 84:133-144.
- Glenn, R.C., P.H. Hsu, M.L. Jackson, and R.B. Corey. 1959. Flow sheet for soil phosphate fractionation. *Agronomy Abstracts*, p.9.
- Jackson, M.L. 1956. *Soil Chemical Analysis*. Prentice-Hall. Englewood Cliffs, New Jersey, 498 p.
- Myers, J.C. 1967. A study of drainage conditions on a hillside receiving sewage effluent at weekly intervals. M. S. Thesis. The Pennsylvania State University, University Park, Pennsylvania

- Parizek, R.R., L.T. Kardos, W.E. Sopper, E.A. Myers, D.F. Davis, M.A. Farrell, and J.B. Nesbitt. 1967. Waste Water Renovation and Conservation. Penn State Studies No. 23, The Pennsylvania State University, 71pp.
- Peech, M., L.T. Alexander, L.A. Dean, and J. F. Reed. 1947. Method of Soil Analysis for soil fertility investigations. United States Dept. of Agric. Circular No. 757. Wash., D.C.
- Peterson, G.W. and R.B. Corey. 1965. Modified Chang and Jackson Procedure for Routine Fractionation of Inorganic Phosphorus. Soil Sci. Soc. Amer. Proc. 30:563.
- Rebuck, E.C. 1967. The Hydrologic Regime Due to Sprinkler Irrigation of Treated Municipal Effluent on Sloping Land. M.S. Thesis. The Pennsylvania State University, University Park, Pennsylvania
- Sopper, W.E. 1971. Disposal of Municipal Waste Water Through Forest Irrigation. Environ. Pollution 1:263-284.

DISCUSSION

- Hortenstine: You described your method on soil phosphorus, that is your chemical method, but nothing on the method of determining soil solution phosphorus. What method did you use on this?
- Hook: The technique we used is one of the standard methods, the ammonium molybdate-sulfuric acid procedure.
- Pearce: Are there levels of phosphorus that can build up in the soil that will be toxic to plants?
- Hook: We certainly haven't come anywhere near levels that would be toxic to plants and I don't know even what level would be that high. There might be others here that have an idea of what would be toxic levels...Dr. Kardos says there's probably never any toxicity with phosphorus. The phosphorus is just not available enough in the soils although you may have a lot of it there. For example, I mentioned, or might have mentioned, there were about 600 micrograms of phosphorus per gram of soil extracted in the total fractionation procedure. Of this only a very small fraction was actually in solution at any one time.
- Goydan: How can one estimate the phosphorus requirement for the bacteria so that you would be able to achieve optimum degradation?
- Hook: Again, I don't know that I'm really qualified to answer that. The concentration is maintained in the soils, that is background concentration has always been sufficient for any bacteria. What minimal levels you could get, I don't know. I've never seen concentration

lower than about 0.005 ppm, and I don't know that even that would be below the level microbes would need. The phosphorus is there in very low concentration and it's a matter normally, at least for higher organisms, of how fast it can come into solution and get to the plants and similarly it would be how fast it would get to the microbes. I doubt that it would ever be limiting.

Goydan:

In some industrial effluents where you don't have phosphorus inherent in the waste, sludge or effluent, and in other cases where you may not even have the necessary nitrogen requirements, would you need a means to predict the fertilizer requirements, say if you're preparing the field?

Kardos:

I'll have to go along with what Mr. Hock said. I don't think there's ever going to be a situation with waste water renovation where phosphorus will be limiting. The actual amount which the soil micro population will need will be absolutely supplied by anything that the effluent will have. Does that answer the question?

Unknown:

If the effluent doesn't have phosphorus. In that case, I would still say that the natural soil process which is there should be quite sufficient to supply the needs. I can only remember one case that I noticed where there was a response to phosphorus, a microbial response to phosphorus in soils, and that was a sandy soil. Again, I think the soil phosphorus would be quite available and adequate.

Ellis:

In response to the question before the last one, I've never seen a case where we've had what I consider phosphorus toxicity but the literature is full of examples of phosphate-induced deficiencies. For example, I've seen field beans that at zero phosphate levels yield 30 to 34 bushels per acre and at 800 lbs. of phosphorus per acre, they'll yield 6. It turns out to be a zinc deficiency. So we might have to really be careful of our management if we get into areas of high phosphate applications.

EFFECT OF LAND DISPOSAL OF WASTEWATER ON EXCHANGEABLE CATIONS
AND OTHER CHEMICAL ELEMENTS IN THE SOIL

Louis T. Kardos and William E. Sopper
Department of Agronomy and School of Forest Resources

325D

The chemical changes that occur in soil through which the applied wastewater percolates have usually been given less attention than the changes occurring in the wastewater itself. This is understandable since most investigations of land disposal of wastewater have been directed by sanitary engineers rather than soil scientists. In a review of the literature by Edwards (1968) it was indicated that most of the concern with respect to soil chemical changes was with respect to changes in the amounts of sodium relative to the other exchangeable cations in the soil. This concern with exchangeable sodium stems from the well-documented research in irrigation agriculture which has shown that when the exchangeable sodium percentage reaches a value of about 15 a deterioration of soil structure and adverse effects on infiltration can be expected in medium and fine textured soils.

Henry et al (1954) in a 3 year experiment using sewage effluent containing 680 ppm of Na increased the exchangeable Na level to 2.37 m.e./100g and significantly decreased the exchangeable Ca and Mg, but exchangeable K was unaffected. In spite of the high exchangeable Na content there was no mention of any difficulty with infiltration.

In an investigation of primary sewage effluent spreading on five California soils with relatively low clay content (3-10%), Sanitary Engineering Research Laboratory (1955), it was reported that exchangeable calcium and magnesium decreased while exchangeable sodium, potassium and ammonium increased. Permeability of the soil was not affected, probably because of the low clay content.

Edwards (1968) in soil samples taken in 1966 after 236 inches of wastewater had been applied to the corn rotation area of the Penn State Wastewater Renovation Project found no significant change in the status of the exchangeable cations from that found in 1963 after 48 inches of wastewater had been applied. By 1966 the exchangeable sodium percentage (ESP) in the wastewater treated areas had increased with respect to the control area about 4-fold in the upper foot and 1½ to 2-fold in the next four feet. However the maximum ESP value in 1966 was only 3.3 and occurred in the upper foot of the 2-inch per week treatment area. In 1966 exchangeable hydrogen, calcium and magnesium still occupied 93% of the total exchange capacity in the

upper foot and 95 to 96% in the next four feet. The sodium adsorption ratio (SAR) value in the wastewater,

$$\text{defined as: } \text{SAR} = \frac{\text{Na}^+}{\frac{\text{Ca}^{++} + \text{Mg}^{++}}{2}}$$

ranged from 1.20 to 1.62 in the period 1963-66. Ion concentrations are expressed as milliequivalents per liter. Agricultural Handbook No. 60 (1954) defines an irrigation water as having a low sodium hazard if the SAR value is less than ten. On this basis the Penn State wastewater would qualify as an excellent irrigation water.

Kline (1967) examined soil samples from the forested areas taken in the fall, 1963; spring, 1964; and fall, 1965. He found larger differences between 1963 and 1965 samples for exchangeable Na on the treated plots but differences between control and treated areas in 1965 were similar to those found in 1963. Differences in exchangeable Na between control and treated areas were significant to a greater depth in the soil where two inches was applied weekly to red pine than where only one inch was applied. Exchangeable Na was significantly greater to a depth of five feet in the 2-inch red pine area but only to a depth of three feet in the 1-inch red pine. In all cases exchangeable Na remained below 0.5 m.e./100g and did not exceed an ESP value of 3.0. There was no consistent pattern of differences in the other exchangeable cations except that exchangeable Ca tended to be higher than the control on the 2-inch red pine treated area and exchangeable K tended to be higher than the control on the 1-inch red pine area.

The present report extends the information given by Edwards (1968) through the soil sampling in 1969 and also reports on changes in the status of exchangeable Mn, adsorbed chloride and boron, kjeldahl nitrogen and organic matter in the crop rotation area and in some of the forested areas.

Summarized over the five soil depths (one foot increments to a depth of five feet), Figure 1 indicates that in the corn rotation area only in the case of exchangeable Mg and Na was there a significant change due to wastewater treatment. The Mg increases occurred most strongly in the upper foot. Below the second foot greater increases occurred with the one-inch per week treatment than with the two-inch treatment. Exchangeable Mg increased in a similar manner in the forest areas.

The Na increases were also greatest in the upper foot and in this upper zone it appears that both the one and two inch per week treatments have peaked at a value of approximately 0.5 m.e. per 100 grams




Figure 1. Exchangeable cations in soil samples from corn rotation area which has been receiving 0, 1 and 2 inches of wastewater, averaged over five one-foot depth intervals and over six sampling years, 1963, 1965-69.

of soil, equivalent to an ESP value of approximately 2.5 to 3.0%. Samples taken in 1971 from the forested areas (Table 1) showed a range in maximum exchangeable Na from 0.5 m.e./100g in the 1-inch red pine area on the fine textured Hublersburg soil to 0.2 m.e./100g in the 2-inch hardwood area on the sandy Morrison soil. These values were equivalent, respectively, to ESP values of 2.9 and 3.2. Thus it appears highly probable that with the present effluent quality, with an SAR value less than 2.0, one need not be concerned about a sodium hazard to soil structure and permeability.

With respect to the other principal exchangeable cations, K, Ca and H, there were no significant treatment effects in the corn rotation area (Figure 1). Since this area had been limed during the farm management program prior to its use in the wastewater experiment a sharp decrease of Ca with depth was present originally and this depth effect has persisted. In the unlimed forest areas (Table 1) the depth difference in initial exchangeable Ca content between the upper foot and the deeper layers was not as great and some increase in Ca in the upper foot occurred as a result of both the 2-inch and 1-inch per week wastewater treatment. Effects of wastewater treatment on exchangeable K in the forest areas were small and nonsignificant. Exchangeable H in the forest area was inconsistently affected by wastewater treatment except on the sandy Morrison soil which received the greatest amounts of wastewater. On this site the exchangeable H in 1971 in the upper foot was 13.7 m.e./100g in the control area and only 7.3 m.e./100g in the wastewater area.

In the corn rotation area the small increase in exchangeable Mg and Na were reflected in an increase in base saturation which in turn was reflected in a significant increase in pH in the upper two feet for both the 1- and 2-inch treatments.

Although manganese is not commonly measured among the exchangeable cations it was included because of the possible effect of the increased wetness on the solubilization of manganese by oxidation-reduction reactions. The data indicated that differences due to wastewater treatments were not significant in the more aerobic and less acid upper two feet but that wastewater treatment did increase exchangeable Mn in the next three feet, with the differences being significant at the 1% level with the 1-inch per week and at the 5% level with the 2-inch per week treatment. On the forested areas the one-inch wastewater additions decreased the exchangeable Mn in the upper foot in the red pine area and in the upper three feet in the hardwood area, however, exchangeable Mn increased in the deeper layers. In the two inch treatment areas, exchangeable Mn increased below the upper foot in the old field area on the fine textured Hublersburg soil but decreased at all depths in the hardwood area on the sandy Morrison soil. This situation conforms to the nitrification-denitrification activity described for these two

Table 1. Exchangeable cations in 1971 in soils at five depths from forest areas which have been receiving 0 and 1 or 2 inches at weekly intervals.

Area	Soil Depth feet	Wastewater applied - inches per week										Mn μg/g
		K		Ca	Mg	Na m.e./100 grams		H				
		0	1	0	1	0	1	0	1	0	1	
Red Pine ^{1/}												
1	0.1	0.3	1.8	3.1	0.4	1.3	0.2	0.3	15.9	16.8	34.4	22.9
2	0.3	0.1	1.9	1.7	1.2	0.7	0.2	0.3	11.1	10.3	12.9	18.4
3	0.1	0.3	1.3	0.7	1.5	0.7	0.3	0.5	11.8	16.4	12.0	19.9
4	0.5	0.4	1.6	0.5	1.5	0.6	0.2	0.4	--	--	10.5	13.0
5	0.4	0.4	1.4	0.4	1.5	0.5	0.3	0.4	--	--	9.6	17.4
Wastewater applied - inches per week												
		0	1	0	1	0	1	0	1	0	1	
Hardwood ^{1/}												
1	0.1	0.2	1.0	1.9	0.2	1.1	0.2	0.3	25.3	16.2	52.9	26.9
2	0.3	0.3	1.2	1.1	1.2	1.5	0.2	0.3	18.2	14.7	32.7	18.9
3	0.2	0.3	1.1	1.0	1.7	1.4	0.2	0.4	12.6	12.9	23.5	17.4
4	0.2	0.4	1.0	1.4	2.1	1.2	0.2	0.4	--	--	14.9	16.3
5	0.3	0.4	0.8	1.1	1.7	1.3	0.2	0.4	--	--	13.1	21.4

Table 1. Continued.

Area	Soil Depth feet	K	Ca	Mg	Na	H	Mn						
				m.e./100 grams				μg/g					
Wastewater applied - inches per week													
		0	2	0	2	0	2	0	2				
Old Field ^{1/}	1	0.1	0.4	2.0	3.3	0.2	1.7	0.2	0.3	14.9	15.5	15.9	14.5
	2	0.0	0.2	2.2	2.0	0.8	1.3	0.2	0.3	11.6	16.4	12.1	17.2
	3	0.0	0.1	1.1	1.4	1.4	1.2	0.2	0.3	12.0	16.7	10.6	15.8
	4	0.0	0.2	1.5	1.0	1.6	1.4	0.2	0.3	--	--	9.5	15.7
	5	0.0	0.1	1.2	1.1	1.5	1.4	0.2	0.3	--	--	8.7	16.1
Wastewater applied - inches per week													
		0	2	0	2	0	2	0	2	0	2	0	2
Hardwood ^{2/}	1	0.0	0.1	0.5	1.9	0.1	0.5	0.2	0.2	13.7	7.3	32.7	4.1
	2	0.2	0.0	1.1	1.0	0.8	0.4	0.2	0.2	13.4	5.2	11.0	4.9
	3	0.3	0.1	0.8	1.3	1.0	0.7	0.2	0.2	11.5	9.4	10.9	5.7
	4	0.2	0.0	0.5	1.0	0.8	0.8	0.2	0.2	--	--	9.9	6.4
	5	0.0	0.1	0.5	0.7	1.0	0.8	0.2	0.2	--	--	7.3	4.2

^{1/} On Hubbersburg silt loam soil with irrigation during April-Nov. period since 1963.

^{2/} On Morrison sandy loam soil with irrigation year round since No. 23, 1965.

sites in the chapter by Kardos and Sopper (1973). The nitrate data indicate that anaerobic conditions occur in the Hublersburg soil but not in the Morrison. As a consequence of the reducing conditions, oxides of manganese would be expected to become more soluble and interact with the exchange sites in the Hublersburg soil. On the other hand, the large decrease in exchangeable hydrogen in the Morrison soil combined with its strongly aerobic character should result in a decreased solubility of the oxides of manganese.

Kardos and Sopper (1973) reported that chloride concentration in the soil water was five-fold higher in the wastewater treated corn rotation area than in the control area. Since the Hublersburg soil has been shown to contain substantial amounts of free iron oxides (Hook, Kardos and Sopper, 1973) and such oxides have a substantial capacity for adsorbing anions, soil samples were extracted with hot, $0.05N \cdot NH_4O_3$ to determine the adsorbed chloride content. The adsorbed chloride increased with soil depth and the differences between the wastewater treatments were not significant in the first foot but chloride in the 2-inch treatment at the second and third foot was significantly greater than in the control and chloride in the fourth and fifth foot was significantly different for all three wastewater treatments. The average chloride content of the 2-inch wastewater area at the fourth and fifth foot was approximately 40% greater than that of the control area. The relatively large values in the control area compared to values found in forested control areas by Kline (1967) are probably due to chlorides from the muriate of potash in the commercial fertilizer which was added annually to the corn rotation control area.

The amount of adsorbed chloride found in 1969 was surprisingly large and the total for the five-foot depth, 1216 pounds per acre, was approximately 3.8 times as much as was added in the 2-inch wastewater treatment that year. Soils with less free iron oxides like the Morrison sandy loam which contains only one-half to one-third as much as the Hublersburg silt loam (Hook, Kardos and Sopper, 1973), would not retain as much chloride.

Other soil constituents which were examined were ammonium acetate extractable boron which increased as wastewater treatment level increased but the slight differences were not significant. Kjeldahl nitrogen and organic matter were erratically variable from year to year and differences were not significant.

In conclusion, changes in soil chemical quality have occurred as a result of the wastewater treatments but these changes have been relatively small and do not appear to pose any problems for the future.

ACKNOWLEDGMENT

Research reported here is part of the program of the Waste Water Renovation and Conservation Project of the Institute for Research on Land and Water Resources, and Hatch Projects No. 1481 and 1809 of the Agricultural Experiment Station, The Pennsylvania State University, University Park, Pennsylvania. Portions of this research were supported by funds from Demonstration Project Grant WPD 95-01 received initially from the Division of Water Supply and Pollution Control of the Department of Health, Education, and Welfare and subsequently from the Federal Water Pollution Control Administration, Department of the Interior. Partial support was also provided by the Office of Water Resources Research, USDI, as authorized under the Water Resources Research Act of 1964, Public Law 88-379 and by the Pinchot Institute for Environmental Forestry Research, Forest Service, USDA.

REFERENCES

- Edwards, Ivor K. The Renovation of Sewage Plant Effluent by the Soil and by Agronomic Crops. Ph.D. Thesis in Agronomy. 174 pp. Sept. 1968. The Pennsylvania State University.
- Henry, C. D., R. E. Moldenhauer, L. E. Engelbert, and E. Truog, 1954. Sewage effluent disposal through crop irrigation. *Sewage and Industrial Wastes* 26: 123-133.
- Hook, James E., L. T. Kardos and W. E. Sopper. 1973. Effect of Land Disposal of Wastewaters on Soil Phosphorus Relations. Proc. Symp. on Recycling Treated Municipal Wastewater and Sludge through Forest and Cropland. The Pennsylvania State University Press.
- Kardos, Louis T. and W. E. Sopper. 1973. Renovation of Municipal Wastewater through Land Disposal by Spray Irrigation. Proc. Symp. on Recycling Treated Municipal Wastewater and Sludge through Forest and Cropland. The Pennsylvania State University Press.
- Kline, Glenn N. Effect of Sewage Effluent on the Chemical Properties of the Soil in a Hardwood Stand, Red Pine Plantation and Open Old Field. M.Sc. Thesis in Forestry. 78 pp. Sept. 1967. The Pennsylvania State University.
- Sanitary Engineering Research Laboratory. 1955. An Investigation of Sewage Spreading on Five California Soils. Tech. Bul. 12. I.E.R. Series 37. Sanitary Engineering Laboratory, University of California, Berkeley, California.
- United States Salinity Laboratory Staff. 1954. Diagnosis and Improvement of Saline and Alkali Soils. U.S. Dept. of Agric., Agriculture Handbook No. 60. L. A. Richards, Editor.

FACTORS AFFECTING NITRIFICATION-DENITRIFICATION IN SOILS

F. E. Broadbent
Department of Soils and Plant Nutrition
University of California, Davis

326D

The oxidation of ammonium to nitrate in soils by microorganisms has been the subject of a great many research efforts dating back to the beginning of scientific agriculture. The nature of the nitrifying bacteria and their responses to a broad range of environmental conditions have been amply documented in the literature. It is not my intention to review this literature in any detail here today. Suffice it to say that nitrifying bacteria are present in almost all soils and that they are active over a wide range of moisture and temperature conditions (Frederick, 1956; Justice and Smith, 1962; Reichman et al, 1966; Robinson, 1957; Tyler, et al, 1959).

Although the nitrifiers are obligate aerobes they are able to function in oxygen concentrations substantially lower than that of the atmosphere. For example, Amer and Bartholomew (1) measured nitrification rates in a soil in relation to the oxygen concentration of the ambient atmosphere. As expected, the rate of nitrate production decreased with decreasing oxygen concentration. About half as much nitrification occurred at 2.1% oxygen as at 20%. Below 0.4% oxygen nitrification essentially ceased and at 0.2% there was a net loss of nitrate indicating that denitrification was taking place. The activities of nitrifying bacteria may also be curtailed by low pH which frequently may result from acid produced by the nitrifiers themselves.

Although a number of heterotrophic microorganisms have been found capable of oxidizing ammonium to nitrite and a few to nitrate, present evidence indicates that their activity is minimal in relation to that of the autotrophic nitrifying bacteria. It can be said for all practical purposes that nitrification does not require organic materials as a source of energy.

Denitrification, also recognized quite early as a microbial process, has not been studied quite so intensively as has nitrification, but recent concern over the presence of nitrate in waters has revived interest in it. The capacity of denitrifying bacteria to convert a potential pollutant to an innocuous gas which is a normal atmospheric constituent suggest denitrification as an ideal decontamination process. Whereas even such an eminent soil microbiologist as Waksman (1932) once dismissed denitrification

as "of no economic significance in well aerated not too moist soils in the presence of moderate amounts of organic matter or nitrate", today this process is being studied and utilized by people representing a range of interest varying all the way from engineering to medicine.

CONDITIONS FOR NITRIFICATION-DENITRIFICATION

Whereas nitrifying bacteria are autotrophic, denitrifiers are heterotrophic. Nitrifiers are obligate aerobes, denitrifiers are facultative anaerobes. Denitrification cannot take place in the presence of any significant concentration of oxygen. Nitrification is an energy yielding process, denitrification an energy requiring one. It would seem then that by virtue of their contrasting environmental requirements nitrification and denitrification would be mutually exclusive processes. My remarks here today will be concerned primarily with variations on the theme that in fact nitrification and denitrification can and do occur simultaneously in the same soil lake, pond or stream, often in locations which are physically separated by only very short distances.

The classical case is the rice paddy. Flooded soils are known to develop two distinct layers after submergence; a surface oxidizing layer only a few millimeters thick and a deep subsurface layer which is in a chemically reduced state (Pearsall, 1950; Shiori and Tanada, 1954). In the shallow surface layer of soil and in the flood water above the soil nitrification readily proceeds because oxygen is present. However, if nitrate so formed diffuses into the reduced layer, it is utilized as an electron acceptor and nitrogen gas is released. Indirect evidence for this sequence of events is provided by the data of Table 1 which shows that when tagged ammonium sulfate was added to a flooded soil nitrogen was lost if the surface of the flood water was in contact with the atmosphere. However, when oxygen was excluded by substitution of pure nitrogen gas for air in contact with the flood water surface so as to prevent nitrification no loss of nitrogen from the system occurred.

More direct evidence is given in Table 2, which shows that nitrogen gas evolved from a flooded soil in an oxygen atmosphere was derived from added ammonium sulfate. In a krypton atmosphere virtually no evolution of nitrogen was observed, because nitrate was not produced.

Greenland (1962) suggested the possibility of simultaneous nitrification and denitrification in Ghanaian soils several years ago. In many situations both in soils and waters there exists the possibility of oxygen depleted layers or microenvironments

Table 1. Recovery of Tagged N from Flooded Maahas Clay Incubated in Air and in N₂ after Addition of 100 ppm N as (NH₄)₂SO₄^{1/}

Incubation time	NH ₄ -N	Organic N	Total
days	ppm	ppm	ppm
	<u>Incubated in Air</u>		
0	97.0	1.1	98.1
14	76.2	15.3	91.5
30	47.8	18.0	65.8
	<u>Incubated in N₂</u>		
0	97.0	1.1	98.1
14	68.9	31.8	100.1
30	41.5	58.2	99.7

^{1/} From Broadbent and Tusneem (1971)

Table 2. Tagged N in Various Fractions in Flooded Sacramento Clay 24 Days after Addition of 100 ppm Tagged N as (NH₄)₂SO₄¹

Atmosphere	NH ₄ -N	NO ₃ -N	Organic + clay-fixed N	N ₂ gas	Total
	ppm	ppm	ppm	ppm	ppm
Oxygen	4.9	8.1	68.4	9.3	90.7
Krypton	13.3	0.2	83.9	0.2	97.6

¹ From Broadbent and Tusneem (1971)

where the rate of oxygen utilization exceeds the rate of diffusion of oxygen to the site. For example, the vertical distribution of oxygen in bodies of water frequently reflects the transition from an aerated surface layer to anoxic conditions at some depth below. Ammonia-containing water flowing into a lake, pond or artificial lagoon might undergo nitrification near the surface and the nitrate so produced could become subjected to denitrification through

diffusion into anoxic zones, provided the organic matter content were sufficiently high to support the growth of denitrifying bacteria.

Meek et al. (1969) measured nitrate concentrations and E_h values as a function of depth in a cotton field of high water table in the Imperial Valley, California, after application of 280 kg anhydrous ammonia per hectare. There was a reduction in nitrate concentration and a drop in E_h as the soil solution approached the water table. In another study with soil columns with controlled water tables Meek et al. (1969) found that disappearance of nitrate near the water table was associated with decreases in redox potential, oxygen content of the soil solution, and oxygen levels in the soil atmosphere. They concluded that the quantity of soluble carbon carried down to the saturated zone was also important.

EXPERIMENTAL EVIDENCE OF NITRIFICATION-DENITRIFICATION IN SOILS

Denitrification in Soils of High Water Table

Much of the evidence of nitrification-denitrification and related nitrogen transformations under field conditions has been reviewed recently by Viets and Hageman (1971) who concluded that much unwanted nitrate can be eliminated by managed denitrification in treatment plants and on land that receives large amounts of animal waste. Some of the difficulties attendant to obtaining good quantitative estimates of the extent of denitrification under field conditions are illustrated in an experiment in California with Tulare sandy loam, a soil with a water table at about 4 ft depth. Manure waste from a large dairy, after dilution with a considerable volume of wash water, was passed through a separator to remove solids, which were recycled by using them as bedding for the cows. The liquid effluent containing 50 to 120 ppm soluble N, almost entirely in the ammonium form, was spread on half-acre field plots by three methods of flooding. Analyses of the distribution of ammonium and nitrate nitrogen in quadruplicate plots showed that nitrification was rapid, since the values for $\text{NH}_4\text{-N}$ were very low, below 3 ppm in most instances and never exceeding 5 ppm. Nitrate-N values suggest denitrification below the surface layer, since there was a tendency for nitrate concentration to decrease with depth. However, this distribution can also be explained on the basis of concentration of adsorbed ammonium from the dairy effluent near the soil surface. Another difficulty is that field data of this kind are very variable. For example, the coefficient of variation of the data is 75%. Of particular interest are the low nitrate levels in the intermittently flooded plots, which received more nitrogen than the single flooded plots. The alternation between flooded and

unflooded conditions is particularly favorable to the nitrification-denitrification sequence. For example, three rice soils at the International Rice Research Institute kept in flood fallow lost no nitrogen with no mid-season drying, but lost 120 to 320 kg N/hectare with mid-season drying (Greenland, 1962).

In a laboratory experiment a 1-meter column of Tulare sandy loam was set up to maintain the water table at 70 cm depth while collecting the effluent from the 100 cm depth. Dairy waste containing 65 ppm N as tagged ammonium was applied in amounts equivalent to 156 kg N per hectare (139 lbs N/acre). Subsequently 0.001 M CaCl_2 solution was applied to the column at 5 to 7 day intervals in increments of 12 cm and the column effluent analyzed for soluble nitrogen containing the tracer. A total of 67 cm of water passed through the column. Untagged nitrate initially present in the soil leached out quickly before anaerobic conditions were established. Some tagged nitrate came through as a small pulse near the end of the leaching period. Tagged nitrogen in the leachate was 1.97% of the N added. Analysis of residual N in the soil at the conclusion of the experiment indicated 15.4% of the applied nitrogen remained, making an overall recovery of only 17.4%. Presumably the remainder was denitrified.

A similar experiment with the very sandy subsoil found below the water table in this same area was conducted to evaluate the extent of denitrification in an environment low in available carbon. Total organic C in the subsoil is 0.49%. Tagged nitrate equivalent to 80 kg/hectare (71 lbs/acre) was applied to the column, which was then leached with 0.001 M CaCl_2 intermittently over a period of six weeks until a total of 45 cm effluent had been collected. In this case 6.33 mg or 41% of the tagged nitrate passed through the column. Residual tracer nitrogen in the column was not determined, but was undoubtedly less than the 15.4% found in the experiment cited previously because of the very coarse texture of the subsoil.

Denitrification in Unsaturated Soils

Denitrification in saturated soil is, of course, to be expected. A question of perhaps greater interest in whether denitrification occurs to a significant extent in unsaturated soil profiles. One can readily visualize conditions favorable for denitrification in the micropores of an unsaturated soil, or even in the macropores at depths where the diffusion of oxygen is too slow to meet the oxygen demand. Again, the use of tracer sources of nitrogen provides an answer to the question.

In a preliminary experiment tagged KNO_3 was placed at the surface of a 1-meter column of Yolo fine sandy loam. The column was

then leached intermittently with saturated CaSO_4 solution over a two-week period until the effluent contained no more tagged nitrate. Saturation occurred only at the soil-air interface at the bottom of the column. The elution curves indicated that 12.3 mg or 45.6% of the tagged nitrate-N passed through the column. The gradual increase in untagged N eluted from the column can be attributed to mineralization of organic N. A more detailed accounting of nitrification-denitrification in the Yolo soil was obtained in a larger column containing 6 ft of soil and equipped with porous ceramic probes at 1 ft intervals which allowed withdrawal of a small volume of soil solution when desired. The soil was initially brought to field moisture capacity, then tagged $(\text{NH}_4)_2\text{SO}_4$ equivalent to 100 kb N/hectare (89 lbs/acre) was applied at a depth of 2 inches. Thereafter 3 inches (7.5 cm) of water was applied at bi-weekly intervals over a period of 28 weeks. One day after each water application soil solution samples were taken at each depth and analyzed. After 8 weeks when effluent appeared at the bottom of the column the leachate was regularly collected and analyzed. No significant concentration of nitrate penetrated below 5 ft and at no time did the column effluent contain more than a trace of nitrate, either tagged or untagged. An accounting of the tracer N (Table 3) indicates that the soluble nitrogen which disappeared was largely denitrified.

Table 3. Balance Sheet of Tagged Nitrogen Added as $(\text{NH}_4)_2\text{SO}_4$ to a Free-Draining Column of Yolo Fine Sandy Loam

	N	Percent of total
	mg	%
Added initially	182.0	100
In column leachate	0.0	0
Removed in samples	10.7	5.9
Residual NH_4^+ and NO_3^-	2.3	1.3
In soil organic matter	12.8	7.0
Not accounted for (denitrified)	156.2	85.8

A striking contrast between a partly saturated and an unsaturated column was observed with Venice peat, a very permeable soil containing about 40% organic carbon. One column was free-draining; the other had the water table maintained at 70 cm from the surface. Elution curves indicated that 12.1 mg or 79% of the added nitrate-N

was recovered in the effluent from the unsaturated column, whereas 0.06 mg or 0.4% of the added nitrate passed through the column with a 30 cm saturated layer. It may be observed that only about half as much untagged N passed through the latter column as the unsaturated one and that most of this amount was leached early in the experiment before anaerobic conditions could be established. Denitrification of untagged N undoubtedly occurred.

Direct Evidence of Denitrification of Unsaturated Soil

A shortcoming of all the experiments previously cited is that none of them provides direct evidence of denitrification. Disappearance of tracer nitrogen from a soil is convincing evidence of loss, but the evidence that denitrification is responsible is only presumptive. It would be desirable to provide a complete accounting of all forms of nitrogen by direct analysis, but the experimental difficulties involved in trapping and analyzing gaseous forms of nitrogen without drastic alteration of the soil environment are formidable. A major problem is that of detecting a relatively small quantity of N_2 resulting from nitrate reduction in a vast sea of atmospheric N_2 .

Direct evidence that some N_2 in the soil pore space is indeed the end product of the nitrification-denitrification sequence is given in Tables 4 and 5. These give the composition of soil gases and of the soil solution at various depths in a column of Hanford sandy loam which was continuously leached with a solution of tagged NH_4Cl containing 50 ppm N. The column was designed to permit control of the hydraulic head at all depths, which in practice varied from -3 to -13 cm of water at various depths.

The data of Table 4 show depletion of oxygen and increase of CO_2 and N_2 with increasing depth. Nitrification occurred readily, but may have been confined primarily to the top 28 cm since NH_4^+ in soil solution is very low below that depth. The presence of absorbed NH_4^+ at lower depths is still a possibility. Decreasing nitrate concentration with depth below 28 cm strongly suggests denitrification. Unequivocal evidence is provided by the detection of ^{15}N -tagged nitrogen gas at all depths below 8 cm.

Table 4. Composition of the Soil Atmosphere at Various Depths in a Column of Hanford Sandy Loam Continuously Leached with a Solution Containing 50 ppm N as Tagged NH_4Cl on Day 46.

Depth	Air-filled pores	CO_2	O_2	N_2
cm	%	%	%	%
8	10.7	0.77	17.3	81.9
28	8.1	1.65	8.64	89.7
48	5.5	2.05	2.30	95.6
68	3.4	3.03	1.62	95.3
88	10.3	3.18	2.21	94.6

Table 5. Nitrate-N and Nitrogen Gas Derived from Tagged NH_4Cl in a Column of Hanford Sandy Loam on Day 46.

Depth	$\text{NH}_4^+\text{-N}$	$\text{NO}_3^-\text{-N}$	$\text{NO}_3^-\text{-N}$ tagged	N_2 tagged
cm	ppm	ppm	%	%
8	16.3	14.2	79	0.1
28	3.7	38.9	87	4.10
48	0.5	29.1	91	7.46
68	0.0	23.2	89	8.21
88	0.0	17.2	85	8.30

PRACTICAL SIGNIFICANCE OF NITRIFICATION DENITRIFICATION

Although definitive field data are still scarce, it seems clear that application of water containing nitrate or a potential source of nitrate such as organic N or ammonium salts to the surface of a soil will probably not result in that nitrate moving unimpeded to the water table, having been diminished only by those quantities which are intercepted by plant roots. Indeed, the well known poor uptake efficiency of fertilizer nitrogen by crops, usually not much better than 50% may be due in part to the stimulating effect of plant roots on denitrification. Woldendorp *et al.* (1966) noted

that 15-20% of the nitrate passing through the rhizosphere may be denitrified. A recent report by Kolenbrander (1972) of nitrate and chloride concentrations in well water at a number of pumping stations in Holland over a 45-year period provides some very interesting evidence of widespread denitrification. The wells are located in agricultural areas where the annual input of fertilizers has increased substantially over the years. When the concentrations of nitrate and chloride in the wells are plotted against average annual fertilizer applications it was found that the proportion of chloride which ended up in the groundwater was approximately 5 times the proportion of nitrogen. He concluded that low concentrations of nitrate in deep-level groundwater point to the likelihood of considerable further denitrification during infiltration of drainage water into deeper strata.

In another recent study Pratt et al. (1972) determined nitrate concentrations in saturation extracts of soil in 3-meter profiles of a long term fertility trial with citrus. Assuming no net immobilization or mineralization and that the amount of N denitrified was equal to the total N input minus that found in the soil minus removal in the fruit, they found that up to 43% of the total nitrogen input was lost.

Any precise attempt to follow the course of nitrification-denitrification on a field scale requires a method of discriminating between input nitrogen from fertilizers, wastewater, or other sources, and that which results from decomposition of soil organic matter, which typically contains 5 to 6% N. This can be accomplished by use of ^{15}N tagged materials, as illustrated in some of the soil column data presented here, but the cost of materials enriched with this isotope has been prohibitive for field work. Recently the Atomic Energy Commission's Los Alamos Scientific Laboratory has begun producing ^{15}N -depleted material which can also be used as a nitrogen tracer in natural systems, with the limitation that the amount of dilution which can be tolerated is substantially less than is feasible with highly enriched ^{15}N compounds. However, essentially pure ^{14}N compounds are expected to become available in ton quantities at costs which permit their utilization in field trials. It is expected that experiments with isotopically tagged materials in the natural environment, some of which are already underway, will permit a complete accounting of the fate of nitrogen applied to soils and will provide better quantitative measures of nitrification-denitrification and related nitrogen transformations under a variety of environmental conditions.

REFERENCES

- Amer, F. M. and W. V. Bartholomew. 1951. Influence of oxygen concentration in soil air on nitrification. *Soil Sci.* 71, 215-219.
- Broadbent, F. E. and M. E. Tusneem. 1971. Losses of nitrogen from some flooded soils in tracer experiments. *Soil Sci. Soc. Amer. Proc.* 35, 922-926.
- Frederick, L. R. 1956. The formation of nitrate from ammonium nitrogen in soils I. Effect of temperature. *Soil Sci. Soc. Amer. Proc.* 20, 496-500.
- Greenland, D. J. 1962. Denitrification in some tropical soils. *Agric. Sci.* 58, 227-233.
- International Rice Research Institute Annual Report 1969. p. 139-140.
- Justice, J. K. and R. L. Smith. 1962. Nitrification of ammonium sulfate in a calcareous soil as influenced by combination of moisture, temperature and levels of nitrogen. *Soil Sci. Soc. Amer. Proc.* 26, 246-250.
- Kolenbrander, G. J. 1972. Does leaching of fertilizers affect the quality of groundwater at the waterworks? *Stikstof* 15, 8-12.
- Meek, B. D., Grass, L. B., and A. J. MacKenzie. 1969. Applied nitrogen losses in relation to oxygen status of soils. *Soil Sci. Soc. Amer. Proc.* 33, 575-578.
- Meek, B. D., Grass, L. B., Willardson, L. S. and A. J. MacKenzie. 1970. Nitrate transformations in a column with controlled water table. *Soil Sci. Soc. Amer. Proc.* 34, 235-239.
- Pearsall, W. H. 1950. The investigation of wet soils and its agricultural implications. *Emp. Jour. Expt. Agric.* 18 (72), 289-298.
- Pratt, P. F., Jones, W. W. and V. E. Hunsaker. 1972. Nitrate in deep soil profiles in relation to fertilizer rates and leaching volume. *Jour. Environ. Quality* 1, 97-102.
- Reichman, G. A., Grunes, D. L. and F. G. Viets, Jr. 1966. Effect of soil moisture on ammonification and nitrification in two northern plains soils. *Soil Sci. Soc. Amer. Proc.* 30, 363-366.
- Robinson, J. B. D. 1957. The critical relationship between soil moisture content in the region of the wilting point and mineralization of soil nitrogen. *Jour. Agric. Sci.* 49, 100-105.
- Shiori, M., and T. Tanada. 1954. The chemistry of paddy soils in Japan. *Min. Agric. and Forestry. Japanese Gov't. Tokyo.* 45 p.
- Tyler, K. B., Broadbent, F. E. and G. N. Hill. 1959. Low temperature effects on nitrification in four California soils. *Soil Sci.* 87, 123-129.
- Viets, F. G., Jr. and R. H. Hageman. 1971. Factors affecting the accumulation of nitrate in soil, water, and plants. *Agric. Handbook No. 43, ARS, USDA.*

- Waksman, S. A. 1932. Principles of soil microbiology, ed. 2.
Williams and Wilkins Co., Baltimore.
- Woldendorp, J. W., Dilz, K. and G. J. Kolenbrander. 1966. The fate
of fertilizer nitrogen on permanent grassland soils. Proc.
1st Gen. Mtg. Europ. Grassland Fed. 1965, 53-76.

DISCUSSION

- Hanson: Was the 6 ft column of Hanford sandy loam a mixed soil
with organic matter all the way through the column
supplying an energy source for the bacteria?
- Broadbent: Yes. It had organic matter all the way down. This is
extremely deep soil. The organic matter tails off to
about 30% of the surface layer at around 6 ft.
- Hanson: Did you attempt to simulate the field soil in terms of
the profile?
- Broadbent: Yes. This was an attempted simulation of field
distribution.
- Overman: Obviously in turning the nitrogen cycle, you had to turn
the carbon cycle also. Do you feel that decomposing
organic matter in the upper profile will supply carbon
several feet down near the water table?
- Broadbent: This, of course, depends on a great many soil properties.
But, in general, I would say yes.

BIOTOXIC ELEMENTS IN SOILS

T. D. Hinesly and R. L. Jones
Department of Agronomy
University of Illinois

128E

Application of stabilized municipal waste treatment plant residues on agricultural lands is the most economically viable solution to a growing solids disposal problem. Yet, it is a small problem from the standpoint of its utilization by agriculture. If all municipal wastewaters generated in the continental United States were given secondary treatment and the resulting solids stabilized for utilization as a fertilizer and soil amendment, about 10 to 12 million dry tons of solids would be available each year. The utilization of the solids in amounts just sufficient to meet the needs of non-leguminous crops for supplemental nitrogen would require an annual application of about 10 dry tons per acre. Thus, not much over one million acres of land would be required at one time to utilize the total continental United States production of sludge solids. Only enough sludge solids would be available to treat slightly more than 0.2 percent of the 465 million acres of crop land or slightly less than 0.06 percent of the total 1,904 million acres contained in the continental United States. However, because of its potential as a source of sorely needed stable organic matter, municipal sludge exhibits its greatest value as a resource when used as an amendment for the reclamation of surface-mined lands. Since over 0.5 million acres of land strip-mined for coal already exist in various states of devastation while another 0.5 million acres have been or will be stripped during the 20-year period from 1964 to 1984, there is no scarcity of land which needs the nutrients and organic matter supplied in sludge. If properly used in the reclamation of such lands, a discussion of the accumulation of biotoxic elements in soils as a result of sludge recycling would be purely academic. For example, unusual concentration levels of chemical elements are released by weathering of shales in strip-mine spoil banks where, in the absence of adequate contents of organic matter, problems already exist which can be ameliorated with applications of stabilized municipal sludges.

It is recognized that the solids from many small wastewater treatment plants will probably continue to be recycled to crop land. Also, the number of proponents for using land for the disposal or renovation of partially treated wastewater appears to be growing. Therefore, it is essential to review what is known with regard to the accumulation of biotoxic elements in soils because in either case the growing of crops will be part of the system. Nearly all chemical elements, whether classed as essential or nonessential for the life

processes of plants and/or animals can be considered as biotoxic at some concentration levels. It is necessary to attempt to identify those chemical elements which tend to be ubiquitously present in relatively high concentration in municipal wastewaters and sludges and might accumulate in soils in forms available to crop plants at concentrations which may be injurious to plants or to animals consuming the produce.

MICROBIAL HAZARDS IN DISPOSING OF WASTEWATER ON SOIL

D. H. Foster and R. S. Engelbrecht
Department of Civil Engineering
University of Illinois

327D

Those who are considering land disposal of wastewater and sludges are faced with a peculiar dilemma. On the one hand, they may be applauded for recovering a resource and applying it in useful ways - to irrigate crops and restore despoiled areas such as strip mines. On the other hand, they are damned for spreading a host of pollutants including pathogenic organisms around in the environment. It is the purpose of this paper to explore the public health dangers that may arise from the ultimate disposal of wastes on land and to assess how well founded is the public apprehension concerning health hazards. The paper is not intended to be an alarming account of hypothetical hazards designed to downgrade the potential benefits to be derived from land application of wastewater and sludges. Rather, it is felt that engineers, agriculturists, and governmental officials should be provided with the type of information that will allow a rational, unemotional, and realistic assessment of the potential public health problems associated with the application of wastewater to land.

If one were to catalog the species of pathogens of man and animals which could be present in raw wastewater, the list would be a long one indeed. The tremendous variety of pathogens which may occur in domestic wastewater are derived principally from the feces and urine of infected human and animal hosts finding a direct route into the sewer. Surface runoff in areas provided with combined sewer systems will result in mammalian and avian pathogens reaching the wastewater collection system. The relative densities of the pathogens present in the wastewater will depend on a number of complex factors; and, therefore, it is difficult to say with any degree of assurance what the general pathogenic character of a particular wastewater will be. A thorough knowledge of the health of the population in a given situation, the possibility of "disease carrier" states in the population, an understanding of the sources contributing to the wastewater, and a knowledge of the relative ability of the pathogen to survive outside its host under a variety of environmental conditions is necessary. The literature can establish guidelines but each situation should be evaluated individually.

SURVIVAL OF PATHOGENS IN WASTEWATER

The principal pathogens present in wastewater may be divided into four convenient groups (Table 1). Far more is known about

Table 1. Major Groups of Wastewater Pathogens

-
1. Bacteria
 - Salmonella
 - Shigella
 - Mycobacterium
 2. Protozoa
 - Entamoeba Histolytica
 - Naegleria
 3. Helminth Parasites
 - Ascaris
 - Ancylostoma
 - Necator
 - Taenia
 - Trichuris
 4. Viruses
-

the occurrence of bacteria in wastewater than any of the other groups. Massive outbreaks of bacterial disease due to sewage polluted water have long been considered by many to be a thing of the past. Yet one has only to look back as recently as 1965 to find a water-borne bacterial epidemic of large proportions (Greenberg and Ongerth, 1966). Enough is not yet known to pinpoint the cause of sporadic isolated cases of typhoid and other potentially water-borne diseases so as to be able to definitely eliminate fecally polluted water from the list of possible causes. Use of wastewater for irrigation in the vicinity of isolated cases of enteric disease could lead to the suspicion in the public's mind that the two are somehow related, whether or not this is in fact the case. This subject should receive a closer examination.

Pathogenic Bacteria in Wastewater

Over 400 serotypes of the genus *Salmonella* have thus far been identified (Salle, 1967). Members of this group have frequently been isolated from feces, sewage, receiving waters and have even been

found in finished drinking water supplies (Beard, 1938; Browning and Mankin, 1966; Salle, 1967; and Seligman and Reitler, 1965). The most important member of this group is Salmonella typhosa, the agent of typhoid fever. Salmonella paratyphi and Salmonella schottmuel-leri, the agents of paratyphoid, may also be present in wastewater. Several other members of the Salmonella group have been pointed out as causative agents of gastrointestinal disturbances and, as a result, have been found in the feces of infected persons (Browning and Mankin, 1966; and Seligman and Reitler, 1965). The survival of Salmonellae in wastewater is dependent on temperature, the presence of organic matter and predation. Survival of typhoid organisms in wastewater for more than 35 days at room temperature have been reported by Wilson and Blair (1931), but generally survival for shorter periods of time have been noted. Heukelekian and Schulhoff (1935) found survival to be related to temperature with 99 percent destruction of typhoid organisms in wastewater occurring 6 to 10 days at both 22° and 37°C, while persistence increased to 17 days at 2°C. Green and Beard (1938) found survival to be up to 19 days and 27 days at indoor (20°C) and lower outdoor temperatures (7°C), respectively. A 99.9 percent kill occurred within 12 days under these conditions.

Others (Heukelekian and Schulhoff, 1935; and Rochaix, 1930) have demonstrated that organic matter and the presence of predator organisms can have a significant effect on the survival of Salmonella bacteria. When organic matter in the form of feces or urine were added to unpolluted water, growth of Salmonella was observed. In the presence of competitive organisms, survival of Salmonella is reduced. Survival in typical wastewater was reported in one study to be from a few hours to 11 days while survival was increased to as much as 20 months when competing organisms were removed from sewage by sterilization (Rochaix, 1930).

In summary, it may be stated that survival of typhoid and related organisms is relatively brief in wastewater. It should be noted, though, that constant inputs of these organisms is possible and it has been indicated that they were found in wastewater whenever they were sought (Kabler, 1959; and Northington et al, 1970).

Shigella organisms are one of the chief causes of bacillary dysentery but fortunately their presence in wastewater is considered rare (Wang et al, 1956). During a five-year study of irrigation water in Colorado, no Shigella organisms were isolated despite frequent isolations of Salmonella. When competitors were removed by sterilization, Shigella organisms inoculated into wastewater increased rapidly in numbers. However, in unsterilized stools they did not survive long (Wang et al, 1956). Shigella flexneri was implicated in a waterborne outbreak of gastroenteritis involving the irrigation of wastewater on pasture land (Browning and Mankin, 1966); and thus, while its survival may be limited outside the human body, the potential danger of Shigella in wastewater effluents applied

to soil must be recognized.

Mycobacteria have been extensively studied in wastewater since the time of the first findings of M. tuberculosis in feces around 1900. Tubercle bacilli appear to reach wastewater from feces containing swallowed sputum of infected individuals and from undisinfected sputum in sanatoria wastewater. Müller (1959) reported that raw wastewater contained 5 to 100 tubercle bacilli per liter compared to 100 times as many Salmonella organisms in the same volume. The tubercle organisms may be considered to be a regular component of urban wastewater, even without known sanatoria sources, since 90 percent of the raw wastewater samples examined were positive for tubercle bacilli. Of chief concern with these acid-fast bacilli is their ability to withstand a wide variety of environmental conditions for prolonged periods. Musehold (1900) exposed infected river water and wastewater to prevailing outdoor environmental conditions and was able to recover viable tubercle bacilli for up to 5 months. Others (Kroger and Trettin, 1950; Mannsfeld, 1937; and Rhines, 1935) have demonstrated survival times in sewage from 48 days up to 6-1/2 months. Greenberg and Kupka (1957) reviewed the findings of several survival studies and concluded that tubercle bacilli survived natural conditions in sewage and other contaminated materials for relatively long periods of time.

The majority of the studies carried out on Mycobacteria have focused on the presence of M. tuberculosis in sanatoria wastes. These studies may not provide a realistic picture of the danger of infection from contaminated waters. While M. tuberculosis is perhaps the most important potentially waterborne human pathogen of the genus Mycobacterium, other species of this group are capable of infecting man and animals. For example, granuloma may be caused by M. balnei which may be present in chlorinated water used for swimming pools (Cleere, 1960). Agents of bovine tuberculosis may be present in milk and slaughterhouse wastes (Greenberg and Kupka, 1957). On the other hand, sanatoria wastes would generally be expected to contain variable but higher concentrations of tubercle bacilli than general domestic wastes and, therefore, may overestimate the importance of this disease agent. The quantity of these organisms excreted by nonsanatoria patients is a matter of dispute. While nearly all fecal samples examined from sanatoria patients with pulmonary tuberculosis have been shown to contain viable M. tuberculosis (Jensen and Jensen, 1942), reports of these organisms in stools of apparently healthy individuals range from positive findings in under 2 percent of fecal specimens examined in one study to 21 percent in another (Laird et al, 1913; and Wilson and Rosenberger, 1909). Therefore, one could expect the tubercle organisms to be present in domestic wastewater but in quantities which may be expected to be highly variable.

Pathogenic Protozoa in Wastewater

Protozoans pathogenic to man and capable of transmission by the water route are Entamoeba histolytica, the agent of amoebic dysentery, and members of the Hartmannella-Naegleria group, a free-living amoeba causing meningo-encephalitis (Stringer and Kruse, 1970). The cyst stage in the life cycle of protozoa is the principal means of dissemination of dysentery since motile amoebae are fragile entities, dying quickly once they are outside the body (Noble and Noble, 1964). Cysts must be kept moist in order to remain viable for any extended period in the environment. Each mature cyst, upon excysting, is capable of producing four motile amoebae. However, laboratory studies have shown that as many as eight and possibly more cysts may be required to establish an active culture containing adult motile amoebae (Rudolfs et al, 1950). The efficiency of cysts in producing pathogenic adults does not, therefore, appear to be great. Kott and Kott (1967) found the sewage in Haifa, Israel to contain a maximum of nine E. histolytica cysts per liter with a median value of four per liter. Others have estimated that cysts may occur in contaminated waters at levels not likely to be greater than 5000 cysts per liter (Chang and Kabler, 1956). Since many cysts found in wastewater are derived from nonpathogenic protozoans, studies limited to E. histolytica cysts probably are more representative of health hazards from wastewater application on land than estimates of total cyst populations in wastewater. If a maximum of 20 cysts constitutes an infective dose (Rudolfs et al, 1950), the data of Kott (1967) would indicate that one infective dose may be contained in 5 liters of wastewater. The actual cyst concentration in wastewater will probably depend on the percentage of carriers in the population. Therefore, the agents of amoebic dysentery should be considered whenever cyst carrier rates in the population are 10 percent or higher (Northington et al, 1970).

Helminth Parasites in Wastewater

The ova of intestinal parasitic worms are excreted in the feces of infected individuals and may be spread by a wastewater-crop-human chain (Chang, 1965). Liebman (1965) reported ova of Ascaris lumbricoides, the pinworm Oxyuris vermicularis, the whipworm Trichuris trichiura, and the tapeworm Taenia saginata to be present in wastewater at high levels. Cram (1943) noted that hookworm eggs may also be present but others have rarely found the eggs of either Necator americanus or Ancylostoma duodenale in wastewater (Aiba and Sudo, 1965). Since hookworm larvae enter their host from fecally contaminated soil, it could be disseminated by wastewater application on soil. In moderate climates the human contribution of ova to wastewater would appear to be no greater than 10 percent but may reach 30 percent in subtropical regions such as the southern extremities of the United States (Liebman, 1965). The remainder of

the ova are of animal origin. Various authors have reported 59 to 80 worm eggs per liter of sewage (Aiba and Sudo, 1965; and Liebman, 1965). Translated into terms familiar to the engineer, this could mean millions and perhaps billions of eggs reaching a wastewater treatment facility daily. The eggs are generally resistant to environmental conditions, having a thick outer covering to protect them against dessication (Noble and Noble, 1964). Fifteen days at 29°C were required in one study to destroy 90 percent of *Ascaris* ova and they may survive 40°C for up to 60 days (Komiya and Kutsumi, 1965; and Liebman, 1965). In summary, it may be stated that a large quantity of a variety of ova from parasitic worms may be present in wastewater and that they possess a high degree of resistance to many environmental stresses.

Viruses in Wastewater

Over 100 distinct serotypes of viruses (Table 2) may be present in wastewater on a world-wide basis, regardless of climate (Grabow, 1968). They are the smallest of the wastewater pathogens, a fact which may have some bearing on their removal in wastewater treatment and soil percolation.

Table 2. Viruses in Wastewater

Group	No. of Types	Associated Diseases
<u>Enterovirus</u>		
Polio	3	Poliomyelitis
Coxsackie	30	Aseptic Meningitis, Myocarditis
Echo	31	Aseptic Meningitis, Enteritis
Reovirus	3	Enteritis
Adenovirus	31	Respiratory Illnesses
Infectious Hepatitis	Unknown	Jaundice
"Viral" Gastroenteritis	Unknown	Gastroenteritis

Of the enteroviruses, evidence of waterborne disease transmission exists only for poliovirus (Mosley, 1965). Of the other viruses listed, infectious hepatitis and gastroenteritis warrant special attention. The agents of both diseases have yet to be

isolated but both are thought to be viral in origin since they can be transmitted by bacteria-free filtrates of wastewater or fecal suspensions (Dolin et al, 1971; Gordon et al, 1947; and Neefe et al, 1947). The actual concentration of these agents in wastewater is, of course, unknown but they appear to be relatively prevalent if one can use their disease incidence as a yardstick. From 1946 to 1960 there were 142 reported waterborne outbreaks of gastroenteritis and 23 infectious hepatitis epidemics (Weibel et al, 1964). Together they involved nearly 19,000 disease cases. These are only the reported epidemics and it is likely that many more unreported waterborne epidemics and sporadic cases occurred. Furthermore, disease is only a clinical manifestation of establishment of a parasitic infection. It has been estimated that far more viral infections occur than actual disease incidences (Mosley, 1965). Clearly then, a large quantity of virus may be present in the wastewater, and surviving the multiple treatment and natural barriers in their path to finally result in disease. The initial concentration in wastewater must be high for the chance contact of man and virus to have any chance of successful infection. Viruses as a group are generally more resistant to environmental stresses than many of the bacteria. For example, Clarke et al (1964) compared the survival of viruses in wastewater to three enteric bacteria. Survival of virus in wastewater at 20°C was longer in all cases than the bacteria studied and ranged from 23 to 41 days. The time required for 99.9 percent reduction of viral numbers reportedly ranges from 2 to 100 days for various members of the enteric virus group (Akin et al, 1971). Virus survival was inversely related to temperature. Other factors, such as pH value, which could conceivably affect virus survival have not been thoroughly investigated.

It has been estimated that the virus concentration of raw wastewater is approximately 7000 units per liter (Clarke, et al, 1964). Kelly and Sanderson (1960), using a semiquantitative technique for virus recovery, reported the virus density in raw wastewater to be 4000 units per liter during the warmer months of the year and 200 units during the colder months. Shuval (1969) recently found the virus density in raw wastewater in five Israeli cities to average 1050 virus units per liter and ranged from as few as 5 to as many as 11,184 units per liter. Lund et al (1969) observed maximum values of 100,000 virus units per liter. One problem in interpreting these various findings is that viruses are rather fastidious in their growth requirements. The techniques for sample concentration, the host cell system, and the type of culture technique used will all be selective with respect to the viruses enumerated. No universal procedure or system is presently available for cultivation of all viruses. It is likely, therefore, that many of the investigations of virus density in wastewater have not included all viruses present due to the selectivity of techniques employed. In addition, many of the previous studies involved

centrifugation or filtration of samples to remove particulates associated with the wastewater before enumerating the viruses present (Lund et al, 1969). Lund's work did not involve these forms of sample treatment and the higher values for virus density obtained indicate that other workers may have lost many viruses in the sediment they removed. If Lund's values for the virus density of raw wastewater are correct, it is readily apparent that tremendous quantities of virus arrive at wastewater treatment plants daily.

REMOVAL OF PATHOGENS IN WASTEWATER TREATMENT PROCESSES

In order to assess the importance of pathogens in land application of wastewater and sludges, one must not only know how many are present in the raw wastewater or in the settled sludges, but also the efficiency of various treatment processes in removing or destroying them. The degree of treatment and types of unit operations used in treating wastewater for application on soil may vary and, therefore, the approach adopted here will be to discuss each treatment operation or process separately. It should be noted that much of the information available in the literature on the efficiency of various treatment steps is derived from laboratory studies. Where available data exists comparison of laboratory and field data would suggest that laboratory research often overestimates the efficiency that can be obtained in the field. Therefore, some mental adjustment of laboratory data to be presented may be appropriate.

Primary Sedimentation

Primary treatment of wastewater appears to exhibit a variable efficiency in removing pathogens depending in part on the type of pathogen studied (Table 3). Bloom et al (1958) isolated *Salmonellae* from six of seven different primary effluent samples. The raw sludge also contained members of this genus with 19 of 20 samples being positive for *Salmonella* organisms. McKinney et al (1958) were unable to isolate *S. typhosa* from raw wastewater sludge. Müller (1959) found tubercle bacilli to be reduced by 50 percent by primary sedimentation while Kelly et al (1955) found a 57 percent reduction. Reductions of tubercle bacilli from 48 to 54 percent during settling of raw sewage have been reported by others (Heukelekian and Albanese, 1956). Considerable quantities of the *Mycobacterium* may occur in the sludge produced in primary sedimentation. Pramer et al (1950) demonstrated 67-fold concentration of tubercle bacilli in raw sludge as compared to that in the influent wastewater. These studies would indicate that bacterial pathogens are ineffectively removed from wastewater by primary

treatment and, furthermore, the process produces sludges which constitute a hazard without further treatment.

Table 3. Removal of Pathogens by Primary Treatment

Pathogen	Reported Removal Efficiency
<u>Salmonella</u>	151/ ¹
<u>Mycobacterium</u>	48 to 57
Amoebic Cysts	No. reduction in 3 hours
Helminth Ova	72 to 98
Virus	3 to extensive removal

1/ Based on Frequency of Isolation

Removal of amoebic cysts by primary treatment has not been extensively studied. Cram (1943) observed that 3 hours settling in laboratory units had little effect on the density of E. histolytica cysts in the supernatant. Eggs of parasitic worms were removed more effectively. Cram's work showed that some hookworm eggs still remained in the upper 1/3 of a laboratory settling basin after 2-1/2 hours sedimentation. Ascaris ova, on the other hand, appeared to settle within 15 minutes with the eggs concentrated in the sludge. Taenia saginata ova have been reportedly removed to the extent of 98 percent within 2 hours (Newton et al, 1949). Others have, on the other hand, indicated removals as low as 72 percent during sedimentation (Greenberg and Dean, 1958). It may be concluded that primary sedimentation for 2-1/2 hours or more cannot be depended upon to produce effluents free of parasitic worm ova or amoebic cysts. Additionally, primary sludges may contain significant quantities of helminth ova (Aiba and Sudo, 1965).

The majority of the studies involving the removal of viruses by primary treatment would indicate that few viruses are removed during this operation. Poliovirus 1 seeded into raw wastewater was removed only to the extent of 3 percent following 3 hours of settling (Clarke et al, 1961). In another study isolations of virus from primary effluent were more frequent compared to isolations in the primary influent (Mack et al, 1962). On the other hand, Bush and Isherwood (1966) suggested that the survival of mice inoculated with primary effluent indicated extensive removal in the primary clarifier since large quantities of virus were known to be present in the influent. Laboratory studies where wastewater has been seeded with virus, such as that of Clarke et al (1961), may

not reflect removal of viruses that would be associated with sewage solids in natural systems. Many studies of field size units have involved filtering out solids from influent samples prior to assaying and would, therefore, not reflect virus particles associated with wastewater solids. Lund's (1969) work demonstrated conclusively that many virus particles are associated with wastewater solids. Indeed, the increase in virus seen in a primary settling tank, as in the study cited above, may reflect the release of virus from raw sludge. It may well be then that removal of virus in primary treatment has been underestimated.

Secondary Treatment

Biological treatment appears to be quite efficient in removing wastewater pathogens but does not produce an effluent which is pathogen free (Table 4). Beard (1938) reported that S. typhosa

Table 4. Removal of Pathogens by Secondary Treatment

Pathogen Group	Reported Removal Efficiency	
	Activated Sludge	Trickling Filters
<u>Salmonella</u>	96 to 99	84 to 99.9
<u>Mycobacterium</u>	Slight to 87	66 to 99
Amoebic Cysts	No Apparent Removal	11 to 99.9
Helminth Ova	No Apparent Removal	62 to 76
Virus	76 to 99	0 to 84

was reduced in density by 96 percent in 6 hours and 99 percent in 8 hours aeration in activated sludge units. When sterile sewage was inoculated with Salmonella and aerated an increase in density was noted indicating that biological action and not aeration per se was responsible for the reductions seen in normal waste treatment (Greenberg and Beard, 1938). M. tuberculosis was affected little by aeration for 24 hours (Pramer et al, 1950). Others have reported similar failure of the activated sludge treatment to completely remove tubercle bacilli even when the aerobic bacterial content had been reduced to 0.2 percent of its original numbers (Jensen and Jensen, 1942). Heukelekian and Albanese (1956) observed an 87 percent reduction in tubercle bacilli following 6 hours aeration

in activated sludge units. Increasing the aeration period to 24 hours affected only another 1 percent removal. The bacilli were rapidly transferred to the sludge phase apparently by adsorption to the settling particles resulting in a sludge tubercle bacilli concentration at the end of 6 hours that was 13 times greater than the supernatant liquor. Therefore, the sludge should also be considered a potential hazard and could infect soil with tubercle bacilli if applied to land without further treatment.

Trickling filters were found to reduce the concentration of paratyphoid organisms by 84 to 99 percent (Kabler, 1959). Low rate trickling filters were apparently capable of removing up to 99.9 percent of *S. typhosa* while a 95 percent reduction was accomplished even at loadings of 12 mgad (Lund et al, 1969). A 99 percent reduction in *M. tuberculosis* by trickling filters has also been observed (Pramer et al, 1950). On the other hand, only a 66 percent reduction has been noted (Heukelekian and Albanese, 1956). It should be pointed out that the removal in activated sludge was higher by more than 20 percent than in trickling filters in this same study. Activated sludge treatment has no apparent effect on *E. histolytica* cysts, even when aeration was extended to 48 hours (Cram, 1943). It should be recalled that primary sedimentation also seemingly produces no reduction in cyst numbers so that cyst densities in the effluents of activated sludge plants may change little from those in the influent. Removal varied from 88 to 99.9 percent in laboratory scale trickling filter plants in one study and another full scale study has reported 11 to 50 percent reduction in cyst densities in wastewater (Cram, 1943; and Kott and Kott, 1967).

Ova of intestinal parasites are apparently not affected by the activated sludge process (Cram, 1943; and Newton et al, 1949); and, in fact, the literature indicates that activated sludge mixed liquor provides an excellent hatching medium for the eggs (Kabler, 1959). Trickling filters, on the other hand, reduced ova concentrations 62 to 76 percent but may produce live larvae in the effluent when the filters slough off surface growth (Newton et al, 1949). In general, activated sludge appears to be ineffective in removal of both cysts and ova; and, while trickling filters are somewhat more efficient, they still pass significant portions of the incoming pathogens out the effluent. Secondary settling will not affect much further reduction of cysts; and, therefore, the final effluent will contain these pathogens (Kott and Kott, 1967). Final clarifiers could be expected to bring about similar removals of parasitic worm ova as observed in primary sedimentation, i.e. 70 to 90 percent.

Laboratory activated sludge units seeded with virus have shown 96 to 99 percent removal of Coxsackie A9 virus and lesser efficiency

with Poliovirus 1 (Clarke et al, 1961). Since many virus particles are apparently naturally bound to solids, studies of activated sludge systems seeded with virus may not be representative of "real world" situations. Lund (1969) estimated that 95 to 99 percent of viruses were removed by activated sludge on the basis of frequency of isolations in the influent and effluent. Studies of full scale wastewater treatment following community-wide administration of oral polio vaccines showed 76 to 90 percent removal of virus by activated sludge (England et al, 1967). Since swab samples for naturally occurring viruses were positive for 90 to 93 activated sludge effluent samples, one may conclude that viruses are generally present in the effluent.

Theios et al (1967) concluded that activated sludges was more efficient in removing virus than trickling filters based on studies of full scale plants during a polio vaccine campaign. In another study, the frequency of isolations in the influent and effluent of trickling filters has been reported to be approximately equal (Kelly and Sanderson, 1959). Shuval (1969) found trickling filter efficiency to be 0 to 84 percent in removing viruses. Trickling filters cannot be depended upon to produce a significant reduction in viruses.

Anaerobic Digestion of Sludges

Large quantities of pathogenic bacteria, helminth ova, and viruses can be found in sludges from primary and secondary clarifiers. Smaller quantities of amoebic cysts may also occur. These raw sludges would constitute a hazard if disposed of on land without further treatment. Anaerobic digestion at 30 to 35°C accomplishes a considerable reduction in the organic content of the sludge and may result in destruction of pathogens. *S. typhosa* survived to the extent of 0.3 to 17 percent after only 12 hours in batch digestion studies (McKinney et al, 1958). Use of continuously fed digesters demonstrated reductions of 84 to 92 percent for 6 and 20 days digestion, respectively.

Mycobacteria may survive a digestion period of more than 35 days in laboratory units and were reduced from 9700 to 3000 per ml in field scale units (Heukelekian and Albanese, 1956). No appreciable decrease in numbers occurred in the dried digested sludge even after 25 days drying. Others have observed a 90 percent reduction in tubercle bacilli during digestion (Pramer et al, 1950). Reports of survival of tubercle bacilli in dried sludges exposed to natural conditions indicate survival times of from 6-1/2 months to 2 years (Jensen and Jensen, 1942; and Müller, 1959).

The data reviewed by Chang (1965) on survival of helminth ova in digesters indicated that at least one month detention is necessary

for their destruction. *Ascaris* ova are not affected by 3 months digestion and 10 percent remain viable even after 6 months (Cram, 1943). Cysts, though probably not present in sludge in large quantities, are readily destroyed in 10 days at 30°C. Poliovirus has been isolated from digester sludge despite exposure to 50°C for up to 50 to 60 days. No virus was isolated from digested sludge in another study where only 2 samples were examined (Kelly and Sanderson, 1959). When sludge samples from a digester seeded with a swine virus were fed to germ free piglets, no indication of piglet infection was observed for all samples taken after the fourth day of digestion at 34.5°C (Meyer et al, 1971). Coxsackie B5 survived thermophilic anaerobic digestion for 30 days while bacteriophage survived mesophilic digestion for 4 months (Grigoryeva et al, 1969). It is apparent that some viruses are capable of withstanding sludge digestion for long periods while others are not. Determination of the range of survival of viruses representative of each of the major virus groups during digestion is required before potential hazards arising from application of liquid and dried digested sludges on land can be fully assessed.

Disinfection of Wastewater

The disinfection of wastewater is perhaps one of the most thoroughly studied areas with respect to the reduction of numbers of pathogenic organisms by waste treatment processes. This is as it should be, since final effluent disinfection is the last line of defense before the wastewater and the pathogens it might contain are placed in the environment. Unfortunately, much of the research has been ill-defined with little appreciation of the fact that a disinfectant may react with components of the system other than the pathogens; and, thus, change its potency for pathogen destruction. With chlorine, the most commonly used wastewater disinfectant in the United States, the initial dosage, the pH value, contact time, temperature, quantity of nitrogenous compounds present, and their nature, i. e. whether they are organic or inorganic, should be stated in order to interpret results of chlorination experiments; all these factors will have impact on the disinfecting capability of chlorine. Since much of this information is not available in many of the studies to be reviewed here, only general statements of relative resistance will be given.

Kabler (1951) found that resistance of *E. coli* and *Pseudomonas aeruginosa* to free chlorine at neutral pH values was approximately the same but less than that for *S. typhosa* and *Shigella dysenteriae*. Resistance to combined chlorine was comparable between these organisms but was considerably greater than that found for free chlorine. Survival with 0.3 mg/l of free chlorine was negligible while under the same conditions the test organisms were able to completely survive contact with 0.3 mg/l of combined chlorine. A reduction in

temperature from the 20 to 25°C range down to 2 to 6°C resulted in a further loss of bactericidal action of combined chlorine. Mycobacteria have layers of lipids and mycolic acids in their cell walls which cause a higher degree of chlorine resistance in this group of bacteria (Grabow et al, 1969). A review of over a dozen different wastewater disinfection studies led Greenberg (1957) to conclude that a combination of biological purification and effluent chlorination with a chlorine dosage of 20 mg/l with a 2 to 3 hour contact time or a chlorine residual of at least 1 mg/l following a 1 hour contact was necessary to destroy tubercle bacilli. Chlorine dosages up to 340 mg/l and 2 hour contact times have been found necessary to destroy Mycobacteria in other studies (Musehold, 1900). Higher chlorine residuals and longer contact times are thus required to inactivate tuberculosis organisms in comparison to other bacterial pathogens.

Cysts are apparently the most chlorine resistant waterborne pathogens. When the cysticidal properties of 2 mg/l each of free, combined inorganic, and combined organic chlorine residuals were compared in one study, it was observed that a 10 minute and 40 minute contact time was necessary for a 99.9 percent kill for the first two categories of compounds while organic chloramines failed to destroy more than 50 percent of the cysts even after 100 minutes of contact (Stringer and Kruse, 1970). Since wastewater effluents may contain organic and inorganic nitrogenous compounds, break-point effluent chlorination may be required in order to destroy cysts present in secondary effluents.

The reported response of viruses to chlorine varies widely depending on the condition used in a given study and the type of virus examined. Poliovirus 1 and Coxsackie A2 are much more resistant to chlorine than coliforms while adenovirus 3 is apparently more sensitive. Infectious hepatitis virus is able to survive 30 minutes contact time with 1 mg/l total residual chlorine in fecal suspensions if no other treatment is provided. Liu (1971) studied the chlorine resistance of 20 human enteric viruses seeded in Potomac River water. The least chlorine resistant virus, Reovirus 1, required only 2.7 minutes contact with 0.5 mg/l of free chlorine for 99.99 percent inactivation. Coxsackie A5 and Echovirus 12 required 53.5 and 60 minutes contact, respectively, to reach the same level of inactivation under these conditions. Combined chlorine has very little viricidal capability (Kruse et al, 1970). It is evident that the resistance of viruses to chlorine is quite variable. Since more than 80 viruses have not been subjected to detailed studies of their resistance, the disinfection conditions necessary to kill all viruses in wastewater

effluents is still an open question. It would appear that as with cysts, a free chlorine residual at a contact time of at least 1/2 hour is necessary to destroy many of the viruses.

PATHOGENS APPLIED TO SOIL

Table 5 is an attempt to summarize the data on the removal of pathogens in wastewater. Where definitive data do not exist for removal efficiency at a particular treatment step, values have been assumed based on any available information. Removal percentages assumed are given in parentheses. A uniform disinfection efficiency of 99.9 percent has been assumed. If the conditions necessary to destroy the more chlorine resistant pathogens were applied to wastewater, kills of relatively sensitive organisms such as Salmonella, greater than 99.9 percent would be obtained, thus further reducing the quantity of some pathogens. However, since the survival time of the remaining organisms may be quite long in soil, continuous application of wastewater onto soil could result in an accumulation of pathogens. An equilibrium value could be reached where die-off and removal through percolation and runoff is balanced by the daily input of new pathogens. The longer the survival time in soil the greater the equilibrium level. S. typhosa reportedly survive up to 85 days in soil but with soils which have poor moisture retaining power, survival in periods of drought may be as brief as 2 days (Beard, 1938; and Mallmann and Litsky, 1951). With continuous application of wastewater soils may not have sufficient opportunity to dry out; and, therefore, survival of Salmonella could be prolonged. Mycobacteria can survive dry conditions in soil for more than 150 days and survival times as long as 15 months have been reported (Greenberg and Kupka, 1957). While protozoan cysts are sensitive to dessication, Ascaris and Ancylostoma ova remain viable for long periods and have withstood conditions where the moisture content of soil was less than 6 percent and temperatures above 40°C for 60 to 80 days (Cram, 1943). Viable Ascaris eggs have been recovered up to 170 days under more favorable conditions. Little definitive information on the survival of virus in soil exists, but one could expect it to be of the same order of magnitude as survival in wastewater where persistence as long as 100 days has been reported (Akin et al, 1971).

If one accepts the figures given in Table 5 as reasonably accurate estimates of the possible quantities of pathogens that may be applied to land from chlorinated effluents, then one might conclude that considerable numbers of pathogens could be placed in the environment. The density of organisms on land will be even greater if they accumulate in the soil. Any degree of treatment less than secondary treatment in combination with free residual effluent

Table 5. Estimated Wastewater Pathogens Applied to Soil

Pathogen	Number of Organism Per Million Gallons					Organisms Applied Per Acre Per Day ^{2/}
	Wastewater	Primary Effluent	Secondary Effluent	Disinfection ^{1/}		
<u>Salmonella</u>	2×10^{10}	1×10^{10} (50%) ^{3/}	5×10^8 (95%)	5×10^5		3.9×10^3
<u>Mycobacterium</u>	2×10^8	1×10^8 (50%)	1.5×10^7 (85%)	1.5×10^4		1.2×10^2
<u>E. histolytica</u>	1.5×10^7	1.3×10^7 (10%)	1.2×10^7 (10%)	1.2×10^4		9.3×10^1
<u>Helminth Ova</u>	2.5×10^8	2.5×10^7 (90%)	5×10^6 (80%)	5×10^3		3.9×10^1
<u>Virus</u>	4×10^{10}	2×10^{10} (50%)	2×10^9 (90%)	2×10^6		1.6×10^4

^{1/} Conditions sufficient to yield a 99.9% kill

^{2/} Applied at a rate of 2 inches per week

^{3/} Estimated pathogen percentage removal efficiency of the treatment

disinfection will result in greater quantities of pathogens being applied to soil. If, for example, the wastewater is not chlorinated the quantities of pathogens applied will be 3 logs greater. Yet are these quantities sufficient to result in much danger of disease transmission? The density of pathogens with the application of chlorinated secondary effluent for any one of the pathogens cited would not be greater than 1 viable pathogen per four square feet per day. At the other extreme, the total pathogen load for unchlorinated secondary effluent is approximately 460 per square foot per day.

PUBLIC HEALTH HAZARDS

Several studies have attempted to assess the hazards involved in the application of wastewater on land and provide interesting comparisons to the figures in Table 5. Basically, the studies have been concerned with 1) hazards from aerosols in spray irrigating the wastewater on land, 2) contamination of edible crops, and 3) contamination of water from runoff and percolation.

Aerosol generation from spray irrigation could produce particles of a size which would either pass into the lungs or pass from the bronchi to the pharynx and into the intestine (Sorber and Guter, 1972). Infections such as Salmonellosis could therefore result from such exposure. However, enteric bacteria such as Salmonella are apparently not long lived as unprotected aerosols. Tubercle bacilli are resistant to drying and, therefore, should survive in the atmosphere as aerosols for extended periods. Greenberg (1957) felt the use of sewage sprays containing Mycobacteria to be especially dangerous. Inhalation would place the bacilli in the location where they can do the most damage as causative agents of pulmonary tuberculosis. Viability of airborne virus is relatively long. For example, in one study the majority of poliovirus aerosols persisted for more than 23 hours when the relative humidity was high (Walker, 1970). Reports of disease incidences resulting from contact with aerosols from spray irrigation have not appeared in the literature but this area should warrant further study.

Crop contamination research has mainly focused on vegetables which normally are eaten raw such as tomatoes, radishes, etc. Other studies have dealt with irrigation of pasture land for grazing of livestock. When tomatoes were field sprayed with feces or wastewater containing Salmonella and Shigella, survival of these organisms did not exceed 7 days (Rudolfs et al, 1951). However, a radish patch to which tubercle bacilli contaminated wastewater sludge had been applied yielded viable bacilli after 3 months exposure to the elements (Musehold, 1914). Rudolfs' (1951) statement that cessation of application of fecally contaminated fertilizer one month before

harvesting offers a margin of safety against bacterial disease would not seem to apply to *M. tuberculosis*. *E. histolytica* cysts are quite sensitive to dessication and do not survive longer than 3 days of dry weather when applied to crops such as lettuce and tomatoes (Rudolfset al, 1951). Immature *Ascaris* ova were not found to survive field conditions longer than 35 days (Rudolfs et al, 1951). Rudolfs noted that exposure of immature ova to the prevailing environmental conditions retarded their development into motile embryos. It must be pointed out, however, that studies of Cram (1943) and others (Kabler, 1959) have shown that the secondary waste treatment environment provides an excellent medium for development of ova. It is likely, therefore, that mature rather than immature ova would be present in large quantities in the effluent. If this is the case, Rudolfs' work may have underestimated the ability of *Ascaris* ova to survive and mature under field conditions. In general, there appears to be a danger of pathogen contamination of vegetables to be eaten raw if wastewater is applied to fields within 2 to 3 months of harvesting. If this is the case, it could limit its usefulness for crops such as lettuce and radishes which have short growing seasons.

Irrigation of fields for forage crops has produced interesting results which could eliminate some of the concern expressed about contamination of vegetables. Grass sprayed with 4×10^6 tubercle bacilli per square foot was fed to guinea pigs with no apparent effects (Greenberg and Kupka, 1957). Heavier inoculations, however, resulted in deaths in both guinea pigs and bovine test animals. The predicted values for tubercle bacilli applied to land in unchlorinated effluents obtained from the data of Table 5 (i.e. 2.7×10^6 bacilli per square foot) would indicate that the daily pathogen load would be at least six orders of magnitude below the levels which had no effect on guinea pigs. The danger to man and animals from ingestion of tubercle bacilli from crops irrigated with wastewater would appear to be slight.

The movement of bacterial and viral pathogens in percolation and runoff has been extensively reviewed in the literature (Krone, 1968; Krone et al, 1958; and Romero, 1970). Generalizations are difficult, but it appears that virus and bacteria movement in soils is related directly to the hydraulic infiltration rate and inversely with media particle diameters. Factors influencing bacterial and viral inactivation in soil such as oxygen tension, temperature, and the presence of competing organisms and antimicrobial agents will also be determining variables. Other factors which have an influence on adsorption phenomena in soils such as pH value, multivalent cation concentration, and clay content of the soil will influence removal of pathogens, particularly virus, in soils. The majority of the studies reviewed indicate that the upper layers of soil are most efficient in removing bacteria. At Lodi, California, coliform levels were observed to decrease to below drinking water

standards within 7 feet of the surface (Romero, 1970). Other research demonstrates that 92 to 97 percent of applied coliforms were retained in the uppermost 1 cm of agricultural soil. Even in the coarse gravel-sand used at Santee, California, most applied bacteria did not travel more than 200 feet. Cram (1943) reported *Ascaris* eggs would pass a 12 inch layer of sand but were removed by 24 inches as were hookworm ova and *E. histolytica* cysts. Drewry (1968) studied removal of viruses in a variety of soil lysimeters and concluded that no column studied was saturated with virus over more than 2 cm. Up to 5 percent of the applied virus passed the columns but generally removals were quite high, particularly in the upper layers. Virus seeded into the influent of the Santee percolation beds could not be recovered from samples concentrated by swabs located in an observation well 200 feet from the influent application site (Akin et al, 1971). It is likely, therefore, that pathogens do not travel to any great extent in soils and are removed principally in the upper layers. Even where organisms do travel up to 50 feet from the point of entry into the soil, "soil defense" mechanisms such as antibiotic activity and competition will begin to act and cause increased die-off resulting in a retreat of the bacterial front (Romero, 1970).

It should be noted that pathogens removed in the upper layers of soil will be concentrated near the soil area where crops will be grown. Pathogens could directly pass to crops such as lettuce or beets from soil contamination or be carried to above ground crops by flies or dust. The dust-borne epidemic of Salmonellosis in Israel indicates that this is not outside the realm of possibility. Fractures or channels in underlying geological formations will also affect pathogen movement in soil. Vogt (1961) reported a waterborne epidemic of infectious hepatitis which followed limestone fractures from a septic tank to individual wells considerable distances away from the source. Laboratory and field studies cannot be completely relied upon as to distance of travel since small quantities of pathogens may escape removal, particularly in fractured geological formations. Epidemiological evidence of bacteria and viruses travelling considerable distances to water supplies is discomfiting, particularly since levels of pathogens sufficient to result in infection may not be detectable in dilute solution with presently available techniques.

SUMMARY AND CONCLUSIONS

This paper has present a good deal of data couched in terms of possible or potential hazards. How real are the hazards in terms of the realities of actual cases of disease resulting from wastewater application on soil? The epidemiological evidence suggests that few disease incidences have been related to this practice. Krone (1968) reviewed an incident involving sewage contamination of fruits and

vegetables on a farm in 1919 which resulted in 8 cases of typhoid fever. A possible 2500 cases of gastroenteritis due to Shigella and Salmonella occurred in California in 1965 under highly unusual circumstances (Heukelekian and Albanese, 1956). Wastewater applied to a pasture traveled overland to a gopher hole and then into a poorly protected municipal water supply well. The chances of such an event repeating itself are highly unlikely. The literature is quite unusual in the paucity of information available on irrigation-caused epidemics. This may well reflect an absence of a problem despite other evidence indicating that significant quantities of pathogens are placed on soil by this practice. On the other hand, it may only reflect prejudices which regard only significant outbreaks of disease to be worthy of investigation. Epidemiological tools are insensitive for isolated or sporadic small scale outbreaks. Resulting sporadic infection may not result in actual clinical symptoms but could create foci for disease dissemination by other modes of transmission. While the potential for low-level transmission of disease is speculative, it is a possibility worthy of investigation. Until such time as the danger of sporadic disease transmission can be ruled out, a high degree of treatment of applied wastewater including free residual chlorination would seem to be indicated. Geological conditions underlying soil to which wastewater is applied should not contain channels or fractures which may permit pathogens to move long distances. More than one month, preferably more than two months, should be allowed between the last application of wastewater and harvesting edible crops. In this way both actual hazards of disease transmission and public apprehension may be reduced.

REFERENCES

- Aiba, S., and R. Sudo. 1965. Discussion of paper by H. Liebman, in Adv. in Water Poll. Res., 282, Vol. 2, Pergamon Press, London.
- Akin, E. W., W. H. Benton, and W. F. Hill, Jr. 1971. Enteric viruses in ground and surface water: a review of their occurrence and survival, 13th Water Quality Conf., 59, University of Illinois.
- Beard, P. J. 1938. The survival of typhoid in nature, Jour. Amer. Water Works Assn., 30, 124.
- Berg, G. 1966. Virus transmission by the water vehicle, III, Removal of viruses by water treatment procedures, Health Lab. Sci., 3, 170.
- Bloom, H. H., W. N. Mack, and W. L. Mallman. 1958. Enteric viruses and salmonellae isolations. II, Media comparison for salmonellae, Sew. and Indust. Wastes, 30, 1455.
- Browning, G. E. and J. O. Mankin. 1966. Gastroenteritis epidemic owing to sewage contamination of public water supply, Jour. Amer. Water Works Assn., 58, 1465.

- Bush, A. F. and J. D. Isherwood. 1966. Virus removal in sewage treatment, Jour. San. Engr. Div., Amer. Soc. Civil Engr., 92, 99.
- Clarke, N. A., G. Berg, P. W. Kabler, and S. L. Chang. 1964. Human enteric viruses in water: source, survival and removability, Adv. in Water. Poll. Res., 523, Vol. 2, Pergamon Press, London.
- Clarke, N. A., R. E. Stevenson, S. L. Chang, and P. W. Kabler. 1961. Removal of enteric viruses from sewage by activated sludge treatment, Amer. Jour. Pub. Health, 58, 1118.
- Cleere, R. L. 1960. Resume of swimming pool granuloma, Sanitation, 23, 105.
- Chang, S. L. and P. W. Kabler. 1956. Detection of cysts of endamoeba histolytica in tap water by use of membrane filter, Amer. Jour. Hygiene.
- Cram, E. B. 1943. The effect of various treatment processes on the survival of helminth ova and protozoan cysts in sewage, Sew. Works Jour., 15, 1119.
- Dolin, R., N. R. Blacklow, H. Dupont, S. Formal, R. F. Buscho, J. A. Kasel, R. P. Chames, R. Hornick, and R. M. Chanock. 1971. Transmission of acute non-bacterial gastroenteritis to volunteers by oral administration of stool filtrates, Jour. Infectious Diseases, 123, 307.
- Drewry, W. A. and R. Eliassen. 1968. Virus movement in ground water, Jour. Water Poll. Control Fed., 40, R257.
- England, B., R. E. Leach, B. Adame, and R. Shiosaki. 1967. Virologic assessment of sewage treatment at Santee, California, in Transmission of Viruses by the Water Route, G. Berg, ed., 401, Interscience, New York.
- Gordon, I., M. S. Ingraham, and R. F. Korn. 1947. Transmission of epidemic gastroenteritis to human volunteers by oral administration of fecal filtrates. Jour. Exper. Med., 86, 409.
- Grabow, W. O. K. 1968. The virology of waste water treatment, Water Res., 2, 675.
- Grabow, W. O. K., N. A. Grabow, and J. S. Burger. 1969. The bactericidal effect of lime flocculation/flotation as a primary unit process in a multiple system for the advanced purification of sewage works effluent, Water Res., 3, 943.
- Green, C. E. and P. J. Beard. 1938. Survival of E. typhi in sewage treatment plant processes, Amer. Jour. Pub. Health, 28, 762.
- Greenberg, A. E. and B. H. Dean. 1958. The beef tapeworm, measles, beef, and sewage - a review, Sew. and Indust. Wastes, 30, 262.
- Greenberg, A. E. and E. Kupka. 1957. Tuberculosis transmission by wastewaters - a review, Sew. and Indust. Wastes, 29, 524.
- Greenberg, A. E. and H. J. Ongerth. 1966. Salmonellosis in Riverside, California, Jour. Amer. Water Works Assn., 58, 1145.
- Grigoryeva, L. V., G. I. Korchak, and T. V. Bey. 1969. Survival of bacteria and viruses in sewage sludges, Mikrobiol. Zh., 31, 659.

- Heukelekian, H. and M. Albanese. Enumeration and survival of human tubercle bacilli in polluted waters, II, Effect of sewage treatment and natural purification, Sew. and Indust. Wastes, 28, 1094.
- Heukelekian, H. and H. B. Schulhoff. 1935. Studies on the survival of *B. typhosus* in surface waters and sewage, N. J. Agric. Expt. Sta. Bull., 589.
- Jensen, K. A. and K. E. Jensen. 1942. Occurrence of tubercle bacilli in sewage and experiments on sterilization of tubercle bacilli-containing sewage with chlorine, Acta Tuberc. Scandinavica, 16, 217.
- Kabler, P. K. 1959. Removal of pathogenic microorganisms by sewage treatment processes, Sew. and Indust. Wastes, 31, 1373.
- Kabler, P. W. 1951. Relative resistance of coliform organisms and enteric pathogens in the disinfection of water with chlorine, Jour. Amer. Water Works Assoc., 43, 553.
- Kelly, S. M., M. E. Clark, and M. B. Coleman. 1955. Demonstration of infectious agents in sewage, Amer. Jour. Pub. Health, 45, 1438.
- Kelly, S. M. and W. W. Sanderson. 1960. The density of enteroviruses in sewage, Jour. Water Poll. Control Fed., 32, 1269.
- Kelly, S. and W. W. Sanderson. 1959. The effect of sewage treatment on viruses, Sew. and Indust. Wastes, 31, 683.
- Komiya, Y. and H. Kutsumi. 1965. Discussion of paper by H. Liebman, in Adv. in Water Poll. Res., 276, Vol. 2, Pergamon Press, London.
- Kott, H. and Y. Kott. 1967. Detectability and viability of endamoeba *histolytica* cysts in sewage effluents, Water and Sew. Works, 114, 117.
- Kroger, E. and G. Trettin. 1950. Abwasseruntersuchung auf tuberkelbakterien, Zentralbl. f. Bakt. Abt. I. Orig., 157, 851.
- Krone, R. B. July 30, 1968. The movement of disease producing organisms through soil, presented at the Symp. on the Use of Municipal Sewage Effluent for Irrigation, Louisiana Poly. Instit., Ruston, La.
- Krone, R. B., G. T. Orlob and C. Hodgkinson. 1958. Movement of coliform bacteria through porous media, Sew. and Indust. Wastes, 30, 1.
- Kruse, C. W. Y. C. Hsu, A. C. Griffiths, and R. Stringer. 1970. Halogen action of bacteria, viruses and protozoa, Proc. National Specialty Conf. on Disinfection, 113, Amer. Soc. Civil Engr., New York.
- Laird, A. T., G. L. Kite, and D. A. Stewart. 1913-1914. The presence of tubercle bacilli in the feces, Jour. Med. Res., 24, 31.
- Liebman, H. 1965. Parasites in sewage and the possibilities of their extinction, Adv. in Water Poll. Res., Vol. 2, 269, Pergamon Press, London.

- Liu, O. C., H. R. Seraichekas, E. W. Akin, D. A. Brashear, E. L. Katy, and W. F. Hill, Jr. 1971. Relative resistance of 20 human enteric viruses to free chlorine in Potomac water, 13th Water Qual. Conf., University of Illinois.
- Lund, E., C. E. Hedstrom, and N. Jantzen. 1969. Occurrence of enteric viruses in wastewater after activated sludge treatment, Jour. Water Poll. Control Fed., 41, 169.
- Lund, E. 1970. Observations on the virus binding capacity of sludge, presented at 5th International Conf. on Water Poll. Res., San Francisco, Calif.
- Mack, W. N., J. R. Frey, B. J. Riegler, and W. L. Mallman. 1962. Enterovirus removal by activated sludge treatment, Jour. Water Poll. Control Fed., 34, 1133.
- Mallmann, W. L. and W. Litsky. 1951. Survival of selected enteric organisms in various types of soil, Amer. Jour. Pub. Health, 41, 38.
- Mannsfield, M. 1937. Untersuchungen über die resistenz der tuberkelbazillen im abwasser., Acta Soc. Biol. Latviae, 7, 153.
- McKinney, R. E., H. E. Langely, and H. D. Tomlinson. 1958. Survival of salmonella typhosa during anaerobic digestion, Sew. and Indust. Wastes, 30, 1469.
- Meyer, R. C., F. C. Hinds, H. R. Isaacson, and T. D. Hinesly. 1971. Porcine enterovirus survival and anerobic sludge digestion, Proc. Intl. Symp. on Livestock Wastes, 183, Amer. Soc. Agric. Engr., St. Joseph, Michigan.
- Mosley, J. W. 1965. Transmission of viral diseases by drinking water, Transmission of Viruses by the Water Route, G. Berg, ed., Interscience, New York.
- Müller, G. 1959. Tuberkelbakterien im schlam mechanisch-biologisch arbeitender abwasserreinigungsanlagen, Städtehyg., 5, 46.
- Musehold, P. 1900. Über die widerstand fähigkeit der mit dem lungenauswerfherausbeforderten tuberkelbazillen im abwassern, im flusswasser und im kultiverten boden, Arbeiten a.d. Kaiserlichen Gesundheitant, 17, 56.
- Neeffe, J. R., J. B. Baby, J. G. Reinhold, and J. Stokes, Jr. 1947. Inactivation of the virus of infectious hepatitis in water, Amer. Jour. Pub. Health, 37, 365.
- Newton, W. L., H. J. Bennett, and W. B. Figgat. 1949. Observations on the effects of various sewage treatment processes upon the eggs of taenia saginata, Amer. Jour. Hygiene, 49, 166.
- Noble, E. R. and G. A. Noble. 1964. Parasitology: The Biology of Animal Parasites, 2nd ed., Lea and Febiger, Philadelphia.
- Northington, C. W., S. L. Chang, and L. T. McCabe. 1970. Health aspects of wastewater reuse, in Water Quality Improvement by Physical and Chemical Processes, E. F. Gloyna and W. W. Eckenfelder, eds., University of Texas Press.
- Pramer, D., H. Heukelekian, and R. A. Ragotzkie. 1950. Survival of tubercle bacilli in various sewage treatment processes, I, Development of a method for the quantitative recovery of mycobacteria from sewage, Pub. Health Reports, 65, 851.

- Rhines, C. 1935. The longevity of tubercle bacilli in sewage and stream water, Amer. Rev. Tuberc., 31, 493.
- Rochaix, A. 1930. Experiments on the persistence and disappearance of pathogenic bacteria in sewage, Ann. D'Hyg., 8, 669.
- Romero, J. C. 1970. The movement of bacteria and viruses through porous media, Ground Water, 8, 37.
- Rudolfs, W., L. L. Falk, and R. A. Ragotzkie. 1951. Contamination of vegetables grown in polluted soil, I, Bacterial contamination, Sew. Works Jour., 23, 253.
- Rudolfs, W., L. L. Falk, and R. A. Ragotzkie. 1951. Contamination of vegetables grown in polluted soil, II, Field and laboratory studies on endamoeba cysts, Sew. Works Jour., 23, 478.
- Rudolfs, W., L. L. Falk, and R. A. Ragotzkie. 1951. Contamination of vegetables grown in polluted soil, III, Field studies on ascaris eggs, Sew. Works Jour., 23, 656.
- Rudolfs, W., L. L. Falk, and R. A. Ragotzkie. 1950. Literature on the occurrence and survival of enteric, pathogenic, and relative organisms in soil, water, sewage, and sludges, and on vegetation, I, Bacterial and virus diseases, Sew. and Indust. Wastes, 22, 1261.
- Salle, A. J. 1967. Fundamental principles of bacteriology, 6th ed., McGraw-Hill, New York, N. Y.
- Seligman, R., and R. Reitler. 1965. Enteropathogens in water with low esch. coli titer, Jour. Amer. Water Works Assn., 57, 1572.
- Shuval, H. I. 1969. Detection and control of enteroviruses in the water environment, in Developments in Water Qual. Res., H. I. Shuval, ed., Ann Arbor-Humphreys, Ann Arbor.
- Sorber, C. A. and K. J. Guter. 1972. Health and hygiene aspects of spray irrigation, in Wastewater Management by Disposal on the Land, S. C. Reed, Coordinator, Cold Regions Res. and Engr. Lab., Corps of Engineers, U. S. Army, Hanover, N. H.
- Stringer, R. and C. W. Kruse. 1970. Amoebic cysticidal properties of halogens in water, Proc. National Specialty Conf. on Disinfection, 319 Amer. Soc. Civil Engr., New York, N. Y.
- Theios, E. P., J. G. Morris, M. J. Rosenbaum, and A. G. Baker. 1967. Effect of sewage treatment on recovery of poliovirus following mass oral immunization, Amer. Jour. Pub. Health, 57, 295.
- Vogt, J. E. 1961. Infectious hepatitis outbreak in Posen, Michigan, Proc. 1961 Symp. on Groundwater Contamination, 87, USPHS Tech. Rept. W61-5.
- Walker, B. 1970. Viruses respond to environmental exposure, Jour. Environ. Health, 32.
- Wang, W. L. L., S. G. Dunlop, and R. G. Deboer. 1956. The survival of shigella in sewage, I, An effect of sewage and fecal suspensions on shigella flexneri, Appl. Micro., 4, 34.
- Weibel, S. R., F. R. Dixon, R. B. Weidner, and L. J. McCabe. 1964. Waterborne disease outbreaks 1946-60, Jour. Amer. Water Works Assn. 56, 947.

Wilson and Rosenberger. 1909. The duration of the actively infectious stage of tuberculosis. Jour. Amer. Med. Assn., 7, 449.

Wilson, W. J., and E. M. Blair. 1931. Further experience of the bismuth sulfite media in the isolation of bacillus typhosus and B. paratyphosus B from feces, sewage, and water, Jour. Hygiene, 31, 138.

VEGETATION RESPONSES TO IRRIGATION WITH TREATED MUNICIPAL WASTEWATER

3280

William E. Sopper and Louis T. Kardos
School of Forest Resources and Department of Agronomy
The Pennsylvania State University

Many water pollution problems have been created and worsened by the disposal of treated municipal wastewater into streams, lakes, and oceans. There are currently about 16,000 sewage treatment plants in the United States discharging more than 26 billion gallons of effluent daily. This is only a beginning. As environmental quality pressures mount more plants will have to be built to meet new stringent water quality standards. This move from dispersed simple wastewater treatment by many individual septic tanks to collection and concentration of wastewater for treatment at a single plant provides only a partial solution to water pollution problems. Advanced secondary treatment eliminates the health hazard associated with untreated wastes and most of the organic matter is decomposed into its inorganic components. However, it is the concentrated discharge of these mineral-enriched effluents into a balanced aquatic environment which causes ecological chaos and disrupts the natural recycling process.

CHEMICAL COMPOSITION OF MUNICIPAL SEWAGE EFFLUENT

The chemical composition of municipal effluent is illustrated in Table 1 based upon samples collected during 1971 from the University treatment plant. This plant services both the University and the borough of State College. Treatment consists of both primary and secondary treatment. Secondary treatment includes standard and high-rate trickling filters and a modified activated sludge process followed by final settling. Weekly variations in concentration of constituents are shown by the range between maximum and minimum values. The total amount of each constituent applied per acre per year at the 2-inch per week rate is also given in Table 1.

The fertilizer value of these wastewaters is readily evident. The amount of N-P-K applied through spray irrigation of effluent in forested areas at the rate of 2 inches per week during the past 9 years is given in Table 2. The average annual applications provided commercial fertilizer constituents equivalent to approximately 208 pounds of nitrogen, 200 pounds of phosphate (P_2O_5), and 227 pounds of potash (K_2O). This would be equal to applying about 2000 lbs of a 10-10-11 fertilizer annually.

Table 1. Chemical Composition of Sewage Effluent Applied During 1971

Constituent	Range		Average	Total Amount Applied ^{1/}
	Minimum	Maximum		
	mg/l	mg/l	mg/l	lbs/acre
pH	7.4	8.9	8.1	---
MBAS ^{2/}	0.03	0.88	0.37	5
Nitrate-N	2.6	17.5	8.6	128
Organic-N	0.0	7.0	2.4	36
NH ₄ -N	0.0	5.0	0.9	13
Phosphorus	0.250	4.750	2.651	39
Calcium	23.1	27.8	25.2	375
Magnesium	9.1	15.1	12.9	192
Sodium	18.8	35.9	28.1	419
Boron	0.14	0.27	0.21	3
Manganese	0.01	0.04	0.02	0.2

^{1/} Amount applied on areas which received 2 inches of effluent per week.

^{2/} Methylene blue active substance (detergent residue) values are for 1970, constituent not included in analyses in 1971.

Table 2. Amount of N-P-K Applied Annually in Forested Areas Through Spray Irrigation of Effluent

Year	Total Effluent Applied ^{1/}	N	P	K
	inches	lbs/a	lbs/a	lbs/a
1963 ^{2/}	46	119	54	127
1964	66	256	116	234
1965	62	139	122	199
1966	62	170	129	238
1967	56	157	98	176
1968	62	351	119	261
1969	56	275	66	175
1970	54	217	43	120
1971	58	184	40	174
Mean	58	208	87	189

^{1/} Applied 2 inches per week.

^{2/} First year irrigation started June 18, 1963 and therefore values only represent a partial year.

THE PENN STATE WASTEWATER RENOVATION AND CONSERVATION PROJECT

Treated municipal sewage effluent has been spray irrigated on cropland and in forest stands for a 10-year (1963-72) period. Effluent has been applied in various amounts ranging from 1 inch per week to 6 inches per week and over various lengths of time ranging from as little as 16 weeks during the growing season on cropland to the entire 52 weeks in forests. Rates of application have varied from 0.25 to 0.64 inch per hour.

Types of crops irrigated with effluent were wheat, oats, corn, alfalfa, red clover, and reed canarygrass. Forested areas irrigated consisted of a mixed hardwood forest, a red pine plantation (*Pinus resinosa* Ait.), and a sparse white spruce (*Picea glauca* Muench Voss.) plantation established on an abandoned old field. Detailed descriptions of these areas have been previously reported by Sopper (1968, 1971).

CROP RESPONSES

Yields

The sequence of annual crop rotation is given in Table 3. During the initial years of the project a variety of crops were tested. Since 1968 the two primary crops used have been silage corn and reed canarygrass. As will be discussed later these two crops appear to be the most efficient in terms of the utilization of the crop to remove nutrients applied to a site in the effluent.

Average crop yields obtained from 1963 to 1970 are given in Table 4. During this 8-year period the crop areas irrigated with 2 inches of effluent weekly received a total of 392 inches of wastewater equivalent to applying 10,000 pounds of a 13-6-15 commercial fertilizer. The control area was fertilized with commercial fertilizer ranging from 200 pounds of 0-20-20 per acre for oats to 1000 pounds of 10-10-10 on corn. Effluent irrigation at 2 inches per week resulted in annual yield increases ranging from -8 to 346 percent for corn grain, 5 to 130 percent for corn silage, 85 to 191 percent for red clover, and 79 to 139 percent for alfalfa. Yield differences between the effluent-irrigated and control plots were greatly influenced by growing season precipitation. During the years, 1963 to 1966, when growing season (May 1 - September 30) precipitation was 5 to 8 inches below normal, yields on the irrigated areas were significantly greater than on the control areas, but usually differences between the 1-inch and 2-inch per week applications were not significantly different. In 1967 and 1969, when growing season precipitation was slightly above normal, yield differences were not significant. In 1970, with growing season

TABLE 3. Annual Crop Sequence

Area	1963	1964	1965	1966	1967	1968-72
1	corn ^{1/}	oats	alfalfa	alfalfa	alfalfa	corn
2	wheat	red clover	corn	corn	corn	corn
3	red clover	corn	oats	alfalfa	alfalfa	corn
4	wheat	red clover	corn	corn	corn	corn
5	corn	oats	alfalfa	alfalfa	alfalfa	corn
6	red clover	corn	oats	alfalfa	alfalfa	corn
7	alfalfa	corn	oats	alfalfa	alfalfa	corn

^{1/} Includes 1-inch and 2-inch per week irrigated plots and a control plot.

TABLE 4. Average Annual Crop Yields at Various Levels of Application of Sewage Effluent^{1/}

	0 inch/week	1 inch/week	2 inches/week
1963			
Wheat (bushels/acre)	48	45	54
Corn (bushels/acre)	75	105	106
Alfalfa (tons/acre)	2.18	3.73	5.12
Red clover (tons/acre)	2.48	4.90	4.59
1964			
Red clover (tons/acre)	1.76	5.30	5.12
Corn (bushels/acre)	81	121	116
Corn stover (tons/acre)	3.83	7.29	8.48
Oats (bushels/acre)	82	124	97
1965			
Alfalfa (tons/acre)	2.27	4.67	5.42
Corn (bushels/acre)	63	114	111
Corn silage (tons/acre)	3.11	3.93	4.32
Oats grain (bushels/acre)	45	80	73
Oats straw (tons/acre)	1.62	2.90	2.63
Reed canarygrass (tons/acre)	--	--	6.13
1966			
Alfalfa (tons/acre)	1.95	3.86	4.38
Corn (bushels/acre)	33	98	115
Corn silage (tons/acre)	2.47	4.45	5.68
Reed canarygrass (tons/acre)			4.32

TABLE 4. Continued

	0 inch/week	1 inch/week	2 inches/week
1967			
Corn Pa. 444			
19-inch row (bushels/acre)	98	101	122
38-inch row (bushels/acre)	92	83	84
Corn Pa. 602-A			
19-inch row (bushels/acre)	122	121	114
Corn silage Pa. 602-A			
19-inch row (tons/acre)	4.43	4.47	4.67
Alfalfa (tons/acre)	2.43	3.77	4.36
Reed canarygrass (tons/acre)	--	--	7.03
1968			
Reed canarygrass (tons/acre)			5.09
1969			
Corn Silage			
Pa. 602-A (tons/acre)	5.19	5.77	5.49
Pa. 890-S (tons/acre)	6.90	6.66	7.27
Reed canarygrass (tons/acre)	--	--	5.18
1970			
Corn Silage			
Pa. 602-A (tons/acre)	4.35	6.44	6.00
Pa. 890-S (tons/acre)	5.20	4.97	5.58
Reed canarygrass (tons/acre)	--	--	5.53

Part of table obtained from Kardos (1971); yields in tons per acre reported on a dry weight basis; corn grain yields are expressed on the basis of 56 pounds per bushel at 15.5 percent moisture content.

precipitation again below normal (1.55 inches), yield differences between the control and irrigated areas were again significant but the two levels of irrigation were not.

Nutrient Composition

Under the "living filter" concept the higher plants growing on the soil are an integral part of the system and assist the microbiological and physio-chemical activities occurring within the soil to renovate the sewage effluent through removal and utilization of the nutrients applied. The average nutrient composition of the corn silage and reed canarygrass harvested during 1970 is given in Tables 5 and 6. The crops harvested from the 2-inch per week irrigated areas are usually higher in nitrogen and phosphorus than the control crops. As indicated in Table 5 the differences are not large. This is partially due to the fact that the control area receives a normal application of commercial fertilizer each year. For instance, the silage corn control area has received 600 to 1000 pounds of a 10-10-10 fertilizer per acre annually.

Nutrients Removed by Crop Harvest

The contribution of the higher plants as renovators of the wastewater is readily evident from Tables 7 and 8 when the quantities of nutrients, expressed in pounds per acre, removed in the 1970 crop harvest are given. These data indicate that the vegetative cover can contribute substantially to the durability of a "living filter" system particularly where a crop is harvested and utilized. At the 2-inch-per-week level of effluent irrigation the two corn varieties removed 148 and 160 pounds of nitrogen and 35 and 43 pounds of phosphorus. Reed canarygrass, which is a perennial grass, was even more efficient in that it removed 408 pounds of nitrogen and 56 pounds of phosphorus. The difference is primarily due to the fact that the grass is already established and actively growing in early spring even before the corn is planted.

The amounts of nutrients removed annually vary with the amount of wastewater applied, amount of rainfall, length of the growing season, and the number of cuttings of the reed canarygrass.

The efficiency of crops as renovating agents can be assessed by computing a "removal efficiency" expressed as the ratio of the weight of the nutrient removed in the harvested crop to the weight of the same nutrient applied in the wastewater. Renovation

TABLE 5. Average Nutrient Composition of Two Varieties of Corn Silage Receiving Various Levels of Effluent During 1970

Nutrient	Variety and amount of effluent applied per week					
	Corn Silage, Pa. 890-S			Corn Silage, Pa. 602-A		
	0	1	2	0	1	2
	§	§	§	§	§	§
Nitrogen	1.18	1.24	1.32	1.34	1.36	1.34
Phosphorus	0.22	0.29	0.31	0.21	0.28	0.35
Potassium	1.00	0.98	1.02	1.04	1.10	1.07
Calcium	0.39	0.28	0.25	0.48	0.32	0.23
Magnesium	0.16	0.22	0.22	0.16	0.21	0.19
Chloride	0.21	0.36	0.34	0.19	0.36	0.39
Sodium	µg/g 14	µg/g 171	µg/g 176	µg/g 12	µg/g 167	µg/g 201
Boron	6	8	8	7	7	7

TABLE 6. Average Nutrient Composition of Reed Canarygrass
Irrigated With 2 Inches of Effluent During 1970

Nutrient	First Cut	Second Cut	Third Cut	Weighted Average ^{1/}
	%	%	%	%
Nitrogen	4.06	3.44	3.34	3.69
Phosphorus	0.44	0.51	0.64	0.50
Potassium	2.50	2.26	1.63	2.23
Calcium	0.39	0.40	0.42	0.40
Magnesium	0.36	0.40	0.32	0.36
Chloride	1.50	1.64	0.94	1.57
	µg/g	µg/g	µg/g	µg/g
Sodium	331	329	228	309
Boron	8	8	8	8

^{1/} Based on the average yield for each cutting.

TABLE 7. Quantities of Nutrients Removed by Reed Canarygrass
Irrigated With 2 Inches of Effluent During 1970

Nutrient	First Cut	Second Cut	Third Cut	Total
pounds per acre				
Nitrogen	196.5	134.2	77.5	408.2
Phosphorus	21.3	19.9	14.8	56.0
Potassium	121.0	88.1	37.8	246.9
Calcium	18.9	15.6	9.7	44.2
Magnesium	17.4	15.6	7.4	40.4
Chloride	72.6	64.0	21.8	158.4
Sodium	1.6	1.3	0.5	3.4
Boron	0.04	0.03	0.02	0.09

TABLE 8. Quantities of Nutrients Removed By Two Varieties of Corn Silage Receiving Various Levels of Effluent During 1970

Nutrient	Variety and amount of effluent applied per week					
	Corn Silage, Pa. 890-S		Corn Silage, Pa. 602-A			
	0	1	2	0	1	2
	pounds per acre			pounds per acre		
Nitrogen	129.4	126.1	148.4	117.5	174.4	160.6
Phosphorus	24.3	29.4	34.7	18.6	35.6	42.8
Potassium	105.6	95.7	113.1	91.6	137.1	129.3
Calcium	41.2	27.4	28.5	39.9	41.4	27.0
Magnesium	16.3	21.5	23.7	14.1	27.6	23.2
Chloride	21.6	35.2	37.2	17.1	44.6	46.4
Sodium	0.14	1.66	1.90	0.11	2.13	2.39
Boron	0.06	0.08	0.08	0.06	0.10	0.09

efficiencies for the silage corn and the reed canarygrass crops harvested in 1970 are given in Table 9. At the 1-inch-per-week level of application of wastewater, the two varieties of corn silage removed nutrients equivalent to 242 and 334 percent of the total applied nitrogen, 190 and 230 percent of the applied phosphorus, and 195 and 280 percent of the applied potassium. At the 2-inch-per-week level, both varieties of corn silage removed more than 100 percent of the applied nitrogen, phosphorus, and potassium.

During 1970 the reed canarygrass removed only 75 percent of the applied nitrogen, and 3 percent of the applied phosphorus. These are not typical annual values for the 1965-70 period. During the period 1965 to 1969 only sewage effluent was applied. In 1970 irrigation applications included a combination of sewage effluent and injected liquid digested sludge. During the period 1965-69, 1581 pounds of nitrogen were applied and the harvested reed canarygrass removed 1663 pounds, equivalent to a 105 percent renovation efficiency. In 1970, an additional 546 pounds of nitrogen were applied making the total 2127 pounds applied in 536 inches of wastewater. Since only 408 pounds were removed by crop harvesting the overall 6-year period renovation efficiency was lowered to 97.5%.

During the same period, 797 pounds of phosphorus were applied in the wastewater and 279 pounds removed in crop harvesting resulting in an overall renovation efficiency of 35 percent. Annual renovation efficiencies have varied from 24 to 63 percent for reed canarygrass irrigated at the 2-inch-per-week level. For corn silage it has varied from 39 to 230 percent for the 1-inch-per-week level and from 21 to 143 percent for the 2-inch-per-week level. Hence, it is obvious that some process other than utilization by the vegetative cover must be used to assure the removal of this key eutrophic nutrient. This additional renovation and removal of phosphorus is usually accomplished by way of the large fixing capacity of most agricultural soils for phosphorus. At the Penn State sites, the Hublersburg soils, which range in texture from a silt loam to a silty clay loam, have persistently and effectively removed the phosphorus.

The fate of phosphorus and nitrogen on the reed canarygrass area irrigated with municipal wastewater at 2-inches-per-week since 1965 are shown in Table 10. After 6 years of applying chlorinated effluent, 797 pounds of phosphorus and 2127 pounds of nitrogen had been applied to each acre in 536 inches of effluent. Harvested crops removed 270 pounds of phosphorus, the equivalent of 35 percent of the amount added. Since the concentration of phosphorus in the percolate at the four foot soil depth was only 0.05 mg/l and was no greater than that in an unirrigated adjacent forest area, the net percolation losses of phosphorus from the wastewater treated areas

TABLE 9. Renovation Efficiency of the Silage Corn and Reed Canarygrass Crops Harvested in 1970

Nutrient	Variety and amount of effluent applied					
	Corn Silage, Pa. 890-S		Corn Silage, Pa. 602-A		Reed canarygrass	
	1	2	1	2	1	2
Nitrogen	242	134	334	145	75	75
Phosphorus	190	116	230	143	63	63
Potassium	195	114	280	130	117	117
Calcium	25	16	38	15	9	9
Magnesium	41	28	53	27	19	19
Chloride	20	11	26	14	20	20
Sodium	1	1	2	1	1	1
Boron	8	4	10	4	2	2

TABLE 10. Phosphorus and Nitrogen Balances for Reed Canarygrass Irrigated with Effluent at Two Inches Per Week During the Period 1965 to 1970

Period	Amount Applied		Removed		Retained by soil
	Wastewater	Nutrient	By crop	By leaching	
1965-70	inches	lbs/acre	lbs/acre	lbs/acre	lbs/acre
	536	797 (P)	279 (P)	6.4 (P)	512 (P)
		2127 (N)	2073 (N)	452 (N)	-398 (N)

were assumed to be proportional only to the excess percolation induced by the added wastewater. Further, since precipitation always exceeds potential evapotranspiration on an annual basis, the wastewater was assumed to be totally recharged. On the basis of these assumptions, the net percolation loss of phosphorus from the wastewater irrigated areas was calculated to be 6.4 pounds per acre during the 6-year period, or only 0.8 percent of the amount applied. Thus the soil with its strong absorptive capacity for phosphorus, together with the crop harvests, has persistently removed 99.2 percent of the added phosphorus.

Nitrogen removals by the soil and crop system have also been equally efficient. Over the 6 year period 2127 pounds of nitrogen were added to each acre. Protein removed in the harvested reed canarygrass was equivalent to 2073 pounds of nitrogen per acre. Kjeldahl nitrogen content of the upper foot of soil was approximately 5000 pounds per acre. Average concentration of nitrate-N in the percolate at the four foot soil depth during the 6-year period was 3.5 mg/l in the effluent irrigated areas and 0.2 mg/l in the control areas. On the basis of the same assumptions used above, the excess percolate from the 536 inches of wastewater applied per acre would have carried a total of 452 pounds of nitrogen into the groundwater. This quantity is 398 pounds in excess of the 54 pounds per acre difference between the amount of nitrogen added in the wastewater and the amount removed in the harvested crops and could easily have been derived from the large amounts of native soil nitrogen. Thus the reed canarygrass was effective in removing 97.5 percent of the added nitrogen.

FOREST RESPONSES

Red Pine

Experimental plots were established in a red pine plantation in 1963. These plots have been irrigated with sewage effluent during the past 10 years at rates of 1 inch and 2 inches per week during the growing season (April to November). The plantation was established in 1939 with the trees planted at a spacing of 8 by 8 feet. In 1963 the average tree diameter at breast height was 6.8 inches and average height was 35 feet.

Diameter and height growth measurements were made annually on sample trees selected at random on each irrigated plot and on adjacent control areas. Average annual height growth for the period 1963 to 1970 is given in Table 11. Irrigation with sewage effluent at both rates produced slight increases in height growth during the first 2 years. This slight increase in height growth has been

maintained on the plot receiving 1 inch per week. However, on the plot receiving 2 inches per week, height growth continually decreased up to 1968 when high winds during a wet snowfall completely felled every tree on the plot.

TABLE 11. Average Annual Terminal Height Growth of Red Pine Irrigated with Sewage Effluent

Treatment	Average annual height growth
	feet
Irrigated - 1 inch per week (1963-70)	1.8
Control	1.4
Irrigated - 2 inches per week (1963-68)	1.6
Control	1.7

Diameter growth was computed from annual circumference measurements with dendrometer bands. In addition increment cores were taken in 1972 from sample trees in all areas. The actual measurements of average radius growth taken from the increment cores indicate that the previous diameter growth data reported (Sopper, 1971) which was based upon dendrometer band measurements of tree circumferences was incorrect. Average annual diameter growth based on increment core measurements is given in Table 12. Irrigation at the 1-inch-per-week level increased the average annual diameter growth (1963-68). In addition, during the sixth year (1968) of irrigation the needles of the pines being irrigated at the higher rate began to turn yellow. Boron toxicity was suspected since other investigators (Stone and Baird, 1956) have previously reported that applications of 1.1 pounds of boron per acre were sufficient to induce toxicity symptoms. Approximately 4 pounds of boron per acre are applied annually in the sewage effluent. However, foliar analyses indicated that there was no significant difference between boron concentrations of the needles of trees on the irrigated (33 micrograms per gram) and control (23 micrograms per gram) trees.

White Spruce

Two experimental plots were established in a sparse white spruce plantation on an abandoned old-field area. The trees in 1963 ranged from 3 to 8 feet in height. One plot has been irrigated with sewage effluent during the past 10 years at the rate of 2 inches per

TABLE 12. Average Annual Diameter Growth of Red Pine Irrigated With Sewage Effluent

Treatment	Average annual diameter growth
	inches
Irrigated - 1 inch per week (1963-72)	0.17
Control	0.06
Irrigated - 2 inches per week (1963-68)	0.06
Control	0.07

week, while the second plot has been maintained as a control. Height growth measurements have been made annually. In 1972, all tree diameters were measured and increment cores taken to determine the average annual diameter growth.

Total height of the trees was measured in August 1972. Average height of the trees on the irrigated plot was 20 feet and ranged from 12 to 25 feet. The average height of the trees on the control plot was 9 feet and ranged from 8 to 15 feet. Over the 10-year period average annual height growth was 18 inches on the irrigated areas and 5 inches on the control areas, representing a 360 percent increase as a result of sewage effluent irrigation.

Average diameter of trees on the irrigated plot was 3.7 inches, on the control plot it was 1.1 inches. Measurements taken from increment cores indicated that the average annual diameter growth on the irrigated trees was 0.40 inch and on the control trees 0.18 inch, representing a 122 percent increase.

Old Field Herbaceous Vegetation

The predominant ground cover on the old field area of the spruce plantation was poverty grass (*Danthonia spicata* Beauv.), goldenrod (*Solidago* spp. Ait.), and dewberry (*Rubus Flagellaris* Willd.).

Permanent transect plots were established in 1964 and measured annually to determine the effects of sewage effluent irrigation on the herbaceous ground cover in terms of species composition, height growth, dry matter production and percentage areal cover.

Average annual dry matter production during the 10-year period was 5457 pounds per acre on the irrigated plot and 1810 pounds per acre on the control plot (Table 13). This represents an average

annual increase of 201 percent. Annual increases ranged from 100 to 350 percent.

TABLE 13. Average Annual Dry Matter Production of Herbaceous Vegetation in the Old Field Area

Year	Irrigated plot	Control plot
	lbs/acre	lbs/acre
1963	3381	1470
1964	7607	1763
1965	5672	1675
1966	6417	1435
1967	4075	2010
1968	6044	1550
1969	5909	2015
1970	5505	1605
1971	--	--
1972	5007	2770
Mean	5457	1810

Species composition of the ground vegetation has changed considerably during the 10 years as a result of sewage effluent irrigation. Several species which were predominant prior to wastewater irrigation have been drastically reduced in number or have disappeared completely. For instance, goldenrod (*Solidago* spp.) which had 155,090 stems per acre in 1963 was reduced to 13,612 stems per acre by 1972. White Aster (*Aster pilosus*) which had 122,970 stems per acre in 1963 was not present on the site in 1972. The predominant species on the irrigated plot was clearweed (*Pilea pumila* L.) which covered more than 75 percent of the plot with approximately 19 million stems per acre. This species is typical of shaded moist sites.

Species composition changes are illustrated in Table 14 based on measurements made in 1972. The control plot is representative of preirrigation vegetation conditions.

The average height of the tallest plant species on the irrigated plot was 5.3 feet in comparison to 1.8 feet on the control plot. While the irrigated plot had a complete dense vegetative cover approximately 10 percent of the control was barren of vegetation.

TABLE 14. Predominate Herbaceous Vegetation Species on the Irrigated and Control Plots of White Spruce Area in 1972

Species	Irrigated Plot		Control Plot	
	Percent cover	Average height	Percent cover	Average height
	%	feet	%	feet
Goldenrod (<u>Solidago juncea</u>)	1	2.8	5	1.8
Aster (<u>Aster spp.</u>)	0	--	5	1.1
Dewberry (<u>Rubus flagellaris</u>)	0	--	40	0.8
Strawberry (<u>Fragaria vesca</u>)	5	0.9	10	0.5
Poverty grass (<u>Danthonia spicata</u>)	0	--	20	0.3
Everlasting (<u>Antennaria spicata</u>)	0	--	5	0.1
Goldenrod (<u>S. rugosa</u> , <u>S. graminifolia</u> , <u>S. juncea</u>)	5	5.3	0	--
Milkweed (<u>Asclepias rubra</u>)	5	5.1	0	--
Indian Hemp (<u>Apocynum cannabinum</u>)	5	3.3	0	--
Night shade (<u>Solanum dulcamara</u>)	10	2.3	0	--
Clearweed (<u>Pilea pumila</u>)	75	1.5	0	--

Coniferous Tree Seedling Growth Responses

In 1965 eight coniferous tree species were planted in an old-field area to determine which species might be best suited for sites to be used as disposal areas for sewage effluent. One- and two-year-old seedlings of European larch (*Larix decidua*), Japanese larch (*Larix leptolepis*), white pine (*Pinus strobus*), red pine, white spruce, pitch pine (*Pinus rigida*), Austrian pine (*Pinus nigra*), and Norway spruce (*Picea abies*) were planted in a randomized block design with three blocks irrigated with 2 inches of sewage effluent per week and three blocks maintained as a control. Each block contained 10 trees of each species or a total of 80 trees per block. Average first-year survival on the irrigated plots was 88 percent and on the control plots, 52 percent. At the termination of the study in 1970 survival percentage on the irrigated plots was still 88 percent, whereas the survival percentage on the control plots had decreased to 41 percent. The total height growth of surviving tree seedlings as of 1970 is given in Table 15.

TABLE 15. Total Height Growth of Surviving Tree Seedlings During the Period 1965 to 1970

Species	Irrigated Plots		Control Plots	
	Survival	Height	Survival	Height
	%	feet	%	feet
European larch	23	8.7	0	--
Japanese larch	17	8.4	0	--
White pine	70	6.3	17	2.6
Red pine	40	5.4	20	2.0
White spruce	30	4.3	3	2.8
Pitch pine	3	3.8	3	1.4
Austrian pine	13	3.6	13	2.1
Norway spruce	47	3.6	7	1.6

Results indicate that European and Japanese larch and White pine had the greatest growth response to sewage effluent irrigation.

Hardwood Species Growth Responses

Mixed hardwood forests, consisting primarily of oak species, have been irrigated with sewage effluent at rates ranging from 1 inch to 4 inches per week and for periods ranging from the growing season

(28 weeks) to the entire year (52 weeks). Principal species are white oak (*Quercus alba* L.), chestnut oak (*Q. prinus* L.), black oak (*Q. velutina* L.), red oak (*Q. rubra* L.), scarlet oak (*Q. coccinea* Muench.), red maple (*Acer rubrum*), and hickory (*Carya* spp.).

Average annual diameter growth in various treatment areas from increment core measurements in 1972 is given in Table 16. One inch per week applications produced only slight increases in diameter growth on the older trees (age); however, the 2- and 4-inch-per-week levels in a younger stand resulted in 69 and 40 percent increases, respectively. These values pertain primarily to the oak species. Some of the other hardwood species present on the plots have responded to a greater extent. For instance, increment core measurements made on young red maple and sugar maple (*A. saccharum*), indicate that the average annual diameter growth during the past 10 years has been 0.43 inch on the trees irrigated with 1 inch of effluent per week in comparison to 0.10 inch on control trees, a 330 percent increase in average annual diameter growth. Similarly, increment core measurements made on aspen (*Populus tremuloides*) irrigated with 2 inches of effluent weekly during the growing season indicated that the irrigated trees had an average annual diameter growth of 0.47 inch in comparison to 0.24 inch for unirrigated trees, a 96 percent increase in growth. Saplings which averaged 0.65 inch in diameter in 1963 increased in diameter to an average of 5.3 inches on the irrigated areas in comparison to 3.1 inches on the control areas.

TABLE 16. Average Annual Diameter Growth in Hardwood Forests Irrigated with Sewage Effluent

Weekly irrigation amount	Average diameter growth	
	Control	Irrigated
inches	inch	inch
1 ^{1/}	0.16	0.18
2 ^{2/}	0.13	0.22
4 ^{3/}	0.15	0.21

1/ Irrigated with 1 inch of sewage effluent weekly during growing season from 1963 to 1972.

2/ Irrigated with 2 inches of sewage effluent weekly during the entire year from 1965 to 1972.

3/ Irrigated with 4 inches of sewage effluent weekly during the growing season only from 1964 to 1967; during the dormant season only from 1968 to 1971; and with 2 inches of effluent weekly during the growing season in 1972.

Tree Seedling Reproduction

Mil-acre plots were established in 1964 in the hardwood forest irrigated with 1 inch of effluent weekly. These plots have been measured annually to determine the effect of wastewater irrigation on tree seedling reproduction and growth of herbaceous vegetation. Measurements made in 1972 after 10 years of sewage effluent irrigation indicate a drastic reduction in the number of tree seedlings present in the irrigated area. The initial survey in 1964 indicated about 15,800 tree seedlings per acre in the control area with a slight reduction to 13,600 in 1972. However, in 1964 (the second year of irrigation) there were 14,500 tree seedlings per acre present in the irrigated area and only 1,830 in 1972. No conclusive evidence is yet available to explain these results. These results may be partially due to the fact that effluent irrigation stimulates leaf growth which produces a more dense canopy and reduces light intensity at the forest floor. Average light intensity under the canopy in the irrigated area was less than 50 percent of that under the control plot canopy.

A similar reduction was also found in the number of herbaceous plants in the irrigated area. The initial survey in 1964 indicated about 86,333 stems per acre, whereas in 1972 there were only 14,800 stems per acre. On the control area, the 1964 survey indicated 63,170 stems per acre in comparison to 25,000 stems per acre in 1972.

Mortality

In 1972 a survey was made in the irrigated and control forested areas at the Gamelands site to determine the effect of 8 years of sewage effluent irrigation on mortality. Mortality was defined as all standing dead trees. The irrigated plot received 4 inches of sewage effluent weekly during the growing season only from 1964 to 1967; during the dormant season only from 1968 to 1971; and 2 inches of effluent weekly during the growing season in 1972. The results of the survey are given in Table 17. Results indicated that there was no difference in mortality between the irrigated and control areas. There was, however, a large difference in the number of living trees per acre, particularly, in the 2-inch diameter class. Unirrigated forest areas averaged 290 trees per acre in the 2-inch diameter class compared to only 70 trees per acre in the irrigated forest areas.

Although many of these young saplings are lost through natural suppression, a considerable number are lost in the irrigated areas through ice breakage during winter irrigation. The 1972 survey results indicated that approximately 52 stems per acre showed visible ice damage in the irrigated areas in comparison to 7.5

TABLE 17. Population and Mortality in Forested Stands in Control Plots and Plots Irrigated with Sewage Effluent for Eight Years

Diameter class	Living trees		Mortality	
	Irrigated	Control	Irrigated	Control
inches	stems per acre		stems per acre	
2	70	290	55	42
4	100	110	27	32
6	40	80	20	5
8	60	80	2.5	2.5
10	40	50	--	5
12	30	25	--	--
14	2	7	--	--
16	5	--	--	--
Total	347	642	104.5	106.5

stems per acre in the control areas. Seventy-five percent of these trees were in the 2-inch diameter class and the remainder in the 4-inch diameter class. The species most susceptible to ice damage was red maple. A reasonable amount of ice damage must be expected if disposal systems are to operate throughout the year. In northern latitudes where the temperatures drop below freezing, the system must rely more on the adsorptive capacity of the soil and less on the microbial activity and vegetation for renovation of the wastewater. During the winter period, forested areas provide better infiltration conditions. They also provide larger phosphorus-adsorptive capacity due to the acid conditions associated with forest soils. Ice damage can be minimized through the proper design of the spray-irrigation system and the use of low-trajectory rotating sprinklers (Parizek et al, 1967; Myers, 1973).

A comparison of the results of the 1972 survey made in the effluent-irrigated forest areas with the results of forest surveys (Melton, 1972) of several mixed hardwood stands on a variety of sites in central Pennsylvania indicate that 10 years of effluent irrigation have produced no great differences. The average number of living trees, 5 inches in diameter and greater, in the effluent-irrigated forests was 177 stems per acre in comparison to an average of 155 stems per acre in several natural mixed hardwood stands. Mortality of trees, 5 inches in diameter and greater, in the effluent-irrigated forests was 22.5 stems per acre in comparison to an average 21 stems per acre in several natural mixed hardwood stands.

Annual Nutrient Balance

Foliar samples were collected annually up to 1967 from the hardwoods, red pine, white spruce, and herbaceous vegetation to determine the extent of utilization of the nutrient elements applied in the sewage effluent. The nutrient element contents of the vegetation foliage based on samples collected in August 1967 are given in Table 18. Average concentrations of N, B, P, mg, Cu, and Na were almost consistently higher on the irrigated plots than on the control plots. Conversely, average concentrations of K, Mn, Al, and Zn were generally lower on the irrigated plots. Concentrations of Ca and Fe were highly variable and indicated no distinct trends. It is therefore obvious that the forest vegetation is contributing to the renovation of the percolating effluent; however, its order of magnitude is difficult to estimate because the annual storage of nutrients in the woody tissue and the extent of recycling of nutrients in the forest litter are extremely difficult to measure. Although considerable amounts of nutrients may be taken up by trees during the growing season, many of these nutrients are redeposited annually in leaf and needle litter rather than being hauled away as in the case of harvested agronomic crops. Tree leaves are by far the largest single source of forest soil organic matter, and their annual contribution of mineral elements to the soil greatly exceeds that of all other tree parts combined.

A comparison between the annual uptake of nutrients by an agronomic crop (silage corn) and a hardwood forest is given in Table 19. It is obvious that trees are not as efficient renovating agents as agronomic crops. Whereas harvesting a corn silage crop removes 145 percent of the nitrogen applied in the sewage effluent, the trees only remove 39 percent most of which is returned to the soil by leaf fall. Similarly only 19 percent of the phosphorus applied in the sewage effluent is taken up by trees in comparison to 143 percent by the corn silage crop.

Problems of Forest Irrigation

Three potential problems that may be encountered with effluent irrigation in forested areas are (1) ice damage, (2) windthrow, and (3) bark damage by sprinkler spray. The ice breakage problem has already been discussed. Bark damage by sprinkler spray can be avoided if sprinkler nozzle pressures are operated at or less than 55 p.s.i. Nozzle pressures for the solid set system used in the forests on the Penn State project are approximately 50 p.s.i. Little tree damage has been observed even on small trees within a 2-foot radius of the sprinkler head.

TABLE 18. Average Chemical Content of the Tree Foliage and Herbaceous Vegetation from Samples Collected in 1967

Plot	N	P	K	Ca	Mg	Mn	Fe	Cu	B	Al	Zn	Na
	Percent of dry weight						$\mu\text{g/g}$					
Hardwood 1-inch Irrigated	2.45	0.22	0.86	1.00	0.14	1500	88	8	81	68	26	15
Control	2.20	0.18	0.87	0.99	0.08	1845	80	7	49	66	27	16
Hardwood 2-inch Irrigated	2.97	0.29	0.93	0.77	0.19	1830	81	7	117	50	33	13
Control	2.20	0.18	1.13	1.01	0.09	2725	83	8	65	80	25	16
Red pine 1-inch Irrigated	1.62	0.17	0.58	0.19	0.09	942	41	4	28	142	33	44
Control	1.15	0.16	0.53	0.29	0.09	1103	53	4	19	496	45	8
Red pine 2-inch Irrigated	2.17	0.13	0.52	0.26	0.10	947	58	4	33	97	32	114
Control	1.33	0.15	0.61	0.24	0.08	925	54	3	23	394	40	11
White spruce 2-inch Irrigated	2.19	0.29	0.67	0.84	0.12	517	90	6	38	57	35	117
Control	1.48	0.19	0.71	0.93	0.13	834	57	5	26	100	95	10
Old-field												
Vegetation 2-inch Irrigated	3.28	0.45	2.34	1.23	0.44	235	379	19	39	825	94	473
Control	1.30	0.16	1.19	1.09	0.13	642	400	13	35	958	95	28

TABLE 19. Annual Uptake of Nutrients by a Silage Corn Crop and a Hardwood Forest Irrigated with 2 Inches of Effluent Weekly During 1970

Nutrient	Corn Silage Pa. 602-A	Renovation efficiency ^{1/}	Hardwood forest ^{2/}	Renovation efficiency
	lbs/acre	%	lbs/acre	%
N	161	145	84	39
P	42	143	8	19
K	129	130	26	22
Ca	27	15	22	9
Mg	23	27	5	4

^{1/} Percentage of the element applied in the sewage effluent that is utilized and removed by the vegetation.

^{2/} Calculations based on an average annual leaf fall of 2825 pounds of dry matter per acre (Lutz and Chandler, 1946).

Windthrow of individual trees and large numbers of trees (the 1-acre red pine plot irrigated with 2 inches of effluent weekly) has been the greatest problem. Weekly irrigation of sewage effluent at rates of 1 and 2 inches per week keep the soil moisture status near field capacity and hence encourages the development of shallow tree root systems. In November of 1968, following a weekly application of 2 inches of sewage effluent, a heavy snowfall accompanied by strong winds resulted in the complete blow down of the one-acre plot. Since then several individual trees have also been windthrown in the mixed hardwood forests. Most of these trees have been adjacent to natural forest openings, agricultural fields, or power line rights-of-way. It appears that this problem could be minimized if an unirrigated buffer zone 50 to 100 feet wide were left on the windward side of any irrigated forest area. This buffer zone would provide a wind break against prevailing winds.

CONCLUSIONS

Sewage effluent irrigation during the past 10 years on cropland and in forestland has, for the most part, produced beneficial vegetation responses. Crop yields and tree growth were significantly increased. In addition the value of the vegetation as a renovating agent has been demonstrated to be a vital part of the system. For year-around operations a combination of cropland and forestland will provide the greatest flexibility in operating a system using the "living filter" concept.

ACKNOWLEDGEMENT

Research reported here is part of the program of the Waste Water Renovation and Conservation Project of the Institute for Research on Land and Water Resources, and Hatch Projects No. 1481 and 1809 of the Agricultural Experiment Station, The Pennsylvania State University, University Park, Pennsylvania. Portions of this research were supported by funds from Demonstration Project Grant WPD 95-01 received initially from the Division of Water Supply and Pollution Control of the Department of Health, Education, and Welfare and subsequently from the Federal Water Pollution Control Administration, Department of the Interior. Partial support was also provided by the Office of Water Resources Research, USDI, as authorized under the Water Resources Research Act of 1964, Public Law 88-379 and by the Pinchot Institute for Environmental Forestry Research, Forest Service, USDA.

REFERENCES

- Kardos, L. T. 1971. Recycling sewage effluent through the soil and its associated biosystems, Proc. Int. Symp. on Ident. and Measurement of Environmental Pollutants, pp 119-123, Ottawa, Ontario, Canada.
- Lutz, H. J. and R. E. Chandler. 1946. Forest Soils, John Wiley and Sons, Inc. New York, 514 pp.
- Melton, R. E. 1972. Personal communication.
- Myers, E. A. 1973. Sprinkler irrigation systems: design and operation criteria, Recycling Treated Municipal Wastewater and Sludge Through Forest and Cropland, The University Press.
- Parizek, R. R., L. T. Kardos, W. E. Sopper, E. A. Myers, D. E. Davis, M. A. Farrell, and J. B. Nesbitt. 1967. Waste water renovation and conservation, Penn State Studies No. 23, 71 pp.
- Sopper, W. E. 1971. Effects of trees and forests in neutralizing waste. In Trees and Forests in an Urbanizing Environment, Coop. Ext. Service, Univ. of Massachusetts, p. 43-57.
- Stone, E. L. and G. Baird. 1956. Boron level and boron toxicity in red and white pine, Jour. of Forestry 54:11-12.

ANATOMICAL AND PHYSICAL PROPERTIES OF RED OAK AND
RED PINE IRRIGATED WITH MUNICIPAL WASTEWATER

329 D

W. K. Murphey, R. L. Brisbin, W. J. Young, and B. E. Cutter
School of Forest Resources
The Pennsylvania State University

The amelioration of the mineral content of treated sewage effluent by the forest has been demonstrated (Sopper, 1971). The utility of the forest as a receptor for this effluent could be increased if beneficial tree response occurred. This forest could become an important fiber source if the irrigation resulted in increased growth, more uniform fibers, or fibers which had attributes sought by the papermakers. Primarily, the papermaker would like to have long, thin-walled cells with which to work. With this in mind, two studies were established in which the individual cells produced by effluent-irrigated trees were measured.

Red pine (*Pinus resinosa* Ait.) plantations were irrigated, beginning in 1963, (Table 1) with effluent throughout the growing season at rates of one and two inches per week from spraying heads 42 feet above the forest floor. Another two-inch application, beginning in 1964, utilized spraying heads on five foot risers. Specific gravity, mean annual increment and tracheid dimensions were measured from the growth rings developed throughout the period of irrigation and compared to those of nonirrigated wood grown during the same time or wood grown during a similar period immediately prior to irrigation.

Red oak (*Quercus rubra* L.) trees irrigated throughout the year beginning in 1965, at a rate of two inches per week were sampled to determine if irrigation altered the anatomy of these trees. Comparisons were made with wood in the same trees laid down prior to irrigation.

PROCEDURE

Selection of Sample Trees

Red Pine Study. Eight red pine trees were randomly selected in 1966 from one acre plantation plots irrigated with one-inch or two-inches per week of municipal wastewater. Control trees were obtained from adjacent untreated plots. The crown wood and stem wood were treated as separate populations. Mechanical properties of the wood were measured using American Society for Testing Material Standards (Murphey and Brisbin, 1970).

Table 1. Physical and Anatomical Properties of Red Pine Crown Wood Treatment Mean Separation at the $P \geq 0.05$ Level by Duncan's New Multiple Range Test

Specific Gravity ^a		Specific Gravity ^b		Ring Width		Tracheid Length		Tracheid Diameter		Ceil Wall Thickness	
Plot ^c	Mean ^d	Plot	Mean	Plot	Mean	Plot	Mean	Plot	Mean	Plot	Mean
01	0.335	01	0.333	C1	3.40	C2	1.51	C1	18.62	02	1.64
02	0.338	02	0.334	C2	4.05	02	1.51	U2	18.91	U2	1.68
U2	0.353	U2	0.351	U2	4.49	C1	1.53	C2	19.00	C1	1.70
C1	0.369	C1	0.361	02	4.56	U2	1.54	02	19.62	C2	1.75
C2	0.378	C2	0.377	01	4.83	01	1.63	01	20.61	01	1.77

^aComputed by the maximum moisture content method.

^bComputed by the pycnometric method.

^cPlot 01 - 1 in. irrigated (overhead); plot 02 - 2 in. irrigated (overhead); plot U2 - 2 in. irrigated (under canopy); plot C1 - 1 in control; plot C2 - 2 in. control.

^dAny two means not scored by the same line are significantly different.

Red Oak Study. At the end of the fifth growing season after initiation of treatment, six dominant or codominant red oak trees were randomly chosen from the natural stand irrigated at a rate of two inches per week throughout the year. Also, six control trees were cut from an adjacent nonirrigated area. Treated trees ranged in age from 30 to 58 years. The felled trees were bucked at 4, 10, 20, 30, and 40 foot heights. Discs were removed and the north face marked for orientation. Material was stored at 0° F until sectioned.

Cell Dimensions

The same procedure was utilized for all of the fiber measurements. Cell lengths were measured from macerated samples removed from each growth ring. Splinters were cooked at 135° C for 35 minutes in a solution of triethylene glycol and paratoluene sulfonic acid (Burkhart, 1966). After maceration, complete fiber separation was accomplished by shaking the sample in a container with distilled water and glass beads. The individual fibers were washed thoroughly then randomly retrieved and mounted in a glycerin gel on glass slides. A microprojector was used to project each slide on a screen using Technical Association of Pulp and Paper Industries (TAPPI) T232-SU68, except that each fiber was measured. Twenty-five tracheids were sampled for each growth ring position.

Cross Sections

Cell cross sections and cell wall thickness measurements were made from microtome sections prepared by dehydrating the designated block by passing it through increasing concentrations of absolute alcohol, prior to embedding in celloidin and sectioning. Sections 10-micrometers thick were cut, and celloidin removed by washing with ether. The sections were then stained with safranin and fast green and mounted. A compound microscope equipped with a filar micrometer was used to obtain the 25 measurements made for each growth ring and cell element investigated for each quadrant.

Ring Width Measurements

Individual ring widths were measured on green discs using a De Rouen Dendrochronograph. Two measurements at right angles to each other were made across the diameter of each disc, resulting in four ring width measurements for each disc. Data reported are the mean annual increment values.

Specific Gravity Determination

The specific gravity or density of each growth ring was determined by using one or two of the several techniques available. The maximum moisture content procedure (Smith, 1954) or the standard pycnometric procedure was used for the small material obtained from some of the growth rings, particularly the red pine material. The wider growth rings found in the red oak were measured using the oven-dry weight-oven-dry volume by water immersion technique. Thirty-two observations were made for each mean red pine density value. One hundred and twenty measurements were represented in each mean calculated in the red oak study.

Abnormal Wood

The procedures outline above were conducted to insure no abnormal (compression or juvenile wood in red pine or tension wood in red oak) existed in the samples. Static bending tests, specific gravity determinations and shrinkage values support the contention that no abnormal wood existed in any of the material sampled.

Control Material

In both the red pine and red oak studies specific gravity determinations of the wood grown during the period prior to irrigation indicated that the mean density of the trees grown on the treated and untreated areas were not the same. Since this control period density was not comparable for differences existing prior to treatment for trees located in designated plots, data from control trees were not used. The material that was then used as a control was that wood grown prior to treatment in each of the treated trees. Thus, all data are within tree comparisons. The exception, of course, is the crown wood data where comparisons had to be made between material obtained from treated and untreated red pine trees.

RESULTS

Each variable measured was subjected to analysis of variance. If a difference existed between treatments at the $P \geq 0.05$ level, Duncan's Modified (Bovesian) least significant difference test (1965) was conducted. The results are shown in the following Tables.

Red pine crown wood response to one-inch irrigation is the most striking (Table 1). Although the plot 01 specific gravity is significantly less than all others except plot 02, the ring width and tracheid length are significantly greater than any of those of any other treatment. Tracheid diameters are comparable to those

developed in the two-inch overhead irrigation treatment plot while cell wall thickness is comparable to the two-inch control.

Density is definitely affected by the irrigation with the municipal wastewater. Also notable is the median position of the specific gravity of the plot receiving two inches per week on the undergrowth. Perhaps this is a development associated with the relatively high mineral content of the irrigation water placed on the forest floor rather than on the canopy.

The red pine stem wood means are listed in Table 2. Comparisons are made only between irrigation and pre-irrigation stem wood within plots. Growth rate and tracheid length prior to irrigation did not differ from that during irrigation. Specific gravity for 01 and U2 plots increased due to irrigation. The 02 plot receiving 2 inches per week had significantly lower specific gravity. Generally tracheid diameter increased and cell wall thickness decreased when the red pine was irrigated. Differences were statistically significant except for the tracheids from the red pine receiving 1-inch per week and the latewood of the trees from the U2 plot.

The red oak data shown in Table 3 demonstrated the more complex anatomy of this ring porous species. Those average percent change values listed are those where differences existed at the $P \geq 0.05$ level. Statistically significant changes in anatomy occurred in all but two of the variables measured--fiber cell wall thickness and broad ray width. Percent change was calculated by using the before-treatment mean as the base. From it the during-treatment value was subtracted. The resulting value was divided by the base value and the answer multiplied by 100 to arrive at the percentage. Significance was obtained by analysis of variance and Duncan's test on the mean values.

DISCUSSION

A review (Sopper, 1971) of applications of municipal and industrial wastewater on forest and crop lands is indicative of the lack of regard for the response and possible utility of trees receiving such irrigation. Little work has been done regarding the effects of combined fertilizer and irrigation treatments on forest trees. Smith et al (1972) in a study of six-year-old slash pine found irrigation plus fertilization increased the growth rate with no effect on the specific gravity. In our study the red pine crown wood response to irrigation by the mineral rich effluent was an increase in growth rate with significant decrease in specific gravity. Zahner (1962) examined five-year-old loblolly pine grown under two soil moisture regimes. Trees grown in drought conditions had a higher percentage of summerwood and reduced growth when compared to those trees growing on near field capacity soil. Zobel, Kellison

Table 2. Physical and Anatomical Properties of Red Pine Stem-Formed Wood Grown on Irrigated Plots

Plot Period	Specific gravity	Mean annual increment	Tracheid length		Tracheid diameter		Cell wall thickness	
			mm	μm	Earlywood	Latewood	Earlywood	Latewood
01 Prior to irrigation ^b	0.401	2.81	2.93	38.00	34.41	2.37	6.12	
01 Irrigated ^c	0.408	2.99	2.63	38.81	34.82	2.35	5.79	
02 Prior to irrigation	0.379	2.81	3.07	37.36	33.73	2.00	5.10	
02 Irrigated	0.367	2.50 ^a	2.84	38.20	34.79	1.91	4.48	
U2 Prior to irrigation	0.387	2.40	3.02	37.62	34.00	1.83	5.00	
U2 Irrigated	0.408	1.74	3.14	38.84	34.82	1.77	4.64	

^aControl plot mean annual increment during the treatment period was: C1 = 2.37 mm, C2 = 2.95; neither value is significantly different at the $P \geq 0.05$ level from corresponding treated plot. Prior to irrigation, control plot growth was C1 = 2.89mm and C2 = 3.59mm. The C2 plot grew at a significantly greater rate than all other plots prior to irrigation.

^bGrowth rings 5,6,7, and 8 from bark.

^cGrowth rings 1 and 2 from bark.

Table 3. Response of Red Oak to Irrigation by Municipal Wastewater and the Treatment Effect on Anatomical Properties

Variables	Before treatment	During treatment	Average change*
EW ^a vessel segment length (mm)	0.339	0.441	$\frac{\%}{+30}$
EW vessel segment diameter (mm)	0.255	0.242	-5
EW vessel cell wall thickness (μm)	7.44	8.42	+13
LW ^b vessel segment length	0.472	0.504	+7
LW vessel segment diameter (mm)	0.079	0.076	+4
LW vessel cell wall thickness (μm)	8.49	9.05	+7
Fiber length (mm)	1.360	1.427	+5
Fiber diameter (μm)	13.83	14.11	---
Fiber cell wall thickness (μm)	4.92	4.92	---
Broad ray number	17.04	21.02	-24
Broad ray height (mm)	7.16	7.56	+6
Broad ray width (mm)	0.377	0.369	---
Growth ring width (mm)	2.55	4.18	+63
Specific gravity (O. D. volume)	0.634	0.664	+5
Percent EW	44.9	25.2	-44
Percent LW	55.1	74.8	+36

*Percentage shown is significant at $P \geq 0.05$ level.

^aEW = earlywood

^bLW = latewood

and Kirk (1972) examined wood properties of the crown wood and juvenile wood and compared them to 25-year-old loblolly and slash pines. They found crown wood of mature trees low in specific gravity compared to that of the stem wood. Tracheid dimensions were also less than mature stem wood but tracheid length was greater than juvenile wood. Brunden (1964) states crown wood and stem wood are separate populations. This study confirms the properties of red pine crown and stem wood must be considered separately. Thus no combining of data would be in order. Tracheids are altered favorably if paper pulp is the intended use of the wood. Paper properties related to fiber-to-fiber bonding are improved because the lower density, thinner-walled tracheids conform better in a paper sheet.

The red pine stem wood response to irrigation by municipal wastewater was an increase in density with no change in ring width, except in those trees irrigated from 5-foot risers, or tracheid length. Again the literature related to irrigation plus fertilization is sparse. Most of that which is available concerns non-porous species. Howe (1968) attributed an increase in specific gravity to irrigation of ponderosa pine. Larson (1957, 1963) and Van Buijtenen (1958) state specific gravity increased due to heavy summer precipitation but decreased if heavy spring precipitation occurred. Application of fertilizers resulted in the decrease of specific gravity (Williams and Hamilton 1961, Siddiqui, Gladstone and Marton 1972, Zobel et al 1961). Specific gravity increased in two treatments (01 and U2) and decreased in the third (02). This overhead 2-inch plot was reported to have been dying and infrared pictures of the area indicated these trees were not normal. The plot was blown down the winter following sampling. Posey (1964) reported tracheid length was reduced 5 to 10 percent in fertilized loblolly pine while tangential tracheid diameter was unaffected. Cell wall thickness was reduced in the fertilization studies. Zobel et al (1961) found no differences in tracheid length as a result of fertilization. The 1-inch per week rate did not effect tracheid diameter or earlywood tracheid wall thickness. Latewood tracheid thickness was reduced. Those trees receiving 2-inches per week developed wider tracheids with reduced cell wall thickness. Tracheid length was unchanged in trees irrigated at both levels in this study. Tracheid diameters ranged from unchanged in the 1-inch application to an increase of six percent in latewood tracheids in trees from the U2 plot.

There is much less literature concerning irrigation and fertilizer effects on ring-porous wood than on non-porous wood. Broadfoot (1964) found radial growth increased significantly in several hardwoods when irrigated. Mitchell (1972) reported similar response to nitrogen for several species of hardwoods and from his study concluded, where valid comparisons could be made, there was a trend toward increasing specific gravity with increasing growth rate. Saucier and Ike (1972) state specific gravity and fiber length of young sycamore are positively correlated with rate of growth. Stand

thinning rather than nitrogen accounted for growth in their study. They also concluded the proportional values of fibers, vessels and rays were unaffected by growth rate. Aspen response to irrigation and fertilization reported by Einsphar, Benson and Harder (1972) was considerable. A 140 percent increase in volume occurred in trees in the fertilizer plus water treatment series when compared to the untreated control. Specific gravity was significantly lower. Tissue composition remained the same while fiber length was greater in trees grown in irrigated plot and this increase in fiber length was related to total height of trees. In our study tissue composition did change; however, no statistical relationship existed between any dependent variable when height was the independent variable.

Positive changes occurred in the red oaks due to irrigation with effluent. The five percent reduction in earlywood vessel segment diameter may reduce a problem associated with pulps from ring porous woods. These large barrel-shaped elements are causes of "picking"; the lifting of the surface of paper during printing. The smaller, longer cell may be less likely to pick. Unlike the sycamore (Saucier and Ike 1972), a change in tissue composition did occur in the red oaks. An increase in the number and height of broad rays resulted in an increase in the amount of wood volume occupied by the broad rays from nine percent in the untreated xylem to 11.5 percent of the wood laid down during irrigation. The increase in number and height of broad rays would cause an increase in the percentage of "fines" in a pulp mix. Increase in specific gravity and particularly the change in the amount of latewood from about one-half to three-quarters of the growth ring provides more mass of fibers per unit volume. Coupled with the growth rate change, irrigation with municipal wastewater results in the development of more fiber per treated tree. The increase in fiber and vessel segment length also increased the utility of this wood for pulp. Wangaard and Williams (1970) have shown a relationship exists between fiber length and tear strength for known paper sheet densities and fiber strength. The longer the fiber the stronger the paper for a given fiber strength below a critical sheet density.

Horn (1972) shows a curvilinear relationship exists between burst strength and a ratio between fiber length (L) and cell wall thickness (T) for twelve western softwoods. Although these data are not directly applicable, the probability that a similar relationship exists with the red pine tracheid and red oak fibers and vessel segments is good. Tables 4, 5 and 6 show L/T data for this study. The changes in the L/T value are not large. Changes in the L/T ratio of red pine tracheids similar to those shown by Horn (1972) would result in a five to eight percent increase in burst strength of paper. Also, tracheids from those plots where a significant reduction in cell wall thickness took place should conform better in the paper sheet. In the red pine, differences in L/T between

Table 4. Red Pine Crown Wood Fiber Length to Cell Wall Thickness Ratio Values

Plot	Fiber length	Cell wall thickness	Ratio L/T
	mm	μm	
O1	1.63	1.77	920.9
O2	1.51	1.64	920.7
C1	1.53	1.70	900.0
C2	1.51	1.75	862.9
U2	1.54	1.68	916.7

Table 5. Red Pine Stem Wood Fiber Length to Cell Wall Thickness Ratio Values

Plot	Period	Fiber length mm	Cell wall thickness		Ratio L/T	
			Earlywood	Latewood	Earlywood	Latewood
			μm	μm	μm	μm
01	Prior to irrigation	2.93	2.37	6.12	1236.3	478.8
01	Irrigated	2.63	2.35	5.79	1119.1	454.2
02	Prior to irrigation	3.07	2.00	5.10	1535.0	601.9
02	Irrigated	2.84	1.91	4.48	1486.9	633.9
U2	Prior to irrigation	3.02	1.90	4.85	1589.4	622.6
U2	Irrigated	3.14	1.77	4.64	1774.0	676.7

Table 6. Red Oak Fiber Length to Cell Wall Thickness Ratio Values

Period	Vessels						Fibers	
	Earlywood			Latewood			Length mm	Cell wall thickness μm
	Length mm	Cell wall thickness μm	L/T	Length mm	Cell wall thickness μm	L/T		
Prior to irrigation	0.34	7.4	45.9	0.47	8.5	55.3	1.36	4.9
Irrigated	0.44	8.4	52.4	0.50	9.1	54.9	1.43	4.9
								277.6
								291.8

plots prior to irrigation are indicative of the problem confronting us when making inferences from the data. These trees on the various plots were not similar prior to irrigation thus all inferences must be made within a plot.

One other attribute developed by the xylem grown during irrigation by municipal wastewater is a reduction in the variability about the mean for most cell dimensions measured. Megraw and Nearn (1972) in a study of fertilized Douglas fir stated a reduction in range of within-ring densities should contribute favorably to pulp characteristics.

CONCLUSIONS

The technique of using the forest to ameliorate treated sewage plant effluent while charging the ground water can alter the properties of the wood being produced. Primarily this study was concerned with the utility of wood grown in such a forest for pulp wood. The anatomy of two species studied responded in a similar manner as that reported in the related but not comparable literature. The morphology of the pulp fiber is important in the strength and conformity of the paper sheet and, therefore, the utility of the pulp. Alteration of the dimensions of the pulp fibers by the wastewater were such as to enhance their use as a raw material for paper. The lack of a separate control area did restrict the findings; however, the following conclusions may be made:

1. The response to irrigation by 2 inches of municipal wastewater weekly by red pine crown wood was a lower specific gravity, greater ring width, and no change in tracheid length. The red pine irrigated at 1-inch per week had longer tracheids, and larger, thicker cell walls than the red pine irrigated with 2 inches or the red pine receiving no irrigation.
2. Specific gravity of stem wood of red pine increased in two treatments (01 and U2) and decreased in the third (02). Tracheid length and ring width were unaffected. Increases in earlywood and latewood tracheid diameters occurred in the trees receiving the 4-year, 2-inch per week applications and in the latewood tracheid diameter of the 3-year, 2-inch per week plot. Latewood tracheid cell wall thickness decreased as a result of irrigation by municipal wastewater.
3. Red oak responded favorably to irrigation at the 2-inch per week rate. Specific gravity, percent latewood, and cell dimension changes are considered plus factors in the utility of the material for wood pulp.

The results of these experiments indicate that a 1-inch spray enhanced the fiber properties of red pine. A 2-inch application of the effluent was beneficial if red oak is to be used as a pulp species.

4. If similar projects are to be considered, the multiple relationships of crop response, wastewater amelioration and other facets demonstrated by this entire study should consider effects on forest products, particularly as a wood pulp source in the initial planning. This would permit more inferences regarding the xylem of those trees studied.

REFERENCES

- Broadfoot, W. M. 1964. Hardwoods respond to irrigation, Jour. Forestry 62:579.
- Brunden, M. N. 1964. Specific gravity and fiber length in crown-formed and stem-formed wood, Forest Prod. Jour. 14(1): 13-17.
- Burkhart, L. F. 1966. New technique for maceration of woody tissue, Forest Prod. Jour. 16(7):52.
- Duncan, D. B. 1965. A Bayesian approach to multiple comparisons, Technometrics. 7:171-222.
- Einsphar, D. W., M. K. Benson, and M. L. Harder. 1972. Influence of irrigation and fertilization on growth and wood properties of quaking aspen. Proc. of the Symp. of the Effect of Growth Acceleration on the Properties of Wood. U.S. Dept. Agric. Forest Service, Forest Products Lab., Madison, Wisconsin.
- Horn, R. A. 1972. Fiber morphology considerations in paper properties. Proc. of the Symp. on the Effects of Growth Acceleration on the Properties of Wood, U.S. Dept. of Agric. Forest Service, Forest Products Lab., Madison, Wisconsin.
- Howe, J. P. 1968. Influence of irrigation on ponderosa pine. Forest Prod. Jour. 18(1):84-93.
- Larson, P. R. 1957. Effect of environment on the percentage of summerwood and specific gravity of slash pine, Yale Univ. School Forestry Bull. No. 63.
- Larson, P. R. 1963. The indirect effect of drought on tracheid diameter in red pine, Forest Sci. 9(1):18-27.
- Megraw, R. A. and W. T. Nearn. 1972. Detailed DBH density profiles of several trees from Douglas-fir fertilizer/thinning plots, Proc. of the Symp. on the Effect of Growth Acceleration on the Properties of Wood, U.S. Dept. Agric. Forest Service, Forest Products Lab., Madison, Wisconsin.
- Mitchell, H. L. 1972. Effect of fertilizer on the growth rate and certain wood quality characteristics of sawlog red oak, yellow poplar, and white ash, Proc. of the Symp. on the Effect of Growth Acceleration on the Properties of Wood, U.S. Dept. Agric. Forest Service, Forest Products Lab., Madison, Wisconsin.

- Murphey, W. K. and R. L. Brisbin. 1970. Influence of sewage plant effluent variation on crown wood and stem wood of red pine, Pa. Agric. Expt. Sta. Bull. 772.
- Posey, C. E. 1964. The effects of fertilization upon wood properties of loblolly pine, (*Pinus taeda* L.), North Carolina State College School of Forestry, Tech. Report No. 22, 62pp.
- Saucier, J. R. and A. F. Ike. 1972. Response in growth and wood properties of American sycamore to fertilization and thinning, Proc. of the Symp. on the Effect of Growth Acceleration on the Properties of Wood, U. S. Dept. Agric. Forest Service, Forest Products Lab., Madison, Wisconsin.
- Siddiqui, K. M., W. T. Gladstone, and R. Marton. 1972. Influence of fertilization on wood and pulp properties of Douglas-fir, Proc. of the Symp. on the Effect of Growth Acceleration on the Properties of Wood, U.S. Dept. Agric. Forest Service, Forest Products Lab., Madison, Wisconsin.
- Smith, D. M. 1954. Maximum moisture content method for determining specific gravity of small wood samples, U.S. Dept. Agr. Forest Service, Forest Prod. Lab. Report No. 2014.
- Smith, D., H. Wahlgren, and G. W. Bengtson. 1972. Effect of irrigation and fertilization on wood quality of young slash pine, Proc. of the Symp. on the Effect of Growth Acceleration on the Properties of Wood, U.S. Dept. Agric. Forest Service, Forest Products Lab., Madison, Wisconsin.
- Sopper, W. E. 1971. Effects of trees and forests in neutralizing waste, Trees and Forest in an Urbanizing Environment, Univ. of Mass. Cooperative Ext. Service.
- Van Buijtenen, J. P. 1958. Experimental control of environmental factors and their effect on some aspects of wood anatomy in loblolly pine, TAPPI 41(4):175-178.
- Wangaard, F. F., and D. L. Williams. 1970. Fiber length and fiber strength in relation to tearing resistance of hardwood pulps. TAPPI 53(11):2153-2154.
- Williams, R. E. and J. R. Hamilton. 1961. The effect of fertilization on four wood properties of slash pine, Jour. Forestry 59(9):662-665.
- Zahner, R. 1962. Terminal growth and wood formation by juvenile loblolly pine under two soil moisture regimes. Forest Sci. 8(4):345-352.
- Zobel, B. J., J. F. Goggans, T. E. Maki, and F. Hensen. 1961. Some effects of fertilizers on wood properties of loblolly pine, TAPPI 44(3):186-192.
- Zobel, B. J., R. C. Kellison, and D. G. Kirk. 1972. Wood properties of young loblolly and slash pine, Proc. of the Symp. on the Effect of Growth Acceleration on the Properties of Wood, U.S. Dept. Agric. Forest Service, Forest Products Lab., Madison, Wisconsin.

DISCUSSION

Mace: Did you conduct tests relative to the strength properties?

Cutter: Yes. We did.

Mace: Was it positive or negative for red oak?

Cutter: For red oak it was negative. The modulus of elasticity and modulus of rupture was decreased. We conducted strength properties on both the red pine and the red oak. In the red oak, the specific gravity was increased. You might expect strengths to increase also but it did not. It was decreased as a result of the irrigation with sewage effluent.

DEER AND RABBIT RESPONSE TO THE SPRAY
IRRIGATION OF CHLORINATED SEWAGE EFFLUENT
ON WILD LAND

G. W. Wood, D. W. Simpson and R. L. Dressler
School of Forest Resources
The Pennsylvania State University

330D

That chlorinated sewage effluent can be renovated and recycled to the groundwater table by spray irrigation on agronomic and forest lands appears to have been well documented. Three important gains from this wastewater disposal method are recognized: (1) conservation of the water resource, (2) elimination of a stream pollution source, and (3) increased crop production on the irrigation sites.

While the water, soil, and floral response to wastewater irrigation have been intensively studied, very little attention has been paid to faunal response. The latter will be of tremendous importance in environmental impact statements presented to the public where this treatment system might be deployed. If there is a general belief among the public that this type of land treatment is deleterious to wild birds and mammals, there is small chance that it will be instituted on a large scale. This is primarily true, of course, where the system would be deployed on publicly-owned land. In fact, the institution of the current studies of faunal response to wastewater irrigation was a result of just such sentiment regarding the use of Pennsylvania State Game Lands 176 for expansion of the Penn. State Wastewater Renovation Facility.

OBJECTIVES

The first efforts in evaluating the effects of sewage effluent irrigation on wild animals have been directed toward the principal game species on the treatment areas. The cottontail rabbit (Sylvilagus floridanus) and the white-tailed deer (Odocoileus virginianus) are rated as high priority species by hunters using State Game Lands 176. The first objective was to determine changes in the nutritive value of rabbit and deer foods that were caused by the irrigation treatment. The second objective was to determine the effects of the treatment on deer feeding behavior. That is, do the deer feed on treated sites as readily as untreated sites? Thirdly, it was intended to determine whether or not rabbits could reproduce and survive if they were restricted to treatment sites.

PROCEDURES

Changes in nutritive values of foods were evaluated by simultaneously collecting samples of plant parts by species known to be used as a food source by rabbits and/or deer at various times of the year. These samples were then dried at 65°C for 72 hours, ground in a Wiley mill, subsequently analyzed for crude protein, phosphorus, potassium, calcium, and magnesium. Crude protein determinations were by macro-Kjeldahl methods; P by the vanadomolybdophosphoric acid method (Jackson, 1958), and K, Ca, and Mg by atomic absorption spectrophotometry.

Digestion trials of a standard lab ration for rabbits and of alfalfa hay were run using adult female wild rabbits. These foods were used as standards for comparison of trials using Reed canarygrass from both treated and untreated sites. The digestion coefficients (DC) were calculated by the equation:

$$DC = \frac{\text{wt. of material ingested} - \text{wt. of material in feces}}{\text{wt. of material ingested}}$$

Deer feeding behavior studies are being done using the lead deer technique which was developed at Penn State some 10 years ago. Three animals, one two-year-old male, a yearling male, and a yearling female, have been and are continuing to be used as study animals. Each animal is transported to the study area two to three times each week and observed for a 90-minute period. The study area is 10.2 acres in size. Five acres receive two inches of chlorinated sewage effluent during an eight-hour period each week. An adjacent 5.2 acres serves as the control. The plants that the animals are observed utilizing as food, the time (in seconds) spent feeding on each of these plants, and the time spent on treated and untreated sites are recorded by the observer. Preference for foods by individual species and foods in general on variously treated sites are calculated by the following equation:

$$\text{Preference} = \frac{\frac{\text{Food biomass on site X}}{\text{Food biomass on total study area}}}{\frac{\text{Time spent feeding on site X}}{\text{Total time spent feeding}}}$$

Cottontail rabbit reproduction and survival studies on animals restricted to treatment sites receiving two inches of effluent during a 16-hour period each week have been carried on since May, 1971.

The study method has been to construct four 4-acre rabbit enclosures, two of which are treated and two untreated. The animals in each of these enclosures are periodically trapped, marked for identification, examined for nutritional condition, and released. Trapping has been done using the Mosby-type box trap with a trap density of ten per acre.

RESULTS AND DISCUSSION

Tables 1, 2, and 3 list a total of 32 plant species that were analyzed for total nutrient concentrations. In general, the crude protein, P, K, and Mg concentrations were higher on irrigated sites than adjacent control sites. The opposite was true for Ca. In all but four cases Ca concentrations were apparently lowered by the irrigation treatment.

It will be noted that the greatest differences in nutrient concentrations between treated and untreated sites occur among the plants sampled in the summer and the smallest differences between those sampled in the winter. This is not surprising since summer foods of wild herbivores are primarily composed of perennial and annual herbs, deciduous foliage, and unhardened current woody growth. These all have high proportions of active meristematic tissue, already high in nutrient concentrations, and presumably serves as a deposition site during luxury consumption of available nutrients. Although the differences between areas are not as pronounced during the fall and winter, there still appear to be real differences for many nutrients. That is, concentrations are still higher in winter although to a lesser extent than in summer.

Table 4 presents the results of several digestion trails on rabbit foods. As previously mentioned a standard lab ration for rabbits and alfalfa hay were run as references.

Obviously Reed canarygrass is not as good a food as either of the two from the standpoint of dry matter digestibility. On the other hand, the crude protein concentration is quite adequate and the plant is used as a food source to some extent in agricultural areas. Analysis of the effects of irrigation on its digestibility shows that treatment resulted in no significant changes in percentage of digestible dry matter or crude protein.

Studies of white-tailed deer feeding behavior in relation to the irrigation treatment indicate that the animals use treated sites at least as readily as untreated sites. Table 5 lists the preference indices based on available food biomass from May 1 to June 15 and relative sizes of study sites. When all three test

Table 1. Percentage Concentrations of Nutrients in Forages Collected in Pole-Sized Mixed-Oak Stands Irrigated with Two Inches of Sewage Effluent per Week (T) and on Adjacent Untreated Sites (U)

Species	Plant Part	Treat- ment	Month of Collection	Crude Protein	P	K	Ca	Mg
White Oak (<u>Quercus alba</u>)	leaves	T U	July	22.8 16.9	0.268 0.220	0.843 0.790	1.29 1.85	0.332 0.195
Flowering dogwood (<u>Cornus Florida</u>)	leaves & twigs	T U	July	21.6 12.9	0.414 0.208	1.658 0.902	3.55 3.91	0.721 0.422
Red Oak (<u>Q. rubra</u>)	leaves	T U	July	16.2 14.6	0.227 0.174	0.694 0.673	0.63 1.24	0.220 0.142
Chestnut (<u>Castanea dentata</u>)	leaves	T U	July	20.2 17.2	0.300 0.215	0.976 1.007	1.06 1.24	0.510 0.329
Sassafras (<u>Sassafras albidum</u>)	leaves & twigs	T U	July	32.2 19.7	0.541 0.274	2.824 2.569	0.89 1.32	0.285 0.229
Bracken fern (<u>Pteridium Aquilinum</u>)	fronds	T U	July	29.4 14.5	0.808 0.203	5.421 3.296	0.53 0.64	0.376 0.283
Whorled locstrife (<u>Lysimachia quadrifolia</u>)	leaves & stems	T U	July	25.9 16.1	0.573 0.237	4.820 3.562	0.77 0.73	0.340 0.220

Table 1. Continued

Species	Plant Part	Treat- ment	Month of Collection	Crude Protein	P	K	Ca	Mg
Huckleberry (<u>Gaylussacia</u> sp.)	leaves & twigs	T	July	14.0	0.188	0.705	0.87	0.311
		U		12.0	0.157	0.787	0.97	0.209
		T	Sept.	12.3	0.119	0.479	1.21	0.353
		U		12.4	0.101	0.565	1.48	0.191
Black cherry (<u>Prunus serotina</u>)	leaves & twigs	T	July	24.8	0.323	1.383	1.66	0.546
		U		17.3	0.336	1.973	1.82	0.455
		T	Sept.	19.6	0.195	0.444	1.32	0.400
		U		16.0	0.233	0.831	1.83	0.303
Red maple (<u>Acer rubrum</u>)	leaves & twigs	T	July	20.4	0.444	1.105	1.43	0.511
		U		11.9	0.191	0.748	1.20	0.233
		T	Sept.	17.5	0.389	0.539	1.39	0.408
		U		11.4	0.124	0.308	1.22	0.159
Teaberry (<u>Gaultheria procumbens</u>)	leaves & stems	T	July	11.8	0.224	0.819	1.20	0.372
		U		9.0	0.128	0.718	1.95	0.274
		T	Sept.	11.3	0.134	0.317	1.25	0.407
		U		9.4	0.085	0.277	1.89	0.279
Pokeberry (<u>Phytolacca americana</u>)	leaves & stems	T	July	40.2	0.552	9.383	0.76	1.105
		T	Sept.	32.4	0.451	4.159	0.94	1.439

Table 2. Percentage Concentrations of Nutrients in Forages Collected in Aspen-White Pine Stands Treated with Two Inches of Sewage Effluent per Week (T) and on Adjacent Untreated Sites (U) in October 1971

Species	Plant Part	Treatment	Crude Protein	P	K	Ca	Mg
Striped Pipsissewa (<u>Chimaphila maculata</u>)	leaves & stems	T U	16.6 14.7	0.256 0.267	0.386 0.558	0.938 0.933	0.217 0.137
Pipsissewa (<u>C. cisatlantica</u>)	leaves & stems	T U	12.3 10.2	0.218 0.206	0.125 0.379	1.435 1.300	0.221 0.175
Partidgeberry (<u>Mitchella repens</u>)	leaves & stems	T U	13.8 9.6	0.165 0.234	0.892 0.774	0.651 1.523	0.472 0.428
Ground Cedar (<u>Lycopodium tristachyum</u>)	leaves & stems	T U	9.7 7.0	0.143 0.101	1.142 1.017	0.209 0.234	0.115 0.170
Sheep sorrel (<u>Rumex acetosella</u>)	leaves	T U	19.0 15.6	0.767 0.254	2.175 1.878	0.650 0.654	0.325 0.200
Strawberry (<u>Fragaria</u> sp.)	leaves & stems	T U	15.7 11.0	0.601 0.408	1.278 0.521	1.505 1.680	0.305 0.237
Goldenrod (<u>Solidago</u> sp.)	leaves	T U	14.3 9.4	0.366 0.153	2.500 1.278	1.160 1.209	0.258 0.153
Yellow mustard (<u>Brassica rapa</u>)	leaves	T U	17.6 15.3	0.509 0.431	4.454 4.673	1.063 1.141	0.273 0.181

Table 2. Continued

Species	Plant Part	Treatment	Crude Protein	P	K	Ca	Mg
Plantain (<u>Plantago lanceolata</u>)	leaves	T U	12.1 10.2	0.414 0.449	2.825 2.595	2.111 2.009	0.251 0.132
Broadleaf plantain (<u>P. major</u>)	leaves	T U	15.8 10.3	0.365 0.260	2.072 0.849	1.935 1.558	0.427 0.356
	seed heads	T U	13.9 6.1	0.543 0.267	2.500 1.266	0.742 1.231	0.239 0.158
Birdsfoot trefoil (<u>Lutens corniculatus</u>)	leaves & stems	T U	24.6 21.0	0.340 0.203	1.327 0.514	1.055 1.644	0.183 0.247
White clover (<u>Trifolium repens</u>)	leaves & stems	T U	26.3 25.4	0.395 0.356	2.877 1.780	1.097 1.163	0.315 0.225
Wood sorrel (<u>Oxalis</u> sp.)	leaves & stems	T U	16.2 11.4	0.755 0.815	1.928 1.761	1.031 1.624	0.349 0.288
Virginia creeper (<u>Parthenocissus quinquefolia</u>)	leaves & stems	T U	12.7 9.0	0.404 0.266	0.929 0.682	2.633 2.380	0.350 0.391
Bigtooth aspen (<u>Populus grandidentata</u>)	leaves	T U	14.7 9.4	0.267 0.152	0.308 0.285	1.486 1.557	0.276 0.225
Gray dogwood (<u>Cornus racemosa</u>)	leaves	T U	11.5 8.9	0.263 0.287	0.514 0.324	2.128 2.229	0.371 0.293
Red maple (<u>Acer rubrum</u>)	leaves leaves	U U	12.4 10.3	0.267 0.218	0.316 0.641	1.177 1.072	0.276 0.179

Table 3. Percentage Concentrations of Nutrients in Forages Collected in Aspen-White Pine Stands Treated with Two Inches of Sewage Effluent per Week (T) and on Adjacent Untreated Sites (U) in February 1972

Species	Plant Part	Treatment	Crude Protein	P	K	Ca	Mg
Quaking aspen (<u>Populus tremuloides</u>)	bark	T	8.6	0.187	0.652	1.699	0.134
	browse ^a	U	6.3	0.131	0.571	1.886	0.104
Bigtooth aspen (<u>P. grandidentata</u>)		T	9.1	0.207	0.575	1.677	0.176
	bark	U	9.1	0.202	0.601	1.515	0.143
		T	7.3	0.167	0.583	2.038	0.147
	browse	U	6.9	0.138	0.515	1.702	0.103
Red maple (<u>Acer rubrum</u>)		T	10.2	0.232	0.682	1.489	0.154
	bark	U	7.5	0.191	0.467	1.518	0.167
		T	8.1	0.124	0.360	1.420	0.054
	browse	U	6.7	0.137	0.337	0.936	0.076
Staghorn sumac (<u>Rhus typhina</u>)		T	9.8	0.178	0.497	1.195	0.099
		U	7.3	0.156	0.373	1.768	0.090
	bark	T	10.1	0.201	1.317	0.859	0.114
		U	8.7	0.154	1.424	0.827	0.110
Blackberry (<u>Rubus allegheniensis</u>)	stems	T	6.5	0.139	0.269	0.489	0.106
		U	5.3	0.125	0.332	0.608	0.084
	twigs ^b	T	10.7	0.169	0.349	0.679	0.161
		U	8.4	0.142	0.516	0.794	0.169

^aTerminal two inches of twig growth.

^bTerminal eight inches of twig growth.

Table 4. Digestion Coefficients for Dry Matter and Crude Protein in Cottontail Rabbits

Forage	No. of Rabbits	Dry Matter	Crude Protein
Lab ration	10	.645 $\pm$.013	.697 $\pm$.027
Alfalfa hay	7	.496 $\pm$.016	.695 $\pm$.026
Reed canarygrass			
Irrigated	5	.330 $\pm$.033	.730 $\pm$.053
Control	3	.352 $\pm$.023	.622 $\pm$.088

Table 5. Indices of Site Preference by Semi-Free Ranging White-ailed Deer

	Irrigated	Transition	Non-irrigated
Index based on relative site size			
All test animals	1.33	0.85	0.59
2-yr-old male	0.94	1.32	0.92
Index based on relative amounts of food			
All test animals	1.46	a	0.63
2-yr-old male	1.03	a	0.93

^a The transition zone was not recognized in the biomass sampling.

animals are averaged there appears to be a definite preference for the treated site. This is probably a spurious relationship, however, due to the tendency of the two yearling animals to feed near the unloading area, which happened to be adjacent to the treated site. These animals did very little investigating of alternate feeding areas and fed only sporadically during testing periods. The 2-year-old buck, however, explored and fed readily on all sites. If anything the 2-year-old showed a preference for the transition zone between the treated and untreated sites.

This is a normal and somewhat predictable deer-use response to spatial changes in habitat. That is, the edges receive proportionately greater use. Beyond the "edge effect" response the treated site was used at about the same level as was the untreated.

No lead deer work has been done during the winter period. Studies of site use by wild deer have been conducted, however, using snow track and bed counts. Our observations indicate that the deer readily use irrigated sites during this period of the year for feeding and especially for resting. Numerous beds have been frequently observed in close proximity to the delivery sprinklers. There is some reason to believe that the animals may use the area during actual irrigation periods because of warmer ambient temperatures on the site during the spraying of the effluent which is about 75°F when it leaves the sprinkler.

After 1-1/2 years of studying two populations of rabbits confined to treatment sites and two populations on untreated sites, but similar habitat, we are still unable to get a measure of the influence of irrigation on rabbit reproduction. During the first year of study we were only able to state that there was at least some reproduction in all study populations. This was only because we caught at least one juvenile animal in each area during the trapping period. Since we started with uneven populations at the beginning of the study period in the spring of 1971, total population estimates in the following fall could give no clue as to what natural increases or decreases in the populations had occurred. In an attempt to remedy this situation we adjusted all study populations to six adult animals (2 males, 4 females) in the spring of 1972. Our summer trapping success in 1972 has been similar to that of 1971 allowing only the determination that we have some reproduction in all four populations. Based on our past experience we should be able to get good trapping success in October and November. At that time we should at least be able to determine any net changes in the populations.

Again due to the extreme difficulty of capturing rabbits during the late spring and summer months we have no measure of the influence of the irrigation treatment on rabbit survival during this time. We do have a good measure of winter survival, however. Table 6 presents the population estimates of the study areas based on the assumption of total population capture for Fall, 1971 and Spring, 1972.

Although the percentage survival was higher on non-irrigated sites (80 percent) than on irrigated sites (70 percent), the irrigated sites started with a 30 percent greater density and ended with one still higher by 11 percent. In addition, the animals on treated sites were superior to those on untreated sites with respect to nutritional condition. The former were all healthy

Table 6. Minimum Winter Survival on Irrigated and Non-Irrigated Sites Based on Total Population Capture in the Fall of 1971, and Number of Recaptures in Late Winter of 1972

	Number Marked Fall 1972			Recaptured Late Winter 1972		
	Males	Females	Total	Males	Females	Total
Irrigated site 1	3	6	9	3	4	7
Irrigated site 2	2	2	4	2	0	2
Non-irrigated site 1	2	3	5	2	1	3
Non-irrigated site 2	1	4	5	1	4	5

specimens at the end of the winter while the latter were as much as a third lighter in weight and showing obvious signs of emaciation. This phenomenon can be explained by several observations. First, it has already been pointed out that the nutritional quality of the foods available on irrigated sites was higher than that on non-irrigated sites. Secondly, there was more food available on treated sites during the winter due to the pulling down of sapling trees by the ice formation resulting from the spray irrigation. Thirdly, the ice mounds are laced with crevices and caves which offer and are heavily used by the rabbits for cover.

CONCLUSIONS

The spray irrigation of chlorinated sewage effluent at the rate of two inches per week appears to have a favorable influence on the nutritive value of rabbit and deer forages. Generally the crude protein, P, K, and Mg can be expected to be raised in these forages while the Ca is lowered. Reed canarygrass, the only forage tested for changes in digestibility due to treatment, showed no significant response with respect to digestible dry matter and protein.

Studies using the lead deer technique to determine preference for or avoidance of irrigated sites and forage from these sites indicate that the deer use treated sites at least as readily as untreated sites. During the winter period wild deer do not avoid the area but appear to use it quite readily for resting and feeding.

At this time we have no conclusive evidence of the effects of spray irrigation on rabbit reproduction. We do know that the winter carrying capacity of treated sites exceeds that of untreated sites presumably due to higher levels of available nutrition and improved cover conditions.

DISCUSSION

Unknown: Do you feel that the increase in the numbers of mosquitos and biting flies will at some time be a limiting factor as far as the wildlife is concerned in these areas that are under irrigation?

Wood: We don't have any good information to indicate that we do have increases in arthropod populations. We have only started collecting numerical data on this during the past year and this has been in relation to all of our studies. If this kind of thing is happening then we suspect that there might be a problem because the animal may avoid the area because of the insect nuisance there. We've seen

this in other areas. In some of our clearcut areas where we have deer fenced in and we're looking at the animals response to habitat changes and plant succession it was found that in the summer time the animals usually are in very poor condition. It's just the reverse of what is expected because of the fly populations in the clearcut areas. It's my belief that the animals are constantly running trying to brush off the flies in the brush.

Unknown: How about the incidence of disease caused by the flies?

Wood: We have initiated studies on this with a grant from the Office of Water Resources Research. We take 3 blood samples a year from these deer. They are compared with 2 other sets of penned deer from which we take blood samples. Then we also have rabbits which are out in enclosures in the woods from which we are taking blood samples to determine if we have a difference in the appearance of arbor viruses in these animals. We also are monitoring fecal samples every three days from the three animals that are used in the field and the three penned animals. Coliform counts are run on these and the coliform bacteria serotyped to see if we are getting correlations between serotypes of E-coli in the effluent being sprayed on the site and those occurring in the animal.

Unknown: Do you feel that these data are realistic if these animals are fed on artificial food and are not really wild animals?

Wood: This has always been a criticism of lead deer studies and there have been many modifications made of this. But from a standpoint of whether the animal prefers or avoids a particular area or a particular type of food we believe that the observations are quite good. From the standpoint of the amount of species preference when you're trying to get the exact food habits of the animals this may become limited. However, there have been some studies in the southwest in Arizona that have shown that animals raised in pens and taken out onto the range that those animals were eating the same forages that wild deer that had never seen a pen were using.

Unknown: Do you know of any data that would indicate the response of cattle to pastures that have been irrigated with sewage effluent?

Wood: I'm sorry, I don't.

SPRINKLER IRRIGATION SYSTEMS: DESIGN AND OPERATION CRITERIA

Earl A. Myers
Department of Agricultural Engineering
The Pennsylvania State University

331D

Wastewater must be applied uniformly over the land surface at the proper rate in inches per hour and the appropriate amount in inches per week, if adequate renovation is to be expected. Two areas which greatly affect this judicious application are proper design and diligent management.

This paper first lists the variables involved in the design of an irrigation distribution system, then discusses a number of factors which affect the choice of specific value for each variable, and concludes with comments concerning the various and sundry management decisions that must be made when operating the system.

DESIGN VARIABLES

In the design of a solid-set irrigation system for any wastewater facility, five variables must be considered. These are daily flow from the facility, weekly loading depth on the land area, hourly application rate, sprinkler spacing, and nozzle operating pressure. Each of these variables can be considered to be independent, however, they are also strongly interrelated.

The daily flow from the facility in combination with the weekly loading depth determine the overall size of the irrigation distribution system. The loading depth usually is expressed in inches of wastewater applied each week over the entire disposal area. For a plant outflow of 0.5 mgd (million gallons per day), 64.5 acres are required if the loading depth per week is 2 inches, whereas, if the loading depth is only 1 inch per week, 129 acres will be needed. The 0.5 mgd, 2-inch per week, and 64.5-acre statistics essentially describe Penn State's arrangement at the present time.

The application rate, expressed in inches per hour, in conjunction with the loading depth per week establish the number of irrigation periods per day or per week. Thus, for a 2-inch per week loading depth if the application rate is $1/4$ inch per hour, each irrigation period would be 8 hours and there could be three irrigation periods per day or 21 periods per week. When using an application rate of $1/6$ inch per hour each irrigation period would be 12 hours and there could be only two periods per day or 14 periods per week.

To apply the 0.5 mgd of effluent at the rate of 1/4 inch per hour required 21 periods in each of which approximately 3.1 acres were irrigated. After the application rate was changed to 1/6 inch per hour, 14 periods were required in each of which approximately 4.6 acres were irrigated.

The sprinkler spacing in conjunction with the rate of application establish the number of gallons per minute (gpm) each sprinkler must emit, whereas the sprinkler spacing and the acres per period establish the number of sprinklers which should operate at any one time. Let us consider the 1/4 inch per hour application rate which requires a 3.1-acre area. If we choose a 60 by 80 foot spacing, 28 sprinklers are needed and each sprinkler should emit 12.5 gpm. Had we chosen a 40 by 60 foot or 80 by 100 foot spacing, 56 or 17 sprinklers would have been required and 6.3 or 21 gpm would be needed. Penn State's system has used all of these arrangements and many more.

The fifth variable is the operating pressure at the sprinkler nozzle. This pressure in conjunction with the required gallons per minute of the sprinkler determine the diameter of nozzle hole which is needed. Forty pounds of pressure per square inch (psi) are required to force 6.3 gpm through a 3/16 inch nozzle, whereas 55 psi are needed for 12.5 gpm through a 1/4 inch nozzle. Nozzle diameters used on the Penn State project ranged from 3/32 to 5/16 inch, while pressures ranged from 35 to 65 psi.

Figure 1 lists the design statistics for a typical solid-set irrigation system for a town of 5,000 people. Once a specific figure has been chosen for each of the five variables, much of the remaining design becomes mere arithmetic. The primary engineering involved is in the choice of the proper value for each of the variables.

FACTORS AFFECTING VARIABLES

Wastewater Discharge

The above design example considers only wastewater quantity, which is satisfactory for many municipalities. The quality of the wastewater, however, in most situations must also be considered. Irrigation installations using Penn State's "Living Filter" concept should be utilized only where the wastewater contains pollutants of such type and concentration that can be removed by the soil-crop complex. That is, only certain pollutants can be removed appropriately by the absorptive, biological, chemical, and physical reactions within this biosphere. Other pollutants can completely destroy this living filter, thus producing additional pollution rather




Figure 1. Typical Solid-set Irrigation System Design Statistics for a Town of 5,000 People.

than renovation. Wastewaters containing high concentrations of heavy metals, chlorides, toxic constituents, etc. will probably require special pretreatment before land distribution.

Irrigation Amount

The choice of weekly loading depth depends upon the renovation and hydrologic capabilities of the site relative to the quality of the liquid wastes applied and the water quality constraints imposed by the regulatory agency. Most of the work at Penn State was with an application amount of 100 inches per year applied at 2 inches per week. The material applied was secondary treated and chlorinated domestic municipal effluent from the University and from the Borough of State College.

The renovation capacity of a site depends upon such factors as the soil and the crop to be grown, whereas the degree of renovation required depends upon the pollutants in the waste water and the proposed use of the renovated liquid; both must be considered in selecting the irrigation amount.

Corn and reed canarygrass can remove larger amounts of nitrogen than legumes or trees. The removal of crops also permits larger amounts of application. The deeper the soil and the finer the texture the greater the amounts of phosphorus one can apply because of the greater total chemical fixation capacity. A two-foot depth of soil may be adequate since 90% or more of the crop roots are in this layer. In sandy soils the amount per application period may need to be decreased so that the nutrients are not carried below the plant root zone before they can be used. Soil profiles with controlled shallow water tables which reach up into the biologically active zone may remove substantial amounts of nitrogen by denitrification. On such a site, removal of a harvested crop may not be necessary to obtain adequate nitrogen removal.

The amount of application may have to be decreased when the irrigation site is over a domestic water supply aquifer rather than an aquifer which would be used for agricultural irrigation or some other less demanding use. The amount of application at any location must not produce a water table sufficiently higher to cause direct runoff of untreated water.

The hydrologic capabilities of a site must be considered independently from the site's renovation ability. While sandy surface soils will permit infiltration of high rates of application, the amount one should apply may be controlled by underlying tighter layers. Some soils can appropriately be drained to receive high loadings of liquid wastes while others cannot. Fine textured soils covered with thick stands of vigorously growing hay crops can accept large amounts of water during the summer months, but may produce excessive runoff in early spring or late fall at these loadings.

Since the amount of wastewater applied affects the quantity and quality of water that will leave the watershed, one needs to consider the final disposition of the treated water when choosing the irrigation amount. Final disposition includes potential reuse, as well as, the rate and quality of discharge.

Reuse of renovated water usually is governed by economics and by local legal limits. Potential reusers include industrial, domestic, and agricultural. The renovation requirements for certain industrial uses, cooling for example, may not be as high as for domestic uses, therefore, a greater amount can be applied per week or per year. Under certain terrain and soil conditions it may be possible to treat the effluent in the surface soil and then permit it to resurface at a lower elevation. After it has returned to the surface it may be used directly or it may be stored behind large dams for future use. These reservoirs may also function as recreational areas. Thus, certain reuses permit greater application amounts.

The quantity of water recharged often is considered equal to the amount distributed minus such losses as evapotranspiration associated with plant growth and as direct evaporation from the sprinklers. This, however, assumes that the water actually infiltrates through the soil surface and percolates to the groundwater reservoir. In many instances on Pennsylvania hillsides covered with permeable topsoils but slowly permeable subsoils this is not necessarily true. During the spring thaw and other naturally wet periods, extensive amounts of water may become interflow or may not infiltrate at all. Thus, it is imperative that the design and operation of the system is such that the application amount is controlled to assure renovation that is adequate for the desired reuse.

Additional factors pertaining to the hydrologic regime of irrigated liquid wastes have been described by Parizek and Myers (1968).

Irrigation Rate

An application rate of 1/4 inch per hour was used for most of Penn State's systems during the first five years, whereas most of the present systems have been converted to 1/6 inch per hour. This lower application rate is preferable since one often must irrigate during and after heavy rains, when the crops are very young, in early spring and in late fall, and when the soil is near or at field capacity.

There is also a labor advantage with the 1/6 inch per hour rate. When a manual system is used, a 2-inch application requires a valve turn every eight hours with a 1/4 inch per hour rate and only every

12 hours with a 1/6 inch per hour rate. The valves were turned at 8 A.M., 4 P.M., and midnight with the 1/4 inch per hour arrangement, whereas they are now turned only at 8 A.M. and 8 P.M. This new arrangement obviously is preferred by the personnel turning valves.

Sandy loam soils are somewhat poorer in inherent nutrients and more droughty than preferred for regular agricultural purposes. Since the nutrients and water are supplied by the effluent, however, these soils are excellent for final distribution of most wastewaters. They also permit higher rates of application than finer textured soils and this provides more flexibility in the choice of irrigation system type.

Additional factors which affect the rate of application include: soil structure and permeability, soil cover crop and management procedures, surface topography, and climatic conditions.

Soils having good structure and aggregates which are stable permit higher rates of application, as do highly permeable soils which have rapid and continuing internal drainage. Thick hay and grass cover crops permit a higher application rate than does a bare soil. Good management provides proper crops and cropping procedures which help maintain good soil structure and permeability. Steep surface topography and low temperatures require reduced rates of application to decrease changes of overland flow and runoff.

Sprinkler Spacing And Pressure

The choice of spacing between sprinklers is associated closely with both the application rate and the amount of pressure at the nozzle. The primary factor which affects the choice of spacing is the vegetative cover--open field crops or forests. An 80 by 100 foot spacing is preferred for open fields and a 60 by 80 foot spacing is recommended for wooded areas. These spacings seem to give the best relationship between good distribution and reasonable costs.

Rectangular, square, or triangular sprinkler patterns may be used with solid-set distribution systems. Ordinarily some type of triangular (or staggered rectangular) pattern permits the maximum spacing between lateral lines which reduces installation costs. In order to insure reasonable uniformity of application depth over the area, the maximum spacing between sprinklers should not exceed 75 per cent of the effective sprinkler distribution diameter.

The frequency and intensity of wind affect the spacing of sprinklers, the uniformity of application, and the preference of nozzle pressure and size. As the spacing is increased, the height of the spray stream must be increased according to the laws of projectile motion. As the top of the spray stream arc becomes higher the wind has a greater effect on the distribution pattern.

Thus, windbreaks and border strips often become an integral part of the irrigation distribution system design and must be considered in the economic analysis.

The nozzle pressure and diameter are chosen such that the appropriate rate of wastewater can be distributed uniformly over the specified area. For a specific hole size if the pressure is too high, the water will mist and drift extensively. If the pressure is too low, the emitting stream will not be adequately broken and poor distribution again will result. The best advice is to follow the manufacturers' recommendations of nozzle pressure-diameter combinations.

While the above discussion of application rate, sprinkler spacing, and nozzle operating pressure is appropriate for the design of a solid-set irrigation system; it is not appropriate for the designs of other irrigations systems as: the center pivot, the giant gun, the traveling gun, and various other self-propelled or hand moved systems. In open fields one of these systems may be just as appropriate as the solid-set system and often may be more economical. In most of central Pennsylvania, however, the geology, topography, and tree cover encourage the use of solid-set systems.

Additional Factors

The physical features of the land, in addition to affecting the sprinkler system variables, also affect the design and cost of the entire system. The total head requirement for the system is directly dependent upon the difference in elevation between the pumping plant and distribution areas; as well as the friction loss in the transmission and distribution lines, and the pressure requirements of the sprinkler heads.

Design for a rough, undulating terrain, of course, is more complicated than for a gentle sloping area because of static head changes and more importantly the need for draining all lines during periods of freezing conditions. The rougher the terrain the more difficult this becomes. In areas with complex slopes the laterals may need to be placed on supports to provide the uniform grade required for rapid drainage. The number of drain locations should be kept to a minimum to reduce labor and to permit more efficient management.

The configuration of the distribution area frequently is determined by the availability of land. Inefficient distribution system arrangements involving greater costs often are required due to unavailability of large, concentrated, gently sloping areas having appropriate soil and geological conditions.

Farmers ordinarily irrigate the best soils or fields on their farms. The same should be true for canneries, industries, and municipalities when irrigating their effluents. Unfortunately, too many make the sad choice of acquiring the cheapest land available which often is too wet, is too steep, or has insufficient soil depth to provide adequate renovation.

In the choice of materials, one should remember that dissolved chemicals in the effluent may cause corrosion or electro-chemical deterioration. This deterioration may occur for 12 months each year when irrigating liquid wastes, compared to 1 to 2 months for typical agricultural irrigation. The chemical strength of the wastes, especially animal and certain cannery or industrial wastes, may be many times that of typical agricultural irrigation water.

Laws and regulations concerning liquid wastes frequently restrict design flexibility. The Departments of Public Health in many states do not permit sewage effluent irrigation of crops used for human consumption; with this most people agree. Some also do not permit the irrigation of golf courses. Since regulatory requirements differ from state to state it is essential to find out what their design "suggestions" are as early as possible because they can greatly influence a system design.

Some regulatory agencies arbitrarily "suggest" maximum sprinkler diameters of coverage or minimum specific borders beyond ordinary sprinkler wetting diameters. Unfortunately these suggestions too often become required criteria on a check list, rather than the beginning points for design consideration.

MANAGEMENT DECISIONS

Management of the system will be the deciding factor between success and failure for many wastewater renovation facilities using the living filter approach. Adequate size and flexibility frequently are designed into the system, especially with the aid of state and federal money. Unfortunately, in the hope of saving operational money, systems too often are poorly managed.

Many new concepts and often completely new orientations are required when managing irrigation systems for liquid waste disposal. Whereas farmers now ordinarily manage for crop requirements, in liquid waste irrigation one needs to manage for adequate renovation, and the crop must be secondary. This indicates that usually the municipality or company producing the liquid waste should own the land and not the farmer. No matter how conscientious a farmer is, it will be difficult to convince him to irrigate a crop which already has received twice as much rain as necessary. In wastewater disposal

management one applies maximum amounts of water to the land, not minimum amounts. Most of the research and experience with irrigation to date, however, has been with minimum amounts.

Monitoring of the effluent which leaves the renovation area is an essential part of system management. Both surface and sub-surface water discharge should be monitored in each dominant direction of water egress. Monitoring facilities usually assay only the quality of the discharge from the renovation area. Under proper management, however, quantity also should be considered.

Costs always play a major role in management decisions, especially in determining the amount of original capital outlay relative to the amount that will be required for labor to operate the system. Sewage effluent irrigation systems may be designed to operate from 6 to 12 months per year and for seven days a week. With that many hours of operation, hand moved systems usually cannot be justified. But, can a city afford to pay \$2,000 to \$4,000 per acre for a buried distribution system?

Traveler or center pivot irrigation systems may be used to reduce the capital costs. These types of distribution equipment may be secured for \$150 to \$500 per acre. The center pivot type systems have both capital and labor-saving advantages if the topography, field size and shape, lack of trees and streams, etc. are conducive to their use. Traveler-systems flexibility under adverse field conditions, but require more labor and may cause wind drift nuisance.

As one compares the management decisions between agricultural and liquid waste irrigation, he should ponder seriously the following facts. In agricultural irrigation an individual farmer usually buys the system; he operates this system with a wealth of background and ingenuity; he works with his own equipment; he irrigates his best land; he decides when to irrigate and when not, what crops and soils to irrigate, and how much; and he makes all of his own decisions and legally has the right to do so.

In liquid waste irrigation top level personnel of a municipality, a company, or a corporation usually are responsible for the management policy, however, someone far down the chain of command frequently makes the day to day operational decisions. Management policy generally provides for meeting federal or state agency regulations. The employee making the specific system operational decisions, however, all too often is not aware of the requirements which must be met or of the consequences of improper choices.

When one chooses to irrigate year-round in areas where temperatures drop appreciably below zero there are many additional management decisions that must be made. In addition to the

management of the sprinkler disposal system one must also assure that no pollution results from irrigation on frozen soil. Pumping, pipe system, and sprinkler head problems associated with irrigation during times of below-freezing temperatures have been previously reported by Myers (1966).

Management is the key to irrigation of effluent becoming a significant tool for the conservation of nutrients and renovated water, and for the elimination of much pollution in our present water bodies. Proper management of the crops and of the irrigation rates and amounts can produce the biological balance required. When astute management of soils is added to the above, adequate hydrological balance can also be attained.

ACKNOWLEDGEMENT

Research reported here is part of the program of the Waste Water Renovation and Conservation Project of the Institute for Research on Land and Water Resources, and Hatch Projects No. 1481 and 1809 of the Agricultural Experiment Station, The Pennsylvania State University, University Park, Pennsylvania. Portions of this research were supported by funds from Demonstration Project Grant WPD 95-01 received initially from the Division of Water Supply and Pollution Control of the Department of Health, Education, and Welfare and subsequently from the Federal Water Pollution Control Administration, Department of the Interior. Partial support was also provided by the Office of Water Resources Research, USDI, as authorized under the Water Resources Research Act of 1964, Public Law 88-379.

REFERENCES

- Myers, Earl A. 1966. Engineering problems in year-round distribution of waste water, Proc. National Symp. on Animal Waste Management, ASAE Publication No. SP-0366, pp. 38-41.
- Parizek, R. R. and Myers, E. A. 1968. Recharge of ground water from renovated sewage effluent by spray irrigation, Proc. of the Fourth Amer. Water Resources Conf., New York, New York, pp. 426-443.

COST OF SPRAY IRRIGATION FOR WASTE WATER RENOVATION

John B. Nesbitt
Department of Civil Engineering
The Pennsylvania State University

332 D

The net cost of effluent disposal by spray irrigation is dependent upon the system required to do a specific job, at a specific location, at a specific time, as well as the procedures adopted for management of the spray field. Since different situations require different designs and management procedures, no general overall cost information can be given. However, if certain basic assumptions are made about design and management a rough cost estimate can be made and that will be done here.

The figures presented are based on work done by Allender (1972). He presented a procedure, supported by many charts and nomographs which can be used as computational aids, which will enable an engineer to make a preliminary design and cost estimate of a wastewater renovation system using spray irrigation. Using the work of Allender (1972), the estimated cost of hypothetical systems carrying flows of one, five and ten million gallons per day (mgd) will be presented. The figures are based on certain assumptions regarding design and management. These assumptions may or may not fit another specific situation but they will define the basis of the subsequent estimates. They will be discussed under the general areas of pumping system, delivery system, and operation.

PUMPING SYSTEM

It is assumed that the system will be pumping completely treated (secondary treatment) municipal wastewater as this is the type of effluent on which the Penn State study was based. Since wastewater flows will be variable and pumping rates more or less constant, I have assumed some sort of equalizing storage will be needed and have chosen a pond designed like an oxidation pond with a forty-day detention time. The detention time was selected on the basis of flow records from several Pennsylvania communities. Other designs which use longer storage or eliminate the storage entirely are possible.

The pumping station is a typical wastewater station with the usual stand-by pumps and discharging into a force main. Also included is a fine screen (not a microstrainer) before the pump station to reduce clogging of the sprinkler nozzles.

DELIVERY SYSTEM

In this discussion the delivery system includes the transmission pipeline (force main) and the spray field itself with its land, piping, sprinkler heads, and fittings. Costs for a monitoring system are not included.

The estimates include the purchase of land at \$140 per acre. As this cost can vary from zero to well over \$1,000 an acre, the reader can make the proper adjustment when the final figures are presented. The amount of land required is based on a total application of 2 inches per week at an application rate of 1/6 inch per hour. The land is in open fields.

The sprinkler system uses solid set aluminum piping with 140 foot effective distribution diameter sprinkler heads placed in a rectangular spacing of 98 ft by 70 ft.

The force main is one mile long with a 200 ft elevation lift. This distance is probably short for many larger installations, but may be quite appropriate for the small system where this process may have its widest application.

OPERATION

Operation of the system assumes that the municipality must provide its own sprayfield which is capable of receiving the entire flow. While it is realized that this water can be of great benefit to private agricultural lands, it is felt that continuous, uninterrupted disposal on these private lands would not be possible. On this basis, sale of effluent to owners adjacent to the transmission pipeline would be a definite possibility. Calculations on the returns available from this sale indicated at best it would be an insignificant fraction of the total cost and it has not been included in these estimates.

The crop for these estimates is Reed canarygrass. While the full market potential for this crop has not yet been developed, its use is sufficiently great that a rough estimate of the returns through its sale could be estimated. Alternatively, the cost for its disposal in a sanitary landfill is also estimated.

ESTIMATED SYSTEM COSTS

Now that the basis of design has been established the estimated costs for flows of one, five, and ten million gallons per day (mgd) are shown on Table 1 in 1967 dollars. You will note that capital cost varies from \$439,220 for a one mgd system to \$2,431,280 for a ten

Table 1. Estimated Costs for a Spray Irrigation System (1967 Dollars)

Item	Flow-MGD		
	1	5	10
<u>Capital Cost</u>			
Distribution system	\$ 66,020	\$ 336,700	\$ 675,380
Lagoon	123,000	350,000	600,000
Pumping station, screens	84,000	179,000	258,500
One mile pipeline	71,500	132,000	195,000
Land, survey, site	44,000	219,000	440,000
Engineering and contingencies	50,700	152,100	262,400
Total	\$439,220	\$1,369,500	\$2,431,280
<u>Annual Cost</u>			
Amortization (20 yr @ 6%)	36,750	111,100	197,800
Labor	1,900	1,900	1,900
Power (A), distribution system	2,200	10,800	21,600
Power (B), pump effluent 1 mile and 200 feet in elevation	2,310	11,740	21,260
Maintenance and contingencies	3,410	11,300	20,500
Total	\$ 46,570	\$ 146,840	\$ 263,060

mgd system. Annual cost also shown on Table 1 includes amortization of the capital cost in 20 years at 6% interest and ranges from \$46,570 to \$263,060 for the one and ten mgd flows. Labor would be by personnel also used for other work and is considered constant in this flow range.

The distribution of costs among the various system components can be determined from Table 1. It can be seen that the capital costs are nearly equally distributed among the system components.

It is popular these days to present annual wastewater treatment costs in terms of cents per thousand gallons of wastewater treated. Annual cost on this basis is presented in Figure 1. The solid line is constructed from the data in Table 1. The dashed lines now include estimates of the annual cost for sale or landfill disposal of the Reed canarygrass crop.

The cost shown in Figure 1 compares favorably with other wastewater treatment costs. With complete treatment cost at 15 cents per thousand gallons for a 15 mgd plant, sprinkler irrigation would add about 50 percent to the total treatment costs. Chemical treatment for phosphorus removal is generally estimated at about 5 cents per thousand gallons, and tertiary treatment by filtration and activated carbon at 20 cents. Remember, however, that the sprinkler irrigation cost used for comparison is for a one-mile pipeline to the sprayfield.

Since the cost for wastewater treatment will always revert to the individual homeowner, Figure 2 has been prepared to show the cost on this basis. The transformation from Figure 1 to Figure 2 is based on an average household of 3.5 people at 100 gallons per capita per day. In comparing costs obtained from this graph with a typical municipal sewer bill, remember that the sewer bill contains costs for both collection and treatment and that the costs presented here consider only a one-mile transmission pipeline.

REFERENCES

- Allender, Gerald C. 1972. The cost of a spray irrigation system for the renovation of treated municipal wastewater, Master of Science Thesis, Department of Civil Engineering, The Pennsylvania State University, University Park, Pa.




Figure 1. Cost of Spray Irrigation Per Thousand Gallons. Estimated Cost includes a 1-mile Pipeline plus a 200-foot Elevation Lift.




Figure 2. Cost of Spray Irrigation Per Equivalent Dwelling Unit (E.D.U.). Estimated Cost includes a 1-mile Pipeline plus a 200-foot Elevation Lift.

FINANCING MUNICIPAL WASTE WATER TREATMENT FACILITIES,
INCLUDING LAND UTILIZATION SYSTEMS

333D

Belford L. Seabrook
Division of Municipal Waste Water Programs
Environmental Protection Agency

Today, the number of sewered communities in the United States is just over 16,000, serving 68 percent of the Nation's population. During the next five-year period, we estimate that about 8,000 of these communities will construct new, upgraded, or expanded waste water treatment facilities.

This construction is needed primarily to meet established water use goals for the receiving waters. However, a continuing need for pollution abatement facilities will always exist after standards have been achieved to compensate for a growing population, obsolescence, and industrial expansion. Accomplishing this goal will require dedication at all levels of government and will most certainly require the cooperation of industry.

The Environmental Protection Agency is not approaching industry nor anyone else as an adversary. Water pollution is not just an industry problem or a government problem; it is society's problem. We approach everyone as a partner, convinced that environmental protection is everyone's job and everyone's responsibility. We know that our waters cannot be cleaned up tomorrow, that they cannot be restored easily or without great effort and expense. But we are determined to make a beginning.

From now on "pay-as-you-go" will increasingly be required for insuring against the risks of manipulating nature. This means that provision must be made for the protection and rehabilitation of the environment before, or at the time, these resources are used. The cost of maintaining the environment must be included in the cost of doing business.

GENERAL ACCOUNTING OFFICE STUDIES

The General Accounting Office (GAO) submitted reports on the construction grant program to the Congress in November, 1969, and May, 1970. The reports discussed the effectiveness of the program and the awarding of grants to municipalities in cases which benefit industrial users.

The November, 1969, report pointed out that the suspension of the dollar-limitation clause on grant awards in 1966 provided the

initiative for the growing trend toward the treatment of industrial wastes in joint municipal-industrial plants. The report indicated that, should the trend continue, it could result in many of these industry-associated costs for treatment facilities becoming eligible for Federal assistance. In other words, the volume and cost of treatment facilities receiving Federal financial assistance would increase significantly. In short, the taxpayer would be subsidizing industrial wastewater treatment with no control on the quantity of waste products discharged into the system.

The later GAO report, dated May 8, 1970, called direct attention to the fact that some grants were being awarded for the treatment of industrial wastes only.

RECENT FEDERAL REGULATIONS

On July 2, 1970, Regulations were promulgated on treatment works design, operation and maintenance, planning requirements, and treatment of industrial wastes in municipal systems. The Regulations provide for investment of the anticipated massive amounts of public monies in a more coordinated and effective manner. In addition to responding to criticism from the General Accounting Office, the Regulations provide a solid base from which to achieve the Agency goals of cost-effectiveness in planning, design, and operation of treatment works.

INDUSTRIAL WASTE COST RECOVERY GUIDELINES

Federal guidelines for equitable recovery of costs for industrial waste treatment in municipal systems were issued in October, 1971, to interpret the July 2, 1970, Regulation.

A system of "cost recovery" is to be provided by the grantee wherever industrial wastes are to be treated by a facility built with Federal aid. A municipality must assess industry's share of the operating and capital cost of the community treatment facility. Under present policy, industry's share will be in proportion to the total costs of waste treatment for operation and maintenance, and in proportion to the grantee's costs for capital costs. Thus, the industry is not required to reimburse the municipality or the Federal Government for the grant portion which will provide facilities for treatment of industrial wastes. Pre-treatment must also be provided by industry for wastes that would otherwise be detrimental to the municipal treatment facility and collection system.

However, the legislation now pending in Congress would require recovery of the grant portion from industrial users. I will

discuss this in more detail later.

The guidelines are designed to clarify the general provisions and the criteria of acceptable compliance. The intent of the guidelines is to define the minimum acceptable revenue to be derived from industry for its share of the facility costs. The emphasis is on the necessity for use of average cost pricing for industrial users and all other users, based on the contributed loadings, in terms of both quality and quantity of wastes. Although EPA will approve any system that satisfied the intent of the Regulations, the guidelines will serve to facilitate the determination of compliance with the cost recovery requirements.

The primary Agency interests with respect to the intent of the Regulation, therefore, are:

1. To implement the Agency's basic principle of imposing the cost of waste treatment directly upon the source of pollution;
2. To encourage the use of user charges based upon volume and character of the wastes;
3. To promote equity in terms of improved knowledge and acceptance by the system's users of the necessity of paying for waste treatment and control;
4. To encourage reduction of waste strength through in-plant control and recycling of by-products; and
5. To promote local self-sufficiency.

In order for the Agency to determine compliance with an equitable cost recovery system, the grant application must furnish complete information on existing treatment works and the proposed expansion or modification including:

1. General information about industries located and served (or to be served) by the treatment system;
2. Treatment works capacity, in terms of hydraulic and BOD loadings;
3. Total excess capacity reserved for industrial waste contributors;
4. Methods of financing for capital improvements including amount and amortization schedule;
5. Methods for financing the operation and maintenance

costs including special costs created by industrial wastes;

6. Distribution of the revenues to be collected among classes of users; and
7. Method of collection of revenues.

This then represents the administrative arrangements that were developed to assure equitable allocation of wastewater treatment costs among all users.

A survey is currently being conducted of certain representative existing wastewater land utilization systems throughout the country to collect facts and experiences for the purpose, among others, of evaluating these facts to form the basis for developing Federal guidelines on land application techniques. Hopefully, this information will become available to the public early in 1973. With the caveat that the wastewater land application survey report and the Federal Guidelines can be published in early 1973, planning is currently underway to organize and hold the First EPA National Symposium on Waste Water Land Utilization Techniques, to be held in mid-1973.

OMNIBUS CLEAN WATER BILLS

President Nixon sent a significant number of proposals, representing his water pollution control legislation program, to the 92nd Congress during the first session. A number of proposals have also been submitted by various members of Congress. Late in the 1st session the Senate passed, by an overwhelming vote of 86-0, S. 2770 in lieu of the President's legislative proposals and certain other bills. In the meantime, H. R. 11896 was introduced in the House of Representatives. Hearings were held and the Bill was passed by the House March 29, 1972, by a vote of 378 to 14. The versions approved by the Senate and the House provide for a number of substantial changes. Among the most significant are the following:

1. Both versions provide for the application of the best practicable waste treatment technology after June 30, 1974, following examination of all possible alternatives. The Administrator is directed (in Section 304(d)(2)) to publish within 9 months after enactment information on alternative waste treatment techniques and systems available to implement Section 201 of the Act.
2. The Senate Bill authorizes a maximum Federal share of 70 percent. The House version would authorize a maximum of 75 percent. The Joint Conference Committee

(in June 72) adopted the 75 percent maximum and added the provision that there would be no requirement for matching State grants.

3. The House Bill would make certain sewage collection systems eligible for Federal grants. The Senate Bill does not contain this provision. Both versions, however, provide for separation and treatment of storm water.
4. Under the Senate Bill, the Administrator of EPA is authorized to advance to a municipality up to 5 percent of the estimated reasonable construction cost of a project, after reviewing the engineering feasibility report, to enable municipalities to complete plans and specifications. Such funds need not be returned in the event no further grants are made on the project. The House Bill contains no provisions for such advances.
5. Both the Senate and House versions provide for a charge to be assessed on all users to assure that each class of users pays its share of the cost of operation and maintenance, including replacement of sewage treatment works.
6. Both the House and Senate Bills require that municipalities levy charges on all industrial users to recover the portion of the total capital cost covered by both the local share and the Federal share, allocable to the industrial load portion of the plant capacity.
7. The Senate Bill provides that the Federal share recovered from industrial users of Federally assisted municipal plants be received by the Administrator and deposited in the United States Treasury. The House version provides for the recovered funds to stay with the local wastewater treatment management agency to provide for replacements and other plant needs.
8. The Senate Bill authorizes a total of \$14 billion from Fiscal Year 1972 through Fiscal Year 1975 as the Federal share of the construction costs of municipal sewage treatment facilities. The House version will make available a total of \$20 billion for sewage treatment construction for the same period. The Joint Conference Committee (in June 72) adopted the House figure of \$20 billion.

9. Both bills provide for the development of regional waste treatment management systems.
10. Both bills require that guidelines and regulations be published on pre-treatment of industrial wastes prior to discharge to publicly-owned systems. This applies to pollutants which interfere with, pass through, or are otherwise incompatible with treatment systems. Provision is also made for monitoring of industrial discharges.

At this point it is not possible to predict the final outcome of the proposed legislation with regard to cost recovery for treatment of industrial wastes. However, it is significant that both bills contain similar provisions for recovery of the grant portion for industrial waste treatment.

The House Bill provides that grant funds cannot only be utilized for the construction of land application facilities, but such funds can additionally be utilized for site acquisition, including farmland and forest land. The Joint Conference Committee, which is currently considering the pending legislation has yet to resolve this matter.

The reference above, concerning alternative techniques and systems, applies to land treatment and land utilization systems that are an integral part of municipal wastewater facilities. Construction grants can be made to cover the eligible costs under the current program.

The following criteria will be helpful in evaluating wastewater land utilization techniques:

1. Type of wastewater
 - (a) Raw sewage
 - (b) Primary treated sewage
 - (c) Secondary treated sewage
 - (d) Liquid digested sludge
2. End use of wastewater
 - (a) Disposal
 - (b) Agriculture
 - (c) Industrial reuse
 - (d) Recharge of aquifer
3. Esthetic attitudes of community
4. Availability of suitable land
 - (a) Ownership
 - (b) Leasing

- (c) Green belts
 - (d) Highway median strips
 - (e) Golf courses
 - (f) Farmland/ranchland
5. Length of operating experience
 6. Social costs, including relocation assistance and eviction costs
 7. Institutional restraints
 8. Public health factors
 9. Build up of mineral and heavy metals in the soil
 10. Odor and fly problems
 11. Long-term problems
 - (a) No discharge a fallacy
 - (b) Runoff
 - (c) Sources of water supply

The particular technique and design of a land utilization system for wastewater and liquid digested sludge will depend on the situation and circumstances at each specific project.

LARGE WASTEWATER IRRIGATION SYSTEMS: MUSKEGON COUNTY,
MICHIGAN AND CHICAGO METROPOLITAN REGION

W. J. Bauer and D. E. Matsche
Bauer Engineering, Inc.

334D

The substance of this paper is directed primarily toward a discussion of the costs and benefits of large land treatment systems, using the experience with the Muskegon County, Michigan system now under construction and the work done to date on preliminary planning for a system to serve the Chicago metropolitan region. These two projects will be described briefly, then the cost experience and cost estimates for the various components of the system will be analyzed. The division of the costs into functional components is intended to facilitate the use of these figures by others in analyzing, in a preliminary fashion, the cost of a land treatment system in some other locality where the relative costs of the components may not be the same as those experienced in the Muskegon County project. The selected components for cost analyses are:

1. Collection and transmission.
2. Pretreatment.
3. Irrigation.
4. Drainage.
5. Sludge handling.
6. Return and reuse of treated water.
7. Land acquisition.

In addition to analysis of both the capital and operating costs of these components, potential sources of income from the wastewater irrigation system are evaluated. These are:

1. Agricultural production.
2. Long-term land values.
3. Leasing of space for electric power station.
4. Sale of cooling make-up water.
5. Sale of industrial process water.
6. Leasing of space for solid waste handling.
7. Recreational uses during non-irrigation seasons.

MUSKEGON COUNTY, MICHIGAN SYSTEM

This land treatment system is located in parts of Muskegon County, Michigan on sandy soils common to that portion of Michigan lying along Lake Michigan. Muskegon County is located

approximately opposite Milwaukee, Wisconsin, roughly opposite the midpoint of Lake Michigan. The wastewater management system is physically divided into two parts: a larger portion serving the more heavily urbanized area surrounding Muskegon Lake and Mona Lake; and a smaller portion serving the less urbanized area around White Lake. All of these lakes are large dune-impounded lakes with outlets to Lake Michigan. The purpose of the project is to eliminate the discharge of polluting materials into Lake Michigan from which the water supply for most of the population of Muskegon County is obtained. The population to be served is estimated to be approximately 160,000 persons when the system is fully developed. The design average flows for the fully developed system are estimated to be about 43 mgd, with a peak capacity of roughly 90 mgd which can be sustained for a relatively long time without adversely affecting the final effluent quality. Of this total design flow, about 40% is expected to be industrial and the remainder is expected to be domestic wastewater. Initially, the industrial portion comprises more than half of the total flow, because many of the collecting sewer systems have not been constructed. The largest single industry served is a paper mill with a design average flow of 12 to 16 mgd of wastewater containing waste paper and pulp fibre, plus some waste clay filler.

The larger of the two irrigation sites is an area of about 15 square miles located about 10 miles east of the more heavily urbanized area. It is underlain by medium sand ranging in thickness from a minimum of 20 feet to a typical maximum of 60 feet. There are also areas where the sand thickness is greater than 60 feet. The surficial sand deposits are underlain by an impermeable clay layer which effectively prevents the vertical movement of groundwater. Aerated lagoons with a design average residence time of 3 days are used to provide the biological treatment. The normal procedure to be followed will result in discharging the biologically treated wastewater and associated solids into one of two 850-acre storage lagoons. These storage lagoons provide additional treatment and winter storage of the treated wastewater by being allowed to fluctuate 9 feet in depth. A separate 8 acre settling lagoon will be provided for operating flexibility to allow the bypassing of the storage lagoons and permit the direct irrigation of clarified effluent from the aerated lagoon system.

Percolation through the bottom of the storage lagoon is controlled by intercepting ditches around the lagoons from which it can be pumped either back into the storage lagoon, or to the outlet drainage system, or to the irrigation system. Pumping directly to the outlet drainage system is anticipated only during the initial operations of the system, which will occur before all of the irrigation system is ready to operate.

The flow into the major irrigation system would then come from either the storage lagoons or from the ditch which intercepts leakage from the storage lagoons. In either case, it is planned to chlorinate it to provide a desired reduction in coliform count. During the flow in the long open channels leading to the two irrigation pumping stations, the excess chlorine will be dissipated to prevent adverse effects in the soil. The two irrigation pumping stations are each set up in two parts so that a total of four separate irrigation systems may be served. Together these systems utilize about 55 irrigation rigs of the pivot type, each of which irrigates a circular area. These circular areas range in size from about 40 to 160 acres. A total of approximately 6000 acres of land are thus irrigated. The design application of irrigation water is about 7.5 feet per year, or 2.5 million gallons per acre per year. A total of 15,000 million gallons of water are thus planned to be irrigated in the design year, or an average flow of 41.3 mgd. The remainder of the design flow (1.3 mgd) is handled at the smaller site serving the White Lake area. During the irrigation period of roughly 30 weeks per year the average rate of application would be 3 inches per week. However, maximum rates of 4 inches per week are anticipated during dry weather.

An extensive underdrainage system is provided in the Muskegon County project, comprised primarily of drainage pipe systems which discharge into drainage ditches. In addition, a smaller portion of the irrigation site is drained by wells. Both pumping wells and observation wells are provided. The purposes of the drainage system are to prevent the saturation of the agricultural soils under the most intense periods of irrigation and precipitation, and also to control the direction of movement of the ground water around the perimeter of the irrigation site. It was required by the Department of Public Health that no out-migration of ground water occur. Consequently, the design provides for a small inward migration of ground water from the surrounding areas into the irrigation site.

Authorization to prepare construction plans and specifications for the Muskegon County system was given in July of 1970; bids were taken in May of 1971; bonds were sold to cover the \$16 million local share of the costs in August of 1971; and construction was started in the fall of 1971. Construction has continued during the winter of 71-72 with many of the collection system force mains being completed by August 1972. The land acquisition program began in October of 1971, and by March of 1972 about 85% of it had been acquired without the use of condemnation procedures. Clearing of the land began in April of 1972, and construction of the lagoons, major drainage ditches, and other features of the irrigation site were well under way in August of 1972. It is expected that the initial operation of the system will take place late in 1972 or early in 1973 with the collection, transmission, pretreatment and

storage of a flow of somewhat less than 30 mgd. Leakage through the bottom of the storage lagoon is expected to be rather large until the sludge builds up a sealing layer over that portion of the bottom which is not lined with clay. Design of the leakage interception system is predicated on the assumption that leakage will pass through a minimum of 500 feet of sand before being intercepted by the perimeter ditch, and because the sand contains large amounts of iron and other chemicals for the precipitation of phosphate, the leakage water is expected to meet all of the requirements for effluent from treatment plants discharging into Lake Michigan. Therefore, the initial operation of the system could occur without irrigation. The irrigation and drainage system is expected to be completed during 1973, so that full scale operation will take place during 1974.

The capital costs which are reported here are obtained from the actual bidding for the component construction contracts of this project. The operating costs are estimated from the calculation of energy consumption, labor requirements, and maintenance procedures. The estimate of potential revenues is based upon a forecast of the auxiliary functions which are presently being contemplated at the site, including the construction of a major nuclear power generating station.

CHICAGO METROPOLITAN REGION

A survey scope report for the U. S. Army Corps of Engineers is being produced by the Chicago District on regional wastewater management plans. The region to be served covers approximately 2500 square miles with a present population of about 7 million persons in northern Illinois and northern Indiana. Domestic wastewater, industrial wastewater, discharges from combined sewers, discharge from storm sewers, and runoff from rural watersheds would all be managed in this plan. Alternative treatment technologies, ranging from activated sludge with advanced treatment processes being added on, chemical/physical treatment systems with advanced treatment processes being added on, and biological treatment in lagoons followed by land treatment using irrigation and drainage of agricultural areas are all being considered, both separately and in various combinations. The goal of the study is to produce a comprehensive basis for choosing the course of action to solve the water pollution problems of the Chicago metropolitan region.

The cost estimates presented for this system are based upon a layout of the physical elements of one of the systems being studied, including several hundred miles of water conductors, 75 square miles of lagoons, and 700 square miles of actual irrigation area. Further

details of the layout of the project can be obtained from reports by the Chief of Engineers issued in March of 1972, together with the Technical Appendix and the Cost Data Annex of that report.

The operating costs and estimates of potential revenues are calculated on the same basis as those presented for the Muskegon County project. The capital and operating costs are presented without taking credit for any potential revenues from various possible sources of income.

COST ANALYSES

Muskegon County Project

Collection and Transmission. The costs of the collection and transmission systems for this project are based upon the bids for the following construction contracts:

Contract 10:	66-inch force main, 11 miles	\$ 4,502,025
Contract 11:	Smaller force mains	1,230,930
Contract 12:	Smaller force mains	841,309
Contract 13:	Smaller force mains	1,135,400
Contract 15:	Main pumping station, 90 mgd	1,565,000
Contract 16:	Smaller pumping stations (7)	1,163,169
Total		\$10,437,833

It is significant that most of these costs would be incurred regardless of the type of treatment used, as it is necessary to convey the wastewater to the point of treatment. In the case of Muskegon, the alternative treatment plant was located on a site closer to the city, but all of the same pumping stations would have been required. There would have been a shorter main line from the main pumping station out to the site of the treatment plant.

To these costs should be added about 2 other small pumping stations which were not advertised at the time of the general bidding, plus a proportionate share of the engineering cost. Adding these gives a total of \$11,500,000. Spreading this over the rated average capacity of 43 mgd gives a unit capital cost of 27¢ per gpd average capacity. Spreading this over the rated peaking capacity of 90 mgd gives a unit capital cost of 13¢ per gpd.

The operating cost of the collection and transmission system is estimated as follows:

	<u>Cost/Year</u>
Smaller pumping stations, 5 @ 3 mgd avg. flow with a typical head of 60 feet, 50 hp avg. power consumption at \$75 per hp-yr	\$ 18,000
Service and maintenance labor for preceding	25,000
Intermediate pumping stations, 2 @ 15 mgd flow with typical head of 60 feet, 150 hp. avg. power consumption at \$75 per hp-yr	22,500
Service and maintenance labor for preceding	20,000
Main pumping station, average of 41 mgd flow with typical head of 180 feet, 1200 hp avg. power consumption at \$75 per hp-yr	90,000
Service and maintenance labor for preceding	30,000
Total	<u>\$205,500</u>

Dividing by 15,000 million gallons per year pumped, this amounts to an operating cost of about \$14 per million gallons.

Summarizing the collection and transmission cost of the Muskegon County System we have the following:

Capital cost	\$11.5 million	27¢ per gpd
Operating cost	\$ 0.205 million/yr.	\$14 per mg

Pretreatment. The pretreatment of the wastewater prior to the irrigation involves biological treatment in aerated lagoons, biological treatment of effluent and digestion of sludge in stabilization lagoons, and chlorination of the effluent prior to discharge into the irrigation canals leading to the irrigation pumping stations. The capital cost of the construction items involved in this portion of the project are as follows:

Contract 18: (as awarded)	\$7,044,298
Clay lining	664,020
Soil cement placement	525,000
Cement for soil cement	381,000
Total	<u>\$8,614,298</u>

This is a cost of 20.6¢ per gpd capacity, exclusive of the sludge handling equipment.

The sludge handling equipment would consist of a dredge and pipeline, plus centrifuge to obtain a higher per cent solids, plus several plows to place the sludge into the earth and cover it. The capital cost of these items is estimated to be \$500,000 or 1.2¢/gpd. The total capital cost for pretreatment is then 21.8¢ per gpd. Operating cost of the pretreatment system is estimated as follows:

Electric energy consumption of the mixers and blowers, installed capacity of 2000 kw, with an average load of 1200 kw at \$100/kw-yr.	\$120,000/yr
Electric energy consumption -lighting, and miscellaneous small motors around the control building and chlorination buildings.	10,000/yr
Chlorine consumption for chlorinating the treated effluent prior to irrigation @ 5¢/lb.	50,000/yr
Sludge processing and pumping costs, 300 hp. at \$100 per hp-yr.	30,000/yr
Laboratory and treatment process personnel, including personnel for the taking of water quality samples at wells and points of discharge from the system, 10 persons.	150,000/yr
Sludge disposal personnel, including 2 on the dredge, 2 at the centrifuge, and 2 on the plow.	90,000/yr
Total operating cost of pretreatment	<u>\$450,000/yr</u>

Summarizing the costs of pretreatment:

Capital cost (including engineering)	\$ 10,0 million	23¢/gpd
Operating cost	\$450,000/yr	= \$30/mg

These pretreatment costs include the equivalent of secondary treatment of the effluent, and the utilization of the sludge for soil enrichment purposes.

Irrigation. Capital costs of the irrigation system include the following construction contracts:

Contract 1:	Clearing	\$1,500,000
Contract 6:	Pressure piping	2,194,615
Contract 8:	Electric power distribution	475,193
Contract 17:	Irrigation pumping stations	500,000
Contract 22:	Pivot Irrigation Rigs for 6,000 acres	1,500,000
	Sub-Total	6,169,808
	Total Engineering	600,192
	Total	\$6,770,000
	Cost per gpd capacity(avg.	16¢

Operating cost of the irrigation system may be estimated as follows:

Electric energy consumption, actually consumed over a 7-month period but averaged over the year at the equivalent of 2000 kw @ \$100/kw-yr	\$ 200,000
Operating labor, 10 men	150,000
Allowance for replacement of mechanical equipment and other miscellaneous expenses	50,000
Total operating cost	\$ 400,000
Cost per mg	\$ 27.00

Drainage System. The capital costs of the drainage system are estimated as follows:

Contract 2:	Agricultural drainage pipe	\$ 565,053
Contract 3:	Main drainage pipe	1,970,616
Contract 4:	Highway culvert	84,144
Contract 5:	Main drainage channels	1,104,977
Contract 9:	Well drainage control system	226,332
	Subtotal	\$3,951,122
	Engineering allowance	348,878
	Total	\$4,300,000
	Cost per gpd	10¢

Operating cost of the drainage system is relatively small, as the pumping stations involved are very low head and the maintenance personnel are the same ones as for the irrigation system. We shall ignore the operating cost of the drainage system, as it is included in the irrigation system for all practical purposes.

Return and Reuse of the Treated Water. In the case of the Muskegon County project, all of this cost is included in the cost of the drainage system as the treated water is simply returned to the waterways and drains naturally, ultimately into Lake Michigan where it becomes available once again as water supply.

Land Acquisition. Assembly of the two project sites totaling 10,000 acres required the acquisition of 410 parcels of property including 185 occupied residences. A program of relocation assistance was provided consistent with the requirements of the Federal Uniform Relocation Assistance Act. The costs of the land acquisition program were as follows:

Acquisition of land and structures	\$5,000,000
Relocation assistance	1,000,000
	\$6,000,000
Cost per gpd	14¢

Summary of the Muskegon County Project

The following is a summary of the costs of the Muskegon County project based on 43 mgd.

	Capital Cost ¢ per gpd	Operating Cost \$/mg	Number of Employees
Collection and transmission	27	14	5
Pretreatment	23	30	16
Irrigation	16	27	10
Drainage	10	0	0
Return and reuse	0	0	0
Land Acquisition	14	0	0
Sub-totals	90	71	31
Interest during construction and miscellaneous expenses	4	0	0
Totals	94	71	31
General administrative expense	1	11	9
Totals	95	82	40

CHICAGO REGIONAL PLAN

The costs for the Chicago Regional Plan are given in Table 1 taken from the Technical Appendix to the report of the Office of the Chief of Engineers, Department of the Army (1972). These costs apply to a system with an average flow rate of 2376 mgd with a peaking factor of 1.75.

Extracting the corresponding costs from Table 1, one may construct the following tabular comparison:

<u>Item</u>	<u>Muskegon County</u>	<u>Chicago Region</u>	<u>Ratio</u>
Average flow rate, mgd	43	2376	55
Peaking flow rate, mgd	90	4152	46
Total capital cost, \$millions	40	2000	50
Collection and transmission, \$/gpd..	27¢	30¢	1.11
Pretreatment & storage, \$/gpd.....	23	11	0.48
Irrigation system, \$/gpd.....,.....	16	7	0.58
Drainage system, \$/gpd.....,.....	10	8	0.80
Return and reuse system, \$/gpd.....	0	12	--
Land acquisition.....	14	13	
Subtotals.....	90¢	81¢	0.95
Interest during construction and miscellaneous expenses.....	4	2	0.715
Subtotals.....	94	83	0.89
General administrative expense.....	1	1	0.50
Totals (capital cost)....	95	84	0.89
Operating cost, \$/MG.....	82	106	1.325

The relatively greater collection and transmission costs for the Chicago Regional Plan arise from the 104 mile maximum transmission distance as compared to a maximum distance of about 15 miles for the Muskegon County Project. Likewise, the relatively greater pumping head--1,100 feet versus 230 feet--for the Chicago project largely accounts for the greater operating cost. However, there may be off-setting revenues as discussed in a subsequent section.

The relatively smaller pretreatment and storage costs of the Chicago Regional Plan arise from the much larger lagoons and the resultant great reduction in the volume of earth-moving per million gallons of storage volume.

TABLE 1. Summary of Costs for the Land Treatment Alternative for the Chicago Metropolitan Area

Item	Cost
Capital Cost	
Transmission facilities	
Wastewater tunnel and pipelines	\$ 627,638,000
Reclaimed water tunnel	257,000,000
Wastewater pumping station	80,000,000
Reclaimed water pumping station	22,000,000
	<u>\$ 986,638,000</u>
Land treatment site	
Purchase	291,000,000
Family relocation	27,000,000
Clearing and site preparation	36,588,000
	<u>\$ 354,588,000</u>
Irrigation system	
Irrigation pumping station	23,370,000
Irrigation rigs	58,531,000
Pressure pipe and appurtenance	60,782,000
	<u>\$ 142,683,000</u>
Drainage system	
Drainage pumping station	2,358,000
Plastic drainage pipe	16,616,000
Sewer drainage pipe	172,914,000
	<u>\$ 191,888,000</u>

TABLE 1. Continued

Item	Cost
Aerated lagoon system	
Earthwork	14,300,000
Slope and roadway construction	4,733,000
Aerators and mixers	33,877,000
Inlet, outlet, flow distribution and crossing structures	16,766,000
	<u>\$ 69,676,000</u>
Storage lagoon system	
Earthwork	76,560,000
Slope and roadway construction	17,030,000
Inlet, outlet & chlorination structures	40,392,000
	<u>\$ 133,982,000</u>
Irrigation and drainage channel system	
Excavation	32,295,000
Lining	26,879,000
Crossing, diversion & drop structures	1,253,000
	<u>\$ 60,427,000</u>
Monitoring system	
Observation wells	4,280,000
	<u>\$ 4,280,000</u>
Electrical system	
	<u>\$ 28,340,000</u>

TABLE 1. Continued

Item	Cost
Sludge disposal facilities	<u>23,300,000</u>
Administration and regional lab buildings	\$ 23,300,000
Subtotal capital costs land treatment system	<u>3,565,000</u>
Operating and maintenance cost	
Labor (includes 25% overhead)	
Managerial and administration	910,000
Operating engineers, chemists	2,550,000
Mechanics, electricians	3,430,000
Field inspection, maintenance	5,650,000
Secretarial and janitorial	<u>850,000</u>
Power	\$ 13,390,000
Main wastewater pumping station	33,800,000
Reclaimed water pumping station	7,890,000
Aerated lagoons	9,235,000
Irrigation and drainage pumping stations	6,650,000
Irrigation rigs	<u>1,200,000</u>
Chemicals	\$ 58,775,000
	<u>2,900,000</u>
	\$ 2,900,000

TABLE 1. Continued

Item	Cost
Maintenance and supplies	
Pumping stations	1,150,000
Aerated lagoons	340,000
Chlorination facilities	70,000
Irrigation rigs	1,160,000
Transmission pipeline and tunnels	885,000
	\$ 3,605,000
Misc. building and site maintenance and supplies (incl. transportation)	
	1,530,000
Sludge disposal	11,200,000
	\$ 1,530,000
Total operating and maintenance cost per year	
Present worth for operating and maintenance cost (1975-2025)	\$ 11,200,000
	\$ 91,400,000
Present worth for capital replacement costs (1975-2025)	\$1,255,000,000
	60,140,000
Total present worth for the land treatment system	\$3,315,000,000

^{1/} Department of the Army, Office of the Chief of Engineers. 1972. Regional wastewater management systems for the Chicago Metropolitan Area, Summary Report and Tech. Appendix.

The irrigation and drainage systems are more economical in the Chicago Regional Plan because of the larger diameter irrigation machines, and because of the thicker aquifer.

The return and reuse system of the Chicago Regional Plan is a significant portion of the cost because of the distance of the farm from the points of reuse.

SOURCES OF INCOME

There are a number of potential sources of income from operations which can be accommodated at the land treatment site with little if any interference with the wastewater renovation operations, plus some that are incidental to the proper management of the system.

Agricultural Production

Crops produced on the farm can significantly reduce operating costs. For example, each acre of irrigated land will treat 2.5 million gallons of water each year. If this acre nets \$100 per year in income -- not at all impossible with the substantial quantity of water and fertilizer being applied -- this is an income of \$40 per million gallons of water treated, a significant reduction in net operating cost, representing about 40 percent of it.

Long-term Land Values

Included in the cost of the project is an area of about 200 acres of land for each 1 mgd average flow. This allows for the irrigated land, the land occupied by lagoons, and the land used for the consumption of the sludge as soil enrichment material. The value of this land over the long term could be very significant, particularly as it is in a large block. For example, assuming that some day in the future there is invented a much less expensive and even more effective method of wastewater treatment and renovation, the land could remain largely open and available for some other use. It would be completely equipped with irrigation and drainage systems, permitting high intensity agricultural use, for example. Assuming this to be the case, the cost recovery at some future date could well be \$1000 per acre. This would recover \$200,000 per mgd capacity or, roughly, 20% of the original cost of the project.

Electric Power Stations

Power generation capacity of about 4 kw per capita are forecast for urban areas prior to the year 2000. Space of these stations appears to be difficult to obtain, as there is a strong desire by most persons not to live near one. Space provided by the wastewater

irrigation farm appears to offer the ideal solution, being near the urban areas, furnishing great isolation from human residential areas, furnishing plenty of make-up water for cooling, and in the large storage lagoons offering a possible heat exchanger facility which otherwise would have to be constructed by the electric utility. Taking the design population of the Chicago region to be 10 million persons, and taking the design average flow rate to be 3000 mgd, the possible installed capacity per mgd of wastewater average flow rate is $40,000 \text{ mw}/300 \text{ mgd} = 13 \text{ mw/mgd}$. It is realistic to charge a rental rate of \$3 per year per kilowatt of installed capacity -- this would be 1 percent of the capital cost of the facility -- which would generate a revenue of roughly \$40,000 per year per mgd, or about \$110 per million gallons treated. This is seen to more than offset the total operating cost of the wastewater system, and is thus a very important factor in considering the economics of alternative systems. (This rental would be in addition to tax payments to local bodies.)

Sale of Cooling Water

Still another potential revenue comes from the sale of water for making up the water evaporated by cooling processes. Assuming 13 mw per mgd of treatment capacity, and assuming 12 mgd of average annual evaporation per 1000 mw of installed capacity, the amount of water evaporated would be 0.156 mgd/mgd. At a price of \$50 per million gallons, this would be a revenue of \$7.80 per million gallons treated, say, 7% of the cost of treatment.

Sale of Industrial Process Water

Some industrial processes such as steel mills and paper mills, could logically be located on the site of the wastewater treatment system to make use of the partially treated water prior to irrigation. Rental space to such industries, and sale of water to them, could also produce a significant revenue. It is not estimated here, as the amount would depend upon the individual circumstances.

Solid Waste Processing

There is plenty of space in the irrigation farm area to set up a solid waste processing facility, and to construct land fills with the residual material remaining from such processing. Assuming 1 ton of solid waste per capita per year, a design population of 10 million persons, and an average flow of 3000 mgd including industrial and storm flows, there would be roughly 10 tons of solid waste per million gallons of water treated. Assuming a revenue of \$2 per ton of solid waste processed, this would be a revenue of \$20 per million gallons of water treated, or about 20% of the operating cost. Again,

the amount of potential revenue is significant to the reduction of total costs to the citizen served.

During the non-irrigation season, the 6,000 acre Muskegon irrigation area and the 2,000 acres of unused buffer area could potentially be available for various kinds of recreational activities such as snow-mobiling, riding, hunting and hiking. The storage lagoon surface area also provides a water habitat for various water fowl and other species. In Michigan, the various wastewater lagoon installations completed to date have significantly augmented the water surface wildlife propagation areas.

The value of land treatment sites as a means of containing urban sprawl and of maintaining agricultural areas is difficult to evaluate with a dollar figure, but many would ascribe significant value to this function.

SUMMARY

The capital and operating costs for the Muskegon County, Michigan project and for the Chicago Regional Wastewater Plan have been presented in a form useful for making comparisons with alternative systems. Auxiliary uses of the land irrigation site are described briefly, and the approximate potential revenues from each estimated. It is obvious that the operating costs of the system would be largely if not entirely offset by using the same land irrigation site for many other purposes in addition to that of renovating the wastewater.

No discussion of the benefits of treating the wastewater to drinking water standards is presented here, as these benefits would be comparable for any other system which would achieve the same end result. It has been assumed that the high standards achievable by the land treatment process will be adopted by society as necessary, and that the most economical means to achieve them will be sought. With the possible incomes from other sources, the operating cost of the land treatment system is obviously very low, probably much lower than any other reasonable system of treatment, even ones with far less effectiveness in renovating the water. It is therefore our conclusion that the use of the land treatment system for large metropolitan areas deserves careful evaluation of those responsible for the planning and engineering of solutions to the present problems of water pollution.

ACKNOWLEDGMENT

The Muskegon County project has been financed in part with federal funds from the Environmental Protection Agency under grant number C261503, and also under grant number 11010 GPS for portions of the project work which are of a research and developmental nature. The contents of this paper do not necessarily reflect the views and policies of the Environmental Protection Agency, nor does mention of trade names or commercial products constitute endorsement or recommendation for use.

The Chicago regional wastewater management study is sponsored by the Chicago District, Corps of Engineers, Department of the Army. The official designation is the Chicago-South End of Lake Michigan wastewater management study.

DISCUSSION

Unknown: Would you explain that land acquisition? Is this private large farm land or public land?

Bauer: Yes. In both of these cost estimates we assumed that the land would be acquired from private owners by the agency constructing the system. In the case of Muskegon County, the county is acquiring the land. Most of the land was acquired by direct negotiation. We did have an increase in the cost of the land at Muskegon over the original cost estimates. There are two reasons for that. One is that I suppose that it just was not appraised properly in the first place. We had an independent land appraiser who gave us an estimate of 2½ million dollars as being the acquisition price of all that land and we put it in our cost estimate as 3.2 million. The land is presently about 85% or 90% acquired and projecting on the basis of what has been spent so far, the total acquisition cost is estimated at roughly 5 million at the present time. Now that's 100% local cost. It's not shared by the Federal and State Government. There is another cost, however, that is shared by the Federal Government, in fact, it's totally paid for by Federal funds. There was a law passed during the time that the project was getting underway which said that if Federal money was involved and people were displaced on the land, they were to be compensated. In addition to being compensated for their land, they were to be paid for any other costs they may suffer because of being forced to move. Such things as: additional interest on new mortgages. If they had an old mortgage at a low interest rate and now they have to buy a new place and they have to pay a higher interest rate; if they have moving expenses; maybe they couldn't find any property that was suitable without paying a higher price than they got for their old one and that kind of thing. Those payments added up to roughly somewhat less than a million and that's compensated for by the grant from the Federal Government. So these land costs that I'm putting in here are the acquisition costs plus the relocation costs.

Davis: For both Chicago and Muskegon how much of this land would be used for farming or forest? You referred to using parts of it for lagoons and for electric plants and so on.

Bauer: Generally about 85% of it is used for agriculture and 15% of it would be used for the treatment facilities and related access.

Unknown: What kind of authority do you deem sufficient for the

Bauer: boundary area to come in both Illinois and Indiana? That's a subject that's being studied by somebody else. The Corps of Engineers has engaged a separate consulting firm to study the jurisdictional and the institutional constraints. There are a number of alternatives. One that I'd like to see is a private environmental utility and in that case I think it could be pretty well funded privately. This private environmental utility would enter into contracts with the various cities from which waste water would be taken and would enter into contracts with farm operators and into contracts with the power companies that wanted facilities on the site. It would simply provide an environmental function. It would receive and process solid wastes and so forth. That's one very neat way to do it. It would also provide a very large tax base for the area in which the facility would be located. Another way would be to have an authority created that would go across state lines, something like the TVA. I think there are a number of ways it could be done.

Lyon: I have a question and I guess I'm going to take the prerogative of the panel chairman and ask the last question. What degree of renovation do you expect to get from the irrigation drainage portion of the system?

Bauer: We expect to meet drinking water quality standards and then beyond that we're very interested in removing as much phosphate as possible. We've taken samples of the soil in the farm areas to try to make some assessment of its potential for precipitating out the phosphates and according to the analysis of about 30 samples that have been made so far, in the Chicago region, the calculations show that on the surface of the soil particles is a 10,000 year supply of iron and aluminum for precipitating phosphates. The estimated concentration is about .01 milligrams per liter. Our logic is based on the fact that this is the background level which is observed in natural streams that are fed by water which is percolating through the soil. We've been saying that natural soils have in the upper horizon a sizeable phosphate concentration. They must have, otherwise, the plants wouldn't grow and yet we don't see the soluble phosphates leak down into the ground water and out into the river. We're saying that it is because of the huge surplus of precipitation capacity that exists in that soil. Now we're going to put on more phosphates. We don't know how much we are going to accelerate the use of this precipitation capacity but after going through our analysis we still think that the concentration will be down at that 0.01 milligram per liter level.

IMPLEMENTING THE CHICAGO PRAIRIE PLAN

Frank Kudrna and George Kelly
The Metropolitan Sanitary District of Greater Chicago

064H

The Metropolitan Sanitary District of Greater Chicago has been involved in environmental protection since its creation by the Illinois State Legislature over 80 years ago.

Collection, treatment, and recycle of all domestic and industrial waste is a day-to-day responsibility of the Metropolitan Sanitary District. During its long and successful history, the District has researched, investigated, and practiced numerous methods of chemical and biological treatment. The results of this experience have clearly indicated that the ultimate solution to today's problem of environmental destruction must come through an understanding of the environment and its natural purifying cycles. The Sanitary District has developed a program for the recycle and reuse of sewerage solids, the by-products of the water reclamation process. It is a far-reaching, environmentally sound program based on nature and the natural purifying cycles. The Sanitary District calls its concept, "The Prairie Plan."

The first implementation of "The Prairie Plan" is being carried out on over 7,000 acres of land in Fulton County, Illinois. The District is constructing, out of land lain barren by strip mining, and environmentally safe recycle farm with integrated monitoring, quality control provisions, and multiple-use facilities.

In 1967, the Board of Trustees of the Metropolitan Sanitary District formally adopted the environmentally sound policy of "Solids on Land." A concept for the beneficial recycle of sewerage solids, a by-product previously considered a waste material. With the adoption of this policy, the Board authorized an extensive program of research and testing to develop a system for implementation of this policy. The resulting engineering reports, demonstration projects, and experimental farms have proven that the solid material removed from the used water, once stabilized, can safely, economically and productively be recycled to rebuild soil and sustain agricultural growth as a fertilizer substitute.

The most significant demonstration project has been a cooperative effort between the Sanitary District and the University of Illinois Agronomy Department under the sponsorship of a Federal research grant. This continuing project is being conducted at a test farm at Elwood, Illinois, and is designed to monitor the

immediate and long term environmental effect resulting from the use of solids, now called, "liquid fertilizer."

To demonstrate to the residents of communities outside of its jurisdiction boundaries (Cook County) that liquid fertilization is safe and non-objectionable, the District constructed at least one demonstration project in each of its eight urbanized service basins within and surrounding the Chicago Metropolitan Area. The most significant of these is a working farm at the Hanover Water Reclamation Plant which has, for the past five years, utilized the liquid fertilizer within a successful farming operation. In addition, liquid fertilizer has been applied to park grasslands, has generated topsoil on a landfill in Lake Michigan (Northwestern University), and has generated growth on 37 acres of barren silica sand (Ottawa, Illinois).

The result of the research work and demonstration projects was a clear indication that liquid fertilizer could be safely, economically, and beneficially returned to the soil. Once the small scale programs had proven successful, the Sanitary District developed a concept for the large scale implementation of its recycle program called, "The Prairie Plan."

The Prairie Plan was the methodology for the location and total design development of the 30,000 usable acres of farmland needed for the safe recycle of all wastewater solids generated within the Sanitary District.

Simply stated, the Prairie Plan is a program that utilizes the assimilative capacity of nature for the environmentally sound assimilation of man's by-products. Based on a principle of watershed planning, it utilizes the ground as an immense, natural filter and collection system. Utilizing a single watershed with known physical characteristics as the basis for application, not only do the soil and living plants act as a filter, but there is a natural way to collect all of the filtered runoff at one point for continuous monitoring and water quality control. The result is a flowing stream which is clean, free from silt, and potentially a valuable resource for recreational, commercial, and industrial development.

The Metropolitan Sanitary District, after extensive land investigation, purchased in December of 1970, a parcel of land of approximately 7,000 acres in the northeastern portion of Fulton County located in the upper reaches of the Spoon River Watershed, approximately 200 miles southwest of Chicago.

The land was acquired with the complete knowledge and cooperation of the Fulton County Board of Supervisors. The site, a former strip mine, offered the unique opportunity to not only

recycle liquid fertilizer but to reclaim mine spoil, thereby, increasing the local tax structure.

This site, although a relatively small percent of the entire Spoon River Watershed, is located on the headwaters to several small creek sheds. Its northern boundary follows a natural ridge-line and its eastern boundary is also the upper reaches of the watershed. Its location within the watershed, together with the disruption of existing drainage patterns due to the strip mining operations, has resulted in a site that is basically self-contained in terms of water flow. This condition allows a site plan to be developed around the concept of complete water monitoring and control, assuring environmental quality.

As a first step in the actual site development, an inventory of the physical characteristics of the land was completed. This environmental survey included topographical mapping, boundary mapping, surficial soil mapping, subsurface soil and bedrock investigations, surface drainage investigation and delineation of existing or potential floodplain areas.

The Board of Trustees of the Metropolitan Sanitary District, working in cooperation with the Fulton County Board of Supervisors, in order to assure optimum benefits from the development of its Fulton County Project, brought together a Steering Committee to provide input into the land use planning of its property.

The membership of this Steering Committee includes local elected representatives, interested local citizens, agencies and departments of the State of Illinois (Illinois Environmental Protection Agency, Department of Conservation, Department of Business and Economic Development), the Soil Conservation Service, University of Illinois (Agronomy School and Extension Service), representatives of local educational institutions, as well as staff personnel from the Sanitary District.

The goal of this Committee has, from the beginning, been optimum use for the greatest public benefit; recognizing that although the land in Fulton County was purchased for the primary purpose of the Solids on Land Program, the needs of the local communities could be introduced into the plans with compatible secondary goals of recreation, conservation and natural science education.

The initial land purchase was divided into three zones for planning and development. The land use plan for each of the areas was developed and reviewed under the general direction of the Steering Committee prior to implementation. The result of this action has been a land use policy that reflects the needs of both the citizens of Cook and Fulton Counties.

The primary example of this multiple-use concept has been the leasing of over 700 acres of lake and park land to the citizens of Fulton County by the Metropolitan Sanitary District for the annual fee of \$1. This fishing, camping and recreational site has become a well-known and highly utilized County resource.

The first objective of the Sanitary District was to quickly implement a transportation contract and develop temporary holding basins to provide relief for the increasing liquid fertilizer production in the Chicago area. This relief was provided by the construction of the first of three holding basins, a 2 million cubic yard basin, costing \$586,254. Then a three-year turnkey transportation contract was negotiated involving the shipment of 4 barge loads of fertilizer daily (7500 wet tons), via the Illinois River, 200 miles to Liverpool, Illinois. There, barge docks and unloading facilities were constructed and the material is pumped approximately 10-1/2 miles through a pipeline to the completed holding basins. The cost of the three-year transportation contract that was required to be operational in 90 days was \$17,900,000.

Having solved its immediate problem, the Sanitary District developed farm fields out of the mine spoils and constructed a distribution system consisting of a dredge installed at the holding basins which carried the liquid fertilizer to a distribution header and pump station which then transports it via a series of surface pipelines to mobile water winch vehicles which spray the liquid fertilizer onto the farm fields. A total of 810 acres will be put back into productive agricultural utilization by the end of 1972. And by the end of 1973, over 3,000 acres will be for productive agriculture.

To date, the total cost of construction contracts awarded in the Fulton County area is over \$22,000,000. At present, the District has under design three additional grading contracts, as well as their distribution piping and pumping facilities.

The overall project cost of the Fulton County Operation is at present below the cost of other alternatives. The initial landholdings represent approximately 20% of the ultimate land needed for the recycle of all solids generated within the Sanitary District. As additional lands are acquired, a pipeline from the District will be constructed and the unit cost of the Fulton County Program will be greatly reduced.

The Sanitary District, with its Prairie Plan Program, has developed a way to actually realize the now popularized goals of recycle and reuse. The program has, from its conception, received very favorable local and national press. The District's work continues to be well received at the local level and 3,500

additional acres of land have been acquired as a result of this acceptance.

The slurry pipeline, now being planned, which will transport the liquid fertilizer from Chicago to Fulton County, is being thought of as having a unique multi-use potential of its own. Its location within a rapidly urbanizing region offers the possibility of significant areas of permanent open space, innerconnected with recreational trails, parks and facilities. The pipe is being planned so as to be able to accept inputs along the route from existing and projected urban developments, as well as having the provision for top-off for potential-use areas.

The acquisition and development of 30,000 usable acres of land within the framework of the Prairie Plan offers the possibility for the development of new towns and cities utilizing the open space, clean water and wastes assimilative capacities of the site.

The Prairie Plan, if developed to its full potential, could initiate and provide direction in developing regional parameters for physical economic development, could be the catalyst in the establishment of open-spaced areas, flood control, conservation and recreational space; and provide a new agricultural economic base for soil replenishment. It would become an integrated program for pollution control that would close the loop from user back to resource; converting society's discards into usable forms while maintaining the natural ecological balance.

The overall success of the plan to date has been the direct result of a thorough research and demonstration program and direct cooperative planning with local governments and State regulatory agencies.

The Prairie Plan is a project that is clearly both economically and ecologically sound.

DISCUSSION

- Larson: Do you plan to use the barging transportation system permanently or do you view a pipeline in the future?
- Kudrna: No. The economics are very clear. I think, that the pipeline cost is far less than barging. This is an interim measure because of the time table involved. To get something started and the fact that we only had a portion of our land, we went with the barging operation. But, we foresee in the long term future a pipeline as the most economical transportation method.
- Unknown: Are you using the 1 to 1.5% dry weight per year application rate? The amount that was mentioned yesterday, that is 10 to 15 dry tons per acre?

Kudrna: The loading rate of sludge that we are using and that has been approved by the Illinois EPA for strip mine land is a first year application of 75 dry tons per acre. This will be reduced to 25 tons per acre in a period of 5 years as the organic content builds up. For undisturbed land that already has an organic content, the application rate begins at 25 tons.

Unknown: Do you have some cost figures you can give us?

Kudrna: The cost per ton for the initial operation is approximately 50 dollars a ton which is comparable to other processes. However, of that cost per ton, 34 dollars are attributed simply to transportation. That cost is going to be greatly reduced with the pipeline in the long term solution. Right now, it's either equal to or slightly less than other alternative methods such as heat drying, incineration, Zimpro. However, it will drop as we get into the long term transportation system.

MT. SUNAPEE STATE PARK, NEW HAMPSHIRE
SPRAY IRRIGATION PROJECT

Terrence P. Frost, R. E. Towne, and H. J. Turner
Water Supply and Pollution Control Commission
State of New Hampshire

3235

The Sunapee State Park spray irrigation system in Newbury, New Hampshire, distributes pretreated sewage to mountain slopes forested with mixed hardwoods and scattered conifers interspersed with an occasional apple tree indicating orchard or pastureland abandoned a generation or more ago. Conifers tend to dominate the lower part of the slope with the numbers of oaks and birches increasing toward the upper levels. The system was planned and designed around the Pennsylvania State University project (Parizek et al., 1967).

The Sunapee system is unique in size, degree of slope sprayed, seasonal character, relatively poor soils, high groundwater levels, and atypical sewage quality.

Selection of the land application system was based on several timely occurrences in addition to the Pennsylvania studies. The Sunapee State Park sewage disposal system is tributary to Chandler Brook which drains the mountainous ski-slope terrain into Lake Sunapee slightly less than a mile downstream. In 1969 the state legislature by statute upgraded the lake water quality classification from Class B to Class A. In the words of New Hampshire law "there shall be no discharge of any sewage or wastes into waters of this classification." The A classification, therefore, compelled some form of tertiary or advanced waste treatment technique at the State Park to prevent all wastes, treated or otherwise, from entry into Lake Sunapee. Hence, the selection of spray irrigation techniques which we were eager to apply in New Hampshire in anticipation of keeping the nutrients and other wastewater constituents out of the surface waters and away from the groundwater.

The popular demand for reclassification to A was based, primarily on prestigious considerations and fear of phosphorus from sewage sources and the resulting algae nuisances. Mats of water felt (*Vaucheria* spp.), unpleasant to barefooted bathers, until controlled by the State, seriously interfered with water-based recreation at the Chandler Cove beaches and shoals. The algae nuisance was attributed in part to the treated, nutrient-bearing sewage entering the lake from the Sunapee Mountain recreational complex.

The Sunapee scheme is small. The spray area covers about four acres. The two holding ponds, originally designed as sewage stabilization or oxidation ponds and constructed in 1961, are each about one acre and located at the foot of the mountain. Influent to these sewage lagoons is by gravity flow in thousand-gallon increments pulled automatically from a siphon tank downstream and in series with the two State Park septic tanks. These intermittent siphoned flows provide velocities sufficient to keep the downgrade pipeline clear.

The spray irrigation segment of the Sunapee system is seasonal. Spraying takes place only in the summer for about six weeks between the first of June and mid-July--long enough to draw down the average depth of the two oxidation ponds from six to about two feet. Withdrawal of the top two and half million gallons for spray irrigation renews the ten-month storage volume. Natural runoff is diverted around the storage ponds except during the spray season by plugging one culvert and unplugging another. Prior to land application the stabilization pond effluent was disinfected and discharged annually each spring to the adjacent Chandler Brook during snow melt and subsequent high runoff.

Winter sports enthusiasts, chiefly skiers, enjoy the Park in winter, mid-December to mid-March. About 113,000 tickets are sold each winter at Sunapee State Park. Summer tickets sold average nearly 33,000 for each of the last three years, 1969-1971. Nearly all of the summer tickets are for rides up the mountain and back by gondola ski lift. The Park supervisor advised there are probably as many non-ticket-buying picnickers using the Park as there are lift-riders. The Park is little-used in late spring and late fall.

DESCRIPTION OF THE SITE

Soils

The soils of the forested spray irrigation plot, according to the United States Soil Conservation Service (Pilgrim, 1972) are typical of those found in the low mountain areas of New England. Granite stones are found both on the surface and within the soil. Natural fertility is quite low and the soils are acid. The area is dominated by well-drained soils with soil depth of more than four feet. Stone piles in the area indicate that the soils were farmed during earlier times.

Four distinct soils (Charlton, Millis, Norwell and Paxton) have been identified on the area. All have developed in loamy glacial till material derived principally from granite and mica schist rocks. Paxton, the dominant soil of the area is characterized as follows:

- (1) A 3-inch forest floor surface layer of partially decomposed pine needles and deciduous leaf material;
- (2) A subsoil layer extending to about 24 inches consisting of dark brown, fine, sandy loam. Water moves at a moderate rate through this layer;
- (3) A distinct hardpan layer occurs at about 2 feet and extends to depths greater than 4 feet. This hardpan layer is light olive brown and of fine sandy-loam texture. Vertical water movement is slow through this pan and most water moves laterally down slope on the top of the pan.

Annual soil monitoring is being conducted by the Soil Conservation Service and the New Hampshire Agricultural Experiment Station. Eight soil pits have been established on the area. Pits are opened for soil sampling after the summer spray operation. Soil samples are analyzed for changes in chemical properties.

A comparison of water quality of Sunapee holding pond effluent (spray irrigant) with the quality of holding pond effluents (after secondary treatment) reported by the Corps of Engineers, United States Army, Cold Regions Research and Engineering Laboratory at Hanover, New Hampshire (1972) is given in Table 1.

METHOD OF OPERATION

Oxidation pond effluent chlorinated at 5 milligrams per liter was sprayed for about six weeks during June and July, 1971, onto the somewhat hilly four-and-a-half acre wooded terrain with slopes of 10 to 15 percent.

Spraying was accomplished via three spray lines covering about 1.5 acres each for a total coverage of 4.5 acres. Each of the three spray lines averaged fourteen Rain Bird kicker-type spray heads mounted on 2-foot high risers. Feeder lines ascending the slope are four-inch diameter aluminum irrigation pipe. Lateral spray lines are three-inch diameter conventional farm-type irrigation pipe. Spray nozzles are spaced 50 feet apart. Laterals range from 600 to 700 feet in length. Piping is held in place by metal fence posts. Initially, when laid loose on cement blocks the pipelines rotated under pressure and caused misalignment of risers as well as chronic uncouplings of main and lateral horizontal pipelines.

Distance between lateral lines is about 80 yards. All piping is self-draining to the northernmost holding pond.

Table 1. Comparison of Sunapee Holding Pond Effluent with a Typical Secondary Treatment Plant Effluent

Constituent	Typical Composition*	Sunapee Composition		
	Range	Low	Mean	High
	mg/l		mg/l	
BOD	2-25	12	28	55
SS	3-50	25	83	296
NH ₃ -N	0-10	0.1	2.0	4.4
NO ₂ -N	2-13	0.01	0.14	0.95
NO ₃ -N	7-13	0.16	0.61	1.48
P	4-14	0.7	0.9	1.2
Na	40-100	6.2	17.0	21.2
Cl	40-100	11	23	30
Ca ⁺⁺	1-40	5.8	8.4	14.5
Mg ⁺⁺	1-10	3.45	6.75	11.80
K ⁺	7-10	5.3	6.8	8.1
LAS	5-10	0.1	0.2	0.3
pH	6.5-7.5	7.0	7.9	8.5

* Excerpted from Table 3-I, p. 36, Wastewater Management by Disposal on the Land, Cold Regions Research and Engineering Laboratory, Hanover, New Hampshire, February 1972.

Spray nozzles were of three different sizes, one size to each of the three lines to compensate for elevation differences between the lines. Circular coverage around each riser was about one hundred feet in diameter. Nozzle pressures ranged from 40 to 60 pounds per square inch. Each line delivered approximately 100 gallons per minute during the fourteen hours it operated once each week. Application rate amounted to 0.14 inch per hour, equivalent to a total weekly application of about 2 inches.

Spraying was done Tuesday, Wednesday and Thursday. Automatic, sequencing timers started opening a motorized valve at 6:00 a.m. in the morning. The valve when half-open, energized one of two pumps and the spraying began, continuing until 8:00 p.m. in the evening.

The system is protected against breaks in couplings or piping by use of a time-delay device which will shut off the valve and stop the pump if pressure is not reached within four minutes of starting time. This avoids flooding the pumps and the combination pumphouse and chlorinator room. Both pumps are 15 horsepower,

electrically driven with one hundred gallons per minute pumping capacity against a 100-foot head. Pumps were alternated each week.

Configuration of the sprayed terrain is such that most, if not all, of the runoff from the sprayed area will divert back to the stabilization ponds for ultimate reapplication to the irrigation area.

Four forest floor (duff) pan lysimeters were randomly installed within the spray area and two were placed as controls outside the area, one at a higher and one at a lower elevation than the spray area. Method of placement was to remove the upper 4 to 8 inches of forest floor and soil with as little disturbance as possible, put the duff pan in place, and replace the relatively undisturbed duff layer and soil in the pan. Sterile polyethylene two-liter bottles left in thirty-gallon, friction-top, galvanized, weatherproof cans sunk into the ground down slope of the duff pans were used to collect water samples. The lysimeters were designed and positioned to collect precipitation and spray liquid so that the volume per unit area could be estimated, and the collected percolate analyzed in the laboratory.

A test pit about 3 feet wide by 7 feet long and 5 feet deep was dug within the spray area with lysimeter pans staggered along one wall at the 1-, 2-, 3-, and 4-foot depths and the pit covered with a hinged 4 by 8 foot sheet of 5/8 inch marine plywood. The pit was later abandoned due to high groundwater and doubt as to ability to collect representative samples.

A standard rain gauge was located under the forest canopy near the top of and within the spray area, and a second rain gauge was placed outside the spray area in the open near the holding ponds. Rainfall at the site for 3 years of record, 1969-1971, averaged 37.6 inches. Rainfall for 30 years of record at the United States Weather Service rain gauge at the Concord, New Hampshire airport, about 30 miles from the spray site, averaged 38.8 inches.

Three well-points were driven along the downstream periphery of the slopes and used as test wells. These three test wells, driven to the point of refusal, average about 11 feet in depth and are used to assay groundwater quality on the downslope periphery of the spray area between the irrigation plot and the holding ponds. In addition seven downstream domestic wells and one public spring were routinely sampled.

Two sampling stations were located on Chandler Brook bracketing the spray area. Comparative water samples from water supply wells, test wells, duff pans, holding pond influent and effluent, and the brook were collected and analyzed weekly for the components listed in the various tables. Sampling continued before, during, and after the spray period.

RESULTS

Preliminary analyses of the data indicate that spray irrigating with pretreated sewage stabilization pond effluent at Sunapee State Park in Newbury, New Hampshire has not resulted in any substantial or discernible alteration in the composition of the groundwater in the test wells, water from the drinking water wells, or downstream surface waters. Quality of the percolate water collected from a lysimeter in the spray irrigated area is given in Table 2. For comparison, the quality of the percolate water collected from a lysimeter in the control area is given in Table 3. Condensed analytical results from Test Well B are given in Table 4. Results, unreported here, were similar for other test wells. Water quality samples collected from Chandler Brook upstream of the project are given in Table 5. For comparative purposes, Chandler Brook surface water quality data collected downstream of the project is given in Table 6. Groundwater quality in the Herbert Smith family drinking water well is given in Table 7. No changes that are positively attributable to the project appear in the water quality data for the Smith water supply. There is a possibility that consistently higher nitrate nitrogen results may, later in the study, be attributed to the spray system. The Smith well is about 800 feet from the spray area and is the private water supply nearest the project. Data was accumulated for four other well supplies and one surface spring. None of these supplies exhibited discernible water quality changes attributable to the spray operation.

The uptake or percentage removal of various constituents in the irrigant by the 4 to 8 inches of forest floor materials in the duff pan lysimeters is shown in Table 8.

CONCLUSION

The small, seasonal, atypical sewage spray irrigation system at the Sunapee State Park in Newbury, New Hampshire appears to have worked effectively to date to protect contiguous groundwater and surface waters. Based on experience in New Hampshire and Pennsylvania it is the opinion of the New Hampshire Water Supply and Pollution Control Commission staff that the Sunapee system will probably continue to operate effectively for a long and perhaps indefinite period of time at the present mode of operation.

Table 2. Quality of Percolate Water Collected from a Lysimeter in the Spray Irrigated Area

Constituent	Time	Number of Samples	Range		Mean
			mg/l		mg/l
PO ₄ -P	before	12	0.000	- 0.090	0.033
	during	5	0.025	- 0.072	0.050
	after	15	0.003	- 0.174	0.030
pH	before	15	5.5	- 7.7	6.6
	during	5	5.6	- 6.8	6.3
	after	28	5.2	- 7.0	6.2
Alkalinity	before	15	5	- 23	13
	during	5	12	- 20	17
	after	28	3	- 50	15
NO ₂ -N	before	13	0.000	- 0.046	0.014
	during	5	0.002	- 0.174	0.075
	after	24	0.010	- 1.350	0.291
NO ₃ -N	before	15	0.052	- 2.180	0.860
	during	5	1.17	- 7.17	3.62
	after	28	0.13	- 26.20	7.26
Cl-	before	13	0.5	- 4.8	2.0
	during	5	7.3	- 18.5	12.3
	after	22	1.0	- 17.5	3.0
Ca++	before	14	0.8	- 3.1	2.6
	during	5	5.2	- 9.2	6.8
	after	27	0.1	- 44.2	14.5
K+	before	15	0.7	- 4.9	3.6
	during	5	4.9	- 8.2	6.4
	after	28	1.6	- 10.0	5.8
LAS	before	12	0.1	-	0.1
	during	4	0.1	-	0.1
	after	18	0.1	-	0.1
Mg++	before	14	0.30	- 1.60	0.70
	during	5	0.78	- 1.49	1.12
	after	28	0.01	- 3.66	1.50
Na	before	15	0.3	- 4.5	1.6
	during	5	0.7	- 7.5	4.2
	after	28	0.6	- 11.7	2.1

Table 3. Quality of Percolate Water Collected from a Lysimeter in the Control Area

Constituent	Time	Number of Samples	Range		Mean
			mg/l		mg/l
PO ₄ -P	before	13	0.000	- 0.396	.058
	during	1		-	.020
	after	11	0.003	- 0.144	.028
pH	before	13	5.1	- 6.7	6.1
	during	1		-	6.1
	after	21	5.3	- 7.4	6.4
Alkalinity	before	14	2	- 18	12
	during	1		-	20
	after	20	7	- 25	15
NO ₂ -N	before	12	.001	- .013	.067
	during	1		-	.002
	after	20	.001	- .678	.115
NO ₃ -N	before	13	.089	- .926	.494
	during	1		-	.556
	after	21	.070	- 6.57	1.964
Cl-	before	13	0.4	- 7.0	2.2
	during	1		-	2.0
	after	20	1.0	- 5.1	2.2
Ca++	before	14	0.6	- 11.2	2.5
	during	1		-	2.7
	after	24	0.1	- 12.2	3.2
K+	before	14	3.0	- 8.0	4.7
	during	1		-	6.5
	after	24	1.5	- 11.0	4.5
LAS	before	12	all	0.1	0.1
	during	1		-	0.1
	after	15	0.1	- 0.2	0.1
Mg++	before	14	.46	- 3.20	1.01
	during	1		-	0.62
	after	24	.37	- 1.68	0.94
Na	before	14	0.3	- 9.3	1.8
	during	1		-	0.8
	after	24	0.3	- 1.5	0.8

Table 4. Water Quality of Samples Collected from Test Well B

Constituent	Time	Number of Samples	Range		Mean
			mg/l		mg/l
PO ₄ -P	before	34	0.000	- 0.149	0.018
	during	7	0.006	- 0.017	0.012
	after	30	0.001	- 0.047	0.012
pH	before	36	6.1	- 8.0	7.2
	during	7	6.4	- 7.5	7.0
	after	46	4.6	- 8.0	7.0
Alkalinity	before	35	30	- 46	38
	during	7	31	- 36	34
	after	46	30	- 45	35
NO ₂ -N	before	33	0.000	- 0.163	0.003
	during	7	0.008	- 0.019	0.011
	after	40	0.003	- 0.167	0.040
NO ₃ -N	before	34	0.011	- 1.550	0.191
	during	7	0.051	- 0.460	0.218
	after	45	0.001	- 1.110	0.151
Cl-	before	34	0.5	- 5.5	2.2
	during	7	1.0	- 1.7	1.3
	after	40	1.5	- 5.6	2.8
Ca++	before	37	4.0	- 30.7	10.4
	during	8	7.6	- 12.5	8.5
	after	45	0.2	- 13.8	4.8
K+	before	33	0.7	- 5.1	1.9
	during	8	1.2	- 1.6	1.5
	after	45	0.8	- 3.4	1.5
LAS	before	32	0.1	- 0.1	0.06
	during	7	0.1	- 0.1	0.1
	after	23	0.1	- 0.1	0.1
Mg++	before	34	0.84	- 5.50	1.63
	during	8	0.86	- 1.11	0.99
	after	45	0.29	- 1.58	0.61
Na	before	33	3.6	- 6.6	4.9
	during	8	1.58	- 4.25	3.71
	after	45	2.4	- 7.3	3.5
MPN		34	3	3	3

Table 5. Water Quality of Samples Collected from Chandler Brook
Upstream of the Spray Irrigation Project

Constituent	Time	Number of Samples	Range		Mean
			mg/l		mg/l
PO ₄ -P	before	18	0.003	- 0.032	0.012
	during	7	0.012	- 0.162	0.044
	after	27	0.001	- 0.165	0.029
pH	before	20	6.2	- 6.9	6.5
	during	7	6.2	- 7.2	6.8
	after	41	4.6	- 7.2	6.6
Alkalinity	before	20	7	- 20	14
	during	7	18	- 28	23
	after	41	6	- 60	23
NO ₂ -N	before	20	0.002	- 0.012	0.005
	during	7	0.001	- 0.078	0.014
	after	40	0.001	- 0.715	0.039
NO ₃ -N	before	20	0.076	- 1.34	0.294
	during	7	0.080	- 0.259	0.172
	after	41	0.010	- 2.450	0.272
Cl-	before	20	4	- 175	20
	during	7	10	- 21	15
	after	40	1.0	- 610	24
Ca++	before	20	3.6	- 19.0	7.74
	during	7	6.8	- 12.8	9.99
	after	41	0.50	- 33.0	7.45
K+	before	20	0.5	- 3.1	0.9
	during	7	0.4	- 1.0	0.8
	after	41	0.4	- 2.8	2.0
LAS	before	17	0.1	- 0.1	0.1
	during	6	0.1	- 0.1	0.1
	after	20	0.1	- 0.1	0.1
Mg++	before	20	0.61	- 1.68	1.01
	during	7	0.14	- 1.73	1.04
	after	41	0.37	- 4.60	0.97
Na	before	20	4.0	- 103.0	13.9
	during	7	2.1	- 11.7	8.4
	after	40	3.3	- 27.0	14.2

Table 6. Water Quality of Samples Collected from Chandler Brook
Downstream of the Spray Irrigation Project

Constituent	Time	Number of Samples	Range		Mean
			mg/l		mg/l
PO ₄ -P	before	19	0.002	- 0.031	0.012
	during	7	0.001	- 0.041	0.019
	after	27	0.001	- 0.054	0.014
pH	before	20	6.2	- 7.1	6.7
	during	7	6.7	- 7.0	6.8
	after	40	6.1	- 7.3	6.6
Alkalinity	before	20	6	- 22	15
	during	7	9	- 31	23
	after	40	7	- 35	20
NO ₂ -N	before	16	0.004	- 0.010	0.007
	during	7	0.001	- 0.101	0.019
	after	38	0.001	- 0.825	0.043
NO ₃ -N	before	20	0.098	- 0.467	0.192
	during	7	0.080	- 0.348	0.239
	after	38	0.010	- 0.584	0.180
Cl-	before	20	3	- 29	18
	during	7	0	- 39	27
	after	39	0	- 52	21
Ca++	before	20	3.8	- 12.5	8.1
	during	7	9.3	- 15.2	12.8
	after	40	0.7	- 28.6	10.8
K+	before	20	0.5	- 1.8	0.9
	during	7	0.5	- 1.6	1.2
	after	40	0.4	- 2.5	1.2
LAS	before	18	0.1	- 0.1	0.1
	during	6	0.1	- 0.1	0.1
	after	20	0.1	- 0.1	0.1
Mg++	before	20	0.64	- 1.33	1.05
	during	7	0.98	- 2.23	1.66
	after	40	0.38	- 1.95	1.19
Na	before	20	2.9	- 19.4	10.6
	during	6	2.3	- 22.9	12.4
	after	40	1.8	- 25.6	15.1

Table 7. Water Quality of Samples Collected from the Herbert Smith Well about 800 Feet from the Spray Irrigation Project

Constituent	Time	Number of Samples	Range	Mean
			mg/l	mg/l
PO ₄ -P	before	16	.011 - .042	.026
	during	7	.018 - .057	.035
	after	40	.001 - .71	.080
pH	before	16	6.0 - 6.8	6.3
	during	8	6.2 - 6.9	6.6
	after	39	6.0 - 6.85	6.4
Alkalinity	before	16	7 - 16	13
	during	8	12 - 24	18
	after	40	2 - 75	17
NO ₂ -N	before	16	.000 - .012	.004
	during	8	.001 - .017	.004
	after	38	.000 - .113	.009
NO ₃ -N	before	16	.007 - .096	.043
	during	8	.012 - .184	.096
	after	39	.000 - .57	.116
Cl-	before	14	0.0 - 20.0	1.8
	during	7	0.0 - 26.8	4.6
	after	38	0.0 - 15.5	1.4
Ca++	before	16	3.4 - 7.0	5.5
	during	8	5.0 - 10.0	6.2
	after	40	0.5 - 12.3	5.3
K+	before	16	0.3 - 3.1	0.8
	during	8	0.3 - 0.5	0.4
	after	40	0.2 - 2.0	0.6
LAS	before	14	0 - .1	.1
	during	6	.1 - .1	.1
	after	20	.1 - .1	.1
Mg++	before	16	0.01 - 6.80	1.65
	during	8	0.48 - 1.00	0.72
	after	40	0.40 - 1.80	0.78
Na	before	16	2.0 - 14.8	3.9
	during	8	0.8 - 4.5	3.0
	after	38	0.9 - 8.3	3.2

Table 8. Degree of Wastewater Reclamation by Upper Eight Inches of Forest Floor and Soil

Constituent		Percentage removal ^a	Average
Nitrite	(N)	47 - 94	71
Nitrate	(N)	0 - 46	16
Phosphate	(P)	92 - 98	95
Potassium	(K+)	0 - 32	15
Sodium	(Na+)	46 - 92	68
Chloride	(Cl-)	0 - 81	34
Magnesium	(Mg++)	0 - 54	24
Detergent	(LAS)	50 - 100	87
Calcium	(Ca++)	0 - 80	44

^aValues obtained from 4 duff pan lysimeters.

REFERENCES

- Corps of Engineers. 1972. U.S. Army, Cold Regions Research and Engineering Laboratory, Wastewater management by disposal on land, Hanover, New Hampshire.
- Parizek, R. R., L. T. Kardos, W. E. Sopper, E. A. Myers, D. E. Davis, M. A. Farrell, and J. B. Nesbitt. 1967. Wastewater renovation and conservation, Penn State Studies 23, The Pennsylvania State University, University Park, Penna., 73 p.
- Pilgrim, Sidney. 1972. Personal communication, United States Conservation Service, Durham, New Hampshire.

DISCUSSION

- Francke: Mr. Williams have you had an experience with plastic or rubber lined ponds?
- Williams: No. They're much too expensive for our clients. We've used clay with varying success. With good workmanship and good clay material we can get a good seal. We have tried bentonite and sand and have not had good success. We have tried sprayed-on asphalt and have not had good

success with this either. We have found that soda ash helps to seal a clay lined pond. The ponds that have leaked have ultimately sealed up rather well. The Michigan Dept. of Public Health does not encourage pond systems leaking unless they're planned to leak. Now we do have some that we have planned to leak. We have run hydrogeological surveys and have determined the location of the groundwater table. In these situations there are no wells for domestic purposes down slope from the ponds.

Rhindress: I'm glad that last question was asked. In case anybody has any doubt, in Pennsylvania we do not like leaking lagoons, period.

UTILIZATION OF SPRAY IRRIGATION FOR WASTEWATER DISPOSAL
IN SMALL RESIDENTIAL DEVELOPMENTS

T. C. Williams
Williams and Works, Inc.

335D

Williams & Works has designed sixteen pond and irrigation wastewater treatment systems for various governmental units in Michigan. Eleven of these are completed, and the other five will be operational in 1974. The first pond and irrigation wastewater system was that for the Village of Cassopolis which was constructed in 1964. The Cassopolis system consisted of a series of ponds, Pond No. 1 being an anaerobic cell, Pond No. 2 being a clay-lined facultative pond, Pond No. 3 and Pond No. 4 being unsealed seepage ponds which we anticipated would seal up and become facultative ponds. We expected Ponds Nos. 3 and 4 to leak but not, in the long run, to be able to handle the total influent hydraulic load, and therefore, we provided a spray irrigation system of about five acres on the tail-end of the system so that we would have a way of disposing of any surplus water at the time that the ponds sealed. As it turned out, our seepage ponds have been more than enough to handle the total hydraulic loading and in consequence, we did not have any experience with the spray irrigation system. It is important, we find, to keep the seepage pond areas mowed and to dose them intermittently. So even though this system has been in operation for eight years, we do not have any operating data on the spray irrigation part of the system. In addition to these various pond and irrigation wastewater treatment systems, we have, during the past ten years, designed more than twenty pond systems in which treatment is followed by discharge of the treated wastewater to a nearby water course on a semi-annual basis.

Over the years, we have used the words "lagoon" and "pond" interchangeably. But due to the widespread news coverage given to one of our western Michigan cities when they had odor problems with a sludge lagoon, we have adopted the use of the word "pond" almost exclusively for our purposes. But whether they are lagoons or ponds, we have used one of the following designs for the systems we have developed:

1. Two facultative ponds designed to operate either in parallel or in series at the discretion of the operator. We are writing in our operating manuals that these ponds should be operated in parallel during the winter and in series during the summer. During the winter, very little biological activity takes place in these ponds and it is important that the organic loading be distributed between the two to minimize odor problems in the spring when biological activity resumes.

2. A series of ponds, consisting of an anaerobic cell followed by at least three facultative cells.

3. Mechanically aerated ponds, followed by holding ponds. These artificially aerated ponds can be either surface aerated with floating aerators or can be aerated with compressed air.

An advantage of using the first type is that facultative ponds require a minimum of operational attention. The treatment is accomplished by natural means using the sun and the wind. Also, we have a heavy algae bloom during the irrigation season and as a consequence, the nitrogen, phosphorus and other organics are, to a large degree, bound up in the algae cells at the time of irrigation. When properly loaded, these ponds are quite nuisance free. The major disadvantage to this type of design, in Michigan at least, is the result of our climate which limits the possible loading to a maximum of 20 pounds of BOD per acre. This limitation increases the land requirements, of course, to such an extent that in some cases it is not economically feasible to pursue the development. This is the most expensive pond system in terms of capital requirements but it is the least expensive in terms of operating costs.

The second method, the use of an anaerobic cell followed by facultative ponds, is also a natural system. Significant phosphorus and nitrogen reductions are achieved by the growth of different biota in each pond. An added advantage is the fact that less land is required than for facultative pond systems. When they are properly designed and operated, these anaerobic-facultative systems can also be nuisance free. However, there are instances when it is not possible to control the unit loading on the anaerobic cell and odor problems have resulted. As a part of an EPA sponsored research project on irrigation of pond effluent at Belding, Michigan, data has been collected for the past five months on the anaerobic-facultative pond system. It shows a significant decrease in the phosphorus and nitrogen through the pond system. It has also been noted that while there is an abundance of phosphorus and nitrogen in the last two ponds, there is not always a significant algae bloom. The wastewater to be irrigated from this pond system is much lower in nutrients than that from the activated sludge plant at Penn State. The Belding system is a mature pond system. It has been in operation since 1965 and, incidentally, it does take a significant volume of combined storm and sanitary flow in addition to the strictly sanitary flow from the community.

The third type of design involves the use of artificial aeration and is used most frequently for larger communities because the land requirements are less. The disadvantage is in the additional operating expense necessitated by increased maintenance requirements and the purchase of electricity.

One important consideration in each of the three types of lagoon systems we have designed is the provision for a minimum of five months storage of the wastewater. In our opinion there are three major advantages of this provision:

1. The severe climate in Michigan presents special irrigation problems during the winter. The storage of the wastewater avoids these problems.
2. Operation costs for the treatment portion of the system are substantially reduced as the storage pond can be depended upon to provide a certain portion of the treatment.
3. The storage allows for the development of algae and rotifers. To some extent, a prolific growth of these organisms converts the soluble phosphorus and nitrogen into cells which is of value in the irrigation process as the nutrients are applied to the land in cellular rather than liquid form, and this allows for a slower breakdown and absorption rate.

The selection of the best lagoon design for a particular client should be made on the basis of site availability, economics and operating experience. It is relatively easy to evaluate data pertaining to sites and economics - engineers have been doing that for centuries - but in the area of operating experience, we encounter a severe shortage of data. There is a certain amount of information about the irrigation of effluent from mechanical treatment plants. Unfortunately, however, there are very few systems involving the combination of ponds and irrigation in operation at the present time - and these have been operating for such a short time that there is only a limited amount of data available. At best, we have only theory, guided by opinions.

The following data pertains to the operation and characteristics of the pond system at Belding, Michigan, from March 15 through July, 1972:

General characteristics of the influent:

NH₃-Nitrogen - 25 ppm

Total phosphorus - 2 to 12 ppm P, about 75% of which is
orthophosphate P pH - 7.2
D.O. - 0.0

Pond water quality variations:

Pond 1: $\text{NH}_3\text{-N}$ - 20 ppm in April, 20-25 ppm in August

	<u>Pond 1</u>		<u>Pond 2</u>		<u>Pond 3</u>		<u>Pond 4</u>		<u>Pond 5</u>	
	<u>Apr.</u>	<u>Aug.</u>	<u>Apr.</u>	<u>Aug.</u>	<u>Apr.</u>	<u>Aug.</u>	<u>Apr.</u>	<u>Aug.</u>	<u>Apr.</u>	<u>Aug.</u>
$\text{NH}_3\text{-N}$	20	25	20	5	20	≤ 0.5	20	≤ 0.5	20	≤ 0.5
$\text{NO}_3\text{-N}$		≤ 0.6		≤ 0.6		≤ 0.6		≤ 0.25		≤ 0.25
P	5 - 10		5	5	9	2	9	2	9	2
pH	← 7.2 ← varies considerably with photo-reproduction									
SS	← 60 ppm with great variation ← 20-25 →									
DO	← ≤ 0.1 highly variable, max. 25+ highly variable but never 0.0									

With respect to chemical and particulate changes Ponds 1 and 2 are each uniquely different and Ponds 3, 4 and 5 are similar to each other but different from 1 and 2. In general suspended solids (SS) and concentration of living organisms are directly related. pH values above 8.3 and dissolved oxygen (DO) above 10 ppm occur together and are products of photosynthesis.

In Pond 1 during March through June decomposition of algae is rapid in the anaerobic deeper waters and phosphorus is released as rapidly as it becomes organic bound in the upper layer. Additional phosphorus is solubilized in May as decay of older detritus becomes significant. In July, Pond 1 "went bad" losing most of its aerated upper water and living populations died and settled out.

In Pond 2 the living populations have their greatest range in photosynthetic activity and population concentration resulting in a more stable total phosphorus concentration and occasional extremely high DO values.

In Ponds 3, 4 and 5 as living populations and concomitant populations of dead and settled organisms increased through March and April, total phosphorus decreased. From mid-May through June release of phosphorus by decomposition of dead organisms became dominant. DO and pH responded to photosynthesis in all months but were outstandingly volatile in July.

The selection of the best land disposal method is only slightly more scientific than the means available for determining the best lagoon system. However, by the end of 1973, we anticipate having better data on the various methods we have utilized. Basically, one or more of the following methods are incorporated into the projects we have designed:

- a. Continuously loaded seepage basins.
- b. Intermittently loaded seepage basins.
- c. Intermittently loaded flood irrigation fields.
- d. Portable aluminum pipe systems.
- e. Solid set systems in which the pipes are buried.
- f. Travelling sprinkler.
- g. Center pivot sprinklers.

In selecting the proper land disposal method, consideration must be given to soils, topography, climate, depth to groundwater table, direction of movement of the groundwater table, chemistry of the natural groundwater, proximity of wells tapping the groundwater formation being recharged, and cropping.

In Michigan, it is common practice to chlorinate lagoon effluent before spray irrigation. There is general agreement, however, that chlorination is not necessary in flood irrigation or seepage basin projects except in those instances in which the flood irrigation area is underdrained. The lower power requirements and the avoidance of chlorination costs have combined to make a substantial argument in favor of flood irrigation and seepage methods (a, b, and c). However, it is most difficult to achieve uniform distribution of the nutrients over the entire site with these systems. If the concept to be followed involved the reliance upon soil chemistry for nutrient removal, the method of application is not as important. If, however, the Penn State "Living Filter" concept of nutrient removal by cropping is to be utilized, then spray irrigation is the best method.

Tables 1 and 2 give design data on nine pond and spray irrigation land disposal projects in Michigan. These vary in size from 6,000 to 900,000 gallons per day. Table 3 gives the construction cost per capita. In the following table, these costs have been grouped according to the size of the community:

Table 1. Design Data for Several Spray Irrigation Systems in Michigan

Project	Design Population (year)	Future Population	Design Flow	Loading in lbs. BOD per Day	Total Retention Time	Total Pond Area
Belding	8,000 (1993)		800,000 gpd	1,360	months 4	acres 51.4
Middleville	2,200	3,200 (1990)	150,000 ^{1/}	374	5	22.0
Ottawa Co. Infirmary	63 (1968)	80	6,000	16	7	1.0
East Jordan	3,700 (1990)		370,000	440	7	22.0
Wayland	5,000 (1990)		500,000	850	5	31.0
Harbor Springs	5,000 ^{4/} (1970)		580,000 ^{2/} 460,000 ^{3,5/}	765 ^{2/} 425 ^{3/}	5	21.4
Leoni Twp.	9,000 (1975)	25,000	900,000	1,530	6	35.5

Table 1. continued

Project	Design Population (year)	Future Population	Design Flow	Loading in lbs. BOD per Day	Total Retention Time	Total Pond Area
Roscommon Village	1,550 (1990)		gpd 155,000	264	months 6	acres 16.0
Cassopolis	2,200 (1970)		220,000	374	5.5	18.5

1/ Approximate average measured flow over a 5-year period.

2/ Summer time - approximately 3 months.

3/ Winter time - approximately 9 months.

4/ 4,500 summer population; 2,500 winter population.

5/ Includes 310,000 gpd infiltration.

Table 2. Spray Irrigation Application Rates for Several Spray Irrigation Systems in Michigan

Project	Type of Spray Irrigation	Area of Spray Irrigation	Instant Application Rate	Application Rate	Yearly Application Rate (Period of time)
		acres	in./hr	in./hr	inches
Belding	solid set	15.6	0.12	2.0 3.0 ^{1/} 4.0	80 ^{2/}
Middleville	solid set, portable laterals	25.1 and 5.3	0.12	2.7 ^{3/} 0.12	(7 mo.) 80 ^{2/}
Ottawa Co. Infirmary	portable laterals	3.3	0.25	2	(3 mo.) 80
East Jordan	solid set, portable laterals	42.0	0.12	2.86	(7 mo.) 62
Wayland	traveling, center pivot	20.0 and 33.0		2.5	(7 mo.) 76

Table 2. continued

Project	Type of Spray Irrigation	Area of Spray Irrigation	Instant Application Rate	Application Rate	Yearly Application Rate (Period of time)
Harbor Springs	traveling, center pivot	acres 30.0 and 21.3	in./hr	in./hr	inches
				4.0	(5 mo.)
				4.3	88 ^{4/}
					(5 mo.)
					95
Leoni Twp.	solid set	140	0.36	3.3	(6 mo.)
					86.3
Roscommon Village	solid set	24.0	0.20	3.3	(6 mo.)
					86
Cassopolis	solid set, fixed laterals	8.0	0.04	12.4	(2.5 mo.)
					346

^{1/} Different application rates on different crop areas; there are 5 different areas.

^{2/} The length of the irrigation period is being determined by tests - rest of the effluent will be disposed of into the nearby river.

^{3/} Used for future expansion.

^{4/} Approx. (2) months of storage has to be disposed by other means.

Table 3. Per Capita Costs for Several Spray Irrigation Systems in Michigan

Project	Acres of Land Purchased (Cost per Acre)	Cost of Ponds		Cost of Spray Irrigation		Total Treatment Cost	
		Total	Per Acre	Total	Per Acre	Total	Per Capita (not incl. Land)
<u>Belding</u>	---	\$257,200	\$5,000	\$ 91,980	\$5,100	\$349,200	\$ 42.70
<u>Middleville</u>	124.5 (\$350)	159,600	7,250	62,800	2,060	260,650	118.35
<u>Ottawa Co. Infirmary</u>	already owned the land	<u>1/</u>		<u>1/</u>		32,800	520.00
<u>East Jordan</u>	used the airport property	110,000	5,000	82,500	1,960	380,000	151.00

Table 3. continued

	Acres of Land Purchased (Cost per Acre)	Cost of Ponds		Cost of Spray Irrigation		Total Treatment Cost	
		Total	Per Acre	Total	Per Acre	Total	Per Capita (not incl. Land)
<u>Wayland</u>							
	133	\$165,000	\$5,325	\$33.00	\$1,890	\$365,000	\$ 73.00
	(\$500)						
<u>Harbor Springs</u>							
	-	198,000	9,300	39.80	1,480	849,700	170.00
<u>Leoni Twp.</u>							
	-	526,500	14,200	58.50		1,138,500	126.50
<u>Roscommon Village</u>							
	-	136,696	8,544	88.20	3,777	326,573	210.70
<u>Cassopolis</u>							
	40	83,855	4,540	38.20	1,080	140,355	63.80
	(\$395)						
1/ Package contract, no breakdown available.							

1/ Package contract, no breakdown available.

<u>Population Design</u>	<u>Per Capita Cost</u>
Less than 2,000 - 2 Systems	\$212 to \$520
2,001 - 8,000 - 6 Systems	\$ 43 to \$170
More than 8,000 - 1 System	\$126

Activated sludge treatment plants in Michigan towns between 3,000 and 12,000 population for the same time period, varied from \$77 to \$274 per capita. Generally, in evaluating alternatives, we find that a modified activated sludge treatment plant with chemical precipitation results in the lowest first cost when we take into consideration the land cost for land disposal schemes.

For the past several years in Michigan, grants have totalled 75% of all eligible project costs. The State of Michigan provides 25% in addition to the 50% federal grants available. Since land costs are not grant eligible, land disposal is the "high-priced spread" if only the amount of the initial local bond issue is taken into consideration. However, since all operating costs are also the responsibility of the local community, it is important to give them careful consideration in relation to the entire project. The following table indicates the range of operating costs for various facilities in Michigan. The activated sludge and trickling filter operating costs include an allowance for the cost of removing 80% of the phosphorus by chemical precipitation.

<u>Community</u>	<u>Treatment Provided</u>	<u>Population Served</u>	<u>Operation & Maintenance Cost Per Year Per Customer</u>
City of Grand Rapids	Activated Sludge	More than 300,000	\$ 9.00
City of Ironwood	Activated Sludge	9,000	26.00
City of Otsego	Trickling Filter	4,000	23.00
Village of L'Anse	Activated Sludge	Less than 3,000	37.00
Leoni Township	Aerated Lagoons Followed by Spray Irrigation	9,000	11.00 (Est.)
City of Belding	Anaerobic-Aerobic Pond System Followed by Irrigation	5,000	17.00

Village of Cassopolis	Anaerobic-Aerobic Pond System with Seepage Lagoons	Less than 3,000	Less than \$5.00 per year
--------------------------	--	--------------------	---------------------------------

Land disposal is not a panacea - it is merely another tool. During the same period of time our firm has been developing lagoon-irrigation projects, we have also been designing other types of treatment such as extended aeration systems, rotating bio-disc plants, aerated lagoons followed by chemical precipitation - and on occasion, septic tanks and tile fields. Today, many noble efforts are being expended toward the preservation of our environment, and our water resources in particular. The world is eagerly awaiting the discovery of the best method of treating and disposing of wastewater. In our opinion, it is not good judgment to regard any one method as the best. The dangerous implication in that label is that since "the best" has been found, there is no need to continue to seek better ways of doing the job. The search for better ways should be unending. If no way is considered the best, each wastewater project can be given individual consideration, the proper method can be selected on the basis of professional engineering judgment rather than emotion, and the search for a better way can continue.

ECOLOGICAL AND PHYSIOLOGICAL IMPLICATIONS OF GREENBELT
IRRIGATION WITH RECLAIMED WATER

324 J

V. B. Youngner, W. D. Kesner
Department of Plant Sciences
University of California

and A. R. Berg, L. R. Green
Fire Research Laboratory
Forest Service, USDA

Although Southern California is best known for its farmlands and urban communities, millions of acres are covered with chaparral, sage and woodlands. These wildlands are now largely confined to the foothills and mountains but still extend from the bluffs above the Pacific ocean to the desert (Jaeger and Smith, 1966). To a great extent they remain in a primitive condition, but residential and recreational developments reach into them from every direction producing an intimate association between wilderness and human activity creating numerous problems new to the region.

Southern California has many local climates determined by elevation, proximity to the ocean and relationship to mountain ranges. Nearly all, however, are basically Mediterranean characterized by mild wet winters and long dry, generally warm, summers. Except for occasional brief thunderstorms, little rainfall occurs from April to November (Bailey, 1966).

The native vegetation is well adapted to this climate as many species become dormant or semi-dormant during the latter part of the dry season. As the long drought continues, the shrubs that make up the wildlands become increasingly dry and flammable. Hot dry "Santa Ana" winds often occur in autumn making the fire hazard extremely high.

Fires have been a part of the natural environment of the chaparral for thousands of years, rejuvenating the brush and maintaining a natural balance among shrubs, forbs, grasses and trees (Vogl, 1967; Sweeney, 1967). With the first winter rains following a fire many shrub and small tree species resprout from their bases. The new open spaces once covered by dense brush are quickly filled with shrub seedlings, grasses and other herbaceous plants.

However, today, because of the numerous settlements in these wildlands such fires cause great loss of property and often of human life and therefore are no longer acceptable. Fire control is now a general but costly practice through the region. Not unexpectedly fire control by permitting excessive build-up of potential fuel has made fires that do occur many times more dangerous and difficult to contain. Many studies are underway to find new ways of handling the problem such as controlled burning,

use of growth retardents and construction of fuel breaks.

Other problems are also created by the influx of people into the wildlands. Water consumption is excessive in many places causing a constant lowering of underground water reserves. To conserve more of the water from rain and snow improvement of watershed quality is imperative. Waste disposal facilities, never really adequate, are falling further and further behind causing a serious pollution problem. Nevertheless the demand for recreational facilities such as campground and picnic areas by people from the urban centers is unabated. Although restrictions on movement of people into the wildlands has been considered and even attempted a strong legal basis for this does not at present exist and the destruction of a great scenic natural resource is everywhere evident.

OBJECTIVES AND DESIGN OF PROJECT

In 1970 a research project designed to find a partial solution to these problems was begun through a cooperative effort of the University of California, the U.S. Forest Service and the California Division of Forestry. Financing was obtained from the U.S. Department of Interior, Office of Water Resources Research through the University Water Resources Center and from other agencies principally the San Bernardino County Flood Control District. The objective is to study the feasibility of using wastewater from the mountain communities to irrigate greenbelts of native and introduced plants. The concept is that such greenbelts strategically placed would reduce the wildfire hazard while disposing of wastewater, recharging groundwater reservoirs with purified water, and creating new manageable recreation areas.

Answers to numerous specific questions would determine the practical value of the project. Foremost among these are the following: 1) What rates of water application can be safely used on the rocky often shallow mountain soils? 2) What degree of water purification can be achieved at the different rates of application? 3) Can the moisture content of chaparral plants be raised sufficiently to give them fire retardent qualities? 4) How will irrigation through the dry season affect the growth of chaparral species? 5) What exotic trees, shrubs and grasses will best meet the stated project objectives? 6) Will irrigation change the species composition of the chaparral community?

The study area is located on a gently sloping chaparral covered ridge in the Maloney Canyon of the San Bernardino National Forest (Goodin and Kesner, 1970). Although the elevation of the project site is 4600 to 4700 feet, it is on the Mojave Desert side of the mountains so the mean annual rainfall is only about

25 inches and summer temperatures often reach 90°F. The soils are shallow sandy loams over a granite or decomposed granite parent material. Four distinct soil types have been mapped for the experimental area.

Soil A

Soil A has a dark grayish brown cobbly sandy loam textured surface soil which is slightly acid to neutral. The subsoil is a dark grayish brown loam. This soil ranges in depth from 10 to 18 inches. The parent material is a highly weathered granodiorite which can be augered to a depth of 50 inches or more. Five to 15 percent cobbles and stones are found on the surface of this soil. Along the south end of plots 8-8, 10-2 and 12-2, 15 to 20 percent boulders and stones are found on the surface. Permeability is moderate (2.50 to 5.0 in./hr), maximum water holding capacity 5.5 to 7.5 inches and the erosion hazard is high on cleared areas and moderate on undisturbed vegetated areas.

Soil B

Soil B has a grayish brown to dark grayish brown heavy sandy loam having a slightly acid to neutral surface soil. The subsoil (B horizon) is a light to dark yellowish brown and brown medium to slightly acid sandy clay loam. Parent material is a granodiorite that begins at a depth of 24 to 45 inches which can be augered to a depth of five feet or more. Within the surface horizon cobbles will range from 0 to 15 percent while on the surface they will range from 15 to 25 percent with a few isolated areas having as many as 50 percent. Permeability is moderately slow (0.20 to 0.80 in./hr), maximum water holding capacity is 15 to 25 inches and the erosion hazard is high on the cleared plots and moderate on the vegetative plots.

Soil C

Soil C has a grayish brown to dark grayish brown cobbly heavy sandy loam slightly acid to neutral surface soil. The subsoil (B horizon) is reddish yellow to brownish yellow medium acid to neutral sandy clay loam. Parent rock is a granodiorite that begins at a depth of 12 to 18 inches and easily augered to a depth of five feet or more. Cobbles in the surface soil vary from 0 to 20 percent and from 0 to 25 on the surface with as much as 50 percent on isolated areas. Permeability is moderately slow (0.20 to 0.80 in./hr), maximum water holding capacity is about 8 to 10 inches and the erosion hazard is high on the cleared plots and moderate on the vegetative plots.

Soil D

Soil D has a brown to dark brown loam neutral reaction surface soil. The subsoil (B horizons) is yellowish red, medium to slightly acid clay loam. The parent material is highly weathered granodiorite beginning at a depth of 25 to 35 inches which becomes hard fresh rock within a few inches. Cobble percentages on the surface and in the surface soil horizon ranges from 10 to 20 percent. Permeability is moderately slow (0.20 to 0.80 in./hr). Maximum water holding capacity is 12 to 22 inches and erosion hazard is high on the cleared plots and moderate on the vegetative plots.

The vegetation is typical desert chaparral. *Ceanothus* (*Ceanothus greggii*, Gray and *C. integrirrimus* H. and A.), flannel bush (*Fremonthia californica* Torr.) and bigberry manzanita (*Arctostaphylos galuca* Lindl.) are the principal shrub species. California Black Oak (*Quercus kelloggii*, Newb.) and Coulter Pine (*Pinus coulteri* Don.) are scattered throughout the area. The understory of various grasses and forbs is sparse under the heavy stands of brush but quite dense where the brush is light.

The study area of 25 acres is divided into 48 plots, 100 by 200 feet. Four irrigation treatments (0, 1, 2 and 3.5 inches per week) are followed throughout the dry season. Within each irrigation treatment there are blocks in which the native vegetation remains intact, others in which the native vegetation has been cleared with subplots of introduced trees, shrubs, grasses and forbs. All treatment plots are randomized and replicated three times. Species planted on the cleared plots are shown in Table 1.

Water is applied through eight impact sprinkler heads on seven-foot risers per plot. The entire system is automatically controlled. Wastewater is obtained from the Arrowhead Village sewage disposal system ponds located above the experimental area. The sewage treatment facility provides primary and secondary treatment and 2 ppm chlorination prior to discharge of the water into the effluent ponds. Present discharges from this plant average over 750,000 gpd of which the experimental project uses only about 100,000 gpd. Since the wastewater is derived almost entirely from domestic, non-industry, sources it is of relatively high quality (Table 2). The analyses may be similar to that of most other mountain resort communities in Southern California. Nitrates fluctuate from almost none to a high of 64 ppm. Testing procedures follow those of Standard Methods for the Examination of Water and Wastewater and atomic absorption spectrophotometric methods.

Table 1. Plant Species Introduced in Cleared Study Plots

Scientific Name	Common Name
<u>Abies concolor</u>	White Fir
<u>Pinus attenuata</u>	Knobcone Pine
<u>Pinus Jeffreyi</u>	Jeffrey Pine
<u>Pinus sylvestris</u>	Scotch Pine
<u>Pinus thunbergii</u>	Japanese Black Pine
<u>Pseudotsuga macrocarpa</u>	Big-cone Douglas Fir
<u>Pseudotsuga Menziesii</u>	Douglas Fir
<u>Sequoia gigantea</u>	Big tree
<u>Libocedrus decurrens</u>	Incense Cedar
<u>Pinus Coulteri</u>	Coulter Pine
<u>Pinus Lambertiana</u>	Sugar Pine
<u>Abies magnifica</u>	Red Fir
<u>Pinus ponderosa</u>	Ponderosa Pine
<u>Agrostis palustris</u>	Pencross creeping bentgrass
<u>Festuca ovina</u>	Sheeps fescue
<u>Festuca rubra</u>	Red fescue
<u>Festuca rubra commutata</u>	Chewings fescue
<u>Poa pratensis</u>	Fylking Kentucky bluegrass
<u>Trifolium repens</u>	White clover
<u>Festuca arundinacea</u>	Tall fescue
<u>Oryzopsis miliacea</u>	smilgrass
<u>Ehrharta calycina</u>	veldtgrass
<u>Phalaris tuberosa</u> var. stenoptera	Hardinggrass
<u>Agropyron trichophorum</u>	Pubescent wheatgrass
<u>Agropyron intermedium</u>	Intermediate wheatgrass

A complete weather station installed at the project site provides a continuous record of temperature, humidity, precipitation, wind velocity, wind direction, and evaporation. Soil moisture is measured by electrical resistance blocks placed one, two and four feet below the surface. Groundwater is sampled at various depths by suction tubes (Youngner et al, 1971).

Specific vegetation studies as related to the irrigation treatments include the following: 1) Transpiration of native species as measured by a diffusion porometer (Van Bavel et al, 1965). 2) Photosynthesis of selected native species using the $^{14}\text{CO}_2$ method of Shimshi (1968). 3) Water potential of leaves of selected species measured by the pressure bomb (Scholander et al, 1964). 4) Increase in branch length of native species. 5) Fuel moisture levels (moisture content of twigs and branches

Table 2. Typical Analyses of Sewage Effluent during 1971-72

	1	2	3	4	5	6
Ca (ppm)	19	20	-	24	24	24
Mg (ppm)	4	4	-	3	4	3
Na (ppm)	48	45	62	38	38	40
K (ppm)	8	13	12	16	16	14
NH ₄ N (ppm)	1	29	-	-	-	4
SO ₄ (ppm)	20	20	-	-	-	12
Cl (ppm)	34	36	48	-	-	46
NO ₃ N (ppm)	15	6	4	1	1	2
PO ₄ (ppm)	-	30	-	41.0	44	38
HCO ₃ (ppm)	30	92	109	-	-	153
Conductivity (EC x 10 ⁻⁶)	350	364	410	505	545	390
pH	-	6.7	6.7	7.4	7.3	7.4
Hardness as CaCO ₃	64	66	-	-	-	82
Total dissolved residue (180°C)	258	231	-	-	-	275
F (ppm)	0.4	0.3	-	-	-	0.5
B (ppm)	0.3	0.3	0.0	-	-	0.2

of selected sized). 6) Survival and growth (increase in height) of introduced trees. 7) Biomass, percent cover and frequency of various wild and introduced grasses and forbs.

OBSERVATIONS AND RESULTS

Results must be considered preliminary at this time since the study has been underway less than two years. Nevertheless a number of distinct trends are apparent.

Evaporation rates during the summer months in this area are extremely high often exceeding 3 inches per week. Consequently the low irrigation rate of one inch per week has had little effect on vegetation growth, establishment of new plantings and replenishment of fuel moisture. Apparently most of the water applied in this treatment is lost through evaporation before it can penetrate into the soil.

The two higher irrigation rates have clearly influenced tree establishment (Table 3). The highest application rate (four

Table 3. Percent Survival of Coniferous Trees One Year After Planting

Species	Control	Weekly irrigation in inches		
		1	2	3.5
	%	%	%	%
Scotch Pine	13.0	20.8	65.2	95.8
Japanese Black Pine	22.2	20.8	69.5	63.0
Knobcone Pine	50.0	30.7	33.3	33.3
White Fir	6.3	0.0	0.0	15.3
Ponderosa Pine	15.0	16.6	0.0	34.7
Incense Cedar	10.7	6.6	16.6	25.9
Jeffrey Pine	7.1	13.3	21.2	29.5
Sequoia	4.1	0.0	0.0	4.3
Coulter Pine	14.8	8.7	0.0	10.0
Big Cone Spruce	5.8	5.5	0.0	5.3
Douglas Fir	0.0	11.7	8.7	18.2
Red Fir	0.0	0.0	0.0	4.3
Sugar Pine	0.0	15.1	3.3	17.2

inches per week) has been especially beneficial but the medium rate (two inches per week) has permitted satisfactory establishment of only certain species. Establishment in the non-irrigated treatment was limited to one block with the exception of Knobcone pine which has some survivors in all three replications. This block has the deeper finer textured soil with a higher water holding capacity (Soil B). Variability among replications is perhaps largely a result of differences in soil type.

Excellent stands of most introduced grass species have been obtained under the high irrigation rate. Under the two lower rates only the two wheat grasses Agropyron trichophorum and A. intermedium and red fescue, Festuca rubra, have developed satisfactorily at this time.

On plots cleared of brush and irrigated but not planted to other vegetation wild grasses are the most abundant species at the present. The density of grass stand increases directly with the irrigation rate. Yerba Santa, Eriodictyon trichocalyx, is also abundant and is especially noticable on blocks receiving no water

or only one inch per week. This is a small shrub, spreading by rhizomes, common to burned over or disturbed areas of the chaparral.

Moisture content determinations of the chaparral plants indicate that the two higher irrigation rates significantly increase fuel moisture (Table 4). The low irrigation rate appears to be insufficient to consistently maintain moisture levels above the control. Moisture content differences among plants from the four irrigation treatments are greatest in the smaller, generally younger, twigs of 1/8 inch or less in diameter which have a higher moisture content normally. Samples of this type from the non-irrigated plots range in moisture content from about 55% to about 122% of their dry weights at various seasons. Samples from the highest irrigation treatment range in moisture content from about 95% to about 143% of their dry weights at these same times. Thus a rather large elevation in fuel moisture content has been accomplished during the peak fire season when the brush is normally very dry. This may be particularly important to fire control as it occurs in fine twigs and leaves that may be most readily ignited. Chaparral growth is increased by the effluent water irrigation (Table 5). The increase in shoot length is to be a great extent directly proportional to the amount of water provided. Increased chaparral growth, of course, may not be desirable relative to the fire hazard.

Soil moisture determinations in the irrigation treatments support the vegetation studies. In general soils in the low irrigation treatment do not contain significantly more water at any depth than do those in the control treatment. Considerable variability in soil moisture has been observed in the 2 and 3-1/2 inch per week irrigation treatments. This is not unexpected considering the variation in depth, infiltration rate, and water holding capacity among the four soil types present in the site. Differences in the brush density and type would also influence soil moisture. At this time it seems that only the 3-1/2 inch per week application rate might be expected to significantly add to the underground water reserves under the conditions of this study.

As testing of subsoil moisture was started only in July 1972, data on water purification are still very meager. So far water has been sampled to a maximum depth no greater than four feet because of the rocky parent material encountered below that level. Nevertheless samples from a four-foot depth in the high irrigation plots show nearly 100 percent reduction of phosphates and perhaps as much as 50 percent reduction of nitrates below that of the effluent.

Our first tests for fecal coliform in the groundwater show no colonies in 100 ml samples. Tests of the effluent water show

Table 4. Moisture Content (percent of dry weight) of Ceanothus greggii Branches of Three Sizes as Affected by Irrigation Treatments

Date	Twig diameter in inches											
	0.25 or less				0.25 - 0.50 inch				over 0.50 inch			
	Inches of water per week				Inches of water per week				Inches of water per week			
	0	1	2	3.5	0	1	2	3.5	0	1	2	3.5
1971												
July	84.8	100.2	123.2	129.8	59.3	67.8	72.8	77.2	54.5	59.8	64.3	71.8
Aug.	62.7	75.3	98.8	106.7	54.0	57.0	64.2	64.2	47.0	45.5	58.2	61.8
Sept.	54.5	62.5	83.2	99.8	51.2	54.8	63.0	57.7	49.0	47.3	59.2	57.5
Nov.	61.5	79.0	87.3	94.0	54.5	55.5	55.2	55.7	-	-	-	-
1972												
June	122.0	122.3	136.2	142.9	71.7	71.1	76.9	76.0	57.4	57.8	62.3	63.2
July	85.2	77.2	99.0	97.9	62.7	64.1	66.8	82.9	51.7	56.8	54.5	61.4

as much as 1,228 colonies per 100 ml.

Table 5. Mean Growth of *Ceanothus greggii* Branches as Affected by Irrigation Treatments in 1972

Irrigation Treatment	Location of Branches		
	Top	North Side	South Side
	mm	mm	mm
Control	49	35	60
1 inch per week	92	61	51
2 inches per week	146	64	87
3.5 inches per week	152	118	143

CONCLUSION AND SUMMARY

Although no conclusive results have been obtained during the short time this study has been underway observations to date are sufficiently encouraging to make continued study highly worthwhile. Clearly, irrigation of chaparral during the dry season will increase the moisture content of the wood and leaves. The normal dormancy is apparently strictly draught induced and the brush will readily take up water when it is provided regardless of prevailing high temperature or species phenology. Future experimentation must try to relate these results to degree of fire retardation.

Conversion of chaparral brush lands to grasses and other plants presenting a lower fire hazard appears possible through wastewater irrigation. The most satisfactory species with particular reference to the use of the irrigated areas for recreation must still be determined.

Whether satisfactory water purification can be obtained through the shallow mountain soils is still uncertain but preliminary data are very encouraging.

REFERENCES

- Bailey, H. P. 1966. The climate of Southern California. Univ. of Calif. Press, Berkeley.
Goodin, J. R. and W. D. Kesner. 1970. First annual report of the Moloney Canyon Project. Univ. of Calif. Water Resources Center

- 33 p.
- Jaeger, E. C. and A. C. Smith. 1966. Introduction to the natural history of Southern California. Univ. of Calif. Press, Berkeley.
- Scholander, P. E., H. T. Hammel, A. E. Hemmingsen, and E. D. Bradstreet. 1964. Hydrostatic pressure and osmotic potential in leaves of mangroves and some other plants. Proc. Nat. Acad. Sci. 52, 118-125.
- Shimshi, D. 1968. A rapid method for measuring photosynthesis with labeled carbon dioxide. Jour. Expt. Bot. 20, 381-401.
- Sweeney, J. R. 1967. Ecology of some "Fire Type" vegetation in Northern California. Proc. Calif. Tall Timbers Fire Ecology Conf. 7, 111-125.
- Van Bavel, C. H., F. S. Makayama, and W. L. Ehrler. 1965. Measuring transpiration resistance of leaves. Plant Physiology 40, 535-540.
- Vogl, R. J. 1967. Fire adaptations of some Southern California plants. Proc. Calif. Tall Timbers Fire Ecology Conf. 7, 79-109.
- Youngner, V. B., W. D. Kesner, A. R. Berg and L. R. Green. 1971. Second annual report of the Maloney Canyon Greenbelt Project. Univ. of Calif. Water Resources Center Contribution No. 135, 22 p.

DISCUSSION

- Dissmeyer: I understand in Southern California you've got some water repellent soils due to the combination of vegetation and fire. How has the spray application affected this problem?
- Youngner: As far as the water repellent soils resulting from fire, we have no information on that or what the relationship of our particular study might be to those types of water repellent soils because we've had no fire in recent years through this experimental area. Our particular soil on the site is not water repellent. We have no difficulty in getting water into the soil, it's very permeable. There is some variation but, in general the permeability is high enough so that we have no problem with the rates we're using.
- Unknown: What's happening to the dissolved solids?
- Youngner: What's going to happen to the total dissolved solids in that water? That's something I hope we will find out in time. I don't know. This is one of the things we'll be looking at and I think anything I could say on that would be pure speculation at this point. We are probably going to get a salt build up. Even though the salt

content is not that bad, the two lower irrigation rates in which we're not getting any deep penetration of the water whatsoever, we are going to get a salt build up in time.

Unknown:

What affect will the salt build up have on the vegetation?

Youngner:

Many of the species we are using do accept a fair amount of salt tolerance. Once the root system gets down to a greater depth I don't think the salt problem is going to bother the trees particularly. It will bother some of the other vegetation, such as the grass and so on, which are shallow rooted since the salt is going to be accumulating on the surface and in the surface layers. The shallow rooted plants are going to be most drastically affected by the salt build up.

MUNICIPAL WASTEWATER DISPOSAL ON THE LAND
AS AN ALTERNATE OF OCEAN OUTFALL

336 D

W. A. Cowlshaw and F. J. Roland
Bauer Engineering, Inc.

This paper attempts to take a look at land treatment as an alternative to ocean disposal of partially treated industrial and municipal wastes. The specific decision choice for Falmouth, Massachusetts, a community located on the western end of Cape Cod, will be used to highlight the political, engineering, and resource management factor of decisions that juxtapose land treatment against ocean disposal.

Present state plans (i.e. California) are moving toward requiring a minimum of secondary treatment before ocean disposal and toward the prohibition of ocean disposal of municipal and industrial sludges. Selection of acceptable outfall locations is also becoming a more complex process which will result in the need for more costly transmission and outfall facilities. For example, the ability to discharge into bays and harbor areas is becoming a thing of the past.

An example of the problem of obtaining public acceptability of an outfall location is the debate over the design of the new Melbourne, Australia treatment plant. The Melbourne metropolitan area (population 2.3 million) is located on the inner (west) side of Port Phillip Bay at a distance of 35 miles from the Pacific Ocean.

The original design for the 64 mgd treatment plant, located on the north side of the bay, included an outfall into the bay. Public pressure, however, has forced the development of a plan to pipe the effluent from the plant a distance of 35 miles to Bass Strait.

The problem of the treatment and final disposal of the accumulated sludge solids still must be dealt with. Indications are that land application of organic sludges for agricultural utilization will become a major management technique for this problem. The City of Philadelphia, for example, is presently advertising for bids to haul sewage sludge to land application sites in lieu of ocean dumping.

FACTORS RELATED TO OCEAN DISPOSAL

The principal interrelated factors of concern which form the focus for the national debate on ocean disposal are summarized in the following principal items:

1. Minimum level of waste treatment that will provide a reasonable factor of safety for the ocean environment.
2. Selection of an acceptable point of discharge for any regional area.
3. Disposition of accumulated separated solids produced in the treatment system.
4. Concern for potential long-term dynamic effects on local and general ocean environment and ability to develop cause and effect relationships.
5. Conservation and reuse of treated flows and constituent materials.
6. Selection of plant locations acceptable to residents of region.
7. Residual accumulation effects of periodic upsets in treatment and reduced treatment performance during periods of high stormwater flow.

LAND TREATMENT AS AN ALTERNATIVE

Land treatment provides a resources management choice to ocean disposal for public and technical consideration. Performance aspects of land treatment that offer attraction as a management choice include:

1. Achievement of the highest level of treatment which present technology can provide.
2. Return of renovated water to the immediately available water resource supply.
3. Recovery of nutrients and other materials to assist in agricultural production.
4. Opportunities for multi-purpose site utilization (solid waste disposal, industrial and power utility cooling, recreational and open space uses).

5. Ability to control, monitor and take corrective action in impact areas of possible long-term deleterious effects (heavy metals buildup in soils and crops, nitrate buildup in groundwater).

As the level of required treatment increases no matter what the discharge point or dilution potential, as the point of acceptable discharge becomes more restricted and remote from metropolitan centers and when the sludge disposal problem is required to be dealt with in an environmentally acceptable manner, management at land treatment sites will become increasingly attractive.

EVALUATION OF ALTERNATIVES FOR FALMOUTH, MASSACHUSETTS

The evaluation of land treatment versus ocean disposal for Falmouth, Massachusetts constitutes a pilot study for the entire Cape Cod area. Great concern exists on the Cape for the protection of the local water supplies (in terms of both quality and quantity) and the preservation of the recreational water environment. Projected population increases jeopardize both, threatening, in addition, offshore shellfish beds, interior pond levels and natural assimilative capacities.

As a manifestation of the concern, the Town of Falmouth has been the center of heated public debate for the past few years concerning selection of an acceptable management and facilities plan for waste treatment. A proposed ocean outfall plan to discharge wastes after receiving secondary treatment was rejected by the townspeople by a 2 to 1 vote. Evaluation of other alternatives was requested, specifically the cost and environmental consequences of a land treatment system. The opportunity to develop a land treatment plan was enhanced by the availability of a potential treatment site at the Otis Air Force Base, which is scheduled for deactivation.

System Service Area

The design capacity of the system will serve the 1990 requirements of the Falmouth region, which has a sewered area population of 25,000 during the three summer months and a population of 16,000 during the remainder of the year. The generated flow is 2.7 mgd during the three summer months and 1.6 mgd during the remaining nine months. This results in an average annual flow of 1.9 mgd.

The areas served by the system would include Falmouth Center and Woods Hole.

Ocean Outfall Design

The ocean disposal system which has been designed for the Falmouth area was prepared in response to water quality standards established by the Massachusetts Water Resources Commission and the Federal Water Pollution Control Administration. It has been reviewed and analyzed by numerous engineering firms, and research and conservation groups, including members of the Woods Hole Oceanographic Institution.

The system consists of three basic components: (1) a collection and transport network, (2) biological treatment and (3) an outfall system.

Collection and Transport System - This consists of the network of sewers, force mains and pumping stations required to collect the wastewater from the service areas and transport it to the sewage treatment plant located at Woods Hole, 3,500 feet from Nobska Point.

Biological Treatment - The proposed activated sludge treatment plant would be located on an eight-acre site in Woods Hole. Here, the raw sewage would pass through a pre-treatment structure, primary clarifiers, aeration tanks, secondary clarifiers and a chlorination contact tank before final effluent disposal.

Outfall System - The outfall system for Falmouth consists of a 30-inch diameter pipe extending 3,500 feet from the sewage treatment plant to Nobska Point and an additional 1,950 feet out into Vineyard Sound to a depth of 90 feet. At this location there would be a minimum return of the effluent to beaches and harbors; the tidal flow reaches maximum speeds; and the depth of the water provides for maximum immediate dilution.

The ocean disposal system designed for Falmouth is expected to meet all current secondary effluent standards of the Federal government and the Commonwealth of Massachusetts.

The proposed outfall point has been the subject of considerable study by experts from the Woods Hole Oceanographic Institution, and the United States Geological Survey. It is regarded as the best location for an outfall on the Cape if one is to be constructed. However, at many other locations on the Cape it would be extremely difficult, if not impossible, to obtain an outfall that would approach the performance capability of the Nobska Point location. This is because most of the Cape is surrounded by fairly shallow ocean waters whose tidal currents are slow and which travel close to bathing and shellfish areas.

Land Management System

The land treatment system developed for the Falmouth area entails the conveyance of wastes inland to a pre-treatment and land irrigation site located within and adjacent to Otis Air Force Base. The design capacity of the system will serve the 1990 requirements of the Falmouth region and in addition a flow of 1.0 mgd generated by Otis Air Force Base during the summer months and 0.4 mgd during the remainder of the year. This results in an average total flow during the year of 2.4 mgd. The system consists of four basic components: (1) a collection and transport network, (2) biological treatment, (3) storage lagoons, (4) irrigation system.

Collection and Transport - The collection network consists of 72 miles of 4 to 24 inch laterals. The main transmission lines consist of approximately 3 miles of 8 to 16 inch pipe from the Woods Hole pumping station to the main Falmouth Center pumping station and approximately eight miles of 18-inch pipe from the latter pumping station to the Otis Air Force Base (AFB) sewage treatment plant.

Biological Treatment - The proposed wastewater irrigation system incorporates the existing treatment facilities at Otis Air Force Base. The base plant has been well maintained and can continue to function as a secondary treatment facility for both Falmouth and the Otis Air Force Base wastes.

The basic unit processes using the existing plant include: (1) a sewage comminutor for solids reduction, (2) a diffused air grease-skimming flocculation tank, (3) Imhoff tanks, which provide for primary sedimentation of solids and for solids digestion; (4) trickling filters, which provide biochemical oxidation of organic matter in the sewage; (5) final settling, and (6) sludge drying beds from which solids are returned to the land as a soil conditioner.

Storage Lagoons - Effluent from the final settling tank is discharged to the storage lagoon, where further sedimentation occurs and where the liquids are stored for irrigation. This component of the system provides the necessary flexibility for storing wastewater during periods of heavy rainfall or freezing temperatures.

The storage lagoon is sized to permit detention of four months of winter flow (267 mg). Its surface area is 54 acres, with a working water depth range of 13 to 33 feet. This variable depth results from a lagoon design which takes advantage of the natural topography, thereby minimizing excavation costs.

Irrigation System - The irrigation site area is located in Mashpee Outwash Plain consisting of glacial deposits of sand and gravel. These deposits are very permeable and previous well tests in the area indicate that the proposed wastewater site is geologi-

cally well suited for spray irrigation. Approximately 250 feet beneath the surface of the site lies the hard, dense basement rock.

The total required site including treatment facilities, storage lagoon, irrigation and unused buffer areas is approximately 800 acres. The actual required irrigation area is 490 acres based on a 2-inch per week application rate for an 8-month annual application period.

The method of water application would depend on the final areas selected for use. At present tracts of cleared flat land within the Otis Air Force Base site and a forested game conservation area are being considered for use.

In cultivated areas rotating irrigation rigs would distribute the wastewater on the land. In forested areas a fixed system would be used to minimize the disturbance of the natural setting.

Groundwater Flow

The water applied to the irrigation area will be allowed to percolate through the soil into the groundwater supply. The performance of the wastewater management system will be continuously monitored to assure protection of the groundwater supply near the irrigation site.

Due to the possibility of salt water intrusion, the recharge of groundwater is considered of primary import. Several preliminary studies have been undertaken to estimate the change in groundwater flow due to the application of water at the irrigation site. In general, it is calculated that approximately 775 million gallons of water will be returned to the ground at the spray irrigation site. This is equal to 84 per cent of the total of 920 million gallons of wastewater treated.

Analyses indicate that the groundwater flow changes would be greatest in the vicinity of Coonamesset Pond, toward which some 70 per cent of irrigation water will flow. The Ashumet Pond will receive 20 per cent and the area between these two ponds would receive 10 per cent. The estimated dilution of irrigation water to groundwater is in the order of magnitude of one to one.

ALTERNATIVES COMPARISON

Evaluation of ocean outfall versus land treatment for Falmouth must consider both cost and performance (impact) differences between

the two systems.

Cost Comparison

Estimated facilities development and operating costs for the two alternatives are listed in Table 1. The land treatment system is shown to be least expensive on a unit capacity basis. This is due to the incorporation of the existing Otis Air Force Base facilities in the land system.

Table 1. Comparison of Total Construction Costs for Phase I of Alternative Systems

	<u>Land Treatment</u>	<u>Ocean Disposal</u>
	Design capacity in mgd	
Cost of Facilities <u>1/</u>	2.4	1.9
Wastewater treatment facilities	\$2,130,000	\$3,390,000
Pumping station and force mains	2,440,000	1,460,000
Gravity sewers	<u>3,890,000</u>	<u>3,890,000</u>
Subtotal	\$8,460,000	\$8,740,000
Land acquisition	600,000	75,000
Engineering, legal and administration	<u>846,000</u>	<u>874,000</u>
Total	\$9,906,000	\$9,689,000
Capital cost per mgd capacity	4,127,000	5,099,000
Annual operating cost	83,000	85,000
Average annual total cost per mgd capacity	\$ 336,000	\$ 417,000

1/ Utilization of existing Otis Air Force Base facilities is not entered as a cost item in land treatment system. Cost of land for land site is estimated equivalent value not actual price paid in any project. Annual costs based on 30 year bonding at 6% interest.

Impacts Assessment

The impacts of the alternative systems on the Cape Cod environment can be assessed in terms of the effects on the fresh groundwater table under the Cape and in terms of the effects on shoreline water quality.

Ocean Disposal

This analysis is based on an ocean outfall which it is generally agreed, would offer acceptable levels of discharge and mixing and which would minimize the chances of any effluent returning to harbors, beaches or estuaries of the Cape.

1. Probably the most serious implication of the ocean outfall system is that it diverts a substantial portion of the potential groundwater recharge, finally and irretrievably. After treatment, the entire amount is diverted to the costal waters. Consequently, if pond lowering or intrusion occurs, remedies would be quite costly. It has been estimated that the amount which can be diverted without damage cannot exceed ten to twenty-five per cent of the total annual groundwater recharge of the area serviced. The estimated peak summer population of 1980 (497,000) would withdraw, although not necessarily divert, at a rate equal to approximately twenty-five per cent of the annual recharge.
2. A major impact of the treated sewage effluent on the ocean is that of nutrients: carbon, phosphorus and nitrogen. Although a certain amount of these elements is required to maintain seafood productivity in costal waters, excessive levels cause an overabundance of organic production with consequent undesirable effects on water quality.
3. In addition to the overall performance of the ocean outfall system (treatment and dilution levels), attention should be given to the reliability of the treatment plant itself. Shock loads, which occur quite frequently, could result in the dumping of untreated wastes for substantial periods of time, directly into the ocean.
4. Another consideration is the possible pathogenic bacterial or viral contamination of the receiving water. The effects of such contamination would largely relate to the shellfish areas which are an important economic sector for the Cape.
5. Excessive amounts of organic carbons and toxic substances, such as heavy metals and non-biodegradable hydrocarbons

could cause long-term deleterious effects and should be excluded from any marine outfall system. These elements are rarely found in the Cape wastewater because of the relative lack of industry.

6. A final point is that sludge resultant from the treatment process must be handled outside the system. Separate dumping or spreading areas must be acquired or secured for these waters and procedures established to reduce odors and control leachate.

Land Treatment System

1. The spray irrigation system will return renovated water to the groundwater resource of quality suitable for reuse. If the water is returned at a point proximate to that of withdrawal, it can be considered to be replenishing the developed water supply source. If not, it simply adds to the availability of fresh water on the Cape. There is, therefore, the flexibility of withdrawing and transporting the treated water for use in injection wells or retention ponds to impede instances of intrusion or pond lowering.
2. The irrigation waters supply nutrients and organic matter to the land in sufficient quantities to enhance plant growth. This permits the conservation of commercial fertilizer which poses a special pollution problem in itself.
3. In contrast to the ocean disposal system, the spray irrigation system provides for disposal of both sludge and the septic tank pumpings. After adequate treatment, the activated sludge, including the treated septic tank solids, can initially be applied to the irrigated land as a soil conditioner; it can later be applied to those areas which are not routinely irrigated.
4. The spray irrigation system requires an extensive amount of land. Average requirements vary according to the design application rate, or length of irrigation period. For Cape Cod the land requirements are typically in the range of 200 acre per mgd, based on average annual application rates. Opportunities to alleviate some of the problems of site acquisition are discussed elsewhere in this paper.
5. Irrigation areas can be an asset to the community, however, by providing useful open space. Other potential benefits include the control of urban sprawl and the perservation of agricultural use areas.

CRITICAL FACTORS IN LAND TREATMENT SYSTEMS

The two major aspects of land treatment systems that are the focus of debate on general acceptance are: (1) the social and institutional problems of site acquisition and (2) the possible long-term effects of toxic substances on soils and crops.

Site Acquisition

Acquisition of large land site areas and the relocation of activities located thereon can create severe institutional, political, legal, and cost difficulties. In the Muskegon County project the decision was made to acquire and clear the irrigation site of private activities. This was dictated by regulatory requirements and characteristics of site ownership.

The Falmouth situation, on the other hand, documents the improved implementation potential achievable through joint Federal, State, and local cooperation. Such opportunities would likely be available for many locations along the U.S. coastline and at interior locations. For example, the programmed closure of many military bases presents a special site development opportunity at many locations in addition to that of Falmouth.

In other situations the acquisition problem could be relaxed through the development of irrigation lease arrangements with local farmers. This has been practiced in California and other areas.

Toxic Effects

The problem of potential long-term accumulation of toxic substances in the soil and crops is an issue that is currently being given extensive attention. There have been cited experiences of metals buildup in soils, increased crop intake and reduced crop yield. There has also been experiences (notably, Melbourne) of long-term operations with no apparent reduction in performance. In any assessment effort, it is important that information on metals buildup in soils and crop uptake with land treatment systems under study be related to naturally occurring variations to establish significance of change in any comparative analyses. Process dynamics in nature are subject to many-fold variations.

The uncertainty factor for a long-term toxic effects on land appears to be more critical than that which ocean outfall poses for the marine environment. The relevant questions are, "What is a potential toxic effect of sewage and what are the relative hazards of the impact areas for the various management choices - air, land and water?"

As indicated previously in this paper, the ability to control the effects of a land system to a specific site and the capability to continuously monitor this controlled environment, gives land treatment a strong environmental safety margin.

Land application permits the development of a discrete control break in the food chain back to man and presents many opportunities for corrective action with the identification of a developing problem. Corrective action includes: crop rotation, deep plowing, and limeing. Such control is not feasible in the diffuse aquatic environment of the ocean with its complex overlapping food chain linkages.

CONCLUSIONS

The foregoing analysis indicates that the land disposal-spray irrigation alternatives for managing wastewater would better serve the needs of the Falmouth region - and those of the entire Cape - for its effects in treating wastewater; the spray irrigation system is superior; its pollutant removal efficiency clearly exceeds the ocean outfall system in its effective removal of pollutants.

In addition to the efficiency and reliability of this system for purifying wastewater, it provides numerous related benefits applicable to the regional water resources. These include:

1. The spray irrigation system returns a large percentage of the treated wastewater to the groundwater resources. There is no diversion of water. In addition, the returned water is of a quality suitable for public water supply.
2. The system offers flexibility for retrieving the treated water and transferring it to critical areas of local water table or pond level drop or salt water intrusion.
3. The irrigation of marginal land for agricultural purposes will provide some usable crop - possibly grasses for fodder. The irrigation of forested land will increase production of the undergrowth for game food sources and permit additional monitoring of the site.
4. The utilization of wastewater for land irrigation will virtually assure that there will be no adverse affect on any marine life or on the recreational value of the Cape waters.

5. An integration of the spray irrigation site with numerous other publicly funded projects can achieve such multiple purposes as curtailing urban sprawl or providing additional recreational open space areas.

All of the above advantages of the spray irrigation system are achievable at costs comparable to those for conventional secondary wastewater treatment.

PRESENT STATUS OF PROJECT

At the March 6, 1972 Falmouth Town Meeting, the preparation of a definitive land treatment system engineering report was authorized. This work is to be done by Bauer Engineering, Inc. with assistance by Anderson-Nichols & Company, Inc. of Boston.

Pending final approval of the contract by the Falmouth Department of Public Works and the scope of the work by the Massachusetts Water Resources Commission, Department of Public Health and the Division of Fisheries and Game, the report containing preliminary designs and layouts for the land treatment system will be prepared. This study, which will provide the information needed for State and Federal approval, detailed design and preparation of construction contract documents, will also review alternative treatment arrangements, irrigation site areas and conveyance facilities from the Town to the Otis AFB site area.

Since the Town Meeting, approval for use of the originally designated Otis AFB lands has been obtained. Another subsequent event has been the announcement that the U.S. Air Force activities at the Otis AFB are being terminated with control of the facilities reverting to the state. Consequently, there will be investigations to determine if additional areas can be utilized for irrigation at this site.

Upon completion of this work, it is anticipated that a Town Article will be presented to a future Town Meeting for authorization for the preparation of contract documents needed for construction of the project.

DISCUSSION

- Unknown: Give us the status on this 1970 act that was passed by Congress concerning ocean dumping and how it will affect the ocean outfall.
- Rohland: I'm not familiar with the exact timetable on the federal act. There are also a number of state legislative

activities which deal with sludge management and with the quality of water that you have to achieve before you discharge to the ocean.

Adams: What about the infiltration rates on the land? I would assume that it is pretty sandy soil.

Rohland: I didn't go into a description of the site itself other than to say it's a sandy outwash plain, but it consists of highly permeable sand and gravel material to a depth of about 50 feet where the water table is located.

Unknown: Would you propose any conditioning to slow down the permeability?

Rohland: What we are proposing now is a rate of application in the order of about 2 inches similar to what's being done in many areas. We are not proposing any conditioning of the surface itself. It's the top two or three feet that can provide adequate renovation. We will have a monitoring system installed to evaluate the water that percolates through to the groundwater reservoir.

THE ROLE OF LAND TREATMENT OF WASTEWATER IN THE CORPS
OF ENGINEERS WASTEWATER MANAGEMENT PROGRAM

James F. Johnson
Wastewater Management Task Force
U.S. Army Corps of Engineers

337 D

The continuing problems of environmental degradation, particularly that caused by the discharge of a broad spectrum of pollutants into our water courses, have prompted the Corps of Engineers to assist State, regional, and local governments in developing wastewater management plans toward their solution. As a part of its urban studies program, the Corps will develop an array of plans in consonance with local planning agencies from which the people of the region could choose the specific plan which best meets their needs.

Wastewater management systems are comprised of structural and non-structural components to collect treat, transport, reuse, and dispose of all sources of waterborne wastes. These systems must be comprehensive in scope; they cannot ignore sources of pollutants, technologies, institutions, impacts, or public preferences. This paper will address the role of land treatment in the Corps of Engineers Wastewater Management program, with particular emphasis upon its relationship to the planning process, the impacts associated with land disposal, and certain research needs related to land disposal of wastewater (Johnson, 1972).

The Department of the Army initiated a pilot Wastewater Management Program late in FY 1971 concentrating initially on municipal, industrial, and urban storm runoff wastes. It is expected to complete this pilot program in four major urban areas in FY 1973. These areas are Cleveland - Akron, Detroit - Southeastern Michigan, Chicago - Northwest Indiana, and San Francisco - Sacramento-Stockton. These studies are being conducted in cooperation with all appropriate State and local governmental units as well as the Environmental Protection Agency. In July 1971, the Corps prepared interim feasibility reports for the four areas in addition to the Merrimack Basin in New England (U.S. Army Corps of Engineers, 1971a, b, c, d, e). On a more local scale, the Corps also is developing wastewater management plans for the people of Codorus Creek in Pennsylvania. Currently, a number of urban studies are being initiated that will meet a broader range of urban water needs, and wastewater management could provide benefits in the areas of flood protection, water supply, and recreation, to mention only a few.

PROGRAM OBJECTIVE

The wastewater program is directed toward improving the economic, social, and environmental welfare of the Nation and, in particular, the regions under study. The effects of the wastewater management plans will be measured in accordance with the broad objectives proposed by the Water Resources Council (U.S. Congress, 1971).

In order to effectively plan and measure the performance of wastewater systems in contributing to the objectives, we must first identify specific planning objectives (or needs) which the system will address. The subsequent evaluation of wastewater management systems in terms of these planning objectives would provide the basis for comparison of alternatives. These planning objectives would address such issues as economic growth policies, resource use policies, and desired land use patterns. The planning objectives of the region will be specified in such detail as to preclude consideration of alternatives in direct conflict with higher priority objectives. For instance, elimination of an ecological resource or isolation of a community or segment thereof by an alternative system would constitute a condition that is not acceptable.

PLAN FORMULATION

The process of plan formulation is one involving a series of iterations whereby plans are developed, evaluated, screened, and redeveloped or refined. Specific technical goals direct the wastewater systems toward achieving these objectives.

These technical goals are: (1) to prevent the continued degradation of our water resources by waterborne wastes; and (2) to provide for the efficient reuse of treated or renovated wastewater and by-products. Achievement requires the application of the best technology for the collection, treatment, and management of wastewater (U.S. Army Corps of Engineers, 1972a). At successive screening stages, alternatives will be evaluated in conjunction with an active program of public involvement to assist the development of optimal plans. The refinement of the alternatives that remain through this screening process will reflect the desires expressed in public involvement.

Existing institutions that are related to the management of water and wastewaters will be identified but these will not constrain the development of optimal wastewater management systems. The impacts of the plan on existing institutions will be analyzed, and a series of alternative implementation plans will be developed.

The selection of optimal wastewater plans will be made on the basis of the evaluation of beneficial and detrimental effects of the alternative, as well as a consideration of its associated opportunities and concerns. Information will be presented and displayed to illustrate the comparative differences among alternatives, their cost-effectiveness, and benefits and opportunities foregone by selecting one alternative vis a vis the others. In so doing, the presentation will clearly identify the detrimental effects of each alternative, and to what degree these could have been or could be eliminated. This information will be displayed in such a manner that responsible decision-makers may observe the difference between systems as they relate to major issues and concerns in the study region.

WASTEWATER TREATMENT SYSTEMS

In order to meet the program technical goals, the wastewater systems will employ the most efficient biological, chemical, and physical waste treatment processes (including the soil-vegetative complex) or combinations of these. These processes will be employed in the land treatment systems as well as the more traditional treatment plant systems.

The land treatment facilities being designed generally would consist of biological treatment cells, storage basins, application facilities, and land treatment areas; as well as underdrains or other collective systems to provide for the reuse of treated wastewater. Three means are under study for the application of wastewater on the land:

Spray irrigation is defined as the controlled spraying of liquid onto the land, at a rate measured in inches per week, with the path being infiltration and percolation within the boundaries of the land disposal site.

Overland runoff is defined as the controlled discharge, by spraying or other means, of liquid onto the land, at a rate measured in inches per week, with the flow path being downslope sheet flow.

Rapid infiltration is defined as the controlled discharge, by spreading or other means, of liquid onto the land, at a rate measured in feet per week, with the flow path being high rate infiltration and percolation (U.S. Army Corps of Engineers, 1972b).

Application of Wastewater to Land

The wastewater systems will be planned to promote the wise use of wastewater resources in addition to meeting the water quality non-degradation goal. Significant benefits can be provided with proper planning and operation of the systems.

Because wastewater is a source of nutrient-rich irrigation water, it can be applied to improve the productivity of marginal agricultural lands or improve upon presently productive farmland. In particular, crops with high nitrogen requirements can be enhanced by the properly controlled application of wastewater. In addition, the nutrient-rich water can be applied to forest lands, recreation areas, and other open areas. Such use of wastewater throughout the United States is well documented (Law, 1968; Whetstone, 1967).

Wastewater also could be applied to degraded land such as strip mines and fallow lands to enhance them for future use. Certain lands also can be preserved for planned future use by creating "land banks" through interim use as land treatment sites.

Wastewater Reuse

The renovated wastewater cleansed by the soil-vegetative filter system will be available for reuse for a wide range of purposes. The water could be percolated to recharge the groundwater aquifer. In general, however, the systems call for collecting the cleansed effluent and returning it for specific uses. Reuse opportunities will be identified on the basis of the needs of the region for possible stream flow augmentation, recreational lakes, industrial cooling, industrial process water, industrial boiler feed, and municipal reuse.

Multiple Use of Land and Facilities

There also is an opportunity for the multiple-use of the land and facilities required for wastewater systems. With regard to land treatment systems, we are studying such opportunities as the use of storage lagoons to accept and beneficially use thermal discharges from power plants; the use of irrigation and treatment sites to provide habitat area that could be used for hunting and other recreation; and use of transmission rights-of-way for trails, bikeways, controlled access roads, and utility routes.

There also are significant opportunities in planning for the efficient multiple-use of the required larger tracts of land. In many instances, land treatment sites may favor sites somewhat

distant from population and congestion. The opportunities to locate facilities such as airports, that seek these same characteristics should be identified within the framework of these regional plans. The desirability and potential for siting new towns and regional industrial parks also will be investigated.

FEASIBILITY STUDIES

The feasibility studies were intended to identify the present and future wastewater management problems and to make a preliminary evaluation of the feasibility and consequences of alternative wastewater management plans in the five regions. In transmitting these feasibility reports to the Secretary of the Army and the Congress, the Chief of Engineers concluded that,

There are major improvements possible in the effectiveness of wastewater management systems to remove a broad spectrum of waste constituents be those systems water disposal, land disposal, or some combination thereof;

There exist important opportunities and benefits associated with truly comprehensive wastewater management systems for water and waste constituent reuse, including the potential for new water supplies and recreation; and for a broad range of previously untapped opportunities related to social and environmental enhancement (U.S. Army, Secretary of the Army, 1971).

Of particular interest are the Chief of Engineers additional conclusions that,

Wastewater management systems requiring disposal to the land offer potentially new opportunities in selected areas including increased land production, management and reuse of wastes generated from other activities, and improvements to environmental quality and regional community values;

Further investigations and studies are required with respect to technological concern for both water and land disposal alternatives. Such investigations must evaluate:

- (a) The effectiveness, reliability, and flexibility of large-scale advanced wastewater treatment facilities, both physical-chemical and biological processes;

(b) The long-term viability and integrity of the land to serve as a natural processor of wastewater, and

(c) The relative toxic effects of viruses, pathogenic bacteria, trace metals and other toxic materials upon the environment whether land or in receiving waters;

The institutional implications of the alternative wastewater management strategies will be most critical to any future decisions regarding implementation, and that future studies must fully address such consequences and suggest appropriate means to facilitate necessary institutional changes (U.S. Army Secretary of the Army, 1971).

Survey - Scope Studies

The Congress acting upon the recommendations of the Secretary of Army and the Chief of Engineers gave approval in late 1971 for the Army Corps of Engineers to proceed into the survey-scope stage in Cleveland, Chicago, Detroit, and San Francisco studies in FY 1972. The Merrimack study in Massachusetts is being resumed in FY 1973.

STATE-OF-THE-ART

Concurrently, the Corps has undertaken state-of-the-art investigations to summarize the available knowledge relating to the feasibility of land application as a wastewater treatment process. The Army Corps of Engineers Cold Regions Research and Engineering Laboratory (CRREL) and a group of research consultants at the University of Washington agreed to prepare independent comprehensive technical assessments of the effectiveness and effects of land disposal of secondary treated wastewater (Reed, 1972; Driver, et al, 1972).

Each group studied spray irrigation, overland runoff, and rapid infiltration methods of application and treatment. Preparation of the reports included literature reviews, correspondence with experts involved in existing operations and current research, and personal observations at selected sites. The following were among the most significant conclusions:

(a) The quality of cleansed effluent produce derived from a properly designed and operated land disposal facility would approach drinking water-irrigation water standards.

(b) The land disposal facility and the pretreatment steps must be carefully managed as a total system to provide optimum responses.

(c) Any one of the three application modes can meet the quality standards if proper site conditions exist and proper operational criteria are employed.

(d) Spray irrigation offers the highest degree of reliability and potential longevity of the three modes.

(e) Heavy metals are largely removed from wastewater applied via spray irrigation, with the main mechanisms being ion exchange and fixation.

Both groups concluded that further investigation was needed, particularly in (a) overland runoff removal effectiveness; (b) transport of N and P to surface waters through erosion of overland runoff sites; (c) wind transport of pathogens by aerosols; (d) soil-chemical interactions, to include heavy metals; and (e) interaction of soils, climates, and loading rates to manipulate the carbon-nitrogen ratio.

Current Investigations

Accordingly, the Corps of Engineers is presently involved in exploratory efforts to (a) investigate the effectiveness of rapid infiltration basins at Fort Devons, Massachusetts, and Army installation; (b) analyze soil samples from Melbourne, Australia's sewage farm at Werribee; (c) develop and investigate performance of spray irrigation test cells (28 feet square, 5 feet deep) at CRREL; and (d) evaluate groundwater conditions in a joint effort with the U.S. Geological Survey and the city of Tallahassee, Florida, at the Tallahassee spray irrigation site.

Chicago Special Report

In proceeding through the survey-scope stage of the wastewater management pilot studies, the continued refinement of design costs have resulted in a position for land treatment systems more favorable than their position as presented in the feasibility reports.

In order to place the cost of alternative systems in perspective, the Chief of Engineers early in 1972 undertook a special study of the Chicago Metropolitan area with the assistance of Bauer Engineering for the purpose of (a) formulating the least-cost

wastewater management system alternatives; (b) detailing capital costs and operation, maintenance, and replacement costs of the alternative systems; and (c) analyzing the relative merits of alternative systems.

Although it is recognized that the special study was limited to providing a view of basic land, physical-chemical, and advanced biological treatment systems, the results underscore the comparative economic technical feasibility of land treatment systems.

Specifically, the study concluded that (a) significant strides can be made toward achieving comparably high levels of treatment by all three alternatives studied. These levels appear to be compatible with the current Corps program technical goal of minimizing water quality degradation from waterborne wastes; (b) costs of any one of the systems involves several billions of dollars; and (c) costs for land treatment may be lower both for capital and for operation and maintenance (U.S. Army Corps of Engineers, 1972b).

The current wastewater studies are now well underway through the survey-scope stage. The Corps of Engineers Districts are conducting these studies through a balanced use of in-house management and technical capabilities supported by the technical expertise of architectural and engineering consultants and scientific research firms.

CONCLUSION

The Corps of Engineers recognizes its responsibility to the Nation and the regions under study to provide an array of comprehensive plans addressed to their overall needs. We seek to meet these needs through a planning process in which the full range of technologies is explored, the impacts associated with these technologies are addressed, and the resulting plans achieved within the framework of public involvement are set forth to the people of the regions to assist in their choice. The Corps is not committed to specific technologies, but is convinced that all technologies, including both land application and treatment plant systems, must be investigated thoroughly in order to broaden the range of choice available to allow decision-makers to act in the best public interest.

REFERENCES

- Driver, C. H., B. F. Hrutfiord, D. E. Spyridakis, E. B. Welch, D. D. Wooldridge and R. F. Christman. 1972. Assessment of the effectiveness and effects of wastewater management. U.S.

- Army Corps of Engineers Wastewater Management Report 72-1.
- Johnson, James F. 1972. Regional wastewater management: a new perspective in environmental planning. Water Resources Bulletin 8 (4), 773-779.
- Law, James P. 1968. Agricultural utilization of sewage effluent and sludge, an annotated bibliography. U.S. Federal Water Pollution Control Administration, Wash. D. C.
- Reed, S. C. 1972. Wastewater management by disposal on the land. Special Report 171, Cold Regions Research and Engineers, Hanover, N. H. p. 10-18.
- U.S. Army Corps of Engineers, Buffalo District. 1971a. Alternatives for managing wastewater for Cleveland-Akron Metropolitan and Three Rivers Watershed Areas. Summary and three appendices.
- U.S. Army Corps of Engineers, Chicago District. 1971b. Alternatives for managing wastewater in Chicago-South End Lake Michigan Area. Summary and appendices.
- U.S. Army Corps of Engineers, Detroit District. 1971c. Alternatives for managing wastewater for Southeastern Michigan. Summary and ten appendices.
- U.S. Army Corps of Engineers, San Francisco District. 1971d. Alternatives for managing wastewater in the San Francisco Bay and Sacramento-San Joaquin Delta Area. Summary and six appendices.
- U.S. Army Corps of Engineers, North Atlantic Division. 1971e. The Merrimack: designs for a clean river. Summary and appendices.
- U.S. Army Corps of Engineers. 1972a. Office, Chief of Engineers. Wastewater Management Program: study procedure.
- U.S. Army Corps of Engineers, Office, Chief of Engineers. 1972b. Regional wastewater management systems for the Chicago Metropolitan area. Summary and appendix.
- U.S. Army, Secretary of the Army. 1971. Interim report of the Secretary of the Army of the Pilot Wastewater Management Program.
- U.S. Congress. 1971. Procedures for evaluation of Water and Related Land Resources Projects Committee print 92-20. Wash. D.C.
- Whetstone, G. A. 1967. Re-use of effluent in the future with an annotated bibliography. Texas Water Development Board, Austin, Texas. 187 p.

DISCUSSION

- Lyon: We've had considerable experience with land irrigation in Pennsylvania as you know, and also lagoon systems and we've found that many of them have failed because the work that led up to them was fine in the engineering area and fine in the economic area but very thin in the hydrogeological area. I have this same kind of concern about some of the papers and studies that are being made by the Corps of

Engineers. For example, in Mr. Bauer's paper there's very little discussion of the hydrogeologic renovation capability. What specifically are the standards that the Corps is establishing for the hydrogeologic aspect of these studies?

Johnson: The Corps systems would be able to meet the standards set forth by the Environmental Protection Agency. In other words, they would meet the minimum requirements of any regulation that would be set forth by the EPA. Before we went into any advanced engineering designs today I think the Corps' engineering division, which I think is beyond question as far as intense investigation requirements, would require some sort of an investigation. I'm not sure of the specific items since I'm not representing our engineering division.

MICHIGAN'S EXPERIENCE WITH UTILIZING THE TEN STATES
GUIDELINE FOR LAND DISPOSAL OF WASTEWATER

Donald M. Pierce
Division of Wastewater
Michigan Department of Public Health

325 J

Our experience with land disposal systems in Michigan is very limited. For although nearly 50 communities have designed systems of this kind, only 2 of these have been in operation longer than one year. The widely publicized Muskegon County project will not be in operation until 1973. By the end of this year 15 municipal spray irrigation projects and 5 using spreading or flooding basins will have been completed and in operation, and by the end of 1974 this number will have increased to about 50. Nearly all of these projects are in advanced planning stages. Thus we have had a rather extensive opportunity to use the guidelines adopted by the Great Lakes - Upper Mississippi River Board of State Sanitary Engineers - the so-called "Ten States Standards" (Ground Disposal of Wastewaters, 1971). We have used them with increasing respect and enthusiasm as our experience is extended to an ever widening variety of field conditions. We do not, however, regard them as standards or rigid requirements any more than we do with other facilities, processes and practices for which standards or guidelines have been developed by this group.

Even in this early stage of operational experience some critical deficiencies in design have come to light. We are just beginning to recover from the shock of a series of misjudgments and oversights in technical areas new to us and not customarily within the experience of sanitary engineers -- at least those in the east and midwest. With these admissions I should hasten to say that the problems which have surfaced so early in the growth and development of an offspring heralded as the best hope of the ardent ecologist could probably have been avoided -- all of them -- had the Ten States guidelines for ground disposal of wastewaters been put into practice. The real problem in each case was some lack of understanding, both by the engineers designing the system and those evaluating and approving the design, of the natural forces which control the destiny of complex constituents of the waste particle when applied to the soil. It was not that he did not realize that he was dealing with matters a bit outside of his field. He knew this. It was not that he did not seek advice of other professionals more knowledgeable and experienced than he in these matters. He did this. He conferred with the hydrogeologist or geohydrologist, the soil scientist, the crop specialist, the irrigation specialist and the drainage engineer. He did talk with them and read some of

their publications. He even provided them with some data and got some advice on how much more information and what kind was really needed to refine the design of the system. But here in his blissful ignorance he got off on the wrong foot. He made some value judgments of his own with too little information and just possibly too little real understanding and then he wrapped up the project for construction. Let me elaborate just a little on where he went astray on one project.

A piece of land was chosen after a long search for spray irrigation of wastes from a community of about 2,000 with no adverse industrial waste constituents. Pretreatment was to be provided by primary sedimentation and aerated lagoons followed by disinfection. Wastes were to be spray irrigated on some 75 acres during roughly April - October with provision for 5 months winter storage of the treated wastes. The treated wastes were to be sprayed at an average rate of 2 inches per week on a 16-hour a day basis. All wastes were to be contained within the property. Drainage systems traversing the property were to be abandoned or rerouted around the property. Soil borings on the spray area were interpreted to indicate a percolation capacity sufficient to accommodate the average 2-inch application rate with rates during dry warm weather periods at least double this. This was their first big mistake. No underdrainage was proposed. This was the second big mistake.

The first indication of trouble obvious to the community and its engineers was much higher sewage flow than anticipated. This came to light the first year when the storage lagoon with projected capacity for 5 months storage overflowed in early January. During the ensuing eight months since then, soils have been demonstrated to be incapable of accepting rates of this magnitude without underdrainage and probably not even if good underdrainage. Runoff from the property to nearby drains has continued throughout the summer months. Ponding in low areas has been severe and extensive. What are the consequences of this lack of predesign investigations and thorough analysis? 1) Gross nuisances from the ponding of wastes both on the property and on neighboring properties 2) Discharge of inadequately treated wastes to the surface waters of the state exceeding stream standards, and 3) Continuance of these conditions until a fully adequate program is devised and implemented.

Correction may require construction of an underdrainage system, acquisition of more land and installation of more irrigation equipment. It will also require considerations on vegetative cover, cropping regimens and other management aspects.

In somewhat similar circumstances, two small communities have developed land disposal systems, each utilizing spreading or flooding basins following raw waste stabilization lagoons. Both communities

are quite small, using about 15 acres of land for irrigation to serve a population of less than 1,000. In both locations the basins were designed to accommodate an average application rate of about 3 inches per week for the 6 months period with storage in the lagoons for the winter 6 months. In each community, lagoons were placed in operation this spring with less than 75 percent of the properties connected to the sewer system. At our suggestion, one community directed its engineers and a geologist to confer with soil scientists and others to more fully evaluate the soil's capability. Preliminary analysis indicates application rates should be reduced to about one inch per week. Studies are continuing. At the other community soils are believed to have even less percolation capability. Obviously modifications, both in construction and management methods, must be made by each community to avoid serious pollution problems and gross nuisances.

These cases illustrate unsatisfactory performance attributable to tight soils with loading capabilities less than assumed in the design of the system, coupled with high ground waters, inadequate drainage, and in one case topography conducive to sheet runoff. A quite different set of problems arise, of course, where soils have an extremely high percolation capability with groundwater moving from the disposal site to wells used for domestic water supply. In some respects, however, the designer and his special corps of technical consultants can identify and quantify the problems and their solutions for these conditions with greater precision and confidence than in other less obvious circumstances. Some soils obviously are more difficult to analyze than others as to their hydraulic capability and their ability to remove certain pollutants under a variety of weather conditions, application rates, cropping regimens, drainage systems and other effects. Perhaps most difficult of all are intermediate and long-range behavior patterns.

I must confess that as a state regulatory group we have had less than a delightful experience with land disposal design and operation. Our lack of experience has led to periods of uncertainty and apprehension. We have had to become familiar with technologies strange to us and have become more dependent on the judgment of technicians in a host of special, related disciplines. In some quarters we have been charged with unwarranted conservatism for our judgments in some aspects of design and operation. Quite paradoxically, these same judgments are sometimes viewed by those who oppose the land disposal concept as ridiculously generous in approving systems surely doomed to failure. There is room for both agitation and humor when you stand your ground in the middle.

Surely the most productive and rewarding experience we have had in administering this phase of our water pollution control program is working with the professionals who have had a great depth of knowledge in the many special fields involved. We find them in

state departments of Agriculture, Health and Natural Resources and in similar fields of work at universities and research institutions. It has been heartening to see how they can apply their knowledge to these problems in a truly team fashion and to witness their enthusiasm to delve into the more obscure aspects related to the peculiar and wide ranging characteristics of wastewaters in an equally diverse environment. This conference here this week exemplifies this interest and involvement.

We in Michigan have given the guidelines adopted by the Standards Committee of the Great Lakes - Upper Mississippi River Board of State Sanitary Engineers a good test this past year. With each project review and each field experience we are increasingly impressed that they are soundly conceived and fairly stated. They are gaining favor and acceptance with designing engineers and their consultants as a working guideline and basic reference. We commend them, as such, for your thoughtful and critical consideration and use.

REFERENCES

Ground Disposal of Wastewaters. 1971. Addendum no. 2 to recommended standards for sewage works, Great Lakes - Upper Mississippi River Board of Sanitary Engineers.

FOREST SERVICE POLICY RELATED TO THE USE OF NATIONAL FOREST
LANDS FOR DISPOSAL OF WASTEWATER AND SLUDGE

Olaf C. Olson and Edward A. Johnson
Division of Watershed Management
Forest Service, USDA

326 J

At this time the most accurate statement concerning the Forest Service's position to disposing of wastewaters and sludges on National Forest land is that it is one of cautious optimism. It is cautious due to the dearth of proven results on the longer term effects of prolonged applications on the receiving lands. It is optimistic because of the scattered shorter term examples which have demonstrated that under carefully controlled and managed conditions, wastewaters and sludges can be recycled on selected sites without any apparent adverse effects. We are aware of the benefits to be gained. The wastewaters and sludges that are accepted for disposal have characteristics that can enhance the soil environment for plant growth, provided that the soil-plant system is not overloaded beyond its capacity to assimilate the materials.

However, with some notable exceptions in the area of land reclamation and rehabilitation, it is generally true that the primary concern of the Forest Service at this time is more one of aiding disposal with minimum detrimental impacts than it is one of looking to onsite benefits. This is in support of the established policy that Forest Service programs, wherever possible, contribute to community development and to the improvement of the rural environment in general.

FEDERAL ENVIRONMENTAL QUALITY REQUIREMENTS

All Forest Service policies concerning environmental quality must be in line with policies determined at other levels. We must be aware, therefore, of applicable policies set by the President in his messages to Congress, Executive Orders and Regulations issued in the Federal Register, Council of Environmental Quality (CEQ), and the Environmental Protection Agency (EPA), as well as our own Department of Agriculture (USDA). We must also be aware of applicable State air, water, environmental quality, and public health standards.

Executive Order 11514 of March 5, 1970, contains the following statements:

"Federal agencies shall initiate measures needed to direct their policies, plans, and programs so as to meet environmental goals:

a. Monitor, evaluate, and control on a continuing basis their agencies' activities so as to protect and enhance the quality of the environment.

b. Develop procedures to ensure the fullest practicable provision of timely public information and understanding of Federal plans and programs with environmental impact in order to obtain the views of interested parties.

e. Review their agencies' statutory authority, administrative regulations . . . to identify any deficiencies or inconsistencies therein which prohibit or limit full compliance.

f. Foster investigations, studies, surveys regarding ecosystems and environmental quality.

h. Promote development and use of indices and monitoring systems to assess environmental conditions and trends.

k. Issue guidelines."

Executive Order 11507 of February 4, 1970, concerns prevention, control, and abatement of air and water pollution at Federal facilities. Among other things, it contains the following section (46):

"In those cases where there are no air or water quality standards as defined in section 2(d) of this order in force for a particular geographic area or in those cases where more stringent requirements are deemed advisable for Federal facilities, the respective Secretary, in consultation with appropriate Federal, State, inter-State, and local agencies, may issue regulations establishing air or water quality standards for the purpose of this order, including related schedules for implementation."

Another point of real significance is assigning head of agencies primary responsibility for meeting operational and maintenance requirements in the Standards section. This includes provisions for training of manpower. We are working with EPA and other Federal agencies on training guidelines regarding qualifications and performance for individuals involved with environmental monitoring and surveillance and the continuing review to ensure that requirements are being met. Also, in time it is likely that we might be faced with certification requirements in the States where monitoring is located.

The National Environmental Policy Act of 1969 (PL 91-190) requires Environmental Statements on each proposed major Federal action affecting the human environment. The statements must be of sufficient detail to allow a responsible official to make determination of the environmental impacts to be expected from program implementation. Environmental values must be weighed objectively with economic development and social well-being goals over both the short and the long run. Also, taken into account are the comments of other agencies, individuals, and groups having interest in a project. This last item, consultation with other, is an essential consideration of the Act.

The Multiple Use-Sustained Yield Act of 1960 requires the maintenance of productivity of the land to assume perpetual optimum land . . . output of the various renewable resources.

The Code of Federal Regulations, Title 40, Part 35, with interim regulations on pollution control that became effective July 1, 1972, sets forth requirements for basin control water quality management planning, adequacy of treatment, operation and maintenance of wastewater treatment works for prevention, control, and abatement of water pollution at Federal facilities.

The general objective of the Department of Agriculture is to encourage land and water uses that will yield continuing maximum benefits to the people of the United States. Adjustments in land use to balance onsite and offsite needs should be made in ways that will make land and water available to an expanding population for living space, industry, commerce, and recreation. The systematic use of proven soil and water conservation techniques is encouraged to protect and develop land resources for future uses, to manage the soil resource for human needs, and protect and improve watersheds for both agricultural and urban uses.

The Director of Science and Education in the Secretary's Office of the USDA has stated that in connection with the possible use of National Forest lands for sewage disposal and nutrient recycling, any substance containing toxins in amounts specifically banned from agricultural use by Federal law would not be permitted for land application. This means general and local standards and criteria for disposal of sewage on National Forest lands must be developed to preclude environmental damages and undesirable ecological changes, and an effective monitoring system would be mandatory to ensure compliance with standards. Too, full coordination and cooperation will be maintained with EPA.

LAND AND RESOURCE USE REQUIREMENTS ON NATIONAL FOREST LANDS

As with other "special uses," wastewater and/or sludge disposal on National Forest lands by an out-Service group can only be done under a special use permit. Permit requirements include plans for application, surveillance, and followup management of the area. Sludges that have been stabilized by digestion or some equivalent process are acceptable. Acceptable wastewaters include those that have received primary and secondary treatment plus chlorination to reduce the health hazards. Chlorinated lagoon wastewater may be considered as equivalent to a secondary treatment. Permits require compliance with applicable Federal, State, and local environmental, public health, and water quality laws and standards.

A land manager's decision to approve or disapprove an application for wastewater disposal is based on the possibilities of beneficial or adverse total environmental effects. Each application for a permit requires, therefore, a study and an analysis of the environmental factors involved in relation to the objectives and local land use demands of the area involved. The methods and techniques for applying wastewater on forest and rangelands must be in accord with practices which can be publicly endorsed.

STATUS OF SPECIFIC POLICY DIRECTION

Forest Service national policy direction is gradually being firmed and, naturally, at this stage is influenced by the experience and knowledge of many people and agencies.

It has been recognized that a combined effort within the Forest Service will be needed to formulate a uniform and specific policy direction to wastewater disposal. A strong supporting research program is obviously essential and initial state-of-the-art guidelines for sewage disposal on agricultural and forest lands have been prepared by James O. Evans of the Division of Forest Environment Research of the U.S. Forest Service, Washington, D.C. Certain land use and management plans for the area including required environmental quality surveillance will require periodic updating.

The Eastern Region of the U.S. Forest Service has recently issued a provisional guide entitled "Environmental Protection Criteria for Disposal of Treated Sewage on Forest Lands." The guide attempts to form a bridge between water quality standards and soil quality standards and includes suggested criteria levels that may ensure minimal hazard to environmental values. This

guide was prepared by Hugh Cunningham, soil scientist, Monogahela National Forest, and has proved to be a valuable document.

As mentioned previously, regulation of the disposal system project must depend on a well-designed and implemented system of monitoring (data collection) and the interpretation of these data in terms of their meaning to total resource management on and adjacent to the specific site. Many of the recently passed laws and regulations pertaining to environmental values and the reflections of public attitudes make it essential that we document the effects of our management practices and activities on the soil resource as well as on the air and water resources. Physical, chemical, and biological characteristics and properties are all of concern.

Esthetics will also be provided for disposing of wastewater. The basic character of the landscape should be maintained with man-made alterations fitted to the immediate countryside. Special attention will be given to harmoniously joining size, shape, location, and dispersion of disposal sites so they respond directly to visual characteristics--form, line, color, and texture--of the surrounding landscape.

FUTURE OUTLOOK AND POTENTIAL IMPACTS

Because of use of land for wastewater and sludge disposal places certain restrictions on other land uses, the selection of satisfactory disposal sites is in turn restricted. At the present time, we see the greatest opportunity for large-area disposal sites on those lands upon which activities and uses are already restricted--surface mined areas (land restoration), firebreaks, greenbelts, and the like. These may not be the best sites for this purpose, but widespread use of lands having greater potential or capacity for disposal will depend largely on public acceptance. This, we believe, will come gradually with better understanding of ecosystem functioning and public involvement in the planning efforts at all stages. Small-area disposal sites can and are being located near the areas being serviced.

At the present time, there are 26 sites on National Forests in 14 States involved in planning for land disposal of wastewater and/or sludges by sprinkler or flood irrigation. We expect an increasing number of applications for this type of use on National Forest System land.

A word of prediction as to the future in the use and management of wastes and resources on National Forest lands might be appropriate in closing these remarks. The word is balance;

balance between people's needs as reflected by demand and by the capabilities and opportunities at hand for waste disposal and utilization. The challenge of achieving balance is possible through careful planning and management. We are making progress toward this goal.

SPRAY IRRIGATION - THE REGULATORY AGENCY VIEW

Richard C. Rhindress
Ground Water Quality Management Unit
Pennsylvania Department of Environmental Resources

327 J

The Bureau of Water Quality Management of the Pennsylvania Department of Environmental Resources is the regulatory agency concerned with the protection from pollution of all the waters within the state. As such we have been aware of the growing interest in the various techniques of land disposal for liquid wastes for quite some time. The increasingly stringent waste quality requirements for the discharge of waste water to streams, coupled with the upgrading of requirements for waste water treatment, plus the need for disposal in areas where streams are not readily accessible, have increased the importance of land disposal of liquid wastes. The point has been reached where it must be dealt with squarely as one of the alternatives for the treatment and ultimate disposal of waste water.

A regulatory agency becomes aware of spray irrigation from two separate sources: 1) as a new technique being promoted, and 2) as enforcement officials viewing a number of existing problems. As an environmental protection agency we have an obligation to consider all techniques of waste disposal and to assess their applicability to various wastes and their impact upon the environment. The problems which we recognized from the earliest days of our experience with operating spray irrigation systems indicated that regulation was needed. The imposition of regulation, however, carries with it a responsibility to provide guidance in the construction and location of such facilities so that the potential user can develop a plan satisfactory to the regulatory agency. This paper will discuss the experiences of our Department with spray irrigation, our philosophy concerning the use of land disposal techniques, and some important concepts which we have included in our Spray Irrigation Manual.

DEFINITIONS

At the outset of this paper on spray irrigation we should decide exactly what we mean by spray irrigation. Under the general classification "land disposal of liquid wastes" there have been a number of confused interpretations as to what is spray irrigation. I believe the definition should be, "the application of waste water to the land surface for treatment and/or ultimate disposal, using aerial dispersion (sprinklers) to distribute the effluent evenly over the land surface".

However, there are a number of other land application methods which have been confused with (and one might say "passed off" as) spray irrigation. These methods are mentioned here because we in a regulatory agency have found that we must deal with all of them as variations on a theme. For the most part they are significantly different; they usually require different technologies, and different site selection. One is the technique of spreading: driving a tank truck across a field, letting the effluent spew from the open valve, sometimes with the benefit of a spreading device. Another variation is simply open pipe discharge to a land area, often down a hillside. Third is the dumping of a sewage treatment plant sludges and septic tank sludges onto the land surface, with or without the benefit of spreading or burial. Several persons have chosen to call the application of even these non-sprayable wastes to the land surface a form of spray irrigation. Somewhat more akin to classic spray irrigation is ridge and furrow irrigation, where the effluent is spread through a series of shallow trenches. One other technique is the use of surface flow, much on the idea of a standard sand filter where the effluent is allowed to flood an area of ground and slowly sink into it. None of these techniques are equivalent to spray irrigation; however, to some extent they are each valid techniques of land disposal for liquid wastes when properly executed.

This paper will deal only with classic spray irrigation, the aerial disposal of waste water using a system of sprinklers, piping, and sprinkler nozzles.

STATUS AND REGULATION

Pennsylvania presently has 75 spray irrigation installations in operation, and another 10 to 15 in planning and design stages. The vast majority of these installations are relatively small, serving a single industry or small sewage treatment plant. Most are industrial waste applications. The largest number of these are in southeastern Pennsylvania, primarily in the Great Valley or Piedmont. Most of those which are presently under permit from the state have their permits because they have had pollution problems in the past. Although regulation has always been possible under the Pennsylvania Clean Streams Law, a discharge to the land surface was not clearly recognized as a discharge to the waters of the Commonwealth. It was considered similarly to septic tank installations where the interpretation was that there was no direct discharge, therefore, no need for a permit. Spray irrigated water, of course, does discharge to ground water by percolating down through the soils, overburden, and rocks to the water table. Thus it is definitely a discharge to the waters of the Commonwealth as defined by the Clean

Streams Law. A new program to bring all spray irrigation installations under permit will be implemented with the publication of our spray irrigation manual and new regulations.

GROUNDWATER DISCHARGES

At the same time that spray irrigation was becoming more prominent in Pennsylvania, we, like many other states, were becoming increasingly aware of the need to protect the quality of groundwater. Many septic systems are not, in fact, doing their job of renovating waste completely before it reaches groundwater. Even the best sanitary landfills are recognized as sources of groundwater. Spray irrigation presents itself as a new technique for the treatment and ultimate disposal of waste water. It keeps waste water out of the streams but in doing so poses a very real threat to the quality of groundwater.

Unlike streams which can rebound from polluted conditions in a few years, groundwater does not experience the flushing action of stream flow. It does not experience the purifying effects of air, light, and biological organisms. Instead it flows very slowly, receives little dilution, has essentially no oxygen to degrade pollutants, and flows through a medium where surface tension tends to hold pollutants in contact with it.

The general public thinks that groundwater is clean, fresh and pure, and available in that state wherever they may choose to drill a well. Fortunately, for much of the state, groundwater has these properties.

Although both the law and the public attitude demand that groundwater remain drinkable, the conditions under which groundwater exists deny significant renovation. Therefore, our goal for groundwater quality is that it be usable for domestic purposes without treatment. It is imperative to preserve groundwater in its purest possible state. The technique of spray irrigation poses a very real threat of pollution.

Experience with the presently operating systems is generally poor. Two basic problem areas have been defined: (1) improper system design and (2) management errors.

Design Problems:

Design problems can be traced to several sources. Waste treatment plant designers have had little or no education or experience

with this new technology. Attempts have been made to design systems without the understanding of the following basic tenets of spray irrigation design: First, spray irrigation is only an alternative method for disposal and treatment; Second, spray irrigation must be integrated into the environment rather than imposed upon it; and Third, as a dispersed operation, it will be far more difficult to control and manage.

Spray irrigation, and land disposal, have been advocated as the panacea for wastewater disposal problems. The literature has been attractive and promising. Unfortunately, very little of the literature speaks of potential problems and the limitations of such a technique. Thus, the consulting engineer has often been given a false sense of security. Any proposal to disperse wastes into the environment must consider the multiple constraints that the environment will place upon it. It is only after a thorough consideration of these constraints that the decision can be made that spray irrigation should be used alternatively to some other method of disposal, such as direct discharge to a stream or groundwater. For example, one agricultural waste was applied to a field for a number of years until eventually the soils were so altered that infiltration and percolation of the water was converted entirely to sheet runoff. The fields were entirely ruined and will be long in recovery. The loss of these agricultural lands and the degradation of groundwater in the area has forced the industry into acquiring both new lands and more expensive water source. In this case, it would have been far better to construct a direct pipeline to discharge to a creek over a mile away, or so treat the waste that the soil could accept it.

When using the "living filter" for waste renovation, it is extremely important that the whole wastewater treatment and disposal system be matched to the environmental capabilities rather than impressed upon it. The simple addition of the extra hydraulic load will be a major stress on the system. Further, the requirement that the soil system act as a treatment facility in decaying and renovating the waste is an added stress. Most natural areas are in a state of dynamic equilibrium. This dynamic equilibrium has the ability to respond to passing stresses. However, when a stress is applied uniformly over long periods of time, equilibrium of the ecosystem is severely altered and may, in fact, be destroyed. For example, a soil with a fragipan layer will have a low permeability, and be capable only of accepting infiltrating water at normal precipitation rates. Dosages much above this result in waterlogged soils and runoff or swampiness. A second example: vegetative communities are adapted to a soil and its available moisture capacity. However, when spray irrigation applies a hydraulic stress the vegetative system must adapt with the disappearance

of some species and introduction of others. In addition, streams below the site will have to adapt to a different flow regimen with a different chemical quality. All this is not necessarily bad, although in all but one of our experiences it has been. There are a few cases where environmental improvement may be realized through the stressing of the natural system. The assessment of the natural system, and the strains which it may show as the result of the new stresses are the prime subject matter of the Department's Spray Irrigation Manual.

For several reasons, lack of control has been a major problem in the design of spray irrigation systems. Consultants have usually ignored the valuable assistance available from the agricultural irrigation industry and have pieced together a system of pipes and valves from a catalog. Agricultural irrigation systems are designed simply to get water to a field. There is little concern about loss and leakage until it becomes a major problem. Agricultural systems are designed for ease of mobility and minimum maintenance. They are also used primarily for a short season. Conversely, wastewater irrigation systems are generally to be used year-round, must be watertight, should rarely be moved or moved only in conjunction with a carefully designed plan, and should be considered part of a long-term investment and installation. Also, in the agricultural sense the irrigation system is part of the profit-making package. It is carried on the profit side of the ledger books, whereas a waste disposal system is usually considered as a liability - as something that must be done - but which is not important to the success of the operation. Thus it is rarely adequately budgeted. Further, it is usually located at a considerable distance from the plant and the base of company operations. Often, it is completely out of sight. Thus routine operations such as checking for blockages and turning valves to change irrigated sections of the field are often neglected or relegated to a minor priority in company operations. Thus the need for mechanical, electrical, or computer control of the operations becomes very important to successful continued routine operations. Automation of the controls has been entirely neglected at the majority of sites.

With any new technique, there is the problem of education regarding its values and execution. Poor design of the spray irrigation systems presently in existence is due to the unfamiliarity of the design consultants with a new technique, and the technologies and equipment necessary to carry it out. Training courses and symposia are needed to fill this educational hiatus.

Management Problems:

As mentioned above, management and maintenance are a second major problem area for spray irrigation fields. Management views spray irrigation, or any waste discharge area, as a liability to firm operation and therefore consistently relegates its consideration to a very low priority. Maintenance of a spray field is normally the responsibility of the bottom man on the maintenance staff. He, of course, is usually the man called upon to fill in whenever there is another important task to be done or when other employees may be absent. Spray fields can go unattended for considerable periods of time without causing a problem. A well operated spray field may, in fact, go for many months without appreciable maintenance problems. However, a single malfunction within the system can stress the ecosystem to its irreversible limit. Thus, it is important to have maintenance overseeing the field on a routine basis. Unfortunately, the usual experience in Pennsylvania has been that when inspectors inspect the site, they find evidence that no one has viewed the field or cared to make necessary repairs for quite some time.

Some common problems are contained in the following list:

1. Broken pipe
2. Leaky joints
3. Vegetation blocking sprinklers
4. Valves and/or sprinklers corroded in position
5. Rutted areas from vehicular traffic in wet soils
6. Clogged sprayers
7. Unharvested vegetation
8. Swampy conditions with ponding, with even aquatic flora and fauna
9. Vector problems - flies, mosquitoes and rats
10. Anaerobic soil conditions producing swamp gases and other foul odors
11. Sheet runoff directly to adjacent streams
12. Waste material build-ups which inhibit plant growth - solids and greases.

The above are quite common. In addition to these we find evidence of application of wastes which are entirely non-degradable by the living filter system. These usually are toxic and stress the field beyond recovery.

SOLUTIONS

The solutions to the problems with spray irrigation can come from three levels: the designer, the management, and the regulatory agency.

Design Solutions:

The primary solution for the problem of securing adequate designs is one of education. Engineering schools will have to recognize spray irrigation and other techniques of land disposal as valid waste management alternatives to be included in the curricula. For the continuing education of the graduate designer, the state regulatory agencies and professional societies will need to provide data and information on the new techniques. For the consultant, it is imperative at this time to go to those who have had experience both in the experimental development phases of land disposal and in the regulatory phases, and to learn from their experience. In addition, he should rely heavily upon the expertise available from the irrigation industry.

The following fifteen steps in the implementation of a spray irrigation installation were compiled by Lewis W. Barton, a spray irrigation consultant from Cherry Hill, New Jersey, and the author. They should serve as guidelines to anyone considering land disposal of liquid waste.

1. Before deciding on land disposal or spray irrigation, examine all the alternatives regardless of any apparent restrictions. Consider recycling of wastewater and direct discharge of treated wastes to a stream or to groundwater.
2. Weigh the motives for using land disposal. Is the desired result groundwater recharge? Agricultural irrigation? Green belt irrigation for fire protection? Or just plain final treatment and ultimate disposal? Or some combination?
3. Make a preliminary tour of the area (not just the site) with reference to suitable land, a route for the force main, sites for any pumping stations, field drainage, and lagoons for storage and flow equalization.
4. Study the effluent characteristics in detail. Assess their biodegradability by the living filter. Determine if any inorganics may be present which will not be removed by the soil system or which will poison the environment.
5. Select a site. Choose the best site available. Work with the local real estate man for an option or a lease. Work with hydrogeologist and a soil scientist in making this preliminary site selection. If there is any doubt about the acceptability of the land for spray irrigation use, negotiate options or leases on double and amount of land that you expect to use.
6. Map the selected site, showing contours, topography, soils, geologic structures, bedrock geology, streams, springs, wells, woodland areas, existing buildings, and present land use patterns for the designated acreage.

7. Choose sites for background and down-gradient groundwater quality monitoring.
8. Draft a preliminary proposal to the state regulatory agency which includes the above data and a preliminary approval before proceeding with detailed design and further financial commitments.
9. Design the piping system, force main, and drainage; specify the hardware, field preparation, seeding, fertilizing, and agricultural maintenance.
10. Design and specify the automated programmers which will provide the central operating system, including pump signals and malfunction alarms.
11. Prepare and present the appropriate applications to regulatory agencies.
12. Bid the project and supervise construction. Establish and sample groundwater monitoring points before any other construction proceeds.
13. Prepare an operating manual that is simple and easy to follow. The operating manual is one of the most important pieces of the design engineer's task. It is also probably the most often neglected.
14. The design consultant should include in his contract monthly inspections of the operation for at least the first year. These inspections should involve the consultant, management, the operator, and the regulatory agency.
15. Conduct quarterly inspecting through at least the second year and even into the fourth and fifth year. These inspections will provide for continuing surveillance of system efficiency as well as for keeping the facility out of trouble with the regulatory agency.

Management Solutions:

From the management point of view the main steps which can be taken are the following:

1. Responsibility for spray field maintenance should be a full-time position. Interviews with a number of maintenance personnel have indicated that they consider their job a full-time project. Many have even suggested that we confer with management to help convince them of the amount of work necessary to keep a spray field functioning properly.
2. Put the effluent to some good use rather than just disposing of it; i.e., use it for irrigation where it will be an integral part of company operations.
3. Maintain a schedule of routine inspections.

4. Wherever possible install a buried or permanently set system. Experience has shown that movable systems either do not get moved or suffer from severe wear and tear.
5. Do not try to overload the system as production increases. Redesign or add to the system.

Regulatory Solutions:

Under present Pennsylvania law, the operator of a spray irrigation system which is disposing of sewage is required to obtain a certificate for sewage treatment plant operation. As another step in solving problems with spray irrigation systems, the state may have to extend certification to all spray field operators. In fact, it may be desirable to make "Spray Irrigation Field Operation" one of the classes of certification. Certification of spray field operators would give the regulatory agencies a stronger lever for improved operations, as withdrawal of the certificate for improper operation of the facility could put the operator out of work and place his company in violation of the law for not having a certified operator. The present condition of many spray fields within the Commonwealth suggest that this is a very likely path to follow. Again, the state has an obligation to provide information for training for spray field operator certification.

Other regulatory solutions include normal enforcement activity, design review and permitting, and the issuance of regulations and design standards.

PENNSYLVANIA'S SPRAY IRRIGATION MANUAL

The fast rising number of spray irrigation installations and applications indicate that the Department of Environmental Resources should publish a manual or set of guidelines to site selection and system design. The manual would also include instructions for the preparation of plans and reports for securing a permit. The manual has been published as the "Spray Irrigation Manual", Bureau of Water Quality Management Publication No. 31, and is available from the Bureau, located in the Fulton National Building, Third and Locust Streets, P. O. Box 2063, Harrisburg, Pennsylvania 17120.

Such a manual is necessarily written for a wide audience. It speaks to the consulting engineer and designer, the hydrogeologist and soil scientist. It also speaks to corporate management which may desire a spray irrigation system, and it often speaks to local officials and the land owner who knows very little of the technology or responsibilities involved. In speaking to a wide audience it is both an educational tool and somewhat of a design manual.

Writing a design manual is not entirely feasible since one of the main tenets of spray irrigation is that the system must be integrated into the environment rather than imposed upon it. And since the environment is extremely variable with the respect to groundwater, soils, geology, agriculture, and climate across the state, it is impossible to write a design book for all the possible variations in the environment. The assessment of these variations in the natural environment is what the manual is about. It speaks of concepts and their importance, and how each of them relates to the spray irrigation techniques of land disposal.

Basic criteria for spray irrigation have been set as a baseline from which judgement as to the acceptability of a site can be related. First, we insist that the entire waste handling package must be considered together: the pre-treatment, the storage, flow regulation, and the irrigation system. We emphasize that spray irrigation installations may be utilized only where the wastewater contains pollutants of such type and concentration that they can be satisfactorily treated through distribution to the soil mantle. Generally, only biodegradable wastes are acceptable, and the equivalent of secondary treatment must precede spray irrigation. However, we do allow for variability in earth materials, spray field use, and effluent constituents by stating that treatment requirements and performance criteria will have to be determined on a site-by-site basis. The prime consideration for site selection is the ability of the organic and earth materials to properly treat the waste.

One item which has caused considerable difficulty in drafting the spray irrigation manual has also proven to be a cause of much misunderstanding on the part of manual users. A large number of potential users for spray irrigation are industrial waste generators. These various firms will want to place a wide variety of biodegradable and non-degradable waste on their fields. Because of the wide latitude in constituents and concentrations it would be impossible to write a spray irrigation manual which tries to speak to each of these possible wastes. It is far more practical to write a manual which is oriented toward the spray irrigation of sewage. Considerations of industrial wastes must then be made as they compare to sewage. Flows and concentrations are calculated and adjusted as percentages of normal sewage effluent.

Manual Organization

The remainder of this paper will review important points and concepts in the Pennsylvania Spray Irrigation Manual, with a discussion of the reasoning behind some of the more important ones.

1. Certain criteria have been stated for the pretreatment of waste, application rates, acceptability of soils, agricultural practices, etc. These criteria have been set primarily as guidelines based upon spray irrigation of sewage effluent. However, throughout the manual there are numerous statements which demonstrate our intention to be flexible and willing to consider special applications and experimental designs. Although a number of spray irrigation sites have been in existence throughout the country for many years, they have not benefited from a total environmental impact study before implementation and have usually ended in some form of pollution. The lessons we have learned from them have been mostly negative--what not to do. Thus, we feel that this technique is still in the developmental stage and we are willing to permit justifiable experiments which vary from the basic criteria.

2. For most water pollution control facilities, construction-ready plans are required with the permit application. But, because of the need for land purchasing and extensive testing and drilling programs to determine and subsurface geology and hydrology of the spray field, the Department has instituted the preliminary review to determine the general acceptability of the proposed fields before capital investments or detailed designs are made. For a preliminary review the applicant submits:

- a. A short statement of the nature of the project and wasteload characteristics; information on location, soils and climatology.
- b. Preliminary spray field design and operation plans.

If the Department grants preliminary approval of the spray fields, the applicant is notified and the complete permit application is then submitted. The preliminary approval does not approve the construction or operation, nor does it assure approval of the complete design report. Issuance of the Department of Environmental Resources permit must precede construction and operation.

3. Factors for Consideration: A large section of the manual is devoted to some detailed explanations of factors that must be considered as they affect the renovation of the wastewater and its movement to groundwater. We are very concerned that the best soils and geologic and hydrologic conditions are available for these processes, because once the wastewater reaches the water table only minimal renovation of the waste can be expected. Thus, extreme care must be exercised in assessing these environmental factors.

- a. Earth Materials: The earth materials at a spray irrigation site may consist of soil, unconsolidated surficial deposits, weathered rock, and bedrock. Infiltrating wastewater will pass through these materials

as it percolates to the water table. The earth materials near the land surface serve as a substrate for biological activity, while the unconsolidated materials must be such that a direct rapid movement (short circuit) of the irrigated water to the groundwater does not occur. Coarse sands and gravels, open fractures in bedrock, and shallow soils are all examples of conditions which may result in short circuits. The earth materials should be moderately permeable and of a uniform quality so that they will provide slow but continuous downward movement of the infiltrating wastewater, yielding an adequate residence time for renovative reactions to take place. Detailed information on the geology, soils, and hydrology.

- b. Soils: In addition to meeting the various textural criteria, we urge that during the preparation of the field and installation of the equipment, particular attention be paid to avoiding disruption of the established soil profile as much as possible. Recommended application rates are based on the drainage and permeability of the soil, available moisture capacity, and the depth to the water table.
- c. Geology: Once the irrigated wastewater leaves the soil zone and enters the zone of weathered and fresh bedrock, it is particularly important to know the structure of this rock. Are fractures present which will short-circuit the water directly to the water table or route it preferentially in directions which modify its assumed direct route to the water table? Will the waste react with the rock? The geology also affects the direction of movement within the water table as it flows through and away from the site.
- d. Hydrology: Under most conditions in Pennsylvania, spray irrigated wastewater will recharge the local groundwater. With pretreatment, adequate dispersal of the waste, and properly chosen earth materials, the wastewater should be adequately treated during its passage through the zone of aeration to the water table. Thus, pollution of the receiving groundwater will be prevented. But once the wastewater reaches the water table only minimal renovation can be expected. Thus, to insure that the applicant has considered groundwater, its movement, and the potential result of its contamination, we have required that monitoring facilities be placed beneath the site and in all

directions of groundwater flow away from the site. In addition, a background water quality well must be established where the quality of water flowing into the area may be assessed for comparison. A secondary benefit to monitoring is that the data provide a valuable tool to the operator in limiting potential legal action from nearby groundwater users. These legal actions often are the result of fear and ignorance, thus the acquisition and maintenance of background and discharge data is imperative to the operator. This data also provides the regulatory agency with data for evaluating the efficiency of the operation. The submission of routine (generally, quarterly) reports of water quality data from both background and downgradient monitoring points is required. The exact chemicals that are reported are dependent upon the waste. For sewage, routine reports would include phosphate, ammonia-nitrogen, nitrate-nitrogen and MBAS.

- e. Agricultural Practice: Although the Department has no specific requirements as to agricultural practice, other than the maintenance of the vegetative cover on the field, we recommend that the agricultural management coordinate closely with slopes of the field and the excess hydrologic loads. Research projects such as the one at Penn State University have demonstrated that agricultural product yield can be significantly improved using spray irrigation. Yet, relatively few farmers have been willing to accept the long-term commitment to use the wastewater that is necessary to implement a system. Self-serving industry systems apparently are working. But for municipal sewage systems, this raises the questions of the applicability of funding to the purchase or rental of spray fields, the desire of the community to get into agricultural land management, and an educational problem of convincing would be lessees of the value of a long-term commitment.
- f. Research: As stated above, existing spray irrigation facilities have demonstrated that the technique has not been adequately planned or managed in the past. Certain research facilities and a few showplace operations have demonstrated the value of spray irrigation both for wastewater treatment and disposal, and as an agricultural benefit. However, these projects have been limited in their scope and in the geographic diversity. There is an immediate need to expand

research and demonstration projects to soils and environments which are less ideal than these research installations. New environmental constraints must be tested, and engineering techniques of field preparation and modification should be considered. We can integrate spray irrigation into a natural system and we can learn through applied research how this integration can take place, but spray irrigation cannot be impressed upon natural systems.

SUMMARY

Like all rapidly developing technologies waste treatment and disposal by spray irrigation has suffered from misunderstanding, inadequate design, mismanagement, and misapplication. Conversely it shows great promise as a valuable alternative technique for waste water management. New research and regulatory action will help, but a new attitude of environmental understanding is necessary by all potential users. The key to this understanding is the acceptance of the basic tenet that spray irrigation must be integrated into the environment rather than imposed upon it.

DISCUSSION

- Unknown: Is your experience on these spray irrigation systems any worse or better than the typical treatment plant?
- Rhindress: Unfortunately I can't even discuss that because I have been strictly dealing with this as a geologist. I guess I'll have to turn it over to one of our other staff members, if they want to comment. These systems, however, are almost uniformly poor.
- Reed: I would like to know where we are training this maintenance personnel.
- Rhindress: We're not. It's something that we've got to get working on and get working on fast.
- Hall: I notice in your manual the statement that under usual conditions the ground water mound should be built up and should not reach within 10 feet of the ground surface. It seems from other discussion that I've heard here that this is a pretty difficult limitation. Do you find it that way or not?
- Rhindress: It hasn't been. The manual was just published, so it hasn't been really a criteria for long. That criteria is based on some experiences, one of which is poor

operation. We're being very conservative. Another thing is that we feel and have felt through experience and reading the results of research that we needed a large zone of aeration. We felt that 10 feet would be adequate. We're learning more on this all the time. We felt at the time of writing the manual that 10 feet would be a good level in terms of a safety zone and that needed for the zone aeration.

Williams: I can't let that pass. Your rationale for a 10-foot zone escapes me completely. Why do we need 10 feet of aerated soil? What good does it do? Why not 20 feet or why not 2 inches? This is the groundwater mound when you are operating. This is not the normal groundwater table that you're talking about.

Rhindress: Right. One thing that I must point out and you've apparently not read the manual to this point, practically every value in there has a statement ahead of it or behind it or near it that says this is recommended. We can and will allow practically anything if we can be shown that there is reasonable evidence to believe that it will work. This is a guideline not a set of criteria. As I said earlier, state specifications are not going to be written. They can't be written.

Kardos: But the trouble occurs when you put out a guideline like this and it gets into the hands of engineers. They look at these as state specifications because there are inferences that this is what you're thinking of and if you put in a plan that deviates from that you're going to have trouble getting it approved.

Rhindress: All I can say is if I'm reviewing the plan, they won't have any trouble. I'll try my best to give the plan a fair review.

RESEARCH NEEDS -- LAND DISPOSAL OF MUNICIPAL SEWAGE WASTES

James O. Evans
Forest Service, USDA
Washington, D. C.

338D

This has been a very stimulating symposium -- probably the best and most informative of its kind ever conducted. In fact, we have made the first comprehensive attempt I know of to evaluate overall problems relating to the application of treated sewage effluent and sludge to forest, range, and agricultural land. We can be certain that this will not be the final such venture. At this point it seems appropriate to inquire why have we gathered here? We also might reflect on what we have learned and consider where we should go during the weeks immediately following this symposium.

ASSESSMENT OF THE SITUATION

We are here because of a need -- a need to determine the best methods of handling a residue problem which literally is our own creation. Most certainly the first man practiced land disposal, but gave no thought to pretreatment. Looking back, as Adam's children multiplied and assembled in communities, often the disposal situation became a bit messy. Sometimes streams were used to flush away the problem -- a practice that worked rather well as long as there was no overloading and other personal stream uses were limited either to upstream areas or to sites at sufficient distances downstream.

As our numbers continued to grow and congregate, through necessity we became wiser and eventually developed an impressive array of treatment-disposal facilities, some simple, other complex, and some highly advanced technically. But none of our treatment-disposal methods has proven wholly adequate. Often one kind of pollution has been replaced by another, treatment-disposal costs are increasing, sophisticated methods of disposal by discharge to and dilution in air or water have become commonplace, and regardless of the treatment method used, some residue always remains for ultimate disposal. Potential resources have either been destroyed, wasted, unused, or discharged to sites subjecting them to undesirable enrichment and environmental change.

Today our natural environment is under savage assault. Waste products of our accelerating technological development and expanding population are rapidly becoming our most insidious and deadly

enemies. A special report prepared several years ago for the Senate Committee on Interior and Insular Affairs states:

The challenge is the rapid deterioration of the environmental base, natural and manmade, which is the indispensable foundation of American security, welfare, and prosperity

It is becoming apparent that we cannot continue to enjoy the benefits of our productive economy unless we bring its harmful side effects under control.

Thoughtful Americans will agree that there is but one answer: Quality of the environment must be restored and preserved. The cost will be high -- both in money and in effort. But the costs of environmental pollution are even higher.

Each day in the United States about 100 billion liters (over 26 billion gallons) of sewage wastewater and roughly 10,000 metric tons (11,000 short tons) of dry sludge solids are produced (Evans and Sopper, 1972; Rosenkranz, 1972). Unfortunately all but a small percentage of the nutrient-rich sewage effluents are discharged into the Nation's streams. Sludge is currently disposed as follows: 15 percent in the oceans; 25 percent by incineration; and a perhaps surprising 60 percent by land application (Rosenkranz, 1972). Included in this 60 percent portion are (a) liquid sludge applied as a fertilizer, (b) sludge solids applied as a combination soil conditioner-fertilizer, and (c) sludge buried in landfills.

This symposium has dealt with the matter of recycling municipal sewage wastes by land disposal. We have considered sewage wastes not as refuse, but as useful resources (Evans, 1970). I am certain that each of us knows more now about recycling sewage wastes than he did when he arrived; however, all questions have not yet been answered, and a few nagging new ones may have been uncovered. What research is needed to perfect the use of this so-called new resource? Fortunately, we have a good base upon which to build sound research programs. This fact has been amply demonstrated at this symposium which has produced some excellent papers and provided much useful information about this rediscovered resource.

NEEDED -- A RATIONAL RESEARCH PROGRAM ON RESOURCE RECYCLING

The development of a rational recycling program in an integrated, comprehensive manner requires an almost infinite knowledge about the recycling process and ecosystem response. At the present time we know very little about either.

We must expand research on basic ecosystem function. Stevens et al, (1972) have recommended using interdisciplinary teams of biological, physical, and social scientists to test and analyze large-scale, controlled, environmental manipulations. Land disposal techniques and utilization of sewage effluents and sludges would be included in these manipulations.

Use of open-space land areas for sewage disposal invites consequent and perhaps undesirable ecological change. Foremost, studies must involve understanding the ecology of open-space lands and natural areas. Studies and evaluations should also be made concerning emerging social patterns, viable economic units, transportation and mobility, innovative technological advancements, and physical and biological interactions among components of total communities.

All subjects, including those selected for research, must be visualized as occurring within one large area representing the ecosystem. Land disposal of municipal sewage wastes can be depicted as a small circle connected to other circles of similar dimensions and all located within the larger Ecosystem Circle.

You may say that all this is fine, but our finances and current knowledge will not allow implementation of grandiose schemes. Let us be practical and realistic. What should we do now? Where do we begin?

Following are specific research needs which should and can be investigated now:

IMMEDIATE RESEARCH NEEDS

1. The mechanics for efficient and effective handling of sewage wastes and their disposal on various land areas must be developed. Research is currently underway at Beltsville, Maryland, on the comparative merits of incorporating sludge into soils by burial in trenches at depths of 2 and 4 feet, by deep disking, by rotary tilling, and through other methods. Each of these methods should be compared with various types of aerial spray mechanisms, surface spreading techniques, and subsod or subsoil injection processes.
2. Economic factors relative to various or alternative handling and disposal methods require investigation and evaluation.
3. Although technical solutions to waste-management problems either already exist or can be found without undue effort, answers are also needed to many problems having their roots in the social, economic, legal, and political areas. Existing conditions and

potential developments in the following areas urgently require investigation: (a) esthetics and public acceptance, (b) comparative costs, (c) competing needs and legal aspects, and (d) political implications and trade-offs.

4. It has often been stated that major soil types or benchmark soils throughout the Nation need study with respect to their ability to absorb, assimilate, degrade, adsorb, transmit, alter, and store various organic and inorganic substances present in sewage effluents and sludges. Hill (1972) has determined that several soils occurring extensively in Connecticut exhibit vast differences in permeability to, and capacity for removing ions from, a synthetic sewage effluent. Considerable research is needed on the interactions between various soil types and applied wastes so that major soil groups can be evaluated and rated according to their disposal capability.

5. Transport methods and costs, from sewage source to disposal site or nearby holding area, can play a decisive role in determining the feasibility of a sewage disposal program. They need thorough study and evaluation.

6. Determination of the role of microorganisms in the functioning of natural communities is needed. Also the ability of key soil microorganisms to degrade, stabilize, and render sewage wastes innocuous, and conversely, the impact of the wastes or pollutants on the microorganisms must be determined.

7. Counteraction or reaction between applied wastes and soil insect and small macroanimal populations should be observed and evaluated.

8. Research should be geared to ascertain the degree of ultimate disposal achieved. Many current pollution-abatement technologies achieve little more than sophisticated dilution of sewage wastes.

9. Potential health hazards due to disposal practices require urgent, careful, and extensive investigation:

(a) Unanswered questions have arisen concerning the potential of harm to humans from toxins or pathogens in aerosols produced by aerial spray application of sewage effluent.

(b) Possible health hazards arising from sludge spreading must be evaluated and resolved. This means ascertaining the chance of pathogen transfer to susceptible hosts as a function of time since spreading and previous treatment of the sludge. It should also include assessment of possible toxic substances in plants grown on sludge-treated areas, such as nitrate in certain vegetables.

(c) We must develop improved alternatives or refine current treatments for sludge which will eliminate health hazards posed by pathogens, nitrates, and other toxic substances. Pasteurization is one technique of likely feasibility for elimination of pathogens. Aerobic treatment followed by anaerobic treatment, or the oxidation-reduction process, is a very promising technique for reducing the nitrate hazard.

(d) We must develop alternative treatments in effluent disposal to eliminate health hazards from nitrates and other toxic substances. Here again, the oxidation-reduction process has given promising results.

10. We need to devise superior techniques for irrigating effluent and spreading sludge beneficially on forested land. Such development should be particularly useful in the industrial East and to some extent in the Seattle -- Portland belt of the Pacific Northwest, as well as in other Pacific Coast forestland and brushland areas.

11. We should determine long-term effects of various sludges on appropriate land areas. Sludges should include: (a) conventional digested sludge from domestic sources, (b) chemically stabilized sludge (lime to pH 11, etc.), and (c) sludges from industries (food, paper, textile, forest products, petroleum, etc.) which do not contribute toxic quantities of heavy metals. Appropriate land areas include: (a) pasture, (b) plowed land, (c) orchards, (d) abandoned farmland, (e) forests, (f) deserts, (g) rangeland, (h) taiga and tundra, and (i) mine spoil and other disrupted soils. The effects include vegetation changes and runoff and groundwater quality as a function of dosage.

12. Assessment must be made of the tolerance of crops and forests to various heavy metals deposited with organic sewage sludges, that is, organic sludges which reduce the toxicity of these metals.

13. We should make a thorough assessment of specific tree and agronomic crop growth responses to various effluent and sludge applications.

14. We should determine the quantity and quality of groundwater recharge from effluent irrigation under various situations.

15. We need to determine the methodology for, and efficiency of, effluent and sludge recycling in areas that remain frozen over extended periods of time.

16. We must develop technically superior, better integrated, and more comprehensive environmental monitoring systems.

17. There is an urgent need for specific comprehensive research, including the research listed above, to establish adequate standards and guidelines for the use of sewage effluent as irrigation-fertilization and aquifer recharge water -- and of sewage sludge as a fertilizer and soil conditioner.

18. Research is needed on the possibility of toxic conditions developing in certain plants resulting from excessive phosphate accumulations in soils.

19. And finally, we must consider odor problems. Wherever or whenever odor problems are apt to occur, they must either be prevented, eliminated, or effectively controlled.

One could itemize additional urgent research needs but perhaps a halt to a listing of particular research needs should be made at this point. Before closing, however, I wish to further emphasize that, whenever feasible, in our research planning we must make a habit of taking the broader, and may I suggest more ecological, view. To illustrate this approach, I have outlined an elementary system analysis to the recycling and utilization of wastes in general by land application. The illustration, Recycling and Utilization of Biodegradable Wastes by Land Application (Figure 1), is an adaptation and extension of a schematic display devised by Besley and Reed (1972). The display is enlarged to include waste effluents and forest and rangeland disposal sites. The authors refer pointedly to the common practice in Europe and the Far East of recycling biodegradable wastes to the land. They note the considerable amount of reluctance to use human sewage in this country and the more convenient and economical practice of using less bulky and plant-nutrient-balanced commercial fertilizers.

Through research we can determine whether it really is more economical on both a short-term and a long-term basis to use commercial fertilizers exclusively, rather than sewage wastes. I say exclusively because there just are not enough sewage wastes produced in America to meet the farm fertilizer demands. Also, through research we will discover much more convenient methods of applying sewage nutrients than are currently known.

At this symposium we have taken a good look at land disposal as a possible solution to our municipal sewage wastes problem. Few, if any, of us came here thinking of land disposal as a panacea. Certainly, what has transpired here underlines many of the problems and hazards as well as the benefits.




Fig. 1. Recycling and Utilization of Biodegradable Wastes by Land Application

REFERENCES

- Besley, H. E. and C. H. Reed. 1972. Urban wastes management, Jour. of Environmental Quality, 1(1), 78-81.
- Evans, J. O. 1970. The soil as a resource renovator, Environmental Science and Technology, 4(9), 732-735.
- Evans, J. O. and W. E. Sopper. 1972. Forest areas for disposal of municipal agricultural, and industrial wastes, Unpublished paper to be presented at the Seventh World Forestry Congress, Buenos Aires, Argentina, October 4-18.
- Hill, D. E. 1972. Wastewater renovation in Connecticut soils, Jour. of Environmental Quality, 1(2), 163-167.
- Rosenkranz, W. A. 1972. Unpublished data presented at OST Spring Review Meeting, April 21, Data prepared by Municipal Technology Branch, Division of Research, Environmental Protection Agency, Washington, D. C.
- Stevens, H. K., Bahr, T. G., and R. A. Cole. 1972. Recycling and ecosystem response, The Institute of Water Research, Michigan State University, East Lansing, Michigan, 124 p.

SYMPOSIUM ON RECYCLING TREATED MUNICIPAL WASTEWATER AND SLUDGE
THROUGH FOREST AND CROPLAND

LIST OF PARTICIPANTS

Abel, George A.
Environmental Protection Agency
1200 Sixth Avenue
Seattle, Washington 98100

Adams, Lowell
Environmental Resources Association
P.O. Box 2259
Monterey, California 93940

Alaisa, Cornelio
Dept. of Water Resources Admin.
State of Md., State Office Bldg.
Annapolis, Maryland 21401

Amoroso, Edward
Pa. Dept. of Environmental Resources
P.O. Box 1467
Harrisburg, Pennsylvania 17120

Anderson, Donald F.
E.P.A., Tech. Division Office
1901 N. Fort Myer Drive
Arlington, Virginia 22209

Anderson, Robert
West Virginia University
Room 1132 Ag. Sciences Building
Morgantown, West Virginia 26330

Andreoli, Aldo
Suffolk County Health Department
County Center
Riverhead, New York 11901

Apgar, Mike
Roy F. Weston, Inc.
Lewis Lane
West Chester, Pennsylvania 19380

Ariail, J. David
Environmental Protection Agency
1421 Peachtree Street, N. E.
Atlanta, Georgia 30309

Askins, William
Pope, Evans, and Robbins
11 E. 36th Street
New York, New York 10016

Bagnulo, Aldo H.
N. Va. Planning District Commission
7309 Arlington Boulevard
Falls Church, Virginia 22042

Ball, Robert C.
Michigan State University
Institute of Water Research
East Lansing, Michigan 48823

Bahr, Thomas
Michigan State University
Institute of Water Research
334 Natural Resources Building
East Lansing, Michigan 48823

Barekman, Harlan C.
City of Monett
352 S. Belaire
Monett, Missouri 65708

Barnes, Norman
Skinner Irrigation Company
2530 Spring Grove Avenue
Cincinnati, Ohio 45214

Bauer, W. J.
Bauer Engineering, Inc.
20 North Wacker Drive
Chicago, Illinois 60606

Baumgardner, Robert H. Federal Highway Administration 400 7th Street SW Washington, D. C. 20590	Betts, Clifford A., Jr. Betts Engineer Company, Inc. 518 Lookout Street Chattanooga, Tennessee 37403
Bausum, Howard T. Army Medical, Environmental Engr. Res. Unit Edgewood Arsenal, Maryland 21010	Boelter, Don H. Northern Conifers Lab. North Central Forest Expt. Sta. P.O. Box 872 Grand Rapids, Minnesota 55744
Beavin, Benjamin E., Jr. Beavin Company 104 E. 25th Street Baltimore, Maryland 21218	Boggess, William R. Dept. of Forestry University of Illinois Urbana, Illinois 61801
Beegle, Richard G. Baker-Wibberley & Associates, Inc. P.O. Box 1857 Hagerstown, Maryland 21740	Bohley, Paul B. The Gorman-Rupp Company 305 Bowman Street Mansfield, Ohio 44902
Beemer, Edwin F. 7 Walton Drive New Hope, Pennsylvania 18938	Boke, Richard L. Reynolds Metals Company 6601 West Broad Street Richmond, Virginia 23200
Behrens, John W. Metcalf & Eddy 60 E. 42nd Street New York, New York 10017	Boswell, Fred C., Dr. University of Georgia Georgia Station Experiment, Georgia 30212
Benton, Raymond U.S. Forest Service 6816 Market Street Upper Darby, Pennsylvania 19082	Botts, Lee, Mrs. Lake Michigan Federation 53 West Jackson Boulevard Chicago, Illinois 60604
Berry, Charles R. U.S. Forest Service Carlton Street Athens, Georgia 30601	Bourgeois, W. W. Forestry Service #202-130 Allard Street Sault Ste. Marie, Ontario, Canada
Berry, Wade County of Los Angeles 301 North Baldwin Avenue Arcadia, California 91006	Bouwer, Herman Water Conservation Lab. Soil and Water Res. Div. Agricultural Research Service U.S. Dept. of Agric. Phoenix, Arizona 85040
Berzins, Agris Dayton & Knight Ltd. Box 247, 1865 Marine Drive West Vancouver, B. C., Canada	

Bower, David A.
Muskingum Water Shed Conservancy Dist.
1319 3rd Street, N W
New Philadelphia, Ohio 44663

Bradford, William W.
W. Va. State Department of Health
1800 Washington Street, E.
Charleston, West Virginia 25305

Broadbent, F. E.
Dept. of Soils and Nutrition
University of California
Davis, California 95616

Brown, James L.
University of Minnesota
St. Paul, Minnesota 55100

Brown, Peter G.
Assn. for the Preservation of
Cape Cod
Box 636
Orleans, Massachusetts 02653

Bull, Robert Keith
Harza Engineer
150 S. Wacker Drive
Chicago, Illinois 60606

Burge, Wylie D.
USDA, ARS
Beltsville, Maryland 20709

Buros, Krisen
Black, Crow & Eidness, Inc.
Queens Quarter #673
Christiansted, U.S. Virgin Islands

Burrell, John
William T. Foster Associates
808 Bethlehem Pk.
Erdemheim, Philadelphia, Pa. 19118

Butler, Robert M.
Ag Engineering Dept.
Pennsylvania State University
University Park, Pennsylvania 16802

Buzzell, Timothy
USA-CRREL
Hanover, New Hampshire 03755

Cadagan, Dan J.
Dan J. Cadagan Co.
P.O. Box 8011
Spokane, Washington 99203

Callahan, James E.
U.S. Army Engr. Div., N.E.
424 Trapelo Road
Waltham, Massachusetts 02154

Carlson, Charles
Waterways Experiment Station
OSAEC, U.S. Army Corps of
Engineers
Vicksburg, Mississippi 39180

Carson, Burke, Jr.
Multrum Corp.
Skaneateles, New York 13152

Cartier, R. E., Jr.
Environmental Health Program
Southern West Virginia Regional
Health Council
Route #2, Box 382
Bluefield, West Virginia 24701

Celenza, Paschal
One Plymouth Meeting Hall
Betz Environmental Engineers
Plymouth Meeting, Pa. 19462

Chaney, Rufus L.
USDA-ARS-Biol. Waste Mgmt. Lab.
Rm. 107, Bldg. 007, P.I. Sta.
Beltsville, Maryland 20705

Chapman, John
Valmont Industries
Valley, Nebraska 68064

Chase, F. E.
University of Guelph
Guelph, Ontario, Canada

Cherry, Rodney N. U.S. Geological Survey Rm. 410, 500 Zack Street Tampa, Florida 33602	Crites, Ronald W. Metcalf & Eddy Inc. 1029 Corporation Way Palo Alto, California 94303
Christensen, Lee A. Ag. Econ. Department Michigan State University Room 303, 1405 S. Harrison Road East Lansing, Michigan 48823	Cruess, Robert A. N.H. Water Pollution Control Comm. 105 Loudon Road Concord, New Hampshire 03301
Christman, Richard L. Ohio Dept. of Natural Resources 1500 Dublin Road Division of Lands & Soil Columbus, Ohio 43221	Cunningham, Hugh Monongahela National Forest 824 15th Avenue Marlinton, West Virginia 24954
Clapp, C. E., USDA, ARS-University of Minnesota Saint Paul, Minnesota 55101	Curran, Stephen F. Dept. of Environmental Resources P.O. Box 2351 Harrisburg, Pennsylvania 17105
Click, David M. Army Corps of Engineers Box 1159 Cincinnati, Ohio 45201	Curtis, Willie R. USDA, FS, Northeast Forest Expt. Sta. 204 Center Street Berea, Kentucky 40403
Conway, Charles R. EPA-Region 1 Waltham Federal Center 424 Trapelo Road Waltham, Mass. 02154	Cutter, B. E. School of Forest Resources Pennsylvania State University University Park, Pennsylvania 16802
Conyers, Emery S. Dow Chemical Company 2020 Building Midland, Michigan 48640	Davis, Ellen Town of Brookhaven 205 South Ocean Avenue Patchogue, New York 11772
Cooper, William J. Army Medical Environmental Engr. Res. Unit Edgewood Arsenal Edgewood, Maryland 21010	Davis, David E. North Carolina State University Box 5577 Raleigh, North Carolina 27607
Crane, John S. Harza Engineer Company 150 S. Wacker Drive Chicago, Illinois 60606	Dawson, William R. U.S. Army Corps of Engineers 502 8th Street Huntington, West Virginia 25721
	Delay, Edwin T. U.S. Army Corps of Engineer P.O. Box 919 Charleston, South Carolina 29402

Dennehy, Kenneth M.
Rain Machine, Inc.
P.O. Box 291
Windsor, Connecticut 06095

De Witt, Joseph W.
U.S. Army Corps of Engineers
P.O. Box 889
Savannah, Georgia 31402

Dillon, Donald L.
U.S. Army Corps of Engineers
1114 Commerce Street
Dallas, Texas 75202

Dissmeyer, George E.
U.S. Forest Service
1720 Peachtree Street NE
Atlanta, Georgia 30309

D'itri, Frank
Michigan State University
334 Natural Res. Building
East Lansing, Michigan 48823

Dotson, Kenneth
Environmental Protection Agency
Robert A. Taft Laboratory
Cincinnati, Ohio 45226

Dovak, John L.
Pa. Dept. of Environmental Resources
996 Main Street
Meadville, Pennsylvania 16335

Drawbaugh, Daniel B.
Division of Water
Pa. Dept. of Environmental Resources
Harrisburg, Pennsylvania 17105

Edwards, I. K.
Northern Forest Research Center
5320-122nd Street
Edmonton, Alberta, Canada

Ellingboe, James D.
Bureau of Reclamation U.S.D.A.
18th & C. Streets
Washington, D. C. 20240

Elliott, William R.
Meyer Rohlin, Inc.
1111 Highway 25N
Buffalo, Minnesota 55313

Ellis, Boyd G.
Dept. of Crop and Soil Science
Michigan State University
East Lansing, Michigan 48823

Elwood, John R.
Mass. Div. Water Pollution Control
100 Cambridge Street
Boston, Massachusetts 02202

Emerson, Richard
Mich. Water Resources Commission
Stevens T. Mason Building
Lansing, Michigan 48900

Enfield, Carl G.
Environmental Protection Agency
Washington, D.C. 20460

Evans, James O.
U.S. Forest Service
14th & Independence Avenue
Washington, D.C. 20250

Ewell, Wesley J.
Cape May County Planning Board
Cape May Court House
Cape May, New Jersey 08210

Faucher, Francis D.
MDC Boston
20 Somerset Street
Boston, Massachusetts 02202

Fedler, Richard E.
Donohue & Associates, Inc.
4738 N. 40th Street
Sheboygan, Wisconsin 53081

Feinberg, Eli
State of Florida
Capital Building
Tallahassee, Florida 32304

Flett, Donald R. N. J. State Water Poll. Control Health, Ag. Building Trenton, New Jersey 08625	Frost, Terrence P. Water Pollution Control Commission 105 Loudon Road Concord, New Hampshire 03301
Ferullo, Alfred F. Mass. Div. of Water Poll. Control 100 Cambridge Street Boston, Massachusetts 02202	Gansell, Stuart I. Pa. Department of Environmental Resources 734 W. 4th Street Williamsport, Pennsylvania 17701
Fielding, H. Page Delaware River Basin Commission P.O. Box 360 Trenton, New Jersey 08603	Garner, Eugene F. Metropolitan Sewer Board 350 Metro Square Bldg. 7th & Robert Street Saint Paul, Minnesota 55101
Flanders, P. Howard Vermont Dept. of Water Resources Pavilion Office Building Montpelier, Vermont 05602	Gentry, Claude E. USDA, FS, Northeast Forest Experiment Station 204 Center Street Berea, Kentucky 40403
Forester, Ted H. Missouri Clean Water Commission P.O. Box 154 Jefferson City, Missouri 65101	Gerzetich, Robert M. Consumers Power Company 212 W. Michigan Avenue Jackson, Michigan 49201
Foster, D. H. Dept. of Civil Engineering University of Illinois Urbana, Illinois 61801	Giddings, Todd Todd Giddings & Assoc. 623 W. Foster Avenue State College, Pennsylvania 16801
Foster, William T. William T. Foster Associates 808 Bethlehem Pike Erdemheim, Philadelphia, Pa. 19118	Gifford, Robert D. Walla Walla Dist. Corps of Engr. Bldg. 604, City-County Airport Walla Walla, Washington 99362
Fox, Fred L. Geonics Box 101 North Branch, New Jersey 08876	Ginner, Gary F. Minn. Poll. Control Agency 717 Dela. St., S. E. Minneapolis, Minnesota 55440
Francke, Harry C. Union Carbide Corp.-Nuclear Division P.O. Box y Oak Ridge, Tennessee 37830	Goddard, Maurice K. Dept. of Environmental Resources Commonwealth of Pennsylvania Harrisburg, Pennsylvania 17120
Freeberg, Brian M. Stewart & Walker, Inc. 15th Street & Bemidji Avenue Box 634 Bemidji, Minnesota 55601	

Goedde, Joe
Missouri State Park Board
P.O. Box 176
Jefferson City, Missouri

Goldfine, Neil A.
New Jersey Dept. of Env. Prot.
Box 1390
Trenton, New Jersey

Gottberg, Frank
Sprinkler Irrig. Supply Co.
1316 North Campbell Road
Royal Oak, Michigan 48067

Goydan, Paul A.
Koppers
440 College Park Drive
Monroeville, Pennsylvania 15146

Graves, Diane
N. J. Sierra Club
360 Nassau Street
Princeton, New Jersey 08540

Green, Therman W.
USDA-Forest Service
1720 Peachtree Road NW, Room 716
Atlanta, Georgia 30309

Girgin, Joseph M.
Parsons, Brinckerhoff, Quade &
Douglas
111 John Street
New York, New York 10038

Griego, Alex R.
USDA-Forest Service
517 Gold Avenue SW
Albuquerque, New Mexico 87109

Guerrera, August
Suffolk County Water Authority
P.O. Box 37
Oakdale, New York 11769

Guldin, Lt. Richard W.
Wastewater Management Task Force
4H028 Forrestal Bldg.
Washington, D. C. 20314

Haines, Charles
Wright, McLaughlin Engineers
2059 Bryant Street
Denver, Colorado 80302

Hale, Daniel
Southern W. Va. Reg. Health Council
Route 2, Box 382
Bluefield, West Virginia 24701

Hall, George
Engineer-Operations
Teledyne Triple R
111 Service Road,
Muskegon Co. Airport
Muskegon, Michigan 49441

Hall, Eric P.
Environmental Protection Agency
424 Trapelo Road
Waltham, Massachusetts 02154

Hall, Otis F.
Inst. of Natural & Environmental
Resources
University of New Hampshire
Durham, New Hampshire 03824

Hanczar, William S.
Dept. of Environmental Resources
734 W. 4th Street
Williamsport, Pennsylvania 17701

Handy, Eben N., Jr.
U.S. Army Corps of Engineers
P. O. Box 59
Louisville, Kentucky 40201

Hansen, William
University of Missouri-Forestry
1-31 Ag. Building
Columbia, Missouri 65201

Hanson, Lowell D.
Ag. Extension Service
University of Minnesota
Saint Paul, Minnesota 55101

Harlin, Curtis C. Nat'l Water Quality Control Res. Program Environmental Protection Agency Ada, Oklahoma 74820	Helmey, Edgar L. Soil Conservation Service P.O. Box 985 Federal Square Station Harrisburg, Pennsylvania 17108
Harman, Edgar H. Garrett County Health Department Oakland, Maryland 21550	Hennessey, John J. Brookhaven National Lab Building 134C Upton Long Island, New York 11973
Harman, Oscar R. Environmental Science Garrett Community College McHenry, Maryland, 21520	Higbee, Roger Pa. Dept. of Environmental Resources 300 Liberty Avenue 505 State Off. Bldg. Pittsburgh, Pennsylvania 15222
Harris, W. F. Environmental Sci. Div., Bldg. 3017 Oak Ridge National Laboratories Oak Ridge, Tennessee 37830	Higgins, George C. The Dow Chemical Company 2020 Dow Center Midland, Michigan 48640
Hart, William E. Colorado State University Ft. Collins, Colorado 80521	Hill, L. W. U.S.D.A. Forest Service Institute Tropical Forestry P.O. Box AQ Rio Piedras, Puerto Rico 00928
Hartmann, George Leonard Environmental Protection Agency Region VIII, 1860 Lincoln Street Denver, Colorado 80203	Hinesly, T. D. Dept. of Agronomy University of Illinois Urbana, Illinois 61801
Haskin, Millard Bureau of State Parks Dept. of Environmental Resources 301 Market Street Harrisburg, Pennsylvania 17057	Hinkle, Richard L. Pa. Dept. of Environmental Res. 1875 New Hope Street Norristown, Pennsylvania 19401
Hedlund, V. A., Jr. Valmont Industries Valley, Nebraska 68064	Hoheneder, Joseph C. York Co. Planning Comm. 220 S. Duke Street York, Pennsylvania 17403
Heil, James Suffolk County Health Dept. County Center Riverhead, New York 11901	Hook, J. E. Dept. of Agronomy Pennsylvania State University University Park, Pennsylvania 16802
Helfant, M. A. Town of Brookhaven 205 South Ocean Avenue Patchogue, New York 11772	

Hooper, Frank T. School of Natural Resources University of Michigan Ann Arbor, Michigan 48104	Jones, Henry P. J. Henry Jones, Inc. 3389 S. 8th E. Street Salt Lake City, Utah 84106
Hortenstine, Charles C. Soil Science Dept. (106 Newell) University of Florida Gainesville, Florida 32601	Jones, Robert Lewis University of Illinois S. 410 Turner Hall Urbana, Illinois 61801
Hunt, Patrick G. USA Engineer Waterways Expt. Sta. P.O. Box 631 Vicksburg, Mississippi 39180	Johns, J. M. Johns Equipment Company Route 2, Box 21 Farmville, Virginia 23901
Hunter, Joseph V. Dept. of Environmental Science Rutgers University New Brunswick, New Jersey 08903	Johnson, James F. Waste Water Management Task Force Department of the Army Corps of Engineers Washington, D.C. 20314
Huntington, Lee Ann President's Council on Environmental Quality 722 Jackson Place Washington, D.C. 20006	Jorgensen, Erik Canadian Forestry Service The Dept. of the Environment 4056 W. Memorial Building 344 Wellington Street Ottawa, KIA OH3, Canada
Ifft, Theodore H. USDA Soil Conser. Service 4321 Hartwick Road College Park, Maryland 20740	Kam, William U.S. Geological Survey Trenton, New Jersey 08600 27 Canyon Road Levittown, Pennsylvania 19057
Inge, Andrew Dept. of Environmental Resources Bur. of State Parks, 301 Market St. Harrisburg, Pennsylvania 17101	Kappe, Stanley E. American Academy Environmental Engr. Box 1278 Rockville, Maryland 20850
Irelan, Paul H. Soil Conser. Service Camden County Berlin, New Jersey 08009	Kardos, Louis T. Department of Agronomy Pennsylvania State University University Park, Pennsylvania 16802
Jablonowski, Carl U.S. Dept. of Agriculture Forest Service, Allegh. Natl. Forest P.O. Box 847 Warren, Pennsylvania 16365	

Kasabach, Haig F. NJ Div. of Water Resources P.O. Box 1390 Trenton, New Jersey 08625	Kittle, Benjamin L. Dept. of the Army S. Atlantic Division 510 Title Building 30 Pryor Street Atlanta, Georgia 30300
Keller, James Rist-Frost, Assoc. 21 Bay Street Glenn Falls, New York 12801	Kline, John H. Consumers Power Co. 212 W. Michigan Avenue Jackson, Michigan 49201
Kelley, Harold A. Jones & Henry Engrs. Ltd. 2000 W. Central Avenue Toledo, Ohio 43606	Kolega, John J. University of Connecticut Storrs, Connecticut 06268
Kelly, George T. Metropolitan Sanitary District of Greater Chicago 100 East Erie Street Chicago, Illinois 60611	Kolzow, William C. U.S. Forest Service Building 46 Denver Federal Center Lakewood, Colorado 80225
Kelling, Keith A. University of Wisconsin Soil Department Madison, Wisconsin 53706	Konrad, John G. Department of Natural Resources Box 450 Madison, Wisconsin 53702
Kenyon, David D. New England Division U.S. Army Corps of Engineers 424 Trapel Road Waltham, Massachusetts 02154	Koo, Robert C. J. University of Florida P.O. Box 1088 Lake Alfred, Florida 33850
Kerfoot, William B. Woods Hole Oceanographic Inst. Woods Hole Woods Hole, Massachusetts 02540	Kotyik, Eugene Environmental Protection Service Dept. of Environment 106-501 Univ. Court Winnipeg, P3T2N6 Man., Canada
Kerslake, Richard J. Soil Conserv. Service 1608 Oak Hill Avenue Hagerstown, Maryland 21740	Kraybill, Richard Bureau of Water Quality Management 401 Buttonwood Street West Reading, Pennsylvania 19603
Kestner, Joseph A., Jr. One Kestner Lane Troy, New York 12180	Kraft, Daniel 26 Federal Plaza New York, New York 10007
Kidder, Milady Allegheny Health Department 40th & Penn Avenue Arsenal Health Center Pittsburgh, Pennsylvania 15224	

Krivak, Joseph A.
Planning Branch
Environmental Protection Agency
AFWP, Room 1007
Washington, D. C. 20784

Kronis, Henry
Ministry of the Environment
135 St. Clair Avenue, W
Toronto, Ontario, Canada

Kudrna, Frank L.
Metropolitan Sanitary District of
Greater Chicago
100 East Erie Street
Chicago, Illinois 60611

Kutzman, James S.
Environmental Protection Agency
Suite 204
1421 Peachtree Street, N.E.
Atlanta, Georgia 30309

Larson, Carl
Environmental Resources Association
P.O. Box 2259
Monterey, California 93940

Layman, John
The Stratton Corporation
Stratton Mountain
Stratton, Mountain, Vermont 05340

Leischen, Nicholas
State of Florida
3399 Ponce De Leon
Coral Gables, Florida

Lejcher, Terrence R.
Shawnee National Forest
U.S. Forest Service
Harrisburg, Illinois 62946

Lewis, Donald
Geography Department
University of Toledo
Toledo, Ohio 43606

Lindorff, David
Bureau of Water Quality Management
1875 New Hope Street
Norristown, Pennsylvania 19401

Little, Silas
Northeastern Forest Expt. Sta.
P.O. Box 115
Pennington, New Jersey 08534

Livingston, David
U.S. Silver & Mining Co.
1701 Lake Avenue
Glenview, Illinois 60025

Livingston, Robert
U.S. Silver & Mining Company
1701 Lake Avenue
Glenview, Illinois 60025

Lorenzen, Douglas
Department of Environmental
Resources
Harrisburg, Pennsylvania 17109

Losche, Craig
U.S. Forest Service
c/o Forestry Sciences Lab.
Southern Illinois University
Carbondale, Illinois 62901

Ludington, David
Cornell University
Riley Robb Hall
Ithaca, New York 14850

Lunin, Jesse
U.S. Department of Agriculture
Ag. Research Service
Room 127 Admn. Bldg.
Beltsville, Maryland 20705

Lyon, Walter A.
Bureau of Water Quality Management
Dept. of Environmental Resources
Harrisburg, Pennsylvania 17109

Mace, Arnett College of Forestry University of Minnesota St. Paul, Minnesota 55101	McMaster, Ronald Milford Water Authority Milford, Pennsylvania 18337
MacLauchlin, Robert U.S. Army Corps of Engineers 536 South Clark Street Chicago, Illinois 60605	McNeill, Peggy League of Women Voters Bloomfield Avenue Montclair, New Jersey 07042
Magnuson, Paula Association for the Preservation of Cape Cod Box 636 Orleans, Massachusetts 02653	McNenny, Darrell USDA Forest Service Missoula, Montana 59801
Maneval, David Appalachian Region Commission 1666 Connecticut Avenue, N.W. Washington, D. C. 20235	McWilliam, Peter Christchurch Drainage Board P.O. Box 13006 Armagh Christchurch, New Zealand
Marino, James Pennsylvania Department of Environmental Resources 996 Main Street Meadville, Pennsylvania 16335	Merritt, James Department of the Army, So. Atlantic Div., Corps of Engineers 510 Title Building 30 Pryor Street, S.W. Atlanta, Georgia, 30303
Markstrom, Donald U.S. Forest Service 240 West Prospect Street Fort Collins, Colorado 80521	Metzger, Barbara Environmental Protection Agency 26 Federal Plaza New York City, New York 10007
Marsh, John Engineering Enterprises 123 E. Tonhawa P.O. Box E Norman, Oklahoma 73069	Michael, Alan Pope, Evans and Robbins 11 E. 36th Street New York, New York 11803
McKernan, J. M. York University 4700 Keele Street Downsview 463, Ontario, Canada	Miller, Robert H. Dept. of Agronomy Ohio State University Columbus, Ohio 43210
McLaughlin, William U.S. Forest Service P.O. Box 3623 Portland, Oregon 97208	Miller, Harold Beavin Company 104 E. 25th Street Baltimore, Maryland 21218
	Minning, Robert W. G. Keck & Associates, Inc. 4903 Dawn Avenue East Lansing, Michigan 48823

Mizell, Roger
U.S. Forest Service
1720 Peachtree Street, N.W.
Atlanta, Georgia 30309

Montgomery, Wayne
Harland Bartholomew & Associates
165 North Meramec
Clayton, Missouri 63105

Moore, Harold
University of Delaware
College of Marine Studies
Newark, Delaware 19711

Moorshead, Frank
Roy F. Weston, Inc.
Lewis Lane
West Chester, Pennsylvania 19380

Morgan, Wayne
Kellogg's Supply Company
238 13 Cholame Drive
Diamond Bar, California 91765

Moser, John
Pennsylvania Department of
Environmental Resources
300 Liberty Avenue
Pittsburgh, Pennsylvania 15222

Mudrak, Vincent
Pennsylvania Fish Commission
Box 200-C
Bellefonte, Pennsylvania 16823

Myers, Earl A.
Dept. of Agricultural Engineering
Pennsylvania State University
University Park, Pennsylvania 16802

Near, C. R.
Hastings Irrig. Pipe Co.
P.O. Box 607
Hastings, Nebraska 68901

Neil, Forrest
The Metropolitan District of
Greater Chicago
100 East Erie
Chicago, Illinois 60611

Nesbitt, John B.
Dept. of Civil Engineering
Pennsylvania State University
University Park, Pennsylvania 16802

Newmann, Thomas
Environmental Engineer Service
State Department of Health
Lucas Building
Des Moines, Iowa 50320

Newell, S. David
McDowell Manufacturing Company
P.O. Box 665
DuBois, Pennsylvania 15801

Norris, Logan
U.S. Forest Service
Forestry Sciences Laboratory
3200 Jefferson Way
Corvallis, Oregon 97330

Norum, Edward
McDowell Manufacturing Company
P.O. Box 665
DuBois, Pennsylvania 15801

Nussbaumer, William
Tennessee Valley Authority
TVA Forestry Building
Norris, Tennessee 37918

O'Dell, John
U.S. Soil Conservation Service
R. 200 Fed. Courts Building
316 N. Robert Street
Saint Paul, Minnesota 55101

O'Leary, Phillip
Department of Natural Resources
Box 450
Madison, Wisconsin 53702

Oleson, Harry, Jr.
U.S. Geological Survey
500 Zack Street
Tampa, Florida 33602

Oleson, S. Melodie SW Florida Water Management District P.O. Box 457 Brooksville, Florida 33512	Paschke, Robert Rieke-Carrol-Muller Associates Box 130 Hopkins, Minnesota 55343
Olson, Olaf C. Environmental Management Section Div. of Watershed Management U.S. Forest Service Washington, D.C. 20250	Peffer, Jeffrey Bureau of Water Quality Management 29 Chestnut Street Lewistown, Pennsylvania 17044
Otke, Ken Missouri State Park Board P.O. Box 176 Jefferson City, Missouri 65101	Pepper, Leonard Waterways Express Station Box 631 Vicksburg, Minnesota 39180
Overman, Allen Agriculture Engineering University of Florida Gainesville, Florida 32601	Peterson, James R. Metropolitan Sanitary District of Greater Chicago Research and Development Lab. 5901 W. Pershing Road Cicero, Illinois 60650
Padgett, William U.S. Forest Service 6816 Market Street Upper Darby, Pennsylvania 19082	Peterson, Mark Extension of Agriculture University of Missouri Columbia, Missouri 65201
Parizek, Richard R. Dept. of Geology Pennsylvania State University University Park, Pennsylvania 16802	Pierce, James Van Note-Harvey Associates Box 623 Princeton, New Jersey 08540
Parmelee, Donald C. W. Thornthwaite Associates Route 1, Centerton Elmer, New Jersey 08318	Pierce, Donald M. Division of Wastewater Bur. of Environmental Health Dept. of Public Health Lansing, Michigan 48914
Parrett, Neil U.S. Army Corps of Engineers HQDA (DAEN-CWE-S) Washington, D. C. 20314	Pierce, Robert Water Resources Section Lake Central Region Bureau of Outdoor Recreation Ann Arbor, Michigan 48104
Parrott, Lawrence McDowell Manufacturing Company P.O. Box 665 DuBois, Pennsylvania 15801	Poloncsik, Stephen Environmental Protection Agency 1 North Wacker Drive Chicago, Illinois 60606

Poole, Allan
City of Naperville
305 Jackson Street
Naperville, Illinois 60540

Pound, Charles
Metcalf & Eddy, Inc.
1029 Corporation Way
Palo Alto, California 94303

Pounds, William
Pennsylvania Department of
Environmental Resources
Box 2351
Harrisburg, Pennsylvania 17103

Pulsonetti, P. C.
Town of Brookhaven
205 South Ocean Avenue
Patchogue, New York 11772

Ragone, Stephen
U.S. Geological Survey
1505 Kellum Place
Mineola, New York 11501

Rasmussen, Dale
Hastings Irrig. Pipe Company
P.O. Box #607
Hastings, Nebraska 68901

Ray, Griffith
U.S. Corps of Engineers
Ohio River Division
P.O. Box 1159
Cincinnati, Ohio 45201

Reed, Charles
Agricultural Engineering
Rutgers State University
New Brunswick, New Jersey 08903

Reid, Denyse
Princeton Conservation Commission
Township Hall
Princeton, New Jersey 08540

Reid, Michael
Ministry of the Environment
Plant Operations Branch
135 St. Clair Avenue
Toronto, Ontario, Canada

Reid, Robert
Town of Brookhaven
205 S. Ocean Avenue
Patchogue, New York 11772

Reid, William
Department of the Army
Corps of Engineers
Mobile District
P.O. Box 2288
Mobile, Alabama 36601

Rhindress, Richard C.
Ground Water Quality Management Unit
Division of Water Quality
Dept. of Environmental Resources
Harrisburg, Pennsylvania 17701

Rhodes, John
John C. Reutter Associates
9th & Cooper Streets
Camden, New Jersey 08101

Riddle, William
Riddle Engineering
3847 State Line
Kansas City, Missouri 64111

Risley, Clifford
Environmental Protection Agency
1 North Wacker Drive
Chicago, Illinois 60606

Ritter, William
College of Ag. Science
University of Delaware
Newark, Delaware 19711

Rodrigue, Raymond
Co. Sanitation Dists. of Los Angeles
24501 S. Figueroa Street
Harbor City, California 90710

Rodriguez, Jose Environmental Quality Board P.O. Box 11488 Santurce, Puerto Rico 00910	Schmidt, Joyce State League of Women Voters Environmental Quality Commission Bloomfield Avenue Montclair, New Jersey 07042
Rohland, F. J. Bauer Engineering, Inc. 20 North Wacker Drive Chicago, Illinois 60606	Schorr, Paul N.J. Department of Environmental Protection P.O. Box 1390 Trenton, New Jersey 08600
Rome, Samuel Pres's. Water Pollution Control 67 E. Madison (L. of W. Voters) Chicago, Illinois 60603	Schulze, K. L. Department of Civil Engineers Michigan State University East Lansing, Michigan 48823
Ruddo, Mike W.S.S.C 4017 Hamilton Street Hyattsville, Maryland 20781	Schwert, Donald Department of Forest Zoology College of Forestry University of Syracuse Syracuse, New York 13210
Russell, James McDowell Manufacture Company P.O. Box 665 DuBois, Pennsylvania 15801	Scilley, F. Maynard USDA Soil Conservation Service Room 200, Federal Center Bldg. St. Paul, Minnesota 55101
Ryan, James Department of Soil Science University of Wisconsin Madison, Wisconsin 53700	Scott, Jon Department of Atmospheric Science State University at Albany 1400 Washington Albany, New York 12222
Sabey, B. R. Colorado State University Fort Collins, Colorado 80521	Seabrook, Belford L. Div. of Municipal Waste Water Programs Office of Water Programs Environmental Protection Agency Washington, D. C. 20460
Sargent, Benson Environmental Engineering Division of Protection Pavilion Building Moneplier, Vermont 05602	Shafer, E. L., Jr. Pinchot Institute Northeastern Forest Experiment Station 6816 Market Street Upper Darby, Pennsylvania 19082
Sartz, Richard North Central Forest Experiment Station, Forest Watershed Lab. P.O. Box 872 LaCrosse, Wisconsin 54601	Shaffer, James Department of Natural Resources 65 S. Front Street Columbus, Ohio 43215
Schicht, Richard Illinois State Water Survey P.O. Box 232 Urbana, Illinois 61801	

Shane, Richard
Argonne National Laboratory
9700 S. Cass Avenue, Bldg. 12,
Center for Environmental Studies
Argonne, Illinois 60439

Shanklin, Don
USDA Soil Conservation Service
400 Midtown Plaza, 700 E. Water St.
Syracuse, New York 13031

Slack, Larry
U.S. Geological Survey
Pm. 414, 1309 Thomasville Rd.
Tallahassee, Florida 32303

Small, Maxwell
Brookhaven National Laboratory
Upton, New York 11973

Smith, Clyde
U.S. Army Corps of Engineers
P.O. Box 4970
Jacksonville, Florida 32201

Smith, Ivan
Mid-West Research Institute
425 Volker Blvd.
Prairie Village, Missouri 66208

Smith, James
Town of Amherst
Town Hall
Amherst, Massachusetts 01002

Smith, Milburn
U.S. Army Corps of Engineers
P.O. Box 17300
Fort Worth, Texas 76102

Smith, Thomas
City of Tallahassee
City Hall
Tallahassee, Florida 32303

Solomon, R. Charles
U.S. Army Corps of Engineers
P.O. Box 1715
Baltimore, Maryland 21203

Sopper, William E.
School of Forest Resources
Pennsylvania State University
University Park, Pennsylvania 16802

Sowash, James
Pennsylvania State University
401 Old Main
University Park, Pennsylvania 16802

Speakman, James
Buffalo N.Y. Corps of Engineers
1776 Niagara Street
Buffalo, New York 14207

Stanley, Ronald
U.S. Forest Service
P.O. Box 1050
Tallahassee, Florida 32302

Stanlick, Harold
U.S. Forest Service
633 W. Wisconsin Avenue
Milwaukee, Wisconsin 53074

Stansbury, Jeffrey
5902 32nd Street, N.W.
Washington, D.C. 20015

Stephenson, Marvin
The Rockefeller Foundation
111 W. 50th Street
New York, New York 10020

Stetson, John
U.S. Army Corps of Engineers
2850 SE 82nd
Portland, Oregon 97266

Stevenson, Charles
Tech. Development
Curtice - Burns, Inc.
P.O. Box 670
Rochester, New York 14602

Steward, Kerry
USDA ARS PSR
3205 S.W. 70th Avenue
Fort Lauderdale, Florida 33314

Stewart, Gordon University of Massachusetts Amherst, Massachusetts 01002	Tabor, Lance Southern W. Va. Reg. Health Council Route 2, Box 382 Bluefield, West Virginia 24701
Strand, Bruce R. R. 1 Ava, Illinois	Tanner, Howard Michigan State University 109 Natural Resources Building East Lansing, Michigan 48840
Strauser, Brad U.S. Army Engineer District 210 N. 12th Street St. Louis, Missouri 63101	Tarquin, Anthony University of Texas - El Paso Department of Civil Engineering El Paso, Texas 79968
Stucky, Glenn E. Soil Conservation Service 7600 West Chester Pike Upper Darby, Pennsylvania 19082	Tennant, Harold R. M. Wade Company Irrigation Division 1919 N. W. Therman Street Portland, Oregon 97200
Sturm, William 430 W. Seymore Avenue Cincinnati, Ohio 45216	Thomas, Richard E. Nat'l. Water Quality Control Program Robert S. Kerr Water Res. Center Environment Protection Agency Ada, Oklahoma 74820
Summers, Phillip Forest Service U. S. Department of Agriculture Washington, D. C. 20250	Thompson, D. R. Pennsylvania Department of Environmental Resources Rm. 513, S. Office Building Harrisburg, Pennsylvania 17105
Sutherland, Jeffrey Williams & Works 250 Michigan, N.E. Grand Rapids, Michigan 49503	Thompson, Jack U.S. Army Corps of Engineers Room 5F-079 DAEN-CWE-M Forrestal Building Washington, D. C. 20314
Swafford, Benny DAEN-CWE-Y Forrestal Building Washington, D. C. 20314	Tofflemire, T. James N.Y.S. Department of Environmental Conservation 50 Wolf Road Albany, New York 12200
Sydnor, Bernard Michaux Forest Garden Estates, Ltd. Box 181 Fairfield, Pennsylvania 17320	Turner, John University of Missouri 1-31 Agriculture Building Columbia, Missouri 65201
Taber, James Pennsylvania Department of Environmental Protection Harrisburg, Pennsylvania 17101	

Urie, Dean H.
North Central Forest Experiment Sta.
U.S. Forest Service
Cadillac, Michigan 49601

Vaccaro, Ralph
Woods Hole Oceanographic Inst.
Woods Hole, Massachusetts 02574

Van Aacken, Karen
McCombs-Knutson Assoc., Inc.
12805 Olson Memorial Highway
Minneapolis, Minnesota 55441

Vayansky, Thomas
Pennsylvania Department of
Environmental Resources
300 Liberty Avenue
Pittsburgh, Pennsylvania 15222

Vermillion, Lois
Interstate Commission on
Potomac River Basin
1025 Vermont Avenue, N.W.
Suite 407
Washington, D. C. 20005

Vhora, Mansukhlal
Yule Jordan & Assoc.
Box 337
Camp Hill, Pennsylvania 17011

Vodehnal, Dale
Environmental Protection Agency
Region VIII, Suite 900,
1660 Lincoln Street
Denver, Colorado 80203

Voykin, Dale
Bureau of Water Quality Mgmt.
734 W. Fourth Street
Williamsport, Pennsylvania 16701

Wakat, Cynthia
U.S. Army Corps of Engineers,
Regional Chicago District
2195 Dearborn
Chicago, Illinois 60604

Walker, Ian
Stony-Brook-Millstone Watersheds
Associates
P.O. Box 171
Pennington, New Jersey 08534

Walker, John
USDA, ARS
Plant Industry Station
Beltsville, Maryland 20810

Waller, James
Wilmington District, U.S. Army
Corps of Engineers
Wilmington, North Carolina 28401

Ward, Richard
U.S. Department of Agriculture
P.O. Box 847
Warren, Pennsylvania 16365

Warner, John
USDA Soil Conservation Service
Room 40, Midtown Plaza
700 E. Water Street
Syracuse, New York 13210

Warther, Fred
Lake Contractors Inc.
7100 Lory Lane, Box 24
Lanham, Maryland 20801

Watt, J. Thomas
Van Reuth and Weidner, Inc.
5509 York Road
Baltimore, Maryland 21212

Webb, Jack
Environ. Control Corporation
153 E. Erie, Suite 404
Painesville, Ohio 44077

Weiss, Martin
Deer Island Th. Ph.
Metropolitan District Commission
P.O. Box 100
Winthrop, Maryland 02152

Welch, Allan
Bureau of Water Quality
996 S. Main Street
Meadville, Pennsylvania 16335

Wentzel, Eugene
Pennsylvania Department of
Environmental Resources
401 Buttonwood Street
Reading, Pennsylvania 19602

Westlund, Carlyle
Groundwater Section
Bureau of Water Quality Mgmt.
P.O. Box 2351
Harrisburg, Pennsylvania 17120

Whaling, Patrick J.
Duke University
Beaufort, North Carolina 28516

Whitaker, James
Agricultural Engineering
University of Connecticut
Box U 15
Storrs, Connecticut 06268

White, Richard
Department of Agricultural
Engineering, 2073 Neil Avenue
Ohio State University
Columbus, Ohio 43210

Wikre, Dale
Minnesota Pollution Control Agency
717 Delaware, S.E.
Minneapolis, Minnesota 55440

Wiles, Carlton
Solid Waste Research Division
NERC-CIN EPA, 5555 Ridge Avenue
Cincinnati, Ohio 45242

Williams, T. C.
Williams and Works
250 Michigan Street, N.E.
Grand Rapids, Michigan 49503

Williams, Calrke
Marine Resources Council
Hauppague, New York

Wilson, Charles
Louisiana Tech. University
Ruston, Louisiana 71270

Wilson, George
Geraghty & Miller, Inc.
44 Sintsink Drive East
Port Washington, New York 11050

Winnike, Richard
Corps of Engineers (MRD)
215 N. 17th Street
Room 7020
Omaha, Nebraska 68101

Wong, Walter
County of Monterey
Public Health Department
1270 Natividad Road
Salinas, California 93901

Wood, Gene W.
School of Forest Resources
Pennsylvania State University
University Park, Pennsylvania 16802

Woodcock, Gene
Water Pollution Control Inc.
Box 337
Sumner, Iowa 50674

Wooding, Henry N.
203 Ag. Engr. Building
Pennsylvania State University
University Park, Pennsylvania 16802

Wright, Darwin
Office of Research and Monitoring
Environmental Protection Agency
Washington, D. C. 20460

Yesh, John
Department of Environmental Resources
383 Wyoming Avenue
Kingston, Pennsylvania

Youngner, V. B.
Department of Plant Sciences
University of California
Riverside, California 92502

Zagar, Michael
Minn. Pollution Control Agency
717 Delaware Street, S.E.
Minneapolis, Minnesota 55440

Zagloul, Omar
Lindsay Manufacturing Company
Lindsay, Nebraska 68644

Zampogna, Ralph
Bureau of Water Quality Management
1875 New Hope Street
Norristown, Pennsylvania 19401

Zemaitis, William
Aerobic Systems, Inc.
4 West 58th Street
New York, New York 10019

Zimmerman, R.
Perma Engine
2010 Cogay Avenue
Winnipeg, Manitoba, Canada

Zoda, Arthur
N.J.D.E.P.
John Fitch Plaza
Trenton, New Jersey 08618

Zwalinski, John
Department of Environ. Resources
1875 New Hope Street
Norristown, Pennsylvania 19401

Zweig, Richard
U.S. Forest Service
Room 708, 1720 Peachtree Road
Atlanta, Georgia 30309